



Programación Web Alonso Salcido 4P8-A 8:00-9:00



Marcelo López Almeida

Started on Wednesday, 8 February 2017, 8:55 PM

State Finished

Completed on Wednesday, 8 February 2017, 9:23 PM

Time taken 28 mins 9 secs

Grade 1.00 out of 10.00 (10%)

Question 1

Incorrect

Mark 0.00 out of 1.00

How do you declare an array of objects in JS?

Select one:

- ☒ a. `const array = new Array;` ❌
- ☐ b. `const array = [{id:0},{id:1},{id:2}];`
- ☐ c. `const new Array = array[]`
- ☐ d. `const array = [];`

Your answer is incorrect.

The correct answer is: `const array = [{id:0},{id:1},{id:2}];`

Response history

Step	Time	Action	State	Marks
1	8/02/17, 20:55	Started	Not yet answered	
2	8/02/17, 21:22	Saved: <code>const array = new Array;</code>	Answer saved	
3	8/02/17, 21:23	Attempt finished	Incorrect	0.00


Question 2

Incorrect

Mark 0.00 out of
1.00

What is the behavior of console.table() javascript function?

Select one:

- ☒ a. Allows to log provided data using linear layout 
- ☐ b. Allows to log provided data using tabular layout
- ☐ c. Allows to log provided data using absolute layout

Your answer is incorrect.

The correct answer is: Allows to log provided data using tabular layout

Response history

Step	Time	Action	State	Marks
1	8/02/17, 20:55	Started	Not yet answered	
2	8/02/17, 21:00	Saved: Allows to log provided data using linear layout	Answer saved	
3	8/02/17, 21:23	Attempt finished	Incorrect	0.00

Question 3

Incorrect

Mark 0.00 out of
1.00What is the behaviour of `.map()` function of javascript?

Select one:

- ☐ a. Javascript array **map()** method creates a new array with the results of calling a provided function on every element in this array.
- ☒ b. Javascript array **map()** method creates a new string list with the results of calling a provided function on every element in the API array ❌
- ☐ c. Javascript array **map()** method creates a new arraylist with the results of calling a provided function on every element in this array.
- ☐ d. Javascript array **map()** method creates a new array with the results of calling a provided promises on each element in this array.

Your answer is incorrect.

The correct answer is: Javascript array **map()** method creates a new array with the results of calling a provided function on every element in this array.

Response history

Step	Time	Action	State	Marks
1	8/02/17, 20:55	Started	Not yet answered	
2	8/02/17, 21:02	Saved: Javascript array MAP() method creates a new string list with the results of calling a provided function on every element in the API array	Answer saved	
3	8/02/17, 21:23	Attempt finished	Incorrect	0.00

Question 4

Incorrect

Mark 0.00 out of
1.00

What is the behavior of return statement in javascript functions?

Select one:

- ☐ a. Is a value that javascript function return when all the code of the function finished of execute.
- ☒ b. When JavaScript reaches a **return statement**, the function will stop executing. ✖
- ☐ c. Is a parameter of the function

Your answer is incorrect.

The correct answer is: Is a value that javascript function return when all the code of the function finished of execute.

Response history

Step	Time	Action	State	Marks
1	8/02/17, 20:55	Started	Not yet answered	
2	8/02/17, 21:02	Saved: When JavaScript reaches a RETURN STATEMENT, the function will stop executing.	Answer saved	
3	8/02/17, 21:23	Attempt finished	Incorrect	0.00

Question 5

Incorrect

Mark 0.00 out of
1.00

What is the behavior of ternary operator?

Select one:

- ☐ a. An expression that evaluates to true or false.
- ☐ b. Is like an if
- ☒ c. An expression that evaluates to return a promise or a deferred object ❌
- ☐ d. An expression that evaluates to null or NaN

Your answer is incorrect.

The correct answer is: An expression that evaluates to true or false.

Response history

Step	Time	Action	State	Marks
1	8/02/17, 20:55	Started	Not yet answered	
2	8/02/17, 21:13	Saved: An expression that evaluates to return a promise or a deferred object	Answer saved	
3	8/02/17, 21:23	Attempt finished	Incorrect	0.00

Question 6

Incorrect

Mark 0.00 out of
1.00

What is the behaviour of the reduce() function of javascript?

Select one:

- ☐ a. The reduce() method applies a function against an accumulator and each value of the array (from left-to-right) has to reduce it to a single value.
- ☐ b. The reduce() method applies a function with an accumulator and each value of the array (from left-to-right) has to reduce it to a single value.
- ☐ c. The reduce() method applies a function against an accumulator and each value of the array (from right-to-left) has to reduce it to a single value.
- ☒ d. The reduce() method applies a trigger against an accumulator and each value of the array (from left-to-right) has to reduce it to a single value. ✖

Your answer is incorrect.

The correct answer is: The reduce() method applies a function against an accumulator and each value of the array (from left-to-right) has to reduce it to a single value.

Response history

Step	Time	Action	State	Marks
1	8/02/17, 20:55	Started	Not yet answered	
2	8/02/17, 21:16	Saved: The reduce() method applies a trigger against an accumulator and each value of the array (from left-to-right) has to reduce it to a single value.	Answer saved	
3	8/02/17, 21:23	Attempt finished	Incorrect	0.00

Question 7

Incorrect

Mark 0.00 out of
1.00

What is the meaning of this symbols: =>

Select one:

- ☐ a. Is a "subprogram" that can be *called* by code external
- ☐ b. An anonymous function
- ☐ c. An arrow function expression has a shorter syntax than a function expression and does not bind its own this, arguments, super, or new.target.
- ☒ d. is a "subprogram" that can be *called* by code external and ever returns a value ✖

Your answer is incorrect.

The correct answer is: An arrow function expression has a shorter syntax than a function expression and does not bind its own this, arguments, super, or new.target.

Response history

Step	Time	Action	State	Marks
1	8/02/17, 20:55	Started	Not yet answered	
2	8/02/17, 21:16	Saved: is a "subprogram" that can be <code>_called_</code> by code external and ever returns a value	Answer saved	
3	8/02/17, 21:23	Attempt finished	Incorrect	0.00

Question 8

Correct

Mark 1.00 out of 1.00

What is the name of the second item of array people?

Select one:

- ☐ a. 'Beethoven, Ludwig'
- ☐ b. 'Beckett, Samuel'
- ☒ c. 'Becker, Carl' ✓
- ☐ d. 'Beecher, Henry'

Your answer is correct.

The correct answer is: 'Becker, Carl'

Response history

Step	Time	Action	State	Marks
1	8/02/17, 20:55	Started	Not yet answered	
2	8/02/17, 21:19	Saved: 'Becker, Carl'	Answer saved	
3	8/02/17, 21:23	Attempt finished	Correct	1.00

Question 9

Incorrect

Mark 0.00 out of 1.00

Which are the properties of the each object in inventors array?

Select one:

- ☒ a. last:, year:, passed: ❌
- ☐ b. first:, last:, year:, passeout:
- ☐ c. first:, last:, year:, passed:
- ☐ d. first:, last:, date:, passed:

Your answer is incorrect.

The correct answer is: first:, last:, year:, passed:

Response history

Step	Time	Action	State	Marks
1	8/02/17, 20:55	Started	Not yet answered	
2	8/02/17, 21:21	Saved: last:, year:, passed:	Answer saved	
3	8/02/17, 21:23	Attempt finished	Incorrect	0.00

Question 10

Incorrect

Mark 0.00 out of 1.00

Complete: Psst: have a look at the JavaScript

Answer: ❌

The correct answer is: console

Response history

Step	Time	Action	State	Marks
1	8/02/17, 20:55	Started	Not yet answered	
2	8/02/17, 21:22	Saved: Psst: have a look at the JavaScript Console	Answer saved	
3	8/02/17, 21:23	Attempt finished	Incorrect	0.00

