



Desarrollo de Aplicaciones Web 5H6-A 10:00-11:00



DAVID OSWALDO ALARCON OLIVAS

Started on Monday, 5 June 2017, 9:51 PM

State Finished

Completed on Monday, 5 June 2017, 10:09 PM

Time taken 17 mins 41 secs

Grade 4.00 out of 10.00 (40%)

Question 1

Incorrect

Mark 0.00 out of 1.00

Are files starting with main.* loaded first?

Select one:

- ☐ a. /assets
- ☐ b. /lib
- ☐ c. /server
- ☒ d. /client ✖

Your answer is incorrect.

The correct answer is: /lib

Response history

Step	Time	Action	State	Marks
1	5/06/17, 21:51	Started	Not yet answered	
2	5/06/17, 21:52	Saved: /client	Answer saved	
3	5/06/17, 22:09	Attempt finished	Incorrect	0.00

Question 2

Correct

Mark 1.00 out of 1.00

How would you obtain the URL path component of a the latestReviews collection?

Select one:

- ☐ a. "{{pathFor 'lReviews'}}"
- ☐ b. "{{pathFor latestRev}}"
- ☐ c. "{{pathFor latestReviews}}"
- ☒ d. "{{pathFor 'latestReviews'}}" ✓

Your answer is correct.

The correct answer is: "{{pathFor 'latestReviews'}}"

Response history

Step	Time	Action	State	Marks
1	5/06/17, 21:51	Started	Not yet answered	
2	5/06/17, 21:54	Saved: "{{pathFor 'latestReviews'}}"	Answer saved	
3	5/06/17, 22:09	Attempt finished	Correct	1.00

Question 3

Incorrect

Mark 0.00 out of 1.00

Using Spacebars, what helper returns the URL path component of a route?

Select one:

- ☐ a. {{pathFor}} returns the URL path component of a route
- ☐ b. {{path}} returns the URL path component of a route
- ☒ c. {{url}} returns the URL path component of a route ❌
- ☐ d. {{For}} returns the URL path component of a route

Your answer is incorrect.

The correct answer is: {{pathFor}} returns the URL path component of a route

Response history

Step	Time	Action	State	Marks
1	5/06/17, 21:51	Started	Not yet answered	
2	5/06/17, 21:57	Saved: {{url}} returns the URL path component of a route	Answer saved	
3	5/06/17, 22:09	Attempt finished	Incorrect	0.00

Question 4

Incorrect

Mark 0.00 out of
1.00

What does `{{> postItem}}` do when found in an HTML file and where will `postItem` be found?

Select one:

- ☐ a. Renders the template `postItem`. It will be found in an HTML file with a `<template>` tag like this: `<template name="postItem">`
- ☐ b. Renders the template `postItems`. It will be found in an HTML file with a `<template>` tag like this: `<template name="postItems">`
- ☒ c. Renders the template `postLists`. It will be found in an HTML file with a `<template>` tag like this: `<template name="postLists">` ✖
- ☐ d. Renders the template `postItemList`. It will be found in an HTML file with a `<template>` tag like this: `<template name="postItemList">`

Your answer is incorrect.

The correct answer is: Renders the template `postItem`. It will be found in an HTML file with a `<template>` tag like this: `<template name="postItem">`

Response history

Step	Time	Action	State	Marks
1	5/06/17, 21:51	Started	Not yet answered	
2	5/06/17, 21:59	Saved: Renders the template <code>postLists</code> . It will be found in an HTML file with a <code><template></code> tag like this: <code><template name="postLists"></code>	Answer saved	
3	5/06/17, 22:09	Attempt finished	Incorrect	0.00

Question 5

Incorrect

Mark 0.00 out of
1.00

What is a computation?

Select one:

- ☐ a. Code that runs any time there is a change to the reactive data source it depends on.
- ☐ b. Code that runs to the reactive data source it depends on.
- ☒ c. Code that runs in realtime. ✖
- ☐ d. Code that runs any time there is a change to the reactive data source it depends on.

Your answer is incorrect.

The correct answer is: Code that runs any time there is a change to the reactive data source it depends on.

Response history

Step	Time	Action	State	Marks
1	5/06/17, 21:51	Started	Not yet answered	
2	5/06/17, 22:01	Saved: Code that runs in realtime.	Answer saved	
3	5/06/17, 22:09	Attempt finished	Incorrect	0.00

Question 6

Correct

Mark 1.00 out of
1.00

What is data context?

Select one:

☐ a.

A data context sets Javascript's this inside a template method.

☐ b.

A data context sets Javascript's this inside a template client side manager .

☐ c.

A data context sets Javascript's this inside a template server side manager.

☒ d. A data context sets Javascript's this inside a template helper.

A data context sets Javascript's this inside a template helper. ✓

Your answer is correct.

The correct answer is: A data context sets Javascript's this inside a template helper.

A data context sets Javascript's this inside a template helper.

Response history

Step	Time	Action	State	Marks
------	------	--------	-------	-------

1	5/06/17, 21:51	Started	Not yet answered	
2	5/06/17, 22:04	Saved: A data context sets Javascript's this inside a template helper. A data context sets Javascript's this inside a template helper.	Answer saved	
3	5/06/17, 22:09	Attempt finished	Correct	1.00

Question 7

Incorrect

Mark 0.00 out of
1.00

What purpose does the Iron Router waitOn() function serve?

Select one:

☒ a.

Provides a notification that data has finished loading, which is important because it means the model won't be rendered before all the data has been loaded.

Provides a notification that data has finished loading, which is important because it means the template won't be rendered before all the data has been loaded. ✖

- ☐ b. Provides a notification that data has finished loading, which is important because it means the template won't be rendered before all the data has been loaded.
- ☐ c. Provides a cursor that data has finished loading, which is important because it means the template won't be rendered before all the data has been loaded.
- ☐ d. Provides a notification that data has starting loading data.

Your answer is incorrect.

The correct answer is: Provides a notification that data has finished loading, which is important because it means the template won't be rendered before all the data has been loaded.

Response history

Step	Time	Action	State	Marks
1	5/06/17, 21:51	Started	Not yet answered	
2	5/06/17, 22:07	Saved: Provides a notification that data has finished loading, which is important because it means the model won't be rendered before all the data has been loaded. Provides a notification that data has finished loading, which is important because it means the template won't be rendered before all the data has been loaded.	Answer saved	
3	5/06/17, 22:09	Attempt finished	Incorrect	0.00

Question 8

Incorrect

Mark 0.00 out of 1.00

Where do static assets go?

Select one:

- ☐ a. /client directory
- ☐ b. /public directory
- ☒ c. /assets directory ❌
- ☐ d. /private directory

Your answer is incorrect.
The correct answer is: /public directory

Response history

Step	Time	Action	State	Marks
1	5/06/17, 21:51	Started	Not yet answered	
2	5/06/17, 22:07	Saved: /assets directory	Answer saved	
3	5/06/17, 22:09	Attempt finished	Incorrect	0.00

Question 9

Correct

Mark 1.00 out of
1.00

Which method is using to show to meteor if the code in the server o client side?

Select one:

- ☒ a. `if (Meteor.isClient) {`
`// code here will only be run on the client`
`} ✓`
- ☐ b. `if (Meteor.isBetween) {`
`// code here will only be run on the server`
`}`
- ☐ c.
`if (Meteor.isServer) {`

`// code here will only be run on the client`
`}`
- ☐ d. `if (Meteor.isAsset) {`
`// code here will only be run on the client`
`}`

Your answer is correct.

The correct answer is: `if (Meteor.isClient) {``// code here will only be run on the client`
`}`

Response history

Step	Time	Action	State	Marks
1	5/06/17, 21:51	Started	Not yet answered	
2	5/06/17, 22:08	Saved: <code>if (Meteor.isClient) { // code here will only be run on the client }</code>	Answer saved	
3	5/06/17, 22:09	Attempt finished	Correct	1.00

Question 10

Correct

Mark 1.00 out of
1.00

Which port use meteor to render the server?

Select one:

- ☐ a. localhost:8000
- ☒ b. localhost:3000 ✓
- ☐ c. localhost:9000
- ☐ d. localhost:4000

Your answer is correct.

The correct answer is: localhost:3000

Response history

Step	Time	Action	State	Marks
1	5/06/17, 21:51	Started	Not yet answered	
2	5/06/17, 22:09	Saved: localhost:3000	Answer saved	
3	5/06/17, 22:09	Attempt finished	Correct	1.00