



# Programación Web Alonso Salcido 4P8-A 8:00-9:00



KARELY OLIVAS OLIVAS

**Started on** Wednesday, 8 February 2017, 9:55 PM

**State** Finished

**Completed on** Wednesday, 8 February 2017, 10:06 PM

**Time taken** 11 mins 28 secs

**Grade** 10.00 out of 10.00 (100%)

## Question 1

Correct

Mark 1.00 out of 1.00

How do you declare an array of objects in JS?

Select one:

- ☐ a. const new Array = array[]
- ☒ b. const array = [{id:0},{id:1},{id:2}]; ✓
- ☐ c. const array = new Array;
- ☐ d. const array = [];

Your answer is correct.

The correct answer is: const array = [{id:0},{id:1},{id:2}];

## Response history

Step	Time	Action	State	Marks
1	8/02/17, 21:55	Started	Not yet answered	
2	8/02/17, 21:56	Saved: const array = [{id:0},{id:1},{id:2}];	Answer saved	
3	8/02/17, 22:06	Attempt finished	Correct	1.00

**Question 2**

Correct

Mark 1.00 out of  
1.00

What is the behavior of console.table() javascript function?

Select one:

- ☒ a. Allows to log provided data using tabular layout ✓
- ☐ b. Allows to log provided data using linear layout
- ☐ c. Allows to log provided data using absolute layout

Your answer is correct.

The correct answer is: Allows to log provided data using tabular layout

**Response history**

Step	Time	Action	State	Marks
1	8/02/17, 21:55	Started	Not yet answered	
2	8/02/17, 21:56	Saved: Allows to log provided data using tabular layout	Answer saved	
3	8/02/17, 22:06	Attempt finished	Correct	1.00

**Question 3**

Correct

Mark 1.00 out of  
1.00

What is the behavior of .map() function of javascript?

Select one:

- ☐ a. Javascript array **map()** method creates a new string list with the results of calling a provided function on every element in the API array
- ☐ b. Javascript array **map()** method creates a new arraylist with the results of calling a provided function on every element in this array.
- ☐ c. Javascript array **map()** method creates a new array with the results of calling a provided promises on each element in this array.
- ☒ d. Javascript array **map()** method creates a new array with the results of calling a provided function on every element in this array. ✓

Your answer is correct.

The correct answer is: Javascript array **map()** method creates a new array with the results of calling a provided function on every element in this array.

**Response history**

Step	Time	Action	State	Marks
1	8/02/17, 21:55	Started	Not yet answered	
2	8/02/17, 21:58	Saved: Javascript array MAP() method creates a new array with the results of calling a provided function on every element in this array.	Answer saved	
3	8/02/17, 22:06	Attempt finished	Correct	1.00

**Question 4**

Correct

Mark 1.00 out of  
1.00

What is the behavior of return statement in javascript functions?

Select one:

- ☐ a. When JavaScript reaches a **return statement**, the function will stop executing.
- ☒ b. Is a value that javascript function return when all the code of the function finished of execute. ✓
- ☐ c. Is a parameter of the function

Your answer is correct.

The correct answer is: Is a value that javascript function return when all the code of the function finished of execute.

## Response history

Step	Time	Action	State	Marks
1	8/02/17, 21:55	Started	Not yet answered	
2	8/02/17, 21:59	Saved: Is a value that javascript function return when all the code of the function finished of execute.	Answer saved	
3	8/02/17, 22:06	Attempt finished	Correct	1.00

**Question 5**

Correct

Mark 1.00 out of  
1.00

What is the behaviour of ternary operator?

Select one:

- ☒ a. An expression that evaluates to true or false. ✓
- ☐ b. An expression that evaluates to return a promise or a deferred object
- ☐ c. Is like an if
- ☐ d. An expression that evaluates to null or NaN

Your answer is correct.

The correct answer is: An expression that evaluates to true or false.

**Response history**

Step	Time	Action	State	Marks
1	8/02/17, 21:55	Started	Not yet answered	
2	8/02/17, 22:00	Saved: An expression that evaluates to true or false.	Answer saved	
3	8/02/17, 22:06	Attempt finished	Correct	1.00

**Question 6**

Correct

Mark 1.00 out of  
1.00

What is the behaviour of the reduce() function of javascript?

Select one:

- ☒ a. The reduce() method applies a function against an accumulator and each value of the array (from left-to-right) has to reduce it to a single value. ✓
- ☐ b. The reduce() method applies a trigger against an accumulator and each value of the array (from left-to-right) has to reduce it to a single value.
- ☐ c. The reduce() method applies a function against an accumulator and each value of the array (from right-to-left) has to reduce it to a single value.
- ☐ d. The reduce() method applies a function with an accumulator and each value of the array (from left-to-right) has to reduce it to a single value.

Your answer is correct.

The correct answer is: The reduce() method applies a function against an accumulator and each value of the array (from left-to-right) has to reduce it to a single value.

## Response history

Step	Time	Action	State	Marks
1	8/02/17, 21:55	Started	Not yet answered	
2	8/02/17, 22:04	Saved: The reduce() method applies a function against an accumulator and each value of the array (from left-to-right) has to reduce it to a single value.	Answer saved	
3	8/02/17, 22:06	Attempt finished	Correct	1.00

**Question 7**

Correct

Mark 1.00 out of  
1.00

What is the meaning of this symbols: =&gt;

Select one:

- ☐ a. An anonymous function
- ☒ b. An arrow function expression has a shorter syntax than a function expression and does not bind its own this, arguments, super, or new.target. ✓
- ☐ c. is a "subprogram" that can be *called* by code external and ever returns a value
- ☐ d. Is a "subprogram" that can be *called* by code external

Your answer is correct.

The correct answer is: An arrow function expression has a shorter syntax than a function expression and does not bind its own this, arguments, super, or new.target.

## Response history

Step	Time	Action	State	Marks
1	8/02/17, 21:55	Started	Not yet answered	
2	8/02/17, 22:05	Saved: An arrow function expression has a shorter syntax than a function expression and does not bind its own this, arguments, super, or new.target.	Answer saved	
3	8/02/17, 22:06	Attempt finished	Correct	1.00

Question 8

Correct

Mark 1.00 out of 1.00

What is the name of the second item of array people?

Select one:

- ☐ a. 'Beecher, Henry'
- ☒ b. 'Becker, Carl' ✓
- ☐ c. 'Beethoven, Ludwig'
- ☐ d. 'Beckett, Samuel'

Your answer is correct.

The correct answer is: 'Becker, Carl'

Response history

Step	Time	Action	State	Marks
1	8/02/17, 21:55	Started	Not yet answered	
2	8/02/17, 22:05	Saved: 'Becker, Carl'	Answer saved	
3	8/02/17, 22:06	Attempt finished	Correct	1.00



**Question 9**

Correct

Mark 1.00 out of 1.00

Which are the properties of the each object in inventors array?

Select one:

- ☒ a. first:, last:, year:, passed: ✓
- ☐ b. last:, year:, passed:
- ☐ c. first:, last:, year:, passeout:
- ☐ d. first:, last:, date:, passed:

Your answer is correct.

The correct answer is: first:, last:, year:, passed:

## Response history

Step	Time	Action	State	Marks
1	8/02/17, 21:55	Started	Not yet answered	
2	8/02/17, 22:06	Saved: first:, last:, year:, passed:	Answer saved	
3	8/02/17, 22:06	Attempt finished	Correct	1.00

**Question 10**

Correct

Mark 1.00 out of 1.00

Complete: Psst: have a look at the JavaScript

Answer:  ✓

The correct answer is: console

## Response history

Step	Time	Action	State	Marks
1	8/02/17, 21:55	Started	Not yet answered	
2	8/02/17, 22:06	Saved: Console	Answer saved	
3	8/02/17, 22:06	Attempt finished	Correct	1.00

