

# MPL Plotter Documentation

**Antonio López Rivera**

June 2022





## TABLE OF CONTENTS

<b>1</b>	<b>2D</b>	<b>2</b>
1.1	Comparisons . . . . .	2
1.2	Plotting Methods . . . . .	3
1.3	Placeholders . . . . .	11
1.4	Pane plot method . . . . .	11
<b>2</b>	<b>3D</b>	<b>13</b>
2.1	Plotting Methods . . . . .	13
2.2	Placeholders . . . . .	18
<b>3</b>	<b>Colors</b>	<b>19</b>
3.1	Methods . . . . .	19
3.2	Color Maps . . . . .	19
3.3	Color Schemes . . . . .	20
<b>4</b>	<b>Presets</b>	<b>21</b>
4.1	Precision . . . . .	21
4.2	Preset . . . . .	21
4.3	Publication . . . . .	22
	<b>Python Module Index</b>	<b>23</b>
	<b>Index</b>	<b>24</b>



Making plots for technical documents can be a time sink. MPL Plotter aims to reduce that overhead by allowing you to effortlessly and concisely

- Generate publication quality figures with a single call
- Compare data by plotting different curves in a single plot
- Visualize different kinds of data in figures with many plots

It is opinionated but built with flexibility in mind, which practically means that no default can't be changed, and any and all further customization with Matplotlib is compatible. From ticks to legends to extra axes to whatever suits your needs. There's two ways to use MPL Plotter:

- Calls to the 2D and 3D plotting functions
- Using presets, either those shipped with the library, or custom ones

It does the job for me and I expand it when it can't. Hope you find some use in it!

### 1.1 Comparisons

**comparison** (*x, y, f=None, show=False, autocolor=True, top=None, bottom=None, left=None, right=None, wspace=None, hspace=None, \*\*kwargs*)

#### Inputs

The table below displays the supported numerical input combinations, where:

- array: List or NumPy array with numerical values
- [...]: List containing ...
- result: <curves>

Table 1.1: Valid input combinations.

x	y	Result	Notes
array	array	1	
array	[array, array]	2	Both y's share a single `x`
[array, array]	[array, array]	2	Both x's share a single `y`
[n*[array]]	[n*[array]]	n	Each y has an x

#### Arguments

Arguments are internally classified as FIGURE arguments, AXIS arguments, PLURAL arguments and CURVE arguments, namely:

- Figure Select few arguments which may be input only once in the plotting process, so as to avoid conflicts. Ieg: passing *grid=True* twice (*plt.grid(...)*) will result in no grid being drawn. These are removed from the keyword arguments and used in the last *comparison* call.
- Plural Arguments with a keyword equal to any of the arguments which can be passed to the

*line*



2D plotter, in plural tense. The line plotter is chosen as it shares all general arguments with the other 2D plotter functions. The plural arguments are assumed to be

*lists of length equal to the number of curves*

and thus modify each curve. Ieg: `colors=['red', 'green', 'blue']` will set the color of each curve to 'red', 'green' and 'blue' respectively in a 3-curve plot.

## Defaults

The limits of the plot will be adjusted to the upper and lower limits of all `x`'s and `y`'s.

### Parameters

- **x** (*list of list or list of np.ndarray*) – Domains.
- **y** (*list of list or list of np.ndarray*) – Values.
- **f** (*list of plot*) – Functions used to plot `y(x)`
- **kwargs** – MPL Plotter plotting class keyword arguments for further customization

## 1.2 Plotting Methods

### class canvas

Bases: object

**method\_backend()**

**method\_fonts()**

Fonts

Reference:

- <https://matplotlib.org/2.0.2/users/customizing.html>

### Pyplot method:

`plt.rcParams['<category>.<item>'] = <>`

**method\_figure()**

**method\_setup()**

**method\_grid()**

**method\_background\_color()**

**method\_workspace\_style()**

### class attributes

Bases: object

`method_cb()``method_legend()``method_title()``method_axis_labels()``method_spines()``method_ticks()`

Defaults

**class adjustments**Bases: `object``method_resize_axes()``method_subplots_adjust()`**class plot**Bases: `canvas`, `attributes`, `adjustments``init()``run()``main()``finish()``method_save()``method_show()`



```
class line (x=None, y=None, line_width=2, color='darkred', cmap='RdBu_r', alpha=None, norm=None,
            backend='Qt5Agg', font='serif', math_font='dejavuserif', font_color='black',
            font_size_increase=0, fig=None, ax=None, figsize=None, shape_and_position=111,
            resize_axes=True, scale=None, aspect=1, workspace_color=None, workspace_color2=None,
            background_color_figure='white', background_color_plot='white', background_alpha=1,
            style=None, light=None, dark=None, spine_color=None, spines_removed=(0, 0, 1, 1),
            bound_upper_x=None, bound_lower_x=None, bound_upper_y=None, bound_lower_y=None,
            bounds_x=None, bounds_y=None, pad_demo=False, pad_upper_x=0, pad_lower_x=0,
            pad_upper_y=0, pad_lower_y=0, grid=True, grid_color='lightgrey', grid_lines='-', title=None,
            title_size=12, title_pos_y=1.025, title_weight=None, title_font=None, title_color=None,
            label_x=None, label_size_x=12, label_pad_x=10, label_rotation_x=None,
            label_weight_x=None, label_y=None, label_size_y=12, label_pad_y=10,
            label_rotation_y=None, label_weight_y=None, tick_number_x=5, tick_number_y=5,
            label_coords_x=None, label_coords_y=None, tick_color=None, tick_label_pad=5,
            ticks_where=(1, 1, 0, 0), tick_label_size=10, tick_label_size_x=None, tick_label_size_y=None,
            tick_locations_x=None, tick_locations_y=None, tick_locations_fine=True, tick_labels_x=None,
            tick_labels_y=None, tick_labels_dates_x=False, date_format='%Y-%m-%d', tick_ndecimals=1,
            tick_label_decimals_x=None, tick_label_decimals_y=None, tick_rotation_x=None,
            tick_rotation_y=None, tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2,
            cb_axis_labelpad=10, shrink=0.75, extend='neither', cb_title=None, cb_orientation='vertical',
            cb_title_rotation=None, cb_title_style='normal', cb_title_size=10, cb_title_top_y=1,
            cb_ytitle_labelpad=10, cb_title_weight='normal', cb_title_top=True, cb_y_title=False,
            cb_title_top_pad=None, x_cb_title_top=0, cb_vmin=None, cb_vmax=None,
            cb_hard_bounds=False, cb_outline_width=None, cb_tick_number=5, cb_ticklabelsize=10,
            cb_tick_ndecimal=None, plot_label=None, legend=False, legend_loc='upper right',
            legend_bbox_to_anchor=None, legend_size=13, legend_weight='normal', legend_style='normal',
            legend_handleheight=None, legend_ncol=1, show=False, zorder=None, top=0.93,
            bottom=0.105, left=0.165, right=0.87, hspace=0.2, wspace=0.2, filename=None, dpi=None,
            suppress=True)
```

Bases: `plot`

`plot()`

`mock()`



```
class scatter (x=None, y=None, scatter_size=5, scatter_marker='o', scatter_facecolors=None, color='C0',
               cmap='RdBu_r', alpha=None, norm=None, backend='Qt5Agg', font='serif',
               math_font='dejavuserif', font_color='black', font_size_increase=0, fig=None, ax=None,
               figsize=None, shape_and_position=111, resize_axes=True, scale=None, aspect=1,
               workspace_color=None, workspace_color2=None, background_color_figure='white',
               background_color_plot='white', background_alpha=1, style=None, light=None,
               dark=None, spine_color=None, spines_removed=(0, 0, 1, 1), bound_upper_x=None,
               bound_lower_x=None, bound_upper_y=None, bound_lower_y=None, bounds_x=None,
               bounds_y=None, pad_demo=False, pad_upper_x=0, pad_lower_x=0, pad_upper_y=0,
               pad_lower_y=0, grid=True, grid_color='lightgrey', grid_lines='-', title=None, title_size=12,
               title_pos_y=1.025, title_weight=None, title_font=None, title_color=None, label_x=None,
               label_size_x=12, label_pad_x=10, label_rotation_x=None, label_weight_x=None,
               label_y=None, label_size_y=12, label_pad_y=10, label_rotation_y=None,
               label_weight_y=None, tick_number_x=5, tick_number_y=5, label_coords_x=None,
               label_coords_y=None, tick_color=None, tick_label_pad=5, ticks_where=(1, 1, 0, 0),
               tick_label_size=10, tick_label_size_x=None, tick_label_size_y=None,
               tick_locations_x=None, tick_locations_y=None, tick_locations_fine=True,
               tick_labels_x=None, tick_labels_y=None, tick_labels_dates_x=False,
               date_format='%Y-%m-%d', tick_ndecimals=1, tick_label_decimals_x=None,
               tick_label_decimals_y=None, tick_rotation_x=None, tick_rotation_y=None,
               tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2, cb_axis_labelpad=10,
               shrink=0.75, extend='neither', cb_title=None, cb_orientation='vertical',
               cb_title_rotation=None, cb_title_style='normal', cb_title_size=10, cb_title_top_y=1,
               cb_ytitle_labelpad=10, cb_title_weight='normal', cb_title_top=True, cb_y_title=False,
               cb_title_top_pad=None, x_cb_title_top=0, cb_vmin=None, cb_vmax=None,
               cb_hard_bounds=False, cb_outline_width=None, cb_tick_number=5, cb_ticklabelsize=10,
               cb_tick_ndecimals=None, plot_label=None, legend=False, legend_loc='upper right',
               legend_bbox_to_anchor=None, legend_size=13, legend_weight='normal',
               legend_style='normal', legend_handleheight=None, legend_ncol=1, show=False,
               zorder=None, top=0.93, bottom=0.105, left=0.165, right=0.87, hspace=0.2, wspace=0.2,
               filename=None, dpi=None, suppress=True)
```

Bases: `plot`

`plot()`

`mock()`





```
class heatmap (x=None, y=None, z=None, heatmap_normvariant='SymLog', color=None, cmap='RdBu_r',
               alpha=None, norm=None, backend='Qt5Agg', font='serif', math_font='dejavuserif',
               font_color='black', font_size_increase=0, fig=None, ax=None, figsize=None,
               shape_and_position=111, resize_axes=True, scale=None, aspect=1,
               workspace_color=None, workspace_color2=None, background_color_figure='white',
               background_color_plot='white', background_alpha=1, style=None, light=None,
               dark=None, spine_color=None, spines_removed=(0, 0, 1, 1), bound_upper_x=None,
               bound_lower_x=None, bound_upper_y=None, bound_lower_y=None, bounds_x=None,
               bounds_y=None, pad_demo=False, pad_upper_x=0, pad_lower_x=0, pad_upper_y=0,
               pad_lower_y=0, grid=True, grid_color='lightgrey', grid_lines='-', title=None, title_size=12,
               title_pos_y=1.025, title_weight=None, title_font=None, title_color=None, label_x=None,
               label_size_x=12, label_pad_x=10, label_rotation_x=None, label_weight_x=None,
               label_y=None, label_size_y=12, label_pad_y=10, label_rotation_y=None,
               label_weight_y=None, tick_number_x=5, tick_number_y=5, label_coords_x=None,
               label_coords_y=None, tick_color=None, tick_label_pad=5, ticks_where=(1, 1, 0, 0),
               tick_label_size=10, tick_label_size_x=None, tick_label_size_y=None,
               tick_locations_x=None, tick_locations_y=None, tick_locations_fine=True,
               tick_labels_x=None, tick_labels_y=None, tick_labels_dates_x=False,
               date_format='%Y-%m-%d', tick_ndecimals=1, tick_label_decimals_x=None,
               tick_label_decimals_y=None, tick_rotation_x=None, tick_rotation_y=None,
               tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2, cb_axis_labelpad=10,
               shrink=0.75, extend='neither', cb_title=None, cb_orientation='vertical',
               cb_title_rotation=None, cb_title_style='normal', cb_title_size=10, cb_title_top_y=1,
               cb_ytitle_labelpad=10, cb_title_weight='normal', cb_title_top=True, cb_y_title=False,
               cb_title_top_pad=None, x_cb_title_top=0, cb_vmin=None, cb_vmax=None,
               cb_hard_bounds=False, cb_outline_width=None, cb_tick_number=5, cb_ticklabelsize=10,
               cb_tick_ndecimals=None, plot_label=None, legend=False, legend_loc='upper right',
               legend_bbox_to_anchor=None, legend_size=13, legend_weight='normal',
               legend_style='normal', legend_handleheight=None, legend_ncol=1, show=False,
               zorder=None, top=0.93, bottom=0.105, left=0.165, right=0.87, hspace=0.2, wspace=0.2,
               filename=None, dpi=None, suppress=True)
```

Bases: `plot`

`plot()`

`mock()`



```
class quiver (x=None, y=None, u=None, v=None, quiver_rule=None, quiver_custom_rule=None,
               quiver_vector_width=0.01, quiver_vector_min_shaft=2, quiver_vector_length_threshold=0.1,
               color=None, cmap='RdBu_r', alpha=None, norm=None, backend='Qt5Agg', font='serif',
               math_font='dejavuserif', font_color='black', font_size_increase=0, fig=None, ax=None,
               figsize=None, shape_and_position=111, resize_axes=True, scale=None, aspect=1,
               workspace_color=None, workspace_color2=None, background_color_figure='white',
               background_color_plot='white', background_alpha=1, style=None, light=None, dark=None,
               spine_color=None, spines_removed=(0, 0, 1, 1), bound_upper_x=None,
               bound_lower_x=None, bound_upper_y=None, bound_lower_y=None, bounds_x=None,
               bounds_y=None, pad_demo=False, pad_upper_x=0, pad_lower_x=0, pad_upper_y=0,
               pad_lower_y=0, grid=True, grid_color='lightgrey', grid_lines='-.', title=None, title_size=12,
               title_pos_y=1.025, title_weight=None, title_font=None, title_color=None, label_x=None,
               label_size_x=12, label_pad_x=10, label_rotation_x=None, label_weight_x=None,
               label_y=None, label_size_y=12, label_pad_y=10, label_rotation_y=None,
               label_weight_y=None, tick_number_x=5, tick_number_y=5, label_coords_x=None,
               label_coords_y=None, tick_color=None, tick_label_pad=5, ticks_where=(1, 1, 0, 0),
               tick_label_size=10, tick_label_size_x=None, tick_label_size_y=None, tick_locations_x=None,
               tick_locations_y=None, tick_locations_fine=True, tick_labels_x=None, tick_labels_y=None,
               tick_labels_dates_x=False, date_format='%Y-%m-%d', tick_ndecimals=1,
               tick_label_decimals_x=None, tick_label_decimals_y=None, tick_rotation_x=None,
               tick_rotation_y=None, tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2,
               cb_axis_labelpad=10, shrink=0.75, extend='neither', cb_title=None,
               cb_orientation='vertical', cb_title_rotation=None, cb_title_style='normal', cb_title_size=10,
               cb_title_top_y=1, cb_ytitle_labelpad=10, cb_title_weight='normal', cb_title_top=True,
               cb_y_title=False, cb_title_top_pad=None, x_cb_title_top=0, cb_vmin=None,
               cb_vmax=None, cb_hard_bounds=False, cb_outline_width=None, cb_tick_number=5,
               cb_ticklabelsize=10, cb_tick_ndecimals=None, plot_label=None, legend=False,
               legend_loc='upper right', legend_bbox_to_anchor=None, legend_size=13,
               legend_weight='normal', legend_style='normal', legend_handleheight=None, legend_ncol=1,
               show=False, zorder=None, top=0.93, bottom=0.105, left=0.165, right=0.87, hspace=0.2,
               wspace=0.2, filename=None, dpi=None, suppress=True)
```

Bases: `plot`

`plot()`

`mock()`

`method_rule()`



```

class streamline (x=None, y=None, u=None, v=None, streamline_line_width=1,
                  streamline_line_density=2, color=None, cmap='RdBu_r', alpha=None, norm=None,
                  backend='Qt5Agg', font='serif', math_font='dejavuserif', font_color='black',
                  font_size_increase=0, fig=None, ax=None, figsize=None, shape_and_position=111,
                  resize_axes=True, scale=None, aspect=1, workspace_color=None,
                  workspace_color2=None, background_color_figure='white',
                  background_color_plot='white', background_alpha=1, style=None, light=None,
                  dark=None, spine_color=None, spines_removed=(0, 0, 1, 1), bound_upper_x=None,
                  bound_lower_x=None, bound_upper_y=None, bound_lower_y=None,
                  bounds_x=None, bounds_y=None, pad_demo=False, pad_upper_x=0,
                  pad_lower_x=0, pad_upper_y=0, pad_lower_y=0, grid=True, grid_color='lightgrey',
                  grid_lines='-.', title=None, title_size=12, title_pos_y=1.025, title_weight=None,
                  title_font=None, title_color=None, label_x=None, label_size_x=12, label_pad_x=10,
                  label_rotation_x=None, label_weight_x=None, label_y=None, label_size_y=12,
                  label_pad_y=10, label_rotation_y=None, label_weight_y=None, tick_number_x=5,
                  tick_number_y=5, label_coords_x=None, label_coords_y=None, tick_color=None,
                  tick_label_pad=5, ticks_where=(1, 1, 0, 0), tick_label_size=10,
                  tick_label_size_x=None, tick_label_size_y=None, tick_locations_x=None,
                  tick_locations_y=None, tick_locations_fine=True, tick_labels_x=None,
                  tick_labels_y=None, tick_labels_dates_x=False, date_format='%Y-%m-%d',
                  tick_ndecimals=1, tick_label_decimals_x=None, tick_label_decimals_y=None,
                  tick_rotation_x=None, tick_rotation_y=None, tick_labels_where=(1, 1, 0, 0),
                  color_bar=False, cb_pad=0.2, cb_axis_labelpad=10, shrink=0.75, extend='neither',
                  cb_title=None, cb_orientation='vertical', cb_title_rotation=None,
                  cb_title_style='normal', cb_title_size=10, cb_title_top_y=1, cb_ytitle_labelpad=10,
                  cb_title_weight='normal', cb_title_top=True, cb_y_title=False, cb_title_top_pad=None,
                  x_cb_title_top=0, cb_vmin=None, cb_vmax=None, cb_hard_bounds=False,
                  cb_outline_width=None, cb_tick_number=5, cb_ticklabelsize=10,
                  cb_tick_ndecimals=None, plot_label=None, legend=False, legend_loc='upper right',
                  legend_bbox_to_anchor=None, legend_size=13, legend_weight='normal',
                  legend_style='normal', legend_handleheight=None, legend_ncol=1, show=False,
                  zorder=None, top=0.93, bottom=0.105, left=0.165, right=0.87, hspace=0.2,
                  wspace=0.2, filename=None, dpi=None, suppress=True)

```

Bases: `plot`

`plot()`

`mock()`

`method_rule()`



```

class fill_area (x=None, y=None, z=None, fill_area_between=False, fill_area_below=False,
    fill_area_above=False, color=None, cmap='RdBu_r', alpha=None, norm=None,
    backend='Qt5Agg', font='serif', math_font='dejavuserif', font_color='black',
    font_size_increase=0, fig=None, ax=None, figsize=None, shape_and_position=111,
    resize_axes=True, scale=None, aspect=1, workspace_color=None,
    workspace_color2=None, background_color_figure='white',
    background_color_plot='white', background_alpha=1, style=None, light=None,
    dark=None, spine_color=None, spines_removed=(0, 0, 1, 1), bound_upper_x=None,
    bound_lower_x=None, bound_upper_y=None, bound_lower_y=None, bounds_x=None,
    bounds_y=None, pad_demo=False, pad_upper_x=0, pad_lower_x=0, pad_upper_y=0,
    pad_lower_y=0, grid=True, grid_color='lightgrey', grid_lines='-', title=None,
    title_size=12, title_pos_y=1.025, title_weight=None, title_font=None, title_color=None,
    label_x=None, label_size_x=12, label_pad_x=10, label_rotation_x=None,
    label_weight_x=None, label_y=None, label_size_y=12, label_pad_y=10,
    label_rotation_y=None, label_weight_y=None, tick_number_x=5, tick_number_y=5,
    label_coords_x=None, label_coords_y=None, tick_color=None, tick_label_pad=5,
    ticks_where=(1, 1, 0, 0), tick_label_size=10, tick_label_size_x=None,
    tick_label_size_y=None, tick_locations_x=None, tick_locations_y=None,
    tick_locations_fine=True, tick_labels_x=None, tick_labels_y=None,
    tick_labels_dates_x=False, date_format='%Y-%m-%d', tick_ndecimal=1,
    tick_label_decimals_x=None, tick_label_decimals_y=None, tick_rotation_x=None,
    tick_rotation_y=None, tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2,
    cb_axis_labelpad=10, shrink=0.75, extend='neither', cb_title=None,
    cb_orientation='vertical', cb_title_rotation=None, cb_title_style='normal',
    cb_title_size=10, cb_title_top_y=1, cb_ytitle_labelpad=10, cb_title_weight='normal',
    cb_title_top=True, cb_y_title=False, cb_title_top_pad=None, x_cb_title_top=0,
    cb_vmin=None, cb_vmax=None, cb_hard_bounds=False, cb_outline_width=None,
    cb_tick_number=5, cb_ticklabelsize=10, cb_tick_ndecimal=None, plot_label=None,
    legend=False, legend_loc='upper right', legend_bbox_to_anchor=None, legend_size=13,
    legend_weight='normal', legend_style='normal', legend_handleheight=None,
    legend_ncol=1, show=False, zorder=None, top=0.93, bottom=0.105, left=0.165,
    right=0.87, hspace=0.2, wspace=0.2, filename=None, dpi=None, suppress=True)

```

Bases: `plot`

`plot()`

Fill the region below the intersection of S and Z

`i_below()`

`i_above()`

`intersection()`

`mock()`

```
floating_text (ax, text, font='serif', x=0.5, y=0.5, size=20, weight='normal', color='darkred')
```



## 1.3 Placeholders

**class MockData**

Bases: `object`

**filled\_julia** (*xyz\_2d=False, xyz\_3d=False, df=False*)

**spirograph** ()

**sinewave** ()

**waterdrop** ()

**boltzman** (*x, xmid, tau*)

Evaluate the boltzman function with midpoint *xmid* and time constant *tau* over *x*

## 1.4 Pane plot method

**panes** (*x, y, f=None, fig=None, figsize=None, show=False, rows=1, top=None, bottom=None, left=None, right=None, wspace=None, hspace=None, \*\*kwargs*)

# Inputs The panes function supports numerical inputs in the following forms: | *x* | *y* | result | notes | | — | — | — | — | | array | array | 11 | | array | [array, array] | 12 | Both *y*'s share *x* | | [n\*[array]] | [n\*[array]] | 1n | Each *y* has an *x* | | array | [array, array] | 21 | Both *y*'s share *x* | | [array, array] | [array, array] | 21 | Each *y* has an *x* | | array | [n\*[array], n\*[array]] | 2n | All curves in all (2) panes share a single *x* | | [array, array] | [n\*[array], n\*[array]] | 2n | All curves in each pane share an *x* | | [n\*[array], n\*[array]] | [n\*[array], n\*[array]] | 2n | All curves in all (2) panes have their own *x* | | [n\*[array], ... up to m] | [n\*[array], ... up to m] | mn | All curves in all panes have their own *x* |

where

- *array*: List or NumPy array with numerical values
- [...]: List containing ...
- *result*: <panes><curves per pane>

# Arguments Arguments are internally classified as FIGURE arguments, PLURAL arguments and CURVE arguments, namely:

- **Figure arguments**

Select few arguments which may be input only once in the plotting process, so as to avoid conflicts. Ieg: passing *grid=True* twice (*plt.grid(...)*) will result in no grid being drawn. These are removed from the keyword arguments and used in the last *comparison* call.

- **Special arguments**

Select few arguments (ieg: *plot\_labels*), which satisfy the condition of being lists with a length different to that of *y*



and which, for aesthetic purposes, must be applied only once.

In the case of *plot\_labels*, if *plot\_labels* is a list of length different to that of *y*, it is assumed that

- The *n*th curve of each pane shares a label with the *n*th curve of all other panes

and so a legend displaying the labels of the last pane will be displayed.

- **Plural arguments**

**Arguments with a keyword equal to any of the arguments which can be passed to the *line***

2D plotter, in plural tense. The line plotter is chosen as it shares all general arguments with the other 2D plotter functions. The plural arguments are assumed to be

*lists of length equal to the number of panes*

and thus modify each pane. Ieg: *x\_tick\_labels*=[1, 2, 3] will set the tick labels of the *x* axes to 1, 2 and 3 respectively in a 3-pane plot.

- **Curve arguments**

**Curve arguments are passed as plurals to the comparison function, as they are *lists with a length different to that of y***

(thus they can't apply to each pane) and they are assumed to have a length equal to the number of curves in each plot.

## 2.1 Plotting Methods

### **class canvas**

Bases: object

**method\_backend()**

**method\_fonts()**

Fonts Reference:

- <https://matplotlib.org/2.0.2/users/customizing.html>

**Pyplot method:**

`plt.rcParams['<category>.<item>'] = <>`

**method\_figure()**

**method\_setup()**

**method\_grid()**

**method\_pane\_fill()**

**method\_background\_color()**

**method\_workspace\_style()**

### **class attributes**

Bases: object

**method\_legend()**

**method\_title()**

**method\_axis\_labels()**

**method\_spines()**



```
    method_ticks()

class adjustments
    Bases: object

    method_resize_axes()

    method_subplots_adjust()

    method_remove_axes()

    method_scale()

class plot
    Bases: canvas, attributes, adjustments

    init()

    run()

    main()

    finish()

    method_save()

    method_show()

class color
    Bases: object

    method_cb()

class surf
    Bases: color

    custom()

    method_lighting()

    method_edges_to_rgba()
```





```
class line (x=None, y=None, z=None, line_width=5, line_alpha=1, color='darkred', cmap='RdBu_r',
            scale_x=None, scale_y=None, scale_z=None, backend='Qt5Agg', font='serif',
            math_font='dejavuserif', font_color='black', font_size_increase=0, fig=None, ax=None,
            figsize=(5, 4), shape_and_position=111, azimuth=-138, elev=19, remove_axis=None,
            prune=None, resize_axes=True, aspect_equal=False, box_to_plot_pad=10, spines_juggled=(1,
            0, 2), spine_color=None, blend_edges=False, workspace_color=None, workspace_color2=None,
            background_color_figure='white', background_color_plot='white', background_alpha=1,
            style=None, light=None, dark=None, pane_fill=None, bound_upper_x=None,
            bound_lower_x=None, bound_upper_y=None, bound_lower_y=None, bound_upper_z=None,
            bound_lower_z=None, bounds_x=None, bounds_y=None, bounds_z=None, pad_demo=False,
            pad_upper_x=0, pad_lower_x=0, pad_upper_y=0, pad_lower_y=0, pad_upper_z=0,
            pad_lower_z=0, show_axes=True, grid=True, grid_color='lightgrey', grid_lines='-.', title=None,
            title_weight='normal', title_size=12, title_y=1.025, title_color=None, title_font=None,
            label_x='x', label_weight_x='normal', label_size_x=12, label_pad_x=7, label_rotation_x=None,
            label_y='y', label_weight_y='normal', label_size_y=12, label_pad_y=7,
            label_rotation_y=None, label_z='z', label_weight_z='normal', label_size_z=12, label_pad_z=7,
            label_rotation_z=None, tick_color=None, tick_number_x=5, tick_labels_x=None,
            tick_locations_x=None, tick_rotation_x=None, tick_number_y=5, tick_labels_y=None,
            tick_locations_y=None, tick_rotation_y=None, tick_number_z=5, tick_labels_z=None,
            tick_locations_z=None, tick_rotation_z=None, tick_label_size=10, tick_label_pad_x=4,
            tick_label_decimals_x=1, tick_label_size_x=None, tick_label_pad_y=4,
            tick_label_decimals_y=1, tick_label_size_y=None, tick_label_pad_z=4,
            tick_label_decimals_z=1, tick_label_size_z=None, plot_label=None, legend=False,
            legend_loc='upper right', legend_size=13, legend_weight='normal', legend_style='normal',
            legend_handleheight=None, legend_columns=1, show=False, top=0.975, bottom=0.085,
            left=0.14, right=0.945, hspace=0.2, wspace=0.2, filename=None, dpi=None, suppress=True)
```

Bases: `plot`

`plot()`

`mock()`



```

class scatter (x=None, y=None, z=None, scatter_size=30, scatter_marker='o', scatter_facecolors=None,
               color_rule=None, scatter_alpha=1, color='darkred', cmap='RdBu_r', color_bar=False,
               cb_orientation='vertical', shrink=0.75, extend='neither', cb_vmin=None, cb_vmax=None,
               cb_bounds_hard=False, cb_pad=0.1, cb_outline_width=None, cb_tick_number=5,
               cb_tick_label_decimals=5, ctick_label_size_b=10, ctick_label_pad_b=10, cb_title=None,
               cb_title_top=True, cb_title_y=False, cb_title_top_pos_x=0, cb_title_top_pos_y=1,
               cb_title_pad=10, cb_title_weight='normal', cb_title_rotation=None, cb_title_style='normal',
               cb_title_size=10, scale_x=None, scale_y=None, scale_z=None, backend='Qt5Agg',
               font='serif', math_font='dejavuserif', font_color='black', font_size_increase=0, fig=None,
               ax=None, figsize=(5, 4), shape_and_position=111, azim=-138, elev=19,
               remove_axis=None, prune=None, resize_axes=True, aspect_equal=False,
               box_to_plot_pad=10, spines_juggled=(1, 0, 2), spine_color=None, blend_edges=False,
               workspace_color=None, workspace_color2=None, background_color_figure='white',
               background_color_plot='white', background_alpha=1, style=None, light=None,
               dark=None, pane_fill=None, bound_upper_x=None, bound_lower_x=None,
               bound_upper_y=None, bound_lower_y=None, bound_upper_z=None,
               bound_lower_z=None, bounds_x=None, bounds_y=None, bounds_z=None,
               pad_demo=False, pad_upper_x=0, pad_lower_x=0, pad_upper_y=0, pad_lower_y=0,
               pad_upper_z=0, pad_lower_z=0, show_axes=True, grid=True, grid_color='lightgrey',
               grid_lines='-', title=None, title_weight='normal', title_size=12, title_y=1.025,
               title_color=None, title_font=None, label_x='x', label_weight_x='normal', label_size_x=12,
               label_pad_x=7, label_rotation_x=None, label_y='y', label_weight_y='normal',
               label_size_y=12, label_pad_y=7, label_rotation_y=None, label_z='z',
               label_weight_z='normal', label_size_z=12, label_pad_z=7, label_rotation_z=None,
               tick_color=None, tick_number_x=5, tick_labels_x=None, tick_locations_x=None,
               tick_rotation_x=None, tick_number_y=5, tick_labels_y=None, tick_locations_y=None,
               tick_rotation_y=None, tick_number_z=5, tick_labels_z=None, tick_locations_z=None,
               tick_rotation_z=None, tick_label_size=10, tick_label_pad_x=4, tick_label_decimals_x=1,
               tick_label_size_x=None, tick_label_pad_y=4, tick_label_decimals_y=1,
               tick_label_size_y=None, tick_label_pad_z=4, tick_label_decimals_z=1,
               tick_label_size_z=None, plot_label=None, legend=False, legend_loc='upper right',
               legend_size=13, legend_weight='normal', legend_style='normal',
               legend_handleheight=None, legend_columns=1, show=False, top=0.975, bottom=0.085,
               left=0.14, right=0.945, hspace=0.2, wspace=0.2, filename=None, dpi=None,
               suppress=True)

```

Bases: `plot`, `color`

`plot()`

`mock()`



```
class surface (x=None, y=None, z=None, surface_rstride=1, surface_cstride=1, surface_wire_width=0.1,
    surface_lighting=False, surface_antialiased=False, surface_shade=False, surface_alpha=1,
    surface_cmap_lighting=None, surface_norm=None, surface_edge_color='black',
    surface_edges_to_rgba=False, cmap='RdBu_r', color=None, color_rule=None,
    color_bar=False, cb_orientation='vertical', shrink=0.75, extend='neither', cb_vmin=None,
    cb_vmax=None, cb_bounds_hard=False, cb_pad=0.1, cb_outline_width=None,
    cb_tick_number=5, cb_tick_label_decimals=5, ctick_label_size_b=10,
    ctick_label_pad_b=10, cb_title=None, cb_title_top=True, cb_title_y=False,
    cb_title_top_pos_x=0, cb_title_top_pos_y=1, cb_title_pad=10, cb_title_weight='normal',
    cb_title_rotation=None, cb_title_style='normal', cb_title_size=10, scale_x=None,
    scale_y=None, scale_z=None, backend='Qt5Agg', font='serif', math_font='dejavuserif',
    font_color='black', font_size_increase=0, fig=None, ax=None, figsize=(5, 4),
    shape_and_position=111, azim=-138, elev=19, remove_axis=None, prune=None,
    resize_axes=True, aspect_equal=False, box_to_plot_pad=10, spines_juggled=(1, 0, 2),
    spine_color=None, blend_edges=False, workspace_color=None, workspace_color2=None,
    background_color_figure='white', background_color_plot='white', background_alpha=1,
    style=None, light=None, dark=None, pane_fill=None, bound_upper_x=None,
    bound_lower_x=None, bound_upper_y=None, bound_lower_y=None,
    bound_upper_z=None, bound_lower_z=None, bounds_x=None, bounds_y=None,
    bounds_z=None, pad_demo=False, pad_upper_x=0, pad_lower_x=0, pad_upper_y=0,
    pad_lower_y=0, pad_upper_z=0, pad_lower_z=0, show_axes=True, grid=True,
    grid_color='lightgrey', grid_lines='-.', title=None, title_weight='normal', title_size=12,
    title_y=1.025, title_color=None, title_font=None, label_x='x', label_weight_x='normal',
    label_size_x=12, label_pad_x=7, label_rotation_x=None, label_y='y',
    label_weight_y='normal', label_size_y=12, label_pad_y=7, label_rotation_y=None,
    label_z='z', label_weight_z='normal', label_size_z=12, label_pad_z=7,
    label_rotation_z=None, tick_color=None, tick_number_x=5, tick_labels_x=None,
    tick_locations_x=None, tick_rotation_x=None, tick_number_y=5, tick_labels_y=None,
    tick_locations_y=None, tick_rotation_y=None, tick_number_z=5, tick_labels_z=None,
    tick_locations_z=None, tick_rotation_z=None, tick_label_size=10, tick_label_pad_x=4,
    tick_label_decimals_x=1, tick_label_size_x=None, tick_label_pad_y=4,
    tick_label_decimals_y=1, tick_label_size_y=None, tick_label_pad_z=4,
    tick_label_decimals_z=1, tick_label_size_z=None, plot_label=None, legend=False,
    legend_loc='upper right', legend_size=13, legend_weight='normal', legend_style='normal',
    legend_handleheight=None, legend_columns=1, show=False, top=0.975, bottom=0.085,
    left=0.14, right=0.945, hspace=0.2, wspace=0.2, filename=None, dpi=None,
    suppress=True)
```

Bases: `plot`, `surf`

`plot()`

`mock()`

`floating_text` (`ax`, `text`, `font`, `x`, `y`, `z`, `size=20`, `weight='normal'`, `color='darkred'`)



## 2.2 Placeholders

```
class MockData
    Bases: object
    waterdrop3d()
    random3d()
    hill()
```

## 3.1 Methods

**complementary** (*color*, *fmt*='hex')

Return complementary of [R, G, B] or hex color.

**Parameters**

**fmt** (*string*) – Output format: ‘hex’ or ‘rgb’.

**delta** (*color*, *factor*, *fmt*='hex')

Darker or lighten the input color by a percentage of <factor> ([-1, 1]) of the color spectrum (0-255).

**Parameters**

- **fmt** (*string*) – Output format: ‘hex’ or ‘rgb’.
- **factor** (*float*) – [-1, 1] Measure in which the color will be modified.

## 3.2 Color Maps

**custom** (*red*, *green*, *blue*, *name*='coolheat', *n*=1024)

**Parameters**

- **red** – List of (red fraction, y0, y1) tuples
- **green** – List of (red fraction, y0, y1)
- **blue** – List of (red fraction, y0, y1)
- **name** – Colormap name
- **n** – RGB quantization levels

**Returns**

Colormap



**mapstack** (*maps*, *fractions=None*, *ranges=None*)

Create a colormap stacking an arbitrary number of conventional Matplotlib colormaps.

#### Parameters

- **maps** (*list of str*) – List of colormap NAMES
- **fractions** (*list of float*) – For each original colormap, the fraction it'll take of the merged colormap. [ $0 < \text{fr}_0 < 1$ , ...]
- **ranges** (*list of tuple*) – For each original colormap, the range taken. [ $(0 \leq \text{min} < 1, 0 \leq \text{max} \leq 1)_0$ , ...]

#### Returns

`mpl.colors.LinearSegmentedColormap`

## 3.3 Color Schemes

**colorscheme\_one**()

## 4.1 Precision

## 4.2 Preset

**class** `preset` (*plotter=None, dim=None, \_dict=None*)

Bases: `object`

Preset object class

**save** (*file*)

Save MPL Plotter preset in TOML format

**classmethod** `load` (*file*)

Load MPL Plotter preset from TOML file

**class** `two_d` (*preset*)

Bases: `object`

2D preset plotting methods

**class** `line` (*x=None, y=None, \*\*kwargs*)

Bases: `line`

**class** `scatter` (*x=None, y=None, \*\*kwargs*)

Bases: `scatter`

**class** `heatmap` (*x=None, y=None, z=None, \*\*kwargs*)

Bases: `heatmap`

**class** `quiver` (*x=None, y=None, u=None, v=None, \*\*kwargs*)

Bases: `quiver`

**class** `streamline` (*x=None, y=None, u=None, v=None, \*\*kwargs*)

Bases: `streamline`

**class** `fill_area` (*x=None, y=None, z=None, \*\*kwargs*)

Bases: `fill_area`



```
class three_d(preset)  
    Bases: object  
    3D preset plotting methods  
  
    class line(x=None, y=None, z=None, **kwargs)  
        Bases: line  
  
    class scatter(x=None, y=None, z=None, **kwargs)  
        Bases: scatter  
  
    class surface(x=None, y=None, z=None, **kwargs)  
        Bases: surface
```

## 4.3 Publication



## PYTHON MODULE INDEX

### C

- `mpl_plotter.color`, [18](#)
- `mpl_plotter.color.functions`, [19](#)
- `mpl_plotter.color.maps`, [19](#)
- `mpl_plotter.color.schemes`, [20](#)

### p

- `mpl_plotter.presets`, [20](#)
- `mpl_plotter.presets.precision`, [21](#)
- `mpl_plotter.presets.preset`, [21](#)
- `mpl_plotter.presets.publication`, [22](#)

### t

- `mpl_plotter.three_d`, [12](#)
- `mpl_plotter.three_d.methods`, [13](#)
- `mpl_plotter.three_d.mock`, [17](#)
- `mpl_plotter.two_d`, [1](#)
- `mpl_plotter.two_d.comparison`, [2](#)
- `mpl_plotter.two_d.methods`, [3](#)
- `mpl_plotter.two_d.mock`, [10](#)
- `mpl_plotter.two_d.panes`, [11](#)

### A

adjustments (class in `mpl_plotter.three_d.methods`), 14  
 adjustments (class in `mpl_plotter.two_d.methods`), 4  
 attributes (class in `mpl_plotter.three_d.methods`), 13  
 attributes (class in `mpl_plotter.two_d.methods`), 3

### B

boltzman() (*MockData method*), 11

### C

canvas (class in `mpl_plotter.three_d.methods`), 13  
 canvas (class in `mpl_plotter.two_d.methods`), 3  
 color (class in `mpl_plotter.three_d.methods`), 14  
 colorscheme\_one() (in module `mpl_plotter.color.schemes`), 20  
 comparison() (in module `mpl_plotter.two_d.comparison`), 2  
 complementary() (in module `mpl_plotter.color.functions`), 19  
 custom() (in module `mpl_plotter.color.maps`), 19  
 custom() (*surf method*), 14

### D

delta() (in module `mpl_plotter.color.functions`), 19

### F

fill\_area (class in `mpl_plotter.two_d.methods`), 9  
 filled\_julia() (*MockData method*), 11  
 finish() (*plot method*), 4, 14  
 floating\_text() (in module `mpl_plotter.three_d.methods`), 17  
 floating\_text() (in module `mpl_plotter.two_d.methods`), 10

### H

heatmap (class in `mpl_plotter.two_d.methods`), 6  
 hill() (*MockData method*), 18

### I

i\_above() (*fill\_area method*), 10  
 i\_below() (*fill\_area method*), 10  
 init() (*plot method*), 4, 14  
 intersection() (*fill\_area method*), 10

### L

line (class in `mpl_plotter.three_d.methods`), 14  
 line (class in `mpl_plotter.two_d.methods`), 4  
 load() (*preset class method*), 21

### M

main() (*plot method*), 4, 14  
 mapstack() (in module `mpl_plotter.color.maps`), 19  
 method\_axis\_labels() (*attributes method*), 4, 13  
 method\_backend() (*canvas method*), 3, 13  
 method\_background\_color() (*canvas method*), 3, 13  
 method\_cb() (*attributes method*), 3  
 method\_cb() (*color method*), 14  
 method\_edges\_to\_rgba() (*surf method*), 14  
 method\_figure() (*canvas method*), 3, 13  
 method\_fonts() (*canvas method*), 3, 13  
 method\_grid() (*canvas method*), 3, 13  
 method\_legend() (*attributes method*), 4, 13  
 method\_lighting() (*surf method*), 14  
 method\_pane\_fill() (*canvas method*), 13  
 method\_remove\_axes() (*adjustments method*), 14  
 method\_resize\_axes() (*adjustments method*), 4, 14  
 method\_rule() (*quiver method*), 8



`method_rule()` (*streamline method*), 9  
`method_save()` (*plot method*), 4, 14  
`method_scale()` (*adjustments method*), 14  
`method_setup()` (*canvas method*), 3, 13  
`method_show()` (*plot method*), 4, 14  
`method_spines()` (*attributes method*), 4, 13  
`method_subplots_adjust()` (*adjustments method*), 4, 14  
`method_ticks()` (*attributes method*), 4, 13  
`method_title()` (*attributes method*), 4, 13  
`method_workspace_style()` (*canvas method*), 3, 13  
`mock()` (*fill\_area method*), 10  
`mock()` (*heatmap method*), 7  
`mock()` (*line method*), 5, 15  
`mock()` (*quiver method*), 8  
`mock()` (*scatter method*), 6, 16  
`mock()` (*streamline method*), 9  
`mock()` (*surface method*), 17  
`MockData` (*class in mpl\_plotter.three\_d.mock*), 18  
`MockData` (*class in mpl\_plotter.two\_d.mock*), 11  
module  
  `mpl_plotter.color`, 18  
  `mpl_plotter.color.functions`, 19  
  `mpl_plotter.color.maps`, 19  
  `mpl_plotter.color.schemes`, 20  
  `mpl_plotter.presets`, 20  
  `mpl_plotter.presets.precision`, 21  
  `mpl_plotter.presets.preset`, 21  
  `mpl_plotter.presets.publication`, 22  
  `mpl_plotter.three_d`, 12  
  `mpl_plotter.three_d.methods`, 13  
  `mpl_plotter.three_d.mock`, 17  
  `mpl_plotter.two_d`, 1  
  `mpl_plotter.two_d.comparison`, 2  
  `mpl_plotter.two_d.methods`, 3  
  `mpl_plotter.two_d.mock`, 10  
  `mpl_plotter.two_d.panes`, 11  
`mpl_plotter.color`  
  module, 18  
`mpl_plotter.color.functions`  
  module, 19  
`mpl_plotter.color.maps`  
  module, 19  
`mpl_plotter.color.schemes`  
  module, 20  
`mpl_plotter.presets`  
  module, 20  
`mpl_plotter.presets.precision`  
  module, 21  
`mpl_plotter.presets.preset`  
  module, 21  
`mpl_plotter.presets.publication`  
  module, 22  
`mpl_plotter.three_d`  
  module, 12  
`mpl_plotter.three_d.methods`  
  module, 13  
`mpl_plotter.three_d.mock`  
  module, 17  
`mpl_plotter.two_d`  
  module, 1  
`mpl_plotter.two_d.comparison`  
  module, 2  
`mpl_plotter.two_d.methods`  
  module, 3  
`mpl_plotter.two_d.mock`  
  module, 10  
`mpl_plotter.two_d.panes`  
  module, 11  

## P

`panes()` (*in module mpl\_plotter.two\_d.panes*), 11  
`plot` (*class in mpl\_plotter.three\_d.methods*), 14  
`plot` (*class in mpl\_plotter.two\_d.methods*), 4  
`plot()` (*fill\_area method*), 10  
`plot()` (*heatmap method*), 7  
`plot()` (*line method*), 5, 15  
`plot()` (*quiver method*), 8  
`plot()` (*scatter method*), 6, 16  
`plot()` (*streamline method*), 9  
`plot()` (*surface method*), 17  
`preset` (*class in mpl\_plotter.presets.preset*), 21  

## Q

`quiver` (*class in mpl\_plotter.two\_d.methods*), 7  

## R

`random3d()` (*MockData method*), 18  
`run()` (*plot method*), 4, 14  

## S

`save()` (*preset method*), 21  
`scatter` (*class in mpl\_plotter.three\_d.methods*), 15



`scatter` (*class in `mpl_plotter.two_d.methods`*), 5  
`sinewave()` (*MockData method*), 11  
`spirograph()` (*MockData method*), 11  
`streamline` (*class in `mpl_plotter.two_d.methods`*), 8  
`surf` (*class in `mpl_plotter.three_d.methods`*), 14  
`surface` (*class in `mpl_plotter.three_d.methods`*), 16

## T

`three_d` (*class in `mpl_plotter.presets.preset`*), 21  
`three_d.line` (*class in `mpl_plotter.presets.preset`*),  
22  
`three_d.scatter` (*class in `mpl_plotter.presets.preset`*), 22  
`three_d.surface` (*class in `mpl_plotter.presets.preset`*), 22  
`two_d` (*class in `mpl_plotter.presets.preset`*), 21  
`two_d.fill_area` (*class in `mpl_plotter.presets.preset`*), 21  
`two_d.heatmap` (*class in `mpl_plotter.presets.preset`*),  
21  
`two_d.line` (*class in `mpl_plotter.presets.preset`*), 21  
`two_d.quiver` (*class in `mpl_plotter.presets.preset`*),  
21  
`two_d.scatter` (*class in `mpl_plotter.presets.preset`*),  
21  
`two_d.streamline` (*class in `mpl_plotter.presets.preset`*), 21

## W

`waterdrop()` (*MockData method*), 11  
`waterdrop3d()` (*MockData method*), 18