

MPL Plotter Documentation

Antonio López Rivera

July 2022





TABLE OF CONTENTS

1	2D	2
1.1	Plotting Methods	2
1.2	Composition: <code>comparison</code>	9
1.3	Composition: <code>panes</code>	10
1.4	Placeholders	12
2	3D	13
2.1	Plotting Methods	13
2.2	Placeholders	17
3	Presets	18
3.1	Preset	18
3.2	Precision	19
3.3	Publication	19
4	Colors	20
4.1	Color Maps	20
4.2	Color Schemes	21
4.3	Methods	21
5	Internal Methods	22
5.1	Common	22
5.2	2D Methods	22
5.3	3D Methods	23
	Python Module Index	24
	Index	25



Making plots for technical documents can be a time sink. MPL Plotter aims to reduce that overhead by allowing you to effortlessly and concisely

- Generate publication quality figures with a single call
- Compare data by plotting different curves in a single plot
- Visualize different kinds of data in figures with many plots

It is opinionated but built with flexibility in mind, which practically means that no default can't be changed, and any and all further customization with Matplotlib is compatible. From ticks to legends to extra axes to whatever suits your needs. There's two ways to use MPL Plotter:

- Calls to the 2D and 3D plotting functions
- Using presets, either those shipped with the library, or custom ones

It does the job for me and I expand it when it can't. Hope you find some use in it!



1.1 Plotting Methods

```
class plot
    Bases: canvas, guides, framing, text
    init()
    run()
    main()
    finish()
```



```
class line (x=None, y=None, line_width=2, color='darkred', cmap='RdBu_r', alpha=None, norm=None,
            backend='Qt5Agg', font='serif', math_font='dejavuserif', font_color='black',
            font_size_increase=0, fig=None, ax=None, figsize=None, shape_and_position=111,
            resize_axes=True, scale=None, aspect=1, workspace_color=None, workspace_color2=None,
            background_color_figure='white', background_color_plot='white', background_alpha=1,
            style=None, light=None, dark=None, spine_color=None, spines_removed=(0, 0, 1, 1),
            bound_upper_x=None, bound_lower_x=None, bound_upper_y=None, bound_lower_y=None,
            bounds_x=None, bounds_y=None, pad_demo=False, pad_upper_x=0, pad_lower_x=0,
            pad_upper_y=0, pad_lower_y=0, grid=True, grid_color='lightgrey', grid_lines='-.', title=None,
            title_size=12, title_pad=10, title_weight=None, title_font=None, title_color=None,
            label_x=None, label_size_x=12, label_pad_x=10, label_rotation_x=None,
            label_weight_x=None, label_y=None, label_size_y=12, label_pad_y=10,
            label_rotation_y=None, label_weight_y=None, tick_number_x=5, tick_number_y=5,
            label_coords_x=None, label_coords_y=None, tick_color=None, tick_label_pad=5,
            ticks_where=(1, 1, 0, 0), tick_label_size=10, tick_label_size_x=None, tick_label_size_y=None,
            tick_bounds_fit=True, tick_locations_x=None, tick_bounds_x=None, tick_locations_y=None,
            tick_bounds_y=None, tick_labels_x=None, tick_labels_y=None, tick_labels_dates_x=False,
            date_format='%Y-%m-%d', tick_label_decimals=1, tick_label_decimals_x=None,
            tick_label_decimals_y=None, tick_rotation_x=None, tick_rotation_y=None,
            tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2, cb_axis_labelpad=10,
            shrink=0.75, extend='neither', cb_title=None, cb_orientation='vertical', cb_title_rotation=None,
            cb_title_style='normal', cb_title_size=10, cb_title_top_x=0, cb_title_top_y=1,
            cb_title_top_pad=None, cb_title_side_pad=10, cb_title_weight='normal', cb_title_top=True,
            cb_title_side=False, cb_ymin=None, cb_vmax=None, cb_hard_bounds=False,
            cb_outline_width=None, cb_tick_number=5, cb_ticklabelsize=10,
            cb_tick_label_decimals=None, plot_label=None, legend=False, legend_loc='upper right',
            legend_bbox_to_anchor=None, legend_size=13, legend_weight='normal', legend_style='normal',
            legend_handleheight=None, legend_ncol=1, show=False, zorder=None, top=0.93,
            bottom=0.105, left=0.165, right=0.87, hspace=0.2, wspace=0.2, filename=None, dpi=None,
            suppress=True)
```

Bases: `plot`

`plot()`

`mock()`



```
class scatter (x=None, y=None, scatter_size=5, scatter_marker='o', scatter_facecolors=None, color='C0',
               cmap='RdBu_r', alpha=None, norm=None, backend='Qt5Agg', font='serif',
               math_font='dejavuserif', font_color='black', font_size_increase=0, fig=None, ax=None,
               figsize=None, shape_and_position=111, resize_axes=True, scale=None, aspect=1,
               workspace_color=None, workspace_color2=None, background_color_figure='white',
               background_color_plot='white', background_alpha=1, style=None, light=None,
               dark=None, spine_color=None, spines_removed=(0, 0, 1, 1), bound_upper_x=None,
               bound_lower_x=None, bound_upper_y=None, bound_lower_y=None, bounds_x=None,
               bounds_y=None, pad_demo=False, pad_upper_x=0, pad_lower_x=0, pad_upper_y=0,
               pad_lower_y=0, grid=True, grid_color='lightgrey', grid_lines='-', title=None, title_size=12,
               title_pad=10, title_weight=None, title_font=None, title_color=None, label_x=None,
               label_size_x=12, label_pad_x=10, label_rotation_x=None, label_weight_x=None,
               label_y=None, label_size_y=12, label_pad_y=10, label_rotation_y=None,
               label_weight_y=None, tick_number_x=5, tick_number_y=5, label_coords_x=None,
               label_coords_y=None, tick_color=None, tick_label_pad=5, ticks_where=(1, 1, 0, 0),
               tick_label_size=10, tick_label_size_x=None, tick_label_size_y=None,
               tick_bounds_fit=True, tick_locations_x=None, tick_bounds_x=None,
               tick_locations_y=None, tick_bounds_y=None, tick_labels_x=None, tick_labels_y=None,
               tick_labels_dates_x=False, date_format='%Y-%m-%d', tick_label_decimals=1,
               tick_label_decimals_x=None, tick_label_decimals_y=None, tick_rotation_x=None,
               tick_rotation_y=None, tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2,
               cb_axis_labelpad=10, shrink=0.75, extend='neither', cb_title=None,
               cb_orientation='vertical', cb_title_rotation=None, cb_title_style='normal', cb_title_size=10,
               cb_title_top_x=0, cb_title_top_y=1, cb_title_top_pad=None, cb_title_side_pad=10,
               cb_title_weight='normal', cb_title_top=True, cb_title_side=False, cb_vmin=None,
               cb_vmax=None, cb_hard_bounds=False, cb_outline_width=None, cb_tick_number=5,
               cb_ticklabelsize=10, cb_tick_label_decimals=None, plot_label=None, legend=False,
               legend_loc='upper right', legend_bbox_to_anchor=None, legend_size=13,
               legend_weight='normal', legend_style='normal', legend_handleheight=None,
               legend_ncol=1, show=False, zorder=None, top=0.93, bottom=0.105, left=0.165,
               right=0.87, hspace=0.2, wspace=0.2, filename=None, dpi=None, suppress=True)
```

Bases: `plot`

`plot()`

`mock()`



```
class heatmap (x=None, y=None, z=None, heatmap_normvariant='SymLog', color=None, cmap='RdBu_r',
               alpha=None, norm=None, backend='Qt5Agg', font='serif', math_font='dejavuserif',
               font_color='black', font_size_increase=0, fig=None, ax=None, figsize=None,
               shape_and_position=111, resize_axes=True, scale=None, aspect=1,
               workspace_color=None, workspace_color2=None, background_color_figure='white',
               background_color_plot='white', background_alpha=1, style=None, light=None,
               dark=None, spine_color=None, spines_removed=(0, 0, 1, 1), bound_upper_x=None,
               bound_lower_x=None, bound_upper_y=None, bound_lower_y=None, bounds_x=None,
               bounds_y=None, pad_demo=False, pad_upper_x=0, pad_lower_x=0, pad_upper_y=0,
               pad_lower_y=0, grid=True, grid_color='lightgrey', grid_lines='-', title=None, title_size=12,
               title_pad=10, title_weight=None, title_font=None, title_color=None, label_x=None,
               label_size_x=12, label_pad_x=10, label_rotation_x=None, label_weight_x=None,
               label_y=None, label_size_y=12, label_pad_y=10, label_rotation_y=None,
               label_weight_y=None, tick_number_x=5, tick_number_y=5, label_coords_x=None,
               label_coords_y=None, tick_color=None, tick_label_pad=5, ticks_where=(1, 1, 0, 0),
               tick_label_size=10, tick_label_size_x=None, tick_label_size_y=None,
               tick_bounds_fit=True, tick_locations_x=None, tick_bounds_x=None,
               tick_locations_y=None, tick_bounds_y=None, tick_labels_x=None, tick_labels_y=None,
               tick_labels_dates_x=False, date_format='%Y-%m-%d', tick_label_decimals=1,
               tick_label_decimals_x=None, tick_label_decimals_y=None, tick_rotation_x=None,
               tick_rotation_y=None, tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2,
               cb_axis_labelpad=10, shrink=0.75, extend='neither', cb_title=None,
               cb_orientation='vertical', cb_title_rotation=None, cb_title_style='normal', cb_title_size=10,
               cb_title_top_x=0, cb_title_top_y=1, cb_title_top_pad=None, cb_title_side_pad=10,
               cb_title_weight='normal', cb_title_top=True, cb_title_side=False, cb_vmin=None,
               cb_vmax=None, cb_hard_bounds=False, cb_outline_width=None, cb_tick_number=5,
               cb_ticklabelsize=10, cb_tick_label_decimals=None, plot_label=None, legend=False,
               legend_loc='upper right', legend_bbox_to_anchor=None, legend_size=13,
               legend_weight='normal', legend_style='normal', legend_handleheight=None,
               legend_ncol=1, show=False, zorder=None, top=0.93, bottom=0.105, left=0.165,
               right=0.87, hspace=0.2, wspace=0.2, filename=None, dpi=None, suppress=True)
```

Bases: `plot`

`plot()`

`mock()`



```

class quiver (x=None, y=None, u=None, v=None, quiver_rule=None, quiver_custom_rule=None,
              quiver_vector_width=0.01, quiver_vector_min_shaft=2, quiver_vector_length_threshold=0.1,
              color=None, cmap='RdBu_r', alpha=None, norm=None, backend='Qt5Agg', font='serif',
              math_font='dejavuserif', font_color='black', font_size_increase=0, fig=None, ax=None,
              figsize=None, shape_and_position=111, resize_axes=True, scale=None, aspect=1,
              workspace_color=None, workspace_color2=None, background_color_figure='white',
              background_color_plot='white', background_alpha=1, style=None, light=None, dark=None,
              spine_color=None, spines_removed=(0, 0, 1, 1), bound_upper_x=None,
              bound_lower_x=None, bound_upper_y=None, bound_lower_y=None, bounds_x=None,
              bounds_y=None, pad_demo=False, pad_upper_x=0, pad_lower_x=0, pad_upper_y=0,
              pad_lower_y=0, grid=True, grid_color='lightgrey', grid_lines='-', title=None, title_size=12,
              title_pad=10, title_weight=None, title_font=None, title_color=None, label_x=None,
              label_size_x=12, label_pad_x=10, label_rotation_x=None, label_weight_x=None,
              label_y=None, label_size_y=12, label_pad_y=10, label_rotation_y=None,
              label_weight_y=None, tick_number_x=5, tick_number_y=5, label_coords_x=None,
              label_coords_y=None, tick_color=None, tick_label_pad=5, ticks_where=(1, 1, 0, 0),
              tick_label_size=10, tick_label_size_x=None, tick_label_size_y=None, tick_bounds_fit=True,
              tick_locations_x=None, tick_bounds_x=None, tick_locations_y=None, tick_bounds_y=None,
              tick_labels_x=None, tick_labels_y=None, tick_labels_dates_x=False,
              date_format='%Y-%m-%d', tick_label_decimals=1, tick_label_decimals_x=None,
              tick_label_decimals_y=None, tick_rotation_x=None, tick_rotation_y=None,
              tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2, cb_axis_labelpad=10,
              shrink=0.75, extend='neither', cb_title=None, cb_orientation='vertical',
              cb_title_rotation=None, cb_title_style='normal', cb_title_size=10, cb_title_top_x=0,
              cb_title_top_y=1, cb_title_top_pad=None, cb_title_side_pad=10, cb_title_weight='normal',
              cb_title_top=True, cb_title_side=False, cb_vmin=None, cb_vmax=None,
              cb_hard_bounds=False, cb_outline_width=None, cb_tick_number=5, cb_ticklabelsize=10,
              cb_tick_label_decimals=None, plot_label=None, legend=False, legend_loc='upper right',
              legend_bbox_to_anchor=None, legend_size=13, legend_weight='normal',
              legend_style='normal', legend_handleheight=None, legend_ncol=1, show=False,
              zorder=None, top=0.93, bottom=0.105, left=0.165, right=0.87, hspace=0.2, wspace=0.2,
              filename=None, dpi=None, suppress=True)

```

Bases: `plot`

`plot()`

`mock()`

`method_rule()`



```

class streamline (x=None, y=None, u=None, v=None, streamline_line_width=1,
                  streamline_line_density=2, color=None, cmap='RdBu_r', alpha=None, norm=None,
                  backend='Qt5Agg', font='serif', math_font='dejavuserif', font_color='black',
                  font_size_increase=0, fig=None, ax=None, figsize=None, shape_and_position=111,
                  resize_axes=True, scale=None, aspect=1, workspace_color=None,
                  workspace_color2=None, background_color_figure='white',
                  background_color_plot='white', background_alpha=1, style=None, light=None,
                  dark=None, spine_color=None, spines_removed=(0, 0, 1, 1), bound_upper_x=None,
                  bound_lower_x=None, bound_upper_y=None, bound_lower_y=None,
                  bounds_x=None, bounds_y=None, pad_demo=False, pad_upper_x=0,
                  pad_lower_x=0, pad_upper_y=0, pad_lower_y=0, grid=True, grid_color='lightgrey',
                  grid_lines='-.', title=None, title_size=12, title_pad=10, title_weight=None,
                  title_font=None, title_color=None, label_x=None, label_size_x=12, label_pad_x=10,
                  label_rotation_x=None, label_weight_x=None, label_y=None, label_size_y=12,
                  label_pad_y=10, label_rotation_y=None, label_weight_y=None, tick_number_x=5,
                  tick_number_y=5, label_coords_x=None, label_coords_y=None, tick_color=None,
                  tick_label_pad=5, ticks_where=(1, 1, 0, 0), tick_label_size=10,
                  tick_label_size_x=None, tick_label_size_y=None, tick_bounds_fit=True,
                  tick_locations_x=None, tick_bounds_x=None, tick_locations_y=None,
                  tick_bounds_y=None, tick_labels_x=None, tick_labels_y=None,
                  tick_labels_dates_x=False, date_format='%Y-%m-%d', tick_label_decimals=1,
                  tick_label_decimals_x=None, tick_label_decimals_y=None, tick_rotation_x=None,
                  tick_rotation_y=None, tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2,
                  cb_axis_labelpad=10, shrink=0.75, extend='neither', cb_title=None,
                  cb_orientation='vertical', cb_title_rotation=None, cb_title_style='normal',
                  cb_title_size=10, cb_title_top_x=0, cb_title_top_y=1, cb_title_top_pad=None,
                  cb_title_side_pad=10, cb_title_weight='normal', cb_title_top=True,
                  cb_title_side=False, cb_vmin=None, cb_vmax=None, cb_hard_bounds=False,
                  cb_outline_width=None, cb_tick_number=5, cb_ticklabelsize=10,
                  cb_tick_label_decimals=None, plot_label=None, legend=False, legend_loc='upper
                  right', legend_bbox_to_anchor=None, legend_size=13, legend_weight='normal',
                  legend_style='normal', legend_handleheight=None, legend_ncol=1, show=False,
                  zorder=None, top=0.93, bottom=0.105, left=0.165, right=0.87, hspace=0.2,
                  wspace=0.2, filename=None, dpi=None, suppress=True)

```

Bases: `plot`

`plot()`

`mock()`

`method_rule()`



```

class fill_area (x=None, y=None, z=None, fill_area_between=False, fill_area_below=False,
    fill_area_above=False, color=None, cmap='RdBu_r', alpha=None, norm=None,
    backend='Qt5Agg', font='serif', math_font='dejavuserif', font_color='black',
    font_size_increase=0, fig=None, ax=None, figsize=None, shape_and_position=111,
    resize_axes=True, scale=None, aspect=1, workspace_color=None,
    workspace_color2=None, background_color_figure='white',
    background_color_plot='white', background_alpha=1, style=None, light=None,
    dark=None, spine_color=None, spines_removed=(0, 0, 1, 1), bound_upper_x=None,
    bound_lower_x=None, bound_upper_y=None, bound_lower_y=None, bounds_x=None,
    bounds_y=None, pad_demo=False, pad_upper_x=0, pad_lower_x=0, pad_upper_y=0,
    pad_lower_y=0, grid=True, grid_color='lightgrey', grid_lines='-', title=None,
    title_size=12, title_pad=10, title_weight=None, title_font=None, title_color=None,
    label_x=None, label_size_x=12, label_pad_x=10, label_rotation_x=None,
    label_weight_x=None, label_y=None, label_size_y=12, label_pad_y=10,
    label_rotation_y=None, label_weight_y=None, tick_number_x=5, tick_number_y=5,
    label_coords_x=None, label_coords_y=None, tick_color=None, tick_label_pad=5,
    ticks_where=(1, 1, 0, 0), tick_label_size=10, tick_label_size_x=None,
    tick_label_size_y=None, tick_bounds_fit=True, tick_locations_x=None,
    tick_bounds_x=None, tick_locations_y=None, tick_bounds_y=None,
    tick_labels_x=None, tick_labels_y=None, tick_labels_dates_x=False,
    date_format='%Y-%m-%d', tick_label_decimals=1, tick_label_decimals_x=None,
    tick_label_decimals_y=None, tick_rotation_x=None, tick_rotation_y=None,
    tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2, cb_axis_labelpad=10,
    shrink=0.75, extend='neither', cb_title=None, cb_orientation='vertical',
    cb_title_rotation=None, cb_title_style='normal', cb_title_size=10, cb_title_top_x=0,
    cb_title_top_y=1, cb_title_top_pad=None, cb_title_side_pad=10,
    cb_title_weight='normal', cb_title_top=True, cb_title_side=False, cb_vmin=None,
    cb_vmax=None, cb_hard_bounds=False, cb_outline_width=None, cb_tick_number=5,
    cb_ticklabelsize=10, cb_tick_label_decimals=None, plot_label=None, legend=False,
    legend_loc='upper right', legend_bbox_to_anchor=None, legend_size=13,
    legend_weight='normal', legend_style='normal', legend_handleheight=None,
    legend_ncol=1, show=False, zorder=None, top=0.93, bottom=0.105, left=0.165,
    right=0.87, hspace=0.2, wspace=0.2, filename=None, dpi=None, suppress=True)

```

Bases: `plot`

`plot()`

Fill the region below the intersection of S and Z

`i_below()`

`i_above()`

`intersection()`

`mock()`



1.2 Composition: `comparison`

`comparison` (x , y , $f=None$, $show=False$, $autocolor=True$, $top=None$, $bottom=None$, $left=None$, $right=None$, $wspace=None$, $hspace=None$, $**kwargs$)

Data Input

The table below displays the supported numerical input combinations, where:

- array: List or NumPy array with numerical values
- [...]: List containing ...
- result: <curves>

Table 1.1: Valid input combinations.

x	y	Result	Notes
array	array	1	
array	[array, array]	2	Both y share a single x
[array, array]	[array, array]	2	Both x share a single y
[n*[array]]	[n*[array]]	n	Each y has an x

Argument Classification

Arguments are internally classified as **figure**, **plural** and **curve** arguments, namely:

- Figure

Select few arguments which may be input only once in the plotting process, so as to avoid conflicts. Ieg: passing `grid=True` twice (`plt.grid(...)`) will result in no grid being drawn. These are removed from the keyword arguments and used in the last *comparison* call.

- Plural

Arguments passed with any of the keywords accepted by all 2D plotters -that is, any keyword which does **not** start with the name of its plotting class-, in plural tense. These must be **lists** of length equal to the **number of curves**. Each element in the list is the value of the keyword argument for each curve (eg: passing `colors=['red', 'green', 'blue']` to a 3-curve plot will set the color of the curves to 'red', 'green' and 'blue'.

- Curve

Curve-specific parameters (`color`, `line_width`, `plot_label`)



Defaults

The limits of the plot will be adjusted to the upper and lower limits of all `x`'s and `y`'s.

Parameters

- `x` (*list of list or list of `np.ndarray`*) – Domains.
- `y` (*list of list or list of `np.ndarray`*) – Values.
- `f` (*list of plot*) – Functions used to plot $y(x)$
- `autocolor` (*bool*) – Whether to automatically assign different colors to each curve
- `show` (*bool*) – `plt.show()` after plotting (thereby finishing the plot)
- `top` (*float*) – `plt.subplots_adjust` parameter
- `bottom` (*float*) – `plt.subplots_adjust` parameter
- `left` (*float*) – `plt.subplots_adjust` parameter
- `right` (*float*) – `plt.subplots_adjust` parameter
- `wspace` (*float*) – `plt.subplots_adjust` parameter
- `hspace` (*float*) – `plt.subplots_adjust` parameter
- `kwargs` – MPL Plotter plotting class keyword arguments for further customization

1.3 Composition: panes

panes (*x, y, f=None, fig=None, shape=None, figsize=None, show=False, rows=1, top=None, bottom=None, left=None, right=None, wspace=None, hspace=None, **kwargs*)

Data Input

The table below displays the supported numerical input combinations, where:

- array: List or NumPy array with numerical values
- [...]: List containing ...
- result: <curves>



Table 1.2: Valid input combinations.

x	y	Result	Notes
array	array	11	
array	[array, array]	12	Both y share x
[n*[array]]	[n*[array]]	1n	Each y has an x
array	[array, array]	21	Both y share x
[array, array]	[array, array]	21	Each y has an x
array	[n*[array], n*[array]]	2n	All curves in all (2) panes share a single x
[array, array]	[n*[array], n*[array]]	2n	All curves in each pane share an x
[n*[array], n*[array]]	[n*[array], n*[array]]	2n	All curves in all (2) panes have their own x
[n*[array], ... up to m]	[n*[array], ... up to m]	mn	All curves in all panes have their own x

Argument Classification

Arguments are internally classified as **figure**, **legend**, **plural** and **curve** arguments, namely:

- Figure arguments

Arguments which may be input only once in the plotting process, so as to avoid conflicts (eg: passing `grid=True` twice (`plt.grid(...)`) will result in no grid being drawn). These are removed from the keyword arguments and applied in the last `comparison` call.

- Legend arguments

These are `plot_label/s`, which to avoid redundancy are applied in the last `comparison`. This is done only if the number of curves is the same across all panes, and equal to the number of provided `plot_labels`.

- Plural arguments

Arguments passed with any of the keywords accepted by all 2D plotters -that is, any keyword which does **not** start with the name of its plotting class-, in plural tense. These must be **lists** of length equal to the **number of panes**. Each element in the list is the value of the keyword argument for each pane (eg: `tick_labels_x=[1, 2, 3]` will set the tick labels of the x axes to 1, 2 and 3 respectively in a 3-pane plot).

- Curve arguments

Arguments passed as plurals to the comparison function. These are once more **lists** containing the value of a keyword argument, passed in plural, for each curve following the convention shown above for data input, such that passing `colors=[['red', 'blue'], ['green', 'red']]` to a plot containing 2 panes with 2 curves each will color the curves in the first pane red and blue, and those in the second green and red.

Parameters

- **x** (*list of list or list of np.ndarray or np.ndarray*) – Data



- **y** (*list of list or list of np.ndarray or np.ndarray*) – Data
- **f** (*list of function or list of plot*) – List of plotting functions to use for each curve
- **fig** (*matplotlib.figure.Figure*) – Figure object on which to plot
- **figsize** (*tuple of float*) – Figure size
- **show** (*bool*) – Whether to plt.show() after plotting (thereby finishing the plot)
- **rows** (*int*) – Number of rows
- **top** (*float*) – plt.subplots_adjust parameter
- **bottom** (*float*) – plt.subplots_adjust parameter
- **left** (*float*) – plt.subplots_adjust parameter
- **right** (*float*) – plt.subplots_adjust parameter
- **wspace** (*float*) – plt.subplots_adjust parameter
- **hspace** (*float*) – plt.subplots_adjust parameter
- **kwargs** – MPL Plotter plotting class keyword arguments for further customization

1.4 Placeholders

class MockData

Bases: object

filled_julia (*xyz_2d=False, xyz_3d=False, df=False*)

spirograph ()

sinewave ()

waterdrop ()

boltzman (*x, xmid, tau*)

Evaluate the boltzman function with midpoint xmid and time constant tau over x



2.1 Plotting Methods

```
class plot
    Bases: canvas, guides, framing, text
    init()
    run()
    main()
    finish()
```



```
class line (x=None, y=None, z=None, line_width=5, line_alpha=1, color='darkred', cmap='RdBu_r',
             scale_x=None, scale_y=None, scale_z=None, backend='Qt5Agg', font='serif',
             math_font='dejavuserif', font_color='black', font_size_increase=0, fig=None, ax=None,
             figsize=(5, 4), shape_and_position=111, azimuth=-138, elev=19, remove_axis=None,
             prune=None, resize_axes=True, aspect_equal=False, box_to_plot_pad=10, spines_juggled=(1,
             0, 2), spine_color=None, blend_edges=False, workspace_color=None, workspace_color2=None,
             background_color_figure='white', background_color_plot='white', background_alpha=1,
             style=None, light=None, dark=None, pane_fill=None, bound_upper_x=None,
             bound_lower_x=None, bound_upper_y=None, bound_lower_y=None, bound_upper_z=None,
             bound_lower_z=None, bounds_x=None, bounds_y=None, bounds_z=None, pad_demo=False,
             pad_upper_x=0, pad_lower_x=0, pad_upper_y=0, pad_lower_y=0, pad_upper_z=0,
             pad_lower_z=0, show_axes=True, grid=True, grid_color='lightgrey', grid_lines='-.', title=None,
             title_weight='normal', title_size=12, title_y=1.025, title_color=None, title_font=None,
             label_x='x', label_weight_x='normal', label_size_x=12, label_pad_x=7, label_rotation_x=None,
             label_y='y', label_weight_y='normal', label_size_y=12, label_pad_y=7,
             label_rotation_y=None, label_z='z', label_weight_z='normal', label_size_z=12, label_pad_z=7,
             label_rotation_z=None, tick_color=None, tick_number_x=5, tick_labels_x=None,
             tick_bounds_x=None, tick_rotation_x=None, tick_number_y=5, tick_labels_y=None,
             tick_bounds_y=None, tick_rotation_y=None, tick_number_z=5, tick_labels_z=None,
             tick_bounds_z=None, tick_rotation_z=None, tick_label_size=10, tick_label_decimals=1,
             tick_label_pad_x=4, tick_label_decimals_x=None, tick_label_size_x=None,
             tick_label_pad_y=4, tick_label_decimals_y=None, tick_label_size_y=None,
             tick_label_pad_z=4, tick_label_decimals_z=None, tick_label_size_z=None, plot_label=None,
             legend=False, legend_loc='upper right', legend_size=13, legend_weight='normal',
             legend_style='normal', legend_handleheight=None, legend_columns=1, show=False, top=0.975,
             bottom=0.085, left=0.14, right=0.945, hspace=0.2, wspace=0.2, filename=None, dpi=None,
             suppress=True)
```

Bases: `plot`

`plot()`

`mock()`



```

class scatter (x=None, y=None, z=None, scatter_size=30, scatter_marker='o', scatter_facecolors=None,
               color_rule=None, scatter_alpha=1, color='darkred', cmap='RdBu_r', color_bar=False,
               cb_orientation='vertical', shrink=0.75, extend='neither', cb_vmin=None, cb_vmax=None,
               cb_bounds_hard=False, cb_pad=0.1, cb_outline_width=None, cb_tick_number=5,
               cb_tick_label_decimals=5, cb_tick_label_size=10, cb_tick_label_pad=10, cb_title=None,
               cb_title_top=True, cb_title_y=False, cb_title_top_x=0, cb_title_top_y=1, cb_title_pad=10,
               cb_title_weight='normal', cb_title_rotation=None, cb_title_style='normal', cb_title_size=10,
               scale_x=None, scale_y=None, scale_z=None, backend='Qt5Agg', font='serif',
               math_font='dejavuserif', font_color='black', font_size_increase=0, fig=None, ax=None,
               figsize=(5, 4), shape_and_position=111, azim=-138, elev=19, remove_axis=None,
               prune=None, resize_axes=True, aspect_equal=False, box_to_plot_pad=10,
               spines_juggled=(1, 0, 2), spine_color=None, blend_edges=False, workspace_color=None,
               workspace_color2=None, background_color_figure='white',
               background_color_plot='white', background_alpha=1, style=None, light=None,
               dark=None, pane_fill=None, bound_upper_x=None, bound_lower_x=None,
               bound_upper_y=None, bound_lower_y=None, bound_upper_z=None,
               bound_lower_z=None, bounds_x=None, bounds_y=None, bounds_z=None,
               pad_demo=False, pad_upper_x=0, pad_lower_x=0, pad_upper_y=0, pad_lower_y=0,
               pad_upper_z=0, pad_lower_z=0, show_axes=True, grid=True, grid_color='lightgrey',
               grid_lines='-.', title=None, title_weight='normal', title_size=12, title_y=1.025,
               title_color=None, title_font=None, label_x='x', label_weight_x='normal', label_size_x=12,
               label_pad_x=7, label_rotation_x=None, label_y='y', label_weight_y='normal',
               label_size_y=12, label_pad_y=7, label_rotation_y=None, label_z='z',
               label_weight_z='normal', label_size_z=12, label_pad_z=7, label_rotation_z=None,
               tick_color=None, tick_number_x=5, tick_labels_x=None, tick_bounds_x=None,
               tick_rotation_x=None, tick_number_y=5, tick_labels_y=None, tick_bounds_y=None,
               tick_rotation_y=None, tick_number_z=5, tick_labels_z=None, tick_bounds_z=None,
               tick_rotation_z=None, tick_label_size=10, tick_label_decimals=1, tick_label_pad_x=4,
               tick_label_decimals_x=None, tick_label_size_x=None, tick_label_pad_y=4,
               tick_label_decimals_y=None, tick_label_size_y=None, tick_label_pad_z=4,
               tick_label_decimals_z=None, tick_label_size_z=None, plot_label=None, legend=False,
               legend_loc='upper right', legend_size=13, legend_weight='normal', legend_style='normal',
               legend_handleheight=None, legend_columns=1, show=False, top=0.975, bottom=0.085,
               left=0.14, right=0.945, hspace=0.2, wspace=0.2, filename=None, dpi=None,
               suppress=True)

```

Bases: `plot`

`plot()`

`mock()`



```
class surface (x=None, y=None, z=None, surface_rstride=1, surface_cstride=1, surface_wire_width=0.1,
               surface_lighting=False, surface_antialiased=False, surface_shade=False, surface_alpha=1,
               surface_cmap_lighting=None, surface_norm=None, surface_edge_color='black',
               surface_edges_to_rgba=False, cmap='RdBu_r', color=None, color_rule=None,
               color_bar=False, cb_orientation='vertical', shrink=0.75, extend='neither', cb_vmin=None,
               cb_vmax=None, cb_bounds_hard=False, cb_pad=0.1, cb_outline_width=None,
               cb_tick_number=5, cb_tick_label_decimals=5, cb_tick_label_size=10,
               cb_tick_label_pad=10, cb_title=None, cb_title_top=True, cb_title_y=False,
               cb_title_top_x=0, cb_title_top_y=1, cb_title_pad=10, cb_title_weight='normal',
               cb_title_rotation=None, cb_title_style='normal', cb_title_size=10, scale_x=None,
               scale_y=None, scale_z=None, backend='Qt5Agg', font='serif', math_font='dejavuserif',
               font_color='black', font_size_increase=0, fig=None, ax=None, figsize=(5, 4),
               shape_and_position=111, azimuth=-138, elev=19, remove_axis=None, prune=None,
               resize_axes=True, aspect_equal=False, box_to_plot_pad=10, spines_juggled=(1, 0, 2),
               spine_color=None, blend_edges=False, workspace_color=None, workspace_color2=None,
               background_color_figure='white', background_color_plot='white', background_alpha=1,
               style=None, light=None, dark=None, pane_fill=None, bound_upper_x=None,
               bound_lower_x=None, bound_upper_y=None, bound_lower_y=None,
               bound_upper_z=None, bound_lower_z=None, bounds_x=None, bounds_y=None,
               bounds_z=None, pad_demo=False, pad_upper_x=0, pad_lower_x=0, pad_upper_y=0,
               pad_lower_y=0, pad_upper_z=0, pad_lower_z=0, show_axes=True, grid=True,
               grid_color='lightgrey', grid_lines='-.', title=None, title_weight='normal', title_size=12,
               title_y=1.025, title_color=None, title_font=None, label_x='x', label_weight_x='normal',
               label_size_x=12, label_pad_x=7, label_rotation_x=None, label_y='y',
               label_weight_y='normal', label_size_y=12, label_pad_y=7, label_rotation_y=None,
               label_z='z', label_weight_z='normal', label_size_z=12, label_pad_z=7,
               label_rotation_z=None, tick_color=None, tick_number_x=5, tick_labels_x=None,
               tick_bounds_x=None, tick_rotation_x=None, tick_number_y=5, tick_labels_y=None,
               tick_bounds_y=None, tick_rotation_y=None, tick_number_z=5, tick_labels_z=None,
               tick_bounds_z=None, tick_rotation_z=None, tick_label_size=10, tick_label_decimals=1,
               tick_label_pad_x=4, tick_label_decimals_x=None, tick_label_size_x=None,
               tick_label_pad_y=4, tick_label_decimals_y=None, tick_label_size_y=None,
               tick_label_pad_z=4, tick_label_decimals_z=None, tick_label_size_z=None,
               plot_label=None, legend=False, legend_loc='upper right', legend_size=13,
               legend_weight='normal', legend_style='normal', legend_handleheight=None,
               legend_columns=1, show=False, top=0.975, bottom=0.085, left=0.14, right=0.945,
               hspace=0.2, wspace=0.2, filename=None, dpi=None, suppress=True)
```

Bases: `plot`

`plot()`

`mock()`

`method_lighting()`

`method_edges_to_rgba()`



2.2 Placeholders

```
class MockData
    Bases: object
    waterdrop3d()
    random3d()
    hill()
```

3.1 Preset

```
class preset (plotter=None, dim=None, _dict=None)
    Bases: object
    Preset object class

    save (file)
        Save MPL Plotter preset in TOML format

    classmethod load (file)
        Load MPL Plotter preset from TOML file

class two_d (preset)
    Bases: object
    2D preset plotting methods

    class line (x=None, y=None, **kwargs)
        Bases: line

    class scatter (x=None, y=None, **kwargs)
        Bases: scatter

    class heatmap (x=None, y=None, z=None, **kwargs)
        Bases: heatmap

    class quiver (x=None, y=None, u=None, v=None, **kwargs)
        Bases: quiver

    class streamline (x=None, y=None, u=None, v=None, **kwargs)
        Bases: streamline

    class fill_area (x=None, y=None, z=None, **kwargs)
        Bases: fill_area
```



```
class three_d(preset)  
    Bases: object  
    3D preset plotting methods  
  
    class line(x=None, y=None, z=None, **kwargs)  
        Bases: line  
  
    class scatter(x=None, y=None, z=None, **kwargs)  
        Bases: scatter  
  
    class surface(x=None, y=None, z=None, **kwargs)  
        Bases: surface
```

3.2 Precision

3.3 Publication

4.1 Color Maps

custom (*red, green, blue, name='coolheat', n=1024*)

Parameters

- **red** – List of (red fraction, y0, y1) tuples
- **green** – List of (red fraction, y0, y1)
- **blue** – List of (red fraction, y0, y1)
- **name** – Colormap name
- **n** – RGB quantization levels

Returns

Colormap

mapstack (*maps, fractions=None, ranges=None*)

Create a colormap stacking an arbitrary number of conventional Matplotlib colormaps.

Parameters

- **maps** (*list of str*) – List of colormap NAMES
- **fractions** (*list of float*) – For each original colormap, the fraction it'll take of the merged colormap. [0<fr_0<1, ...]
- **ranges** (*list of tuple*) – For each original colormap, the range taken. [(0=<min<1, 0<max<=1)_0, ...]

Returns

mpl.colors.LinearSegmentedColormap



4.2 Color Schemes

`colorscheme_one()`

4.3 Methods

complementary (*color*, *fmt*='hex')

Return complementary of [R, G, B] or hex color.

Parameters

fmt (*string*) – Output format: ‘hex’ or ‘rgb’.

delta (*color*, *factor*, *fmt*='hex')

Darker or lighten the input color by a percentage of <factor> ([-1, 1]) of the color spectrum (0-255).

Parameters

- **fmt** (*string*) – Output format: ‘hex’ or ‘rgb’.
- **factor** (*float*) – [-1, 1] Measure in which the color will be modified.



INTERNAL METHODS

5.1 Common

`method_backend` (*plot*)

`method_figure` (*plot*)

`method_workspace_style` (*plot*)

`method_background_color` (*plot*)

`method_subplots_adjust` (*plot*)

`method_save` (*plot*)

`method_show` (*plot*)

5.2 2D Methods

`method_setup` (*plot*)

`method_spines` (*plot*)

`method_resize_axes` (*plot*)

`method_cb` (*plot*)

`method_grid` (*plot*)

`method_legend` (*plot*)

`method_tick_locs` (*plot*)

`method_tick_labels` (*plot*)



method_fonts (*plot*)

Reference:

- <https://matplotlib.org/2.0.2/users/customizing.html>

Pyplot method:

`plt.rcParams['<category>.<item>'] = <>`

method_title (*plot*)

method_axis_labels (*plot*)

5.3 3D Methods

method_setup (*plot*)

method_spines (*plot*)

method_pane_fill (*plot*)

method_remove_axes (*plot*)

method_scale (*plot*)

method_resize_axes (*plot*)

method_cb (*plot*)

method_grid (*plot*)

method_legend (*plot*)

method_tick_locs (*plot*)

method_tick_labels (*plot*)

method_fonts (*plot*)

Reference:

- <https://matplotlib.org/2.0.2/users/customizing.html>

Pyplot method:

`plt.rcParams['<category>.<item>'] = <>`

method_title (*plot*)

method_axis_labels (*plot*)

PYTHON MODULE INDEX

C

`mpl_plotter.color.functions`, [21](#)
`mpl_plotter.color.maps`, [20](#)
`mpl_plotter.color.schemes`, [20](#)

m

`mpl_plotter.methods.common`, [22](#)
`mpl_plotter.methods.three_d`, [23](#)
`mpl_plotter.methods.two_d`, [22](#)

p

`mpl_plotter.presets.precision`, [19](#)
`mpl_plotter.presets.preset`, [18](#)
`mpl_plotter.presets.publication`, [19](#)

t

`mpl_plotter.three_d.mock`, [16](#)
`mpl_plotter.three_d.plotters`, [13](#)
`mpl_plotter.two_d.comparison`, [8](#)
`mpl_plotter.two_d.mock`, [12](#)
`mpl_plotter.two_d.panes`, [10](#)
`mpl_plotter.two_d.plotters`, [2](#)

B

`boltzman()` (*MockData method*), 12

C

`colorscheme_one()` (in module `mpl_plotter.color.schemes`), 21

`comparison()` (in module `mpl_plotter.two_d.comparison`), 9

`complementary()` (in module `mpl_plotter.color.functions`), 21

`custom()` (in module `mpl_plotter.color.maps`), 20

D

`delta()` (in module `mpl_plotter.color.functions`), 21

F

`fill_area` (class in `mpl_plotter.two_d.plotters`), 7

`filled_julia()` (*MockData method*), 12

`finish()` (*plot method*), 2, 13

H

`heatmap` (class in `mpl_plotter.two_d.plotters`), 4

`hill()` (*MockData method*), 17

I

`i_above()` (*fill_area method*), 8

`i_below()` (*fill_area method*), 8

`init()` (*plot method*), 2, 13

`intersection()` (*fill_area method*), 8

L

`line` (class in `mpl_plotter.three_d.plotters`), 13

`line` (class in `mpl_plotter.two_d.plotters`), 2

`load()` (*preset class method*), 18

M

`main()` (*plot method*), 2, 13

`mapstack()` (in module `mpl_plotter.color.maps`), 20

`method_axis_labels()` (in module `mpl_plotter.methods.three_d`), 23

`method_axis_labels()` (in module `mpl_plotter.methods.two_d`), 23

`method_backend()` (in module `mpl_plotter.methods.common`), 22

`method_background_color()` (in module `mpl_plotter.methods.common`), 22

`method_cb()` (in module `mpl_plotter.methods.three_d`), 23

`method_cb()` (in module `mpl_plotter.methods.two_d`), 22

`method_edges_to_rgba()` (*surface method*), 16

`method_figure()` (in module `mpl_plotter.methods.common`), 22

`method_fonts()` (in module `mpl_plotter.methods.three_d`), 23

`method_fonts()` (in module `mpl_plotter.methods.two_d`), 22

`method_grid()` (in module `mpl_plotter.methods.three_d`), 23

`method_grid()` (in module `mpl_plotter.methods.two_d`), 22

`method_legend()` (in module `mpl_plotter.methods.three_d`), 23

`method_legend()` (in module `mpl_plotter.methods.two_d`), 22

`method_lighting()` (*surface method*), 16

`method_pane_fill()` (in module `mpl_plotter.methods.three_d`), 23

`method_remove_axes()` (in module `mpl_plotter.methods.three_d`), 23

`method_resize_axes()` (in module `mpl_plotter.methods.three_d`), 23

`method_resize_axes()` (in module `mpl_plotter.methods.two_d`), 22



`method_rule()` (*quiver method*), 6
`method_rule()` (*streamline method*), 7
`method_save()` (in module `mpl_plotter.methods.common`), 22
`method_scale()` (in module `mpl_plotter.methods.three_d`), 23
`method_setup()` (in module `mpl_plotter.methods.three_d`), 23
`method_setup()` (in module `mpl_plotter.methods.two_d`), 22
`method_show()` (in module `mpl_plotter.methods.common`), 22
`method_spines()` (in module `mpl_plotter.methods.three_d`), 23
`method_spines()` (in module `mpl_plotter.methods.two_d`), 22
`method_subplots_adjust()` (in module `mpl_plotter.methods.common`), 22
`method_tick_labels()` (in module `mpl_plotter.methods.three_d`), 23
`method_tick_labels()` (in module `mpl_plotter.methods.two_d`), 22
`method_tick_locs()` (in module `mpl_plotter.methods.three_d`), 23
`method_tick_locs()` (in module `mpl_plotter.methods.two_d`), 22
`method_title()` (in module `mpl_plotter.methods.three_d`), 23
`method_title()` (in module `mpl_plotter.methods.two_d`), 23
`method_workspace_style()` (in module `mpl_plotter.methods.common`), 22
`mock()` (*fill_area method*), 8
`mock()` (*heatmap method*), 5
`mock()` (*line method*), 3, 14
`mock()` (*quiver method*), 6
`mock()` (*scatter method*), 4, 15
`mock()` (*streamline method*), 7
`mock()` (*surface method*), 16
`MockData` (class in `mpl_plotter.three_d.mock`), 17
`MockData` (class in `mpl_plotter.two_d.mock`), 12
module
 `mpl_plotter.color`, 19
 `mpl_plotter.color.functions`, 21
 `mpl_plotter.color.maps`, 20
 `mpl_plotter.color.schemes`, 20
 `mpl_plotter.methods`, 21
 `mpl_plotter.methods.common`, 22
 `mpl_plotter.methods.three_d`, 23
 `mpl_plotter.methods.two_d`, 22
 `mpl_plotter.presets`, 17
 `mpl_plotter.presets.precision`, 19
 `mpl_plotter.presets.preset`, 18
 `mpl_plotter.presets.publication`, 19
 `mpl_plotter.three_d`, 12
 `mpl_plotter.three_d.mock`, 16
 `mpl_plotter.three_d.plotters`, 13
 `mpl_plotter.two_d`, 1
 `mpl_plotter.two_d.comparison`, 8
 `mpl_plotter.two_d.mock`, 12
 `mpl_plotter.two_d.panes`, 10
 `mpl_plotter.two_d.plotters`, 2
 `mpl_plotter.color`
 module, 19
 `mpl_plotter.color.functions`
 module, 21
 `mpl_plotter.color.maps`
 module, 20
 `mpl_plotter.color.schemes`
 module, 20
 `mpl_plotter.methods`
 module, 21
 `mpl_plotter.methods.common`
 module, 22
 `mpl_plotter.methods.three_d`
 module, 23
 `mpl_plotter.methods.two_d`
 module, 22
 `mpl_plotter.presets`
 module, 17
 `mpl_plotter.presets.precision`
 module, 19
 `mpl_plotter.presets.preset`
 module, 18
 `mpl_plotter.presets.publication`
 module, 19
 `mpl_plotter.three_d`
 module, 12
 `mpl_plotter.three_d.mock`
 module, 16
 `mpl_plotter.three_d.plotters`
 module, 13
 `mpl_plotter.two_d`



[module](#), [1](#)
[mpl_plotter.two_d.comparison](#)
[module](#), [8](#)
[mpl_plotter.two_d.mock](#)
[module](#), [12](#)
[mpl_plotter.two_d.panes](#)
[module](#), [10](#)
[mpl_plotter.two_d.plotters](#)
[module](#), [2](#)

P

[panes\(\)](#) (*in module mpl_plotter.two_d.panes*), [10](#)
[plot](#) (*class in mpl_plotter.three_d.plotters*), [13](#)
[plot](#) (*class in mpl_plotter.two_d.plotters*), [2](#)
[plot\(\)](#) (*fill_area method*), [8](#)
[plot\(\)](#) (*heatmap method*), [5](#)
[plot\(\)](#) (*line method*), [3](#), [14](#)
[plot\(\)](#) (*quiver method*), [6](#)
[plot\(\)](#) (*scatter method*), [4](#), [15](#)
[plot\(\)](#) (*streamline method*), [7](#)
[plot\(\)](#) (*surface method*), [16](#)
[preset](#) (*class in mpl_plotter.presets.preset*), [18](#)

Q

[quiver](#) (*class in mpl_plotter.two_d.plotters*), [5](#)

R

[random3d\(\)](#) (*MockData method*), [17](#)
[run\(\)](#) (*plot method*), [2](#), [13](#)

S

[save\(\)](#) (*preset method*), [18](#)
[scatter](#) (*class in mpl_plotter.three_d.plotters*), [14](#)
[scatter](#) (*class in mpl_plotter.two_d.plotters*), [3](#)
[sinewave\(\)](#) (*MockData method*), [12](#)
[spirograph\(\)](#) (*MockData method*), [12](#)
[streamline](#) (*class in mpl_plotter.two_d.plotters*), [6](#)
[surface](#) (*class in mpl_plotter.three_d.plotters*), [15](#)

T

[three_d](#) (*class in mpl_plotter.presets.preset*), [18](#)
[three_d.line](#) (*class in mpl_plotter.presets.preset*),
[19](#)
[three_d.scatter](#) (*class in mpl_plotter.presets.preset*), [19](#)
[three_d.surface](#) (*class in mpl_plotter.presets.preset*), [19](#)
[two_d](#) (*class in mpl_plotter.presets.preset*), [18](#)

[two_d.fill_area](#) (*class in mpl_plotter.presets.preset*), [18](#)
[two_d.heatmap](#) (*class in mpl_plotter.presets.preset*),
[18](#)
[two_d.line](#) (*class in mpl_plotter.presets.preset*), [18](#)
[two_d.quiver](#) (*class in mpl_plotter.presets.preset*),
[18](#)
[two_d.scatter](#) (*class in mpl_plotter.presets.preset*),
[18](#)
[two_d.streamline](#) (*class in mpl_plotter.presets.preset*), [18](#)

W

[waterdrop\(\)](#) (*MockData method*), [12](#)
[waterdrop3d\(\)](#) (*MockData method*), [17](#)