

MPL Plotter Documentation

Antonio López Rivera

June 2022






TABLE OF CONTENTS

1	2D	2
1.1	Composition: <code>comparison</code>	2
1.2	Plotting Methods	3
1.3	Placeholders	11
1.4	Composition: <code>panes</code>	11
2	3D	13
2.1	Plotting Methods	13
2.2	Placeholders	18
3	Colors	19
3.1	Methods	19
3.2	Color Maps	19
3.3	Color Schemes	20
4	Presets	21
4.1	Precision	21
4.2	Preset	21
4.3	Publication	22
	Python Module Index	23
	Index	24



Making plots for technical documents can be a time sink. MPL Plotter aims to reduce that overhead by allowing you to effortlessly and concisely

- Generate publication quality figures with a single call
- Compare data by plotting different curves in a single plot
- Visualize different kinds of data in figures with many plots

It is opinionated but built with flexibility in mind, which practically means that no default can't be changed, and any and all further customization with Matplotlib is compatible. From ticks to legends to extra axes to whatever suits your needs. There's two ways to use MPL Plotter:

- Calls to the 2D and 3D plotting functions
- Using presets, either those shipped with the library, or custom ones

It does the job for me and I expand it when it can't. Hope you find some use in it!

1.1 Composition: comparison

comparison (*x*, *y*, *f=None*, *show=False*, *autocolor=True*, *top=None*, *bottom=None*, *left=None*, *right=None*, *wspace=None*, *hspace=None*, ***kwargs*)

Data Input

The table below displays the supported numerical input combinations, where:

- array: List or NumPy array with numerical values
- [...]: List containing ...
- result: <curves>

Table 1.1: Valid input combinations.

x	y	Result	Notes
array	array	1	
array	[array, array]	2	Both y's share a single `x`
[array, array]	[array, array]	2	Both x's share a single `y`
[n*[array]]	[n*[array]]	n	Each y has an x

Argument Classification

Arguments are internally classified as FIGURE, PLURAL and CURVE arguments, namely:

- Figure Select few arguments which may be input only once in the plotting process, so as to avoid conflicts. Ieg: passing `grid=True` twice (`plt.grid(...)`) will result in no grid being drawn. These are removed from the keyword arguments and used in the last *comparison* call.
- Plural Arguments passed with any of the keywords accepted by all 2D plotters -that is, any keyword which does **not** start with the name of its plotting class-, in plural tense. These must be **lists** of length equal to the **number of curves**. Each element in the list is the value of the keyword argument for each curve (eg: passing `colors=['red', 'green', 'blue']` to a 3-curve plot will set the color of the curves to 'red', 'green' and 'blue'.



- Curve Curve-specific parameters (`color`, `line_width`, `plot_label`)

Defaults

The limits of the plot will be adjusted to the upper and lower limits of all `x`'s and `y`'s.

Parameters

- `x` (*list of list or list of `np.ndarray`*) – Domains.
- `y` (*list of list or list of `np.ndarray`*) – Values.
- `f` (*list of plot*) – Functions used to plot `y(x)`
- `autocolor` (*bool*) – Whether to automatically assign different colors to each curve
- `show` (*bool*) – `plt.show()` after plotting (thereby finishing the plot)
- `top` (*float*) – `plt.subplots_adjust` parameter
- `bottom` (*float*) – `plt.subplots_adjust` parameter
- `left` (*float*) – `plt.subplots_adjust` parameter
- `right` (*float*) – `plt.subplots_adjust` parameter
- `wspace` (*float*) – `plt.subplots_adjust` parameter
- `hspace` (*float*) – `plt.subplots_adjust` parameter
- `kwargs` – MPL Plotter plotting class keyword arguments for further customization

1.2 Plotting Methods

class canvas

Bases: `object`

method_backend()

method_fonts()

Fonts

Reference:

- <https://matplotlib.org/2.0.2/users/customizing.html>

Pyplot method:

`plt.rcParams['<category>.<item>'] = <>`

method_figure()

method_setup()

`method_grid()``method_background_color()``method_workspace_style()`**class attributes**Bases: `object``method_cb()``method_legend()``method_title()``method_axis_labels()``method_spines()``method_ticks()`

Defaults

class adjustmentsBases: `object``method_resize_axes()``method_subplots_adjust()`**class plot**Bases: `canvas`, *attributes*, *adjustments*`init()``run()``main()``finish()``method_save()``method_show()`



```
class line (x=None, y=None, line_width=2, color='darkred', cmap='RdBu_r', alpha=None, norm=None,
            backend='Qt5Agg', font='serif', math_font='dejavuserif', font_color='black',
            font_size_increase=0, fig=None, ax=None, figsize=None, shape_and_position=111,
            resize_axes=True, scale=None, aspect=1, workspace_color=None, workspace_color2=None,
            background_color_figure='white', background_color_plot='white', background_alpha=1,
            style=None, light=None, dark=None, spine_color=None, spines_removed=(0, 0, 1, 1),
            bound_upper_x=None, bound_lower_x=None, bound_upper_y=None, bound_lower_y=None,
            bounds_x=None, bounds_y=None, pad_demo=False, pad_upper_x=0, pad_lower_x=0,
            pad_upper_y=0, pad_lower_y=0, grid=True, grid_color='lightgrey', grid_lines='-', title=None,
            title_size=12, title_pos_y=1.025, title_weight=None, title_font=None, title_color=None,
            label_x=None, label_size_x=12, label_pad_x=10, label_rotation_x=None,
            label_weight_x=None, label_y=None, label_size_y=12, label_pad_y=10,
            label_rotation_y=None, label_weight_y=None, tick_number_x=5, tick_number_y=5,
            label_coords_x=None, label_coords_y=None, tick_color=None, tick_label_pad=5,
            ticks_where=(1, 1, 0, 0), tick_label_size=10, tick_label_size_x=None, tick_label_size_y=None,
            tick_locations_x=None, tick_locations_y=None, tick_locations_fine=True, tick_labels_x=None,
            tick_labels_y=None, tick_labels_dates_x=False, date_format='%Y-%m-%d', tick_ndecimal=1,
            tick_label_decimals_x=None, tick_label_decimals_y=None, tick_rotation_x=None,
            tick_rotation_y=None, tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2,
            cb_axis_labelpad=10, shrink=0.75, extend='neither', cb_title=None, cb_orientation='vertical',
            cb_title_rotation=None, cb_title_style='normal', cb_title_size=10, cb_title_top_y=1,
            cb_ytitle_labelpad=10, cb_title_weight='normal', cb_title_top=True, cb_y_title=False,
            cb_title_top_pad=None, x_cb_title_top=0, cb_vmin=None, cb_vmax=None,
            cb_hard_bounds=False, cb_outline_width=None, cb_tick_number=5, cb_ticklabelsize=10,
            cb_tick_ndecimal=None, plot_label=None, legend=False, legend_loc='upper right',
            legend_bbox_to_anchor=None, legend_size=13, legend_weight='normal', legend_style='normal',
            legend_handleheight=None, legend_ncol=1, show=False, zorder=None, top=0.93,
            bottom=0.105, left=0.165, right=0.87, hspace=0.2, wspace=0.2, filename=None, dpi=None,
            suppress=True)
```

Bases: `plot`

`plot()`

`mock()`



```
class scatter (x=None, y=None, scatter_size=5, scatter_marker='o', scatter_facecolors=None, color='C0',
               cmap='RdBu_r', alpha=None, norm=None, backend='Qt5Agg', font='serif',
               math_font='dejavuserif', font_color='black', font_size_increase=0, fig=None, ax=None,
               figsize=None, shape_and_position=111, resize_axes=True, scale=None, aspect=1,
               workspace_color=None, workspace_color2=None, background_color_figure='white',
               background_color_plot='white', background_alpha=1, style=None, light=None,
               dark=None, spine_color=None, spines_removed=(0, 0, 1, 1), bound_upper_x=None,
               bound_lower_x=None, bound_upper_y=None, bound_lower_y=None, bounds_x=None,
               bounds_y=None, pad_demo=False, pad_upper_x=0, pad_lower_x=0, pad_upper_y=0,
               pad_lower_y=0, grid=True, grid_color='lightgrey', grid_lines='-', title=None, title_size=12,
               title_pos_y=1.025, title_weight=None, title_font=None, title_color=None, label_x=None,
               label_size_x=12, label_pad_x=10, label_rotation_x=None, label_weight_x=None,
               label_y=None, label_size_y=12, label_pad_y=10, label_rotation_y=None,
               label_weight_y=None, tick_number_x=5, tick_number_y=5, label_coords_x=None,
               label_coords_y=None, tick_color=None, tick_label_pad=5, ticks_where=(1, 1, 0, 0),
               tick_label_size=10, tick_label_size_x=None, tick_label_size_y=None,
               tick_locations_x=None, tick_locations_y=None, tick_locations_fine=True,
               tick_labels_x=None, tick_labels_y=None, tick_labels_dates_x=False,
               date_format='%Y-%m-%d', tick_ndecimals=1, tick_label_decimals_x=None,
               tick_label_decimals_y=None, tick_rotation_x=None, tick_rotation_y=None,
               tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2, cb_axis_labelpad=10,
               shrink=0.75, extend='neither', cb_title=None, cb_orientation='vertical',
               cb_title_rotation=None, cb_title_style='normal', cb_title_size=10, cb_title_top_y=1,
               cb_ytitle_labelpad=10, cb_title_weight='normal', cb_title_top=True, cb_y_title=False,
               cb_title_top_pad=None, x_cb_title_top=0, cb_vmin=None, cb_vmax=None,
               cb_hard_bounds=False, cb_outline_width=None, cb_tick_number=5, cb_ticklabelsize=10,
               cb_tick_ndecimals=None, plot_label=None, legend=False, legend_loc='upper right',
               legend_bbox_to_anchor=None, legend_size=13, legend_weight='normal',
               legend_style='normal', legend_handleheight=None, legend_ncol=1, show=False,
               zorder=None, top=0.93, bottom=0.105, left=0.165, right=0.87, hspace=0.2, wspace=0.2,
               filename=None, dpi=None, suppress=True)
```

Bases: `plot`

`plot()`

`mock()`



```

class heatmap(x=None, y=None, z=None, heatmap_normvariant='SymLog', color=None, cmap='RdBu_r',
              alpha=None, norm=None, backend='Qt5Agg', font='serif', math_font='dejavuserif',
              font_color='black', font_size_increase=0, fig=None, ax=None, figsize=None,
              shape_and_position=111, resize_axes=True, scale=None, aspect=1,
              workspace_color=None, workspace_color2=None, background_color_figure='white',
              background_color_plot='white', background_alpha=1, style=None, light=None,
              dark=None, spine_color=None, spines_removed=(0, 0, 1, 1), bound_upper_x=None,
              bound_lower_x=None, bound_upper_y=None, bound_lower_y=None, bounds_x=None,
              bounds_y=None, pad_demo=False, pad_upper_x=0, pad_lower_x=0, pad_upper_y=0,
              pad_lower_y=0, grid=True, grid_color='lightgrey', grid_lines='-', title=None, title_size=12,
              title_pos_y=1.025, title_weight=None, title_font=None, title_color=None, label_x=None,
              label_size_x=12, label_pad_x=10, label_rotation_x=None, label_weight_x=None,
              label_y=None, label_size_y=12, label_pad_y=10, label_rotation_y=None,
              label_weight_y=None, tick_number_x=5, tick_number_y=5, label_coords_x=None,
              label_coords_y=None, tick_color=None, tick_label_pad=5, ticks_where=(1, 1, 0, 0),
              tick_label_size=10, tick_label_size_x=None, tick_label_size_y=None,
              tick_locations_x=None, tick_locations_y=None, tick_locations_fine=True,
              tick_labels_x=None, tick_labels_y=None, tick_labels_dates_x=False,
              date_format='%Y-%m-%d', tick_ndecimals=1, tick_label_decimals_x=None,
              tick_label_decimals_y=None, tick_rotation_x=None, tick_rotation_y=None,
              tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2, cb_axis_labelpad=10,
              shrink=0.75, extend='neither', cb_title=None, cb_orientation='vertical',
              cb_title_rotation=None, cb_title_style='normal', cb_title_size=10, cb_title_top_y=1,
              cb_ytitle_labelpad=10, cb_title_weight='normal', cb_title_top=True, cb_y_title=False,
              cb_title_top_pad=None, x_cb_title_top=0, cb_vmin=None, cb_vmax=None,
              cb_hard_bounds=False, cb_outline_width=None, cb_tick_number=5, cb_ticklabelsize=10,
              cb_tick_ndecimals=None, plot_label=None, legend=False, legend_loc='upper right',
              legend_bbox_to_anchor=None, legend_size=13, legend_weight='normal',
              legend_style='normal', legend_handleheight=None, legend_ncol=1, show=False,
              zorder=None, top=0.93, bottom=0.105, left=0.165, right=0.87, hspace=0.2, wspace=0.2,
              filename=None, dpi=None, suppress=True)

```

Bases: `plot`

`plot()`

`mock()`



```

class quiver (x=None, y=None, u=None, v=None, quiver_rule=None, quiver_custom_rule=None,
              quiver_vector_width=0.01, quiver_vector_min_shaft=2, quiver_vector_length_threshold=0.1,
              color=None, cmap='RdBu_r', alpha=None, norm=None, backend='Qt5Agg', font='serif',
              math_font='dejavuserif', font_color='black', font_size_increase=0, fig=None, ax=None,
              figsize=None, shape_and_position=111, resize_axes=True, scale=None, aspect=1,
              workspace_color=None, workspace_color2=None, background_color_figure='white',
              background_color_plot='white', background_alpha=1, style=None, light=None, dark=None,
              spine_color=None, spines_removed=(0, 0, 1, 1), bound_upper_x=None,
              bound_lower_x=None, bound_upper_y=None, bound_lower_y=None, bounds_x=None,
              bounds_y=None, pad_demo=False, pad_upper_x=0, pad_lower_x=0, pad_upper_y=0,
              pad_lower_y=0, grid=True, grid_color='lightgrey', grid_lines='-.', title=None, title_size=12,
              title_pos_y=1.025, title_weight=None, title_font=None, title_color=None, label_x=None,
              label_size_x=12, label_pad_x=10, label_rotation_x=None, label_weight_x=None,
              label_y=None, label_size_y=12, label_pad_y=10, label_rotation_y=None,
              label_weight_y=None, tick_number_x=5, tick_number_y=5, label_coords_x=None,
              label_coords_y=None, tick_color=None, tick_label_pad=5, ticks_where=(1, 1, 0, 0),
              tick_label_size=10, tick_label_size_x=None, tick_label_size_y=None, tick_locations_x=None,
              tick_locations_y=None, tick_locations_fine=True, tick_labels_x=None, tick_labels_y=None,
              tick_labels_dates_x=False, date_format='%Y-%m-%d', tick_ndecimals=1,
              tick_label_decimals_x=None, tick_label_decimals_y=None, tick_rotation_x=None,
              tick_rotation_y=None, tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2,
              cb_axis_labelpad=10, shrink=0.75, extend='neither', cb_title=None,
              cb_orientation='vertical', cb_title_rotation=None, cb_title_style='normal', cb_title_size=10,
              cb_title_top_y=1, cb_ytitle_labelpad=10, cb_title_weight='normal', cb_title_top=True,
              cb_y_title=False, cb_title_top_pad=None, x_cb_title_top=0, cb_vmin=None,
              cb_vmax=None, cb_hard_bounds=False, cb_outline_width=None, cb_tick_number=5,
              cb_ticklabels_size=10, cb_tick_ndecimals=None, plot_label=None, legend=False,
              legend_loc='upper right', legend_bbox_to_anchor=None, legend_size=13,
              legend_weight='normal', legend_style='normal', legend_handleheight=None, legend_ncol=1,
              show=False, zorder=None, top=0.93, bottom=0.105, left=0.165, right=0.87, hspace=0.2,
              wspace=0.2, filename=None, dpi=None, suppress=True)

```

Bases: `plot`

`plot()`

`mock()`

`method_rule()`



```

class streamline (x=None, y=None, u=None, v=None, streamline_line_width=1,
                  streamline_line_density=2, color=None, cmap='RdBu_r', alpha=None, norm=None,
                  backend='Qt5Agg', font='serif', math_font='dejavuserif', font_color='black',
                  font_size_increase=0, fig=None, ax=None, figsize=None, shape_and_position=111,
                  resize_axes=True, scale=None, aspect=1, workspace_color=None,
                  workspace_color2=None, background_color_figure='white',
                  background_color_plot='white', background_alpha=1, style=None, light=None,
                  dark=None, spine_color=None, spines_removed=(0, 0, 1, 1), bound_upper_x=None,
                  bound_lower_x=None, bound_upper_y=None, bound_lower_y=None,
                  bounds_x=None, bounds_y=None, pad_demo=False, pad_upper_x=0,
                  pad_lower_x=0, pad_upper_y=0, pad_lower_y=0, grid=True, grid_color='lightgrey',
                  grid_lines='-.', title=None, title_size=12, title_pos_y=1.025, title_weight=None,
                  title_font=None, title_color=None, label_x=None, label_size_x=12, label_pad_x=10,
                  label_rotation_x=None, label_weight_x=None, label_y=None, label_size_y=12,
                  label_pad_y=10, label_rotation_y=None, label_weight_y=None, tick_number_x=5,
                  tick_number_y=5, label_coords_x=None, label_coords_y=None, tick_color=None,
                  tick_label_pad=5, ticks_where=(1, 1, 0, 0), tick_label_size=10,
                  tick_label_size_x=None, tick_label_size_y=None, tick_locations_x=None,
                  tick_locations_y=None, tick_locations_fine=True, tick_labels_x=None,
                  tick_labels_y=None, tick_labels_dates_x=False, date_format='%Y-%m-%d',
                  tick_ndecimals=1, tick_label_decimals_x=None, tick_label_decimals_y=None,
                  tick_rotation_x=None, tick_rotation_y=None, tick_labels_where=(1, 1, 0, 0),
                  color_bar=False, cb_pad=0.2, cb_axis_labelpad=10, shrink=0.75, extend='neither',
                  cb_title=None, cb_orientation='vertical', cb_title_rotation=None,
                  cb_title_style='normal', cb_title_size=10, cb_title_top_y=1, cb_ytitle_labelpad=10,
                  cb_title_weight='normal', cb_title_top=True, cb_y_title=False, cb_title_top_pad=None,
                  x_cb_title_top=0, cb_vmin=None, cb_vmax=None, cb_hard_bounds=False,
                  cb_outline_width=None, cb_tick_number=5, cb_ticklabelsize=10,
                  cb_tick_ndecimals=None, plot_label=None, legend=False, legend_loc='upper right',
                  legend_bbox_to_anchor=None, legend_size=13, legend_weight='normal',
                  legend_style='normal', legend_handleheight=None, legend_ncol=1, show=False,
                  zorder=None, top=0.93, bottom=0.105, left=0.165, right=0.87, hspace=0.2,
                  wspace=0.2, filename=None, dpi=None, suppress=True)

```

Bases: `plot`

`plot()`

`mock()`

`method_rule()`



```
class fill_area (x=None, y=None, z=None, fill_area_between=False, fill_area_below=False,
    fill_area_above=False, color=None, cmap='RdBu_r', alpha=None, norm=None,
    backend='Qt5Agg', font='serif', math_font='dejavuserif', font_color='black',
    font_size_increase=0, fig=None, ax=None, figsize=None, shape_and_position=111,
    resize_axes=True, scale=None, aspect=1, workspace_color=None,
    workspace_color2=None, background_color_figure='white',
    background_color_plot='white', background_alpha=1, style=None, light=None,
    dark=None, spine_color=None, spines_removed=(0, 0, 1, 1), bound_upper_x=None,
    bound_lower_x=None, bound_upper_y=None, bound_lower_y=None, bounds_x=None,
    bounds_y=None, pad_demo=False, pad_upper_x=0, pad_lower_x=0, pad_upper_y=0,
    pad_lower_y=0, grid=True, grid_color='lightgrey', grid_lines='-', title=None,
    title_size=12, title_pos_y=1.025, title_weight=None, title_font=None, title_color=None,
    label_x=None, label_size_x=12, label_pad_x=10, label_rotation_x=None,
    label_weight_x=None, label_y=None, label_size_y=12, label_pad_y=10,
    label_rotation_y=None, label_weight_y=None, tick_number_x=5, tick_number_y=5,
    label_coords_x=None, label_coords_y=None, tick_color=None, tick_label_pad=5,
    ticks_where=(1, 1, 0, 0), tick_label_size=10, tick_label_size_x=None,
    tick_label_size_y=None, tick_locations_x=None, tick_locations_y=None,
    tick_locations_fine=True, tick_labels_x=None, tick_labels_y=None,
    tick_labels_dates_x=False, date_format='%Y-%m-%d', tick_ndecimal=1,
    tick_label_decimals_x=None, tick_label_decimals_y=None, tick_rotation_x=None,
    tick_rotation_y=None, tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2,
    cb_axis_labelpad=10, shrink=0.75, extend='neither', cb_title=None,
    cb_orientation='vertical', cb_title_rotation=None, cb_title_style='normal',
    cb_title_size=10, cb_title_top_y=1, cb_ytitle_labelpad=10, cb_title_weight='normal',
    cb_title_top=True, cb_y_title=False, cb_title_top_pad=None, x_cb_title_top=0,
    cb_vmin=None, cb_vmax=None, cb_hard_bounds=False, cb_outline_width=None,
    cb_tick_number=5, cb_ticklabelsize=10, cb_tick_ndecimal=None, plot_label=None,
    legend=False, legend_loc='upper right', legend_bbox_to_anchor=None, legend_size=13,
    legend_weight='normal', legend_style='normal', legend_handleheight=None,
    legend_ncol=1, show=False, zorder=None, top=0.93, bottom=0.105, left=0.165,
    right=0.87, hspace=0.2, wspace=0.2, filename=None, dpi=None, suppress=True)
```

Bases: `plot`

`plot()`

Fill the region below the intersection of S and Z

`i_below()`

`i_above()`

`intersection()`

`mock()`

```
floating_text (ax, text, font='serif', x=0.5, y=0.5, size=20, weight='normal', color='darkred')
```



1.3 Placeholders

class MockData

Bases: object

filled_julia (*xyz_2d=False, xyz_3d=False, df=False*)

spirograph ()

sinewave ()

waterdrop ()

boltzman (*x, xmid, tau*)

Evaluate the boltzman function with midpoint *xmid* and time constant *tau* over *x*

1.4 Composition: panes

panes (*x, y, f=None, fig=None, figsize=None, show=False, rows=1, top=None, bottom=None, left=None, right=None, wspace=None, hspace=None, **kwargs*)

Data Input

The table below displays the supported numerical input combinations, where:

- array: List or NumPy array with numerical values
- [...]: List containing ...
- result: <curves>

Table 1.2: Valid input combinations.

x	y	Result	Notes
array	array	11	
array	[array, array]	12	Both y's <i>share</i> x
[n*[array]]	[n*[array]]	1n	Each y has an x
array	[array, array]	21	Both y's <i>share</i> x
[array, array]	[array, array]	21	Each y has an x
array	[n*[array], n*[array]]	2n	All curves in all (2) panes share a single x
[array, array]	[n*[array], n*[array]]	2n	All curves in each pane share an x
[n*[array], n*[array]]	[n*[array], n*[array]]	2n	All curves in all (2) panes have their own x
[n*[array], ... up to m]	[n*[array], ... up to m]	mn	All curves in all panes have their own x



Argument Classification

Arguments are internally classified as **FIGURE**, **LEGEND**, **PLURAL** and **CURVE** arguments, namely:

- **Figure arguments** Arguments which may be input only once in the plotting process, so as to avoid conflicts (eg: passing `grid=True` twice (`plt.grid(...)`) will result in no grid being drawn). These are removed from the keyword arguments and applied in the last `comparison` call.
- **Legend arguments** These are `plot_label/s`, which to avoid redundancy are applied in the last `comparison`. This is done only if the number of curves is the same across all panes, and equal to the number of provided `plot_labels`.
- **Plural arguments** Arguments passed with any of the keywords accepted by all 2D plotters -that is, any keyword which does **not** start with the name of its plotting class-, in plural tense. These must be **lists** of length equal to the **number of panes**. Each element in the list is the value of the keyword argument for each pane (eg: `tick_labels_x=[1, 2, 3]` will set the tick labels of the x axes to 1, 2 and 3 respectively in a 3-pane plot).
- **Curve arguments** Arguments passed as plurals to the `comparison` function. These are once more **lists** containing the value of a keyword argument, passed in plural, for each curve following the convention shown above for data input, such that passing `colors=[['red', 'blue'], ['green', 'red']]` to a plot containing 2 panes with 2 curves each will color the curves in the first pane red and blue, and those in the second green and red.

Parameters

- **x** (*list of list or list of np.ndarray or np.ndarray*) – Data
- **y** (*list of list or list of np.ndarray or np.ndarray*) – Data
- **f** (*list of function or list of plot*) – List of plotting functions to use for each curve
- **fig** (*matplotlib.figure.Figure*) – Figure object on which to plot
- **figsize** (*tuple of float*) – Figure size
- **show** (*bool*) – Whether to `plt.show()` after plotting (thereby finishing the plot)
- **rows** (*int*) – Number of rows
- **top** (*float*) – `plt.subplots_adjust` parameter
- **bottom** (*float*) – `plt.subplots_adjust` parameter
- **left** (*float*) – `plt.subplots_adjust` parameter
- **right** (*float*) – `plt.subplots_adjust` parameter
- **wspace** (*float*) – `plt.subplots_adjust` parameter
- **hspace** (*float*) – `plt.subplots_adjust` parameter
- **kwargs** – MPL Plotter plotting class keyword arguments for further customization

2.1 Plotting Methods

class canvas

Bases: object

method_backend()

method_fonts()

Fonts Reference:

- <https://matplotlib.org/2.0.2/users/customizing.html>

Pyplot method:

`plt.rcParams['<category>.<item>'] = <>`

method_figure()

method_setup()

method_grid()

method_pane_fill()

method_background_color()

method_workspace_style()

class attributes

Bases: object

method_legend()

method_title()

method_axis_labels()

method_spines()



```
    method_ticks()

class adjustments
    Bases: object

    method_resize_axes()

    method_subplots_adjust()

    method_remove_axes()

    method_scale()

class plot
    Bases: canvas, attributes, adjustments

    init()

    run()

    main()

    finish()

    method_save()

    method_show()

class color
    Bases: object

    method_cb()

class surf
    Bases: color

    custom()

    method_lighting()

    method_edges_to_rgba()
```




```
class line (x=None, y=None, z=None, line_width=5, line_alpha=1, color='darkred', cmap='RdBu_r',
            scale_x=None, scale_y=None, scale_z=None, backend='Qt5Agg', font='serif',
            math_font='dejavuserif', font_color='black', font_size_increase=0, fig=None, ax=None,
            figsize=(5, 4), shape_and_position=111, azimuth=-138, elev=19, remove_axis=None,
            prune=None, resize_axes=True, aspect_equal=False, box_to_plot_pad=10, spines_juggled=(1,
            0, 2), spine_color=None, blend_edges=False, workspace_color=None, workspace_color2=None,
            background_color_figure='white', background_color_plot='white', background_alpha=1,
            style=None, light=None, dark=None, pane_fill=None, bound_upper_x=None,
            bound_lower_x=None, bound_upper_y=None, bound_lower_y=None, bound_upper_z=None,
            bound_lower_z=None, bounds_x=None, bounds_y=None, bounds_z=None, pad_demo=False,
            pad_upper_x=0, pad_lower_x=0, pad_upper_y=0, pad_lower_y=0, pad_upper_z=0,
            pad_lower_z=0, show_axes=True, grid=True, grid_color='lightgrey', grid_lines='-.', title=None,
            title_weight='normal', title_size=12, title_y=1.025, title_color=None, title_font=None,
            label_x='x', label_weight_x='normal', label_size_x=12, label_pad_x=7, label_rotation_x=None,
            label_y='y', label_weight_y='normal', label_size_y=12, label_pad_y=7,
            label_rotation_y=None, label_z='z', label_weight_z='normal', label_size_z=12, label_pad_z=7,
            label_rotation_z=None, tick_color=None, tick_number_x=5, tick_labels_x=None,
            tick_locations_x=None, tick_rotation_x=None, tick_number_y=5, tick_labels_y=None,
            tick_locations_y=None, tick_rotation_y=None, tick_number_z=5, tick_labels_z=None,
            tick_locations_z=None, tick_rotation_z=None, tick_label_size=10, tick_label_pad_x=4,
            tick_label_decimals_x=1, tick_label_size_x=None, tick_label_pad_y=4,
            tick_label_decimals_y=1, tick_label_size_y=None, tick_label_pad_z=4,
            tick_label_decimals_z=1, tick_label_size_z=None, plot_label=None, legend=False,
            legend_loc='upper right', legend_size=13, legend_weight='normal', legend_style='normal',
            legend_handleheight=None, legend_columns=1, show=False, top=0.975, bottom=0.085,
            left=0.14, right=0.945, hspace=0.2, wspace=0.2, filename=None, dpi=None, suppress=True)
```

Bases: `plot`

`plot()`

`mock()`



```

class scatter (x=None, y=None, z=None, scatter_size=30, scatter_marker='o', scatter_facecolors=None,
               color_rule=None, scatter_alpha=1, color='darkred', cmap='RdBu_r', color_bar=False,
               cb_orientation='vertical', shrink=0.75, extend='neither', cb_vmin=None, cb_vmax=None,
               cb_bounds_hard=False, cb_pad=0.1, cb_outline_width=None, cb_tick_number=5,
               cb_tick_label_decimals=5, ctick_label_size_b=10, ctick_label_pad_b=10, cb_title=None,
               cb_title_top=True, cb_title_y=False, cb_title_top_pos_x=0, cb_title_top_pos_y=1,
               cb_title_pad=10, cb_title_weight='normal', cb_title_rotation=None, cb_title_style='normal',
               cb_title_size=10, scale_x=None, scale_y=None, scale_z=None, backend='Qt5Agg',
               font='serif', math_font='dejavuserif', font_color='black', font_size_increase=0, fig=None,
               ax=None, figsize=(5, 4), shape_and_position=111, azim=-138, elev=19,
               remove_axis=None, prune=None, resize_axes=True, aspect_equal=False,
               box_to_plot_pad=10, spines_juggled=(1, 0, 2), spine_color=None, blend_edges=False,
               workspace_color=None, workspace_color2=None, background_color_figure='white',
               background_color_plot='white', background_alpha=1, style=None, light=None,
               dark=None, pane_fill=None, bound_upper_x=None, bound_lower_x=None,
               bound_upper_y=None, bound_lower_y=None, bound_upper_z=None,
               bound_lower_z=None, bounds_x=None, bounds_y=None, bounds_z=None,
               pad_demo=False, pad_upper_x=0, pad_lower_x=0, pad_upper_y=0, pad_lower_y=0,
               pad_upper_z=0, pad_lower_z=0, show_axes=True, grid=True, grid_color='lightgrey',
               grid_lines='-', title=None, title_weight='normal', title_size=12, title_y=1.025,
               title_color=None, title_font=None, label_x='x', label_weight_x='normal', label_size_x=12,
               label_pad_x=7, label_rotation_x=None, label_y='y', label_weight_y='normal',
               label_size_y=12, label_pad_y=7, label_rotation_y=None, label_z='z',
               label_weight_z='normal', label_size_z=12, label_pad_z=7, label_rotation_z=None,
               tick_color=None, tick_number_x=5, tick_labels_x=None, tick_locations_x=None,
               tick_rotation_x=None, tick_number_y=5, tick_labels_y=None, tick_locations_y=None,
               tick_rotation_y=None, tick_number_z=5, tick_labels_z=None, tick_locations_z=None,
               tick_rotation_z=None, tick_label_size=10, tick_label_pad_x=4, tick_label_decimals_x=1,
               tick_label_size_x=None, tick_label_pad_y=4, tick_label_decimals_y=1,
               tick_label_size_y=None, tick_label_pad_z=4, tick_label_decimals_z=1,
               tick_label_size_z=None, plot_label=None, legend=False, legend_loc='upper right',
               legend_size=13, legend_weight='normal', legend_style='normal',
               legend_handleheight=None, legend_columns=1, show=False, top=0.975, bottom=0.085,
               left=0.14, right=0.945, hspace=0.2, wspace=0.2, filename=None, dpi=None,
               suppress=True)

```

Bases: `plot`, `color`

`plot()`

`mock()`



```
class surface (x=None, y=None, z=None, surface_rstride=1, surface_cstride=1, surface_wire_width=0.1,
               surface_lighting=False, surface_antialiased=False, surface_shade=False, surface_alpha=1,
               surface_cmap_lighting=None, surface_norm=None, surface_edge_color='black',
               surface_edges_to_rgba=False, cmap='RdBu_r', color=None, color_rule=None,
               color_bar=False, cb_orientation='vertical', shrink=0.75, extend='neither', cb_vmin=None,
               cb_vmax=None, cb_bounds_hard=False, cb_pad=0.1, cb_outline_width=None,
               cb_tick_number=5, cb_tick_label_decimals=5, ctick_label_size_b=10,
               ctick_label_pad_b=10, cb_title=None, cb_title_top=True, cb_title_y=False,
               cb_title_top_pos_x=0, cb_title_top_pos_y=1, cb_title_pad=10, cb_title_weight='normal',
               cb_title_rotation=None, cb_title_style='normal', cb_title_size=10, scale_x=None,
               scale_y=None, scale_z=None, backend='Qt5Agg', font='serif', math_font='dejavuserif',
               font_color='black', font_size_increase=0, fig=None, ax=None, figsize=(5, 4),
               shape_and_position=111, azim=-138, elev=19, remove_axis=None, prune=None,
               resize_axes=True, aspect_equal=False, box_to_plot_pad=10, spines_juggled=(1, 0, 2),
               spine_color=None, blend_edges=False, workspace_color=None, workspace_color2=None,
               background_color_figure='white', background_color_plot='white', background_alpha=1,
               style=None, light=None, dark=None, pane_fill=None, bound_upper_x=None,
               bound_lower_x=None, bound_upper_y=None, bound_lower_y=None,
               bound_upper_z=None, bound_lower_z=None, bounds_x=None, bounds_y=None,
               bounds_z=None, pad_demo=False, pad_upper_x=0, pad_lower_x=0, pad_upper_y=0,
               pad_lower_y=0, pad_upper_z=0, pad_lower_z=0, show_axes=True, grid=True,
               grid_color='lightgrey', grid_lines='-.', title=None, title_weight='normal', title_size=12,
               title_y=1.025, title_color=None, title_font=None, label_x='x', label_weight_x='normal',
               label_size_x=12, label_pad_x=7, label_rotation_x=None, label_y='y',
               label_weight_y='normal', label_size_y=12, label_pad_y=7, label_rotation_y=None,
               label_z='z', label_weight_z='normal', label_size_z=12, label_pad_z=7,
               label_rotation_z=None, tick_color=None, tick_number_x=5, tick_labels_x=None,
               tick_locations_x=None, tick_rotation_x=None, tick_number_y=5, tick_labels_y=None,
               tick_locations_y=None, tick_rotation_y=None, tick_number_z=5, tick_labels_z=None,
               tick_locations_z=None, tick_rotation_z=None, tick_label_size=10, tick_label_pad_x=4,
               tick_label_decimals_x=1, tick_label_size_x=None, tick_label_pad_y=4,
               tick_label_decimals_y=1, tick_label_size_y=None, tick_label_pad_z=4,
               tick_label_decimals_z=1, tick_label_size_z=None, plot_label=None, legend=False,
               legend_loc='upper right', legend_size=13, legend_weight='normal', legend_style='normal',
               legend_handleheight=None, legend_columns=1, show=False, top=0.975, bottom=0.085,
               left=0.14, right=0.945, hspace=0.2, wspace=0.2, filename=None, dpi=None,
               suppress=True)
```

Bases: `plot`, `surf`

`plot()`

`mock()`

`floating_text` (`ax`, `text`, `font`, `x`, `y`, `z`, `size=20`, `weight='normal'`, `color='darkred'`)



2.2 Placeholders

```
class MockData
    Bases: object

    waterdrop3d()

    random3d()

    hill()
```

3.1 Methods

complementary (*color*, *fmt*='hex')

Return complementary of [R, G, B] or hex color.

Parameters

fmt (*string*) – Output format: ‘hex’ or ‘rgb’.

delta (*color*, *factor*, *fmt*='hex')

Darker or lighten the input color by a percentage of <factor> ([-1, 1]) of the color spectrum (0-255).

Parameters

- **fmt** (*string*) – Output format: ‘hex’ or ‘rgb’.
- **factor** (*float*) – [-1, 1] Measure in which the color will be modified.

3.2 Color Maps

custom (*red*, *green*, *blue*, *name*='coolheat', *n*=1024)

Parameters

- **red** – List of (red fraction, y0, y1) tuples
- **green** – List of (red fraction, y0, y1)
- **blue** – List of (red fraction, y0, y1)
- **name** – Colormap name
- **n** – RGB quantization levels

Returns

Colormap



mapstack (*maps*, *fractions=None*, *ranges=None*)

Create a colormap stacking an arbitrary number of conventional Matplotlib colormaps.

Parameters

- **maps** (*list of str*) – List of colormap NAMES
- **fractions** (*list of float*) – For each original colormap, the fraction it'll take of the merged colormap. $[0 < \text{fr}_0 < 1, \dots]$
- **ranges** (*list of tuple*) – For each original colormap, the range taken. $[(0 \leq \text{min} < 1, 0 \leq \text{max} \leq 1)_0, \dots]$

Returns

`mpl.colors.LinearSegmentedColormap`

3.3 Color Schemes

colorscheme_one()

4.1 Precision

4.2 Preset

class `preset` (*plotter=None, dim=None, _dict=None*)

Bases: `object`

Preset object class

save (*file*)

Save MPL Plotter preset in TOML format

classmethod `load` (*file*)

Load MPL Plotter preset from TOML file

class `two_d` (*preset*)

Bases: `object`

2D preset plotting methods

class `line` (*x=None, y=None, **kwargs*)

Bases: `line`

class `scatter` (*x=None, y=None, **kwargs*)

Bases: `scatter`

class `heatmap` (*x=None, y=None, z=None, **kwargs*)

Bases: `heatmap`

class `quiver` (*x=None, y=None, u=None, v=None, **kwargs*)

Bases: `quiver`

class `streamline` (*x=None, y=None, u=None, v=None, **kwargs*)

Bases: `streamline`

class `fill_area` (*x=None, y=None, z=None, **kwargs*)

Bases: `fill_area`



```
class three_d(preset)  
    Bases: object  
    3D preset plotting methods  
  
    class line(x=None, y=None, z=None, **kwargs)  
        Bases: line  
  
    class scatter(x=None, y=None, z=None, **kwargs)  
        Bases: scatter  
  
    class surface(x=None, y=None, z=None, **kwargs)  
        Bases: surface
```

4.3 Publication



PYTHON MODULE INDEX

C

`mpl_plotter.color`, [18](#)
`mpl_plotter.color.functions`, [19](#)
`mpl_plotter.color.maps`, [19](#)
`mpl_plotter.color.schemes`, [20](#)

p

`mpl_plotter.presets`, [20](#)
`mpl_plotter.presets.precision`, [21](#)
`mpl_plotter.presets.preset`, [21](#)
`mpl_plotter.presets.publication`, [22](#)

t

`mpl_plotter.three_d`, [12](#)
`mpl_plotter.three_d.methods`, [13](#)
`mpl_plotter.three_d.mock`, [17](#)
`mpl_plotter.two_d`, [1](#)
`mpl_plotter.two_d.comparison`, [2](#)
`mpl_plotter.two_d.methods`, [3](#)
`mpl_plotter.two_d.mock`, [10](#)
`mpl_plotter.two_d.panes`, [11](#)

A

`adjustments` (class in `mpl_plotter.three_d.methods`), 14
`adjustments` (class in `mpl_plotter.two_d.methods`), 4
`attributes` (class in `mpl_plotter.three_d.methods`), 13
`attributes` (class in `mpl_plotter.two_d.methods`), 4

B

`boltzman` () (*MockData method*), 11

C

`canvas` (class in `mpl_plotter.three_d.methods`), 13
`canvas` (class in `mpl_plotter.two_d.methods`), 3
`color` (class in `mpl_plotter.three_d.methods`), 14
`colorscheme_one` () (in module `mpl_plotter.color.schemes`), 20
`comparison` () (in module `mpl_plotter.two_d.comparison`), 2
`complementary` () (in module `mpl_plotter.color.functions`), 19
`custom` () (in module `mpl_plotter.color.maps`), 19
`custom` () (*surf method*), 14

D

`delta` () (in module `mpl_plotter.color.functions`), 19

F

`fill_area` (class in `mpl_plotter.two_d.methods`), 9
`filled_julia` () (*MockData method*), 11
`finish` () (*plot method*), 4, 14
`floating_text` () (in module `mpl_plotter.three_d.methods`), 17
`floating_text` () (in module `mpl_plotter.two_d.methods`), 10

H

`heatmap` (class in `mpl_plotter.two_d.methods`), 6
`hill` () (*MockData method*), 18

I

`i_above` () (*fill_area method*), 10
`i_below` () (*fill_area method*), 10
`init` () (*plot method*), 4, 14
`intersection` () (*fill_area method*), 10

L

`line` (class in `mpl_plotter.three_d.methods`), 14
`line` (class in `mpl_plotter.two_d.methods`), 4
`load` () (*preset class method*), 21

M

`main` () (*plot method*), 4, 14
`mapstack` () (in module `mpl_plotter.color.maps`), 19
`method_axis_labels` () (*attributes method*), 4, 13
`method_backend` () (*canvas method*), 3, 13
`method_background_color` () (*canvas method*), 4, 13
`method_cb` () (*attributes method*), 4
`method_cb` () (*color method*), 14
`method_edges_to_rgba` () (*surf method*), 14
`method_figure` () (*canvas method*), 3, 13
`method_fonts` () (*canvas method*), 3, 13
`method_grid` () (*canvas method*), 3, 13
`method_legend` () (*attributes method*), 4, 13
`method_lighting` () (*surf method*), 14
`method_pane_fill` () (*canvas method*), 13
`method_remove_axes` () (*adjustments method*), 14
`method_resize_axes` () (*adjustments method*), 4, 14
`method_rule` () (*quiver method*), 8



`method_rule()` (*streamline method*), 9
`method_save()` (*plot method*), 4, 14
`method_scale()` (*adjustments method*), 14
`method_setup()` (*canvas method*), 3, 13
`method_show()` (*plot method*), 4, 14
`method_spines()` (*attributes method*), 4, 13
`method_subplots_adjust()` (*adjustments method*), 4, 14
`method_ticks()` (*attributes method*), 4, 13
`method_title()` (*attributes method*), 4, 13
`method_workspace_style()` (*canvas method*), 4, 13
`mock()` (*fill_area method*), 10
`mock()` (*heatmap method*), 7
`mock()` (*line method*), 5, 15
`mock()` (*quiver method*), 8
`mock()` (*scatter method*), 6, 16
`mock()` (*streamline method*), 9
`mock()` (*surface method*), 17
`MockData` (*class in mpl_plotter.three_d.mock*), 18
`MockData` (*class in mpl_plotter.two_d.mock*), 11
module
 `mpl_plotter.color`, 18
 `mpl_plotter.color.functions`, 19
 `mpl_plotter.color.maps`, 19
 `mpl_plotter.color.schemes`, 20
 `mpl_plotter.presets`, 20
 `mpl_plotter.presets.precision`, 21
 `mpl_plotter.presets.preset`, 21
 `mpl_plotter.presets.publication`, 22
 `mpl_plotter.three_d`, 12
 `mpl_plotter.three_d.methods`, 13
 `mpl_plotter.three_d.mock`, 17
 `mpl_plotter.two_d`, 1
 `mpl_plotter.two_d.comparison`, 2
 `mpl_plotter.two_d.methods`, 3
 `mpl_plotter.two_d.mock`, 10
 `mpl_plotter.two_d.panes`, 11
`mpl_plotter.color`
 module, 18
`mpl_plotter.color.functions`
 module, 19
`mpl_plotter.color.maps`
 module, 19
`mpl_plotter.color.schemes`
 module, 20
`mpl_plotter.presets`
 module, 20
`mpl_plotter.presets.precision`
 module, 21
`mpl_plotter.presets.preset`
 module, 21
`mpl_plotter.presets.publication`
 module, 22
`mpl_plotter.three_d`
 module, 12
`mpl_plotter.three_d.methods`
 module, 13
`mpl_plotter.three_d.mock`
 module, 17
`mpl_plotter.two_d`
 module, 1
`mpl_plotter.two_d.comparison`
 module, 2
`mpl_plotter.two_d.methods`
 module, 3
`mpl_plotter.two_d.mock`
 module, 10
`mpl_plotter.two_d.panes`
 module, 11

P

`panes()` (*in module mpl_plotter.two_d.panes*), 11
`plot` (*class in mpl_plotter.three_d.methods*), 14
`plot` (*class in mpl_plotter.two_d.methods*), 4
`plot()` (*fill_area method*), 10
`plot()` (*heatmap method*), 7
`plot()` (*line method*), 5, 15
`plot()` (*quiver method*), 8
`plot()` (*scatter method*), 6, 16
`plot()` (*streamline method*), 9
`plot()` (*surface method*), 17
`preset` (*class in mpl_plotter.presets.preset*), 21

Q

`quiver` (*class in mpl_plotter.two_d.methods*), 7

R

`random3d()` (*MockData method*), 18
`run()` (*plot method*), 4, 14

S

`save()` (*preset method*), 21
`scatter` (*class in mpl_plotter.three_d.methods*), 15



`scatter` (*class in `mpl_plotter.two_d.methods`*), 5
`sinewave()` (*MockData method*), 11
`spirograph()` (*MockData method*), 11
`streamline` (*class in `mpl_plotter.two_d.methods`*), 8
`surf` (*class in `mpl_plotter.three_d.methods`*), 14
`surface` (*class in `mpl_plotter.three_d.methods`*), 16

T

`three_d` (*class in `mpl_plotter.presets.preset`*), 21
`three_d.line` (*class in `mpl_plotter.presets.preset`*),
22
`three_d.scatter` (*class in `mpl_plotter.presets.preset`*), 22
`three_d.surface` (*class in `mpl_plotter.presets.preset`*), 22
`two_d` (*class in `mpl_plotter.presets.preset`*), 21
`two_d.fill_area` (*class in `mpl_plotter.presets.preset`*), 21
`two_d.heatmap` (*class in `mpl_plotter.presets.preset`*),
21
`two_d.line` (*class in `mpl_plotter.presets.preset`*), 21
`two_d.quiver` (*class in `mpl_plotter.presets.preset`*),
21
`two_d.scatter` (*class in `mpl_plotter.presets.preset`*),
21
`two_d.streamline` (*class in `mpl_plotter.presets.preset`*), 21

W

`waterdrop()` (*MockData method*), 11
`waterdrop3d()` (*MockData method*), 18