

MPL Plotter Documentation

Antonio López Rivera

March 2022





TABLE OF CONTENTS

1	2D	2
1.1	Comparisons	2
1.2	Plotting Methods	3
1.3	Placeholders	10
1.4	Panes	10
2	3D	12
2.1	Plotting Methods	12
2.2	Placeholders	17
3	Colors	18
3.1	Methods	18
3.2	Color Schemes	19
4	Presets	20
4.1	Custom	20
4.2	Precision	21
4.3	Publication	21
	Python Module Index	22
	Index	23



Making plots for technical documents can be a time sink. MPL Plotter aims to reduce that overhead by allowing you to effortlessly and concisely

- Generate publication quality figures with a single call
- Compare data by plotting different curves in a single plot
- Visualize different kinds of data in figures with many plots

It is opinionated but built with flexibility in mind, which practically means that no default can't be changed, and any and all further customization with Matplotlib is compatible. From ticks to legends to extra axes to whatever suits your needs. There's two ways to use MPL Plotter:

- Calls to the 2D and 3D plotting functions
- Using presets, either those shipped with the library, or custom ones

It does the job for me and I expand it when it can't. Hope you find some use in it!

1.1 Comparisons

comparison (*x*, *y*, *f*=None, *show*=False, *autocolor*=True, *top*=None, *bottom*=None, *left*=None, *right*=None, *wspace*=None, *hspace*=None, ****kwargs**)

Inputs

The table below displays the supported numerical input combinations, where:

- array: List or NumPy array with numerical values
- [...]: List containing ...
- result: <curves>

Arguments

Arguments are internally classified as FIGURE arguments, AXIS arguments, PLURAL arguments and CURVE arguments, namely:

- Figure Select few arguments which may be input only once in the plotting process, so as to avoid conflicts. Ieg: passing *grid=True* twice (*plt.grid(...)*) will result in no grid being drawn. These are removed from the keyword arguments and used in the last *comparison* call.
- Plural Arguments with a keyword equal to any of the arguments which can be passed to the

line

2D plotter, in plural tense. The line plotter is chosen as it shares all general arguments with the other 2D plotter functions. The plural arguments are assumed to be

lists of length equal to the number of curves

and thus modify each curve. Ieg: *colors=['red', 'green', 'blue']* will set the color of each curve to 'red', 'green' and 'blue' respectively in a 3-curve plot.



Defaults

The limits of the plot will be adjusted to the upper and lower limits of all `x`'s and `y`'s.

Parameters

- `x` (*list of list or list of `np.ndarray`*) – Domains.
- `y` (*list of list or list of `np.ndarray`*) – Values.
- `f` (*list of plot*) – Functions used to plot `y(x)`
- `kwargs` – MPL Plotter plotting class keyword arguments for further customization

1.2 Plotting Methods

`class canvas`

Bases: `object`

`method_backend()`

`method_fonts()`

Fonts

Reference:

- <https://matplotlib.org/2.0.2/users/customizing.html>

Pyplot method: `plt.rcParams['<category>.<item>'] = <>`

`method_setup()`

`method_figure()`

`method_grid()`

`class attributes`

Bases: `object`

`method_background_color()`

`method_workspace_style()`

`method_cb()`

`method_legend()`

`method_resize_axes()`

`method_title()`

`method_axis_labels()`

`method_spines()`



method_ticks()

Defaults

class plot

Bases: `mpl_plotter.two_d.methods.canvas`, `mpl_plotter.two_d.methods.attributes`

init()

run()

main()

finish()

method_save()

method_show()

class line (`x=None, y=None, line_width=2, color='darkred', cmap='RdBu_r', alpha=None, norm=None, backend='Qt5Agg', font='serif', math_font='dejavuserif', font_color='black', font_size_increase=0, fig=None, ax=None, figsize=None, shape_and_position=111, resize_axes=True, scale=None, aspect=1, workspace_color=None, workspace_color2=None, background_color_figure='white', background_color_plot='white', background_alpha=1, style=None, light=None, dark=None, spine_color=None, spines_removed=(0, 0, 1, 1), x_upper_bound=None, x_lower_bound=None, y_upper_bound=None, y_lower_bound=None, x_bounds=None, y_bounds=None, demo_pad_plot=False, x_upper_resize_pad=0, x_lower_resize_pad=0, y_upper_resize_pad=0, y_lower_resize_pad=0, grid=True, grid_color='lightgrey', grid_lines='-.', title=None, title_size=12, title_y=1.025, title_weight=None, title_font=None, title_color=None, x_label=None, x_label_size=12, x_label_pad=10, x_label_rotation=None, x_label_weight=None, y_label=None, y_label_size=12, y_label_pad=10, y_label_rotation=None, y_label_weight=None, x_tick_number=5, y_tick_number=5, x_label_coords=None, y_label_coords=None, tick_color=None, tick_label_pad=5, ticks_where=(1, 1, 0, 0), tick_label_size=10, x_tick_label_size=None, y_tick_label_size=None, x_custom_tick_locations=None, y_custom_tick_locations=None, fine_tick_locations=True, x_custom_tick_labels=None, y_custom_tick_labels=None, x_date_tick_labels=False, date_format='%Y-%m-%d', tick_ndecimal=1, x_tick_ndecimal=None, y_tick_ndecimal=None, x_tick_rotation=None, y_tick_rotation=None, tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2, cb_axis_labelpad=10, shrink=0.75, extend='neither', cb_title=None, cb_orientation='vertical', cb_title_rotation=None, cb_title_style='normal', cb_title_size=10, cb_top_title_y=1, cb_ytitle_labelpad=10, cb_title_weight='normal', cb_top_title=False, cb_y_title=False, cb_top_title_pad=None, x_cb_top_title=0, cb_vmin=None, cb_vmax=None, cb_hard_bounds=False, cb_outline_width=None, cb_tick_number=5, cb_ticklabelsize=10, cb_tick_ndecimal=None, plot_label=None, legend=False, legend_loc='upper right', legend_bbox_to_anchor=None, legend_size=13, legend_weight='normal', legend_style='normal', legend_handleheight=None, legend_ncol=1, show=False, zorder=None, filename=None, dpi=None, suppress=True)`

Bases: `mpl_plotter.two_d.methods.plot`

plot()



mock()

```
class scatter (x=None, y=None, point_size=5, marker='o', facecolors=None, color='C0', cmap='RdBu_r',
               alpha=None, norm=None, backend='Qt5Agg', font='serif', math_font='dejavuserif',
               font_color='black', font_size_increase=0, fig=None, ax=None, figsize=None,
               shape_and_position=111, resize_axes=True, scale=None, aspect=1,
               workspace_color=None, workspace_color2=None, background_color_figure='white',
               background_color_plot='white', background_alpha=1, style=None, light=None,
               dark=None, spine_color=None, spines_removed=(0, 0, 1, 1), x_upper_bound=None,
               x_lower_bound=None, y_upper_bound=None, y_lower_bound=None, x_bounds=None,
               y_bounds=None, demo_pad_plot=False, x_upper_resize_pad=0, x_lower_resize_pad=0,
               y_upper_resize_pad=0, y_lower_resize_pad=0, grid=True, grid_color='lightgrey',
               grid_lines='-.', title=None, title_size=12, title_y=1.025, title_weight=None, title_font=None,
               title_color=None, x_label=None, x_label_size=12, x_label_pad=10,
               x_label_rotation=None, x_label_weight=None, y_label=None, y_label_size=12,
               y_label_pad=10, y_label_rotation=None, y_label_weight=None, x_tick_number=5,
               y_tick_number=5, x_label_coords=None, y_label_coords=None, tick_color=None,
               tick_label_pad=5, ticks_where=(1, 1, 0, 0), tick_label_size=10, x_tick_label_size=None,
               y_tick_label_size=None, x_custom_tick_locations=None, y_custom_tick_locations=None,
               fine_tick_locations=True, x_custom_tick_labels=None, y_custom_tick_labels=None,
               x_date_tick_labels=False, date_format='%Y-%m-%d', tick_ndecimals=1,
               x_tick_ndecimals=None, y_tick_ndecimals=None, x_tick_rotation=None,
               y_tick_rotation=None, tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2,
               cb_axis_labelpad=10, shrink=0.75, extend='neither', cb_title=None,
               cb_orientation='vertical', cb_title_rotation=None, cb_title_style='normal', cb_title_size=10,
               cb_top_title_y=1, cb_ytitle_labelpad=10, cb_title_weight='normal', cb_top_title=False,
               cb_y_title=False, cb_top_title_pad=None, x_cb_top_title=0, cb_vmin=None,
               cb_vmax=None, cb_hard_bounds=False, cb_outline_width=None, cb_tick_number=5,
               cb_ticklabelsize=10, cb_tick_ndecimals=None, plot_label=None, legend=False,
               legend_loc='upper right', legend_bbox_to_anchor=None, legend_size=13,
               legend_weight='normal', legend_style='normal', legend_handleheight=None,
               legend_ncol=1, show=False, zorder=None, filename=None, dpi=None, suppress=True)
```

Bases: `mpl_plotter.two_d.methods.plot`

plot()

mock()



```
class heatmap (x=None, y=None, z=None, normvariant='SymLog', color=None, cmap='RdBu_r',
               alpha=None, norm=None, backend='Qt5Agg', font='serif', math_font='dejavuserif',
               font_color='black', font_size_increase=0, fig=None, ax=None, figsize=None,
               shape_and_position=111, resize_axes=True, scale=None, aspect=1,
               workspace_color=None, workspace_color2=None, background_color_figure='white',
               background_color_plot='white', background_alpha=1, style=None, light=None,
               dark=None, spine_color=None, spines_removed=(0, 0, 1, 1), x_upper_bound=None,
               x_lower_bound=None, y_upper_bound=None, y_lower_bound=None, x_bounds=None,
               y_bounds=None, demo_pad_plot=False, x_upper_resize_pad=0, x_lower_resize_pad=0,
               y_upper_resize_pad=0, y_lower_resize_pad=0, grid=True, grid_color='lightgrey',
               grid_lines='-.', title=None, title_size=12, title_y=1.025, title_weight=None, title_font=None,
               title_color=None, x_label=None, x_label_size=12, x_label_pad=10,
               x_label_rotation=None, x_label_weight=None, y_label=None, y_label_size=12,
               y_label_pad=10, y_label_rotation=None, y_label_weight=None, x_tick_number=5,
               y_tick_number=5, x_label_coords=None, y_label_coords=None, tick_color=None,
               tick_label_pad=5, ticks_where=(1, 1, 0, 0), tick_label_size=10, x_tick_label_size=None,
               y_tick_label_size=None, x_custom_tick_locations=None, y_custom_tick_locations=None,
               fine_tick_locations=True, x_custom_tick_labels=None, y_custom_tick_labels=None,
               x_date_tick_labels=False, date_format='%Y-%m-%d', tick_ndecimal=1,
               x_tick_ndecimal=None, y_tick_ndecimal=None, x_tick_rotation=None,
               y_tick_rotation=None, tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2,
               cb_axis_labelpad=10, shrink=0.75, extend='neither', cb_title=None,
               cb_orientation='vertical', cb_title_rotation=None, cb_title_style='normal', cb_title_size=10,
               cb_top_title_y=1, cb_ytitle_labelpad=10, cb_title_weight='normal', cb_top_title=False,
               cb_y_title=False, cb_top_title_pad=None, x_cb_top_title=0, cb_vmin=None,
               cb_vmax=None, cb_hard_bounds=False, cb_outline_width=None, cb_tick_number=5,
               cb_ticklabelsize=10, cb_tick_ndecimal=None, plot_label=None, legend=False,
               legend_loc='upper right', legend_bbox_to_anchor=None, legend_size=13,
               legend_weight='normal', legend_style='normal', legend_handleheight=None,
               legend_ncol=1, show=False, zorder=None, filename=None, dpi=None, suppress=True)
```

Bases: `mpl_plotter.two_d.methods.plot`

plot ()

mock ()



```

class quiver (x=None, y=None, u=None, v=None, color=None, cmap='RdBu_r', alpha=None,
              norm=None, rule=None, custom_rule=None, vector_width=0.01, vector_min_shaft=2,
              vector_length_threshold=0.1, backend='Qt5Agg', font='serif', math_font='dejavuserif',
              font_color='black', font_size_increase=0, fig=None, ax=None, figsize=None,
              shape_and_position=111, resize_axes=True, scale=None, aspect=1, workspace_color=None,
              workspace_color2=None, background_color_figure='white', background_color_plot='white',
              background_alpha=1, style=None, light=None, dark=None, spine_color=None,
              spines_removed=(0, 0, 1, 1), x_upper_bound=None, x_lower_bound=None,
              y_upper_bound=None, y_lower_bound=None, x_bounds=None, y_bounds=None,
              demo_pad_plot=False, x_upper_resize_pad=0, x_lower_resize_pad=0,
              y_upper_resize_pad=0, y_lower_resize_pad=0, grid=True, grid_color='lightgrey',
              grid_lines='-.', title=None, title_size=12, title_y=1.025, title_weight=None, title_font=None,
              title_color=None, x_label=None, x_label_size=12, x_label_pad=10, x_label_rotation=None,
              x_label_weight=None, y_label=None, y_label_size=12, y_label_pad=10,
              y_label_rotation=None, y_label_weight=None, x_tick_number=5, y_tick_number=5,
              x_label_coords=None, y_label_coords=None, tick_color=None, tick_label_pad=5,
              ticks_where=(1, 1, 0, 0), tick_label_size=10, x_tick_label_size=None,
              y_tick_label_size=None, x_custom_tick_locations=None, y_custom_tick_locations=None,
              fine_tick_locations=True, x_custom_tick_labels=None, y_custom_tick_labels=None,
              x_date_tick_labels=False, date_format='%Y-%m-%d', tick_ndecimals=1,
              x_tick_ndecimals=None, y_tick_ndecimals=None, x_tick_rotation=None,
              y_tick_rotation=None, tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2,
              cb_axis_labelpad=10, shrink=0.75, extend='neither', cb_title=None,
              cb_orientation='vertical', cb_title_rotation=None, cb_title_style='normal', cb_title_size=10,
              cb_top_title_y=1, cb_ytitle_labelpad=10, cb_title_weight='normal', cb_top_title=False,
              cb_y_title=False, cb_top_title_pad=None, x_cb_top_title=0, cb_vmin=None,
              cb_vmax=None, cb_hard_bounds=False, cb_outline_width=None, cb_tick_number=5,
              cb_ticklabels_size=10, cb_tick_ndecimals=None, plot_label=None, legend=False,
              legend_loc='upper right', legend_bbox_to_anchor=None, legend_size=13,
              legend_weight='normal', legend_style='normal', legend_handleheight=None, legend_ncol=1,
              show=False, zorder=None, filename=None, dpi=None, suppress=True)

```

Bases: `mpl_plotter.two_d.methods.plot`

`plot()`

`mock()`

`method_rule()`



```

class streamline (x=None, y=None, u=None, v=None, line_width=1, line_density=2, color=None,
                  cmap='RdBu_r', alpha=None, norm=None, backend='Qt5Agg', font='serif',
                  math_font='dejavuserif', font_color='black', font_size_increase=0, fig=None,
                  ax=None, figsize=None, shape_and_position=111, resize_axes=True, scale=None,
                  aspect=1, workspace_color=None, workspace_color2=None,
                  background_color_figure='white', background_color_plot='white',
                  background_alpha=1, style=None, light=None, dark=None, spine_color=None,
                  spines_removed=(0, 0, 1, 1), x_upper_bound=None, x_lower_bound=None,
                  y_upper_bound=None, y_lower_bound=None, x_bounds=None, y_bounds=None,
                  demo_pad_plot=False, x_upper_resize_pad=0, x_lower_resize_pad=0,
                  y_upper_resize_pad=0, y_lower_resize_pad=0, grid=True, grid_color='lightgrey',
                  grid_lines='-.', title=None, title_size=12, title_y=1.025, title_weight=None,
                  title_font=None, title_color=None, x_label=None, x_label_size=12, x_label_pad=10,
                  x_label_rotation=None, x_label_weight=None, y_label=None, y_label_size=12,
                  y_label_pad=10, y_label_rotation=None, y_label_weight=None, x_tick_number=5,
                  y_tick_number=5, x_label_coords=None, y_label_coords=None, tick_color=None,
                  tick_label_pad=5, ticks_where=(1, 1, 0, 0), tick_label_size=10,
                  x_tick_label_size=None, y_tick_label_size=None, x_custom_tick_locations=None,
                  y_custom_tick_locations=None, fine_tick_locations=True, x_custom_tick_labels=None,
                  y_custom_tick_labels=None, x_date_tick_labels=False, date_format='%Y-%m-%d',
                  tick_ndecimal=1, x_tick_ndecimal=None, y_tick_ndecimal=None,
                  x_tick_rotation=None, y_tick_rotation=None, tick_labels_where=(1, 1, 0, 0),
                  color_bar=False, cb_pad=0.2, cb_axis_labelpad=10, shrink=0.75, extend='neither',
                  cb_title=None, cb_orientation='vertical', cb_title_rotation=None,
                  cb_title_style='normal', cb_title_size=10, cb_top_title_y=1, cb_ytitle_labelpad=10,
                  cb_title_weight='normal', cb_top_title=False, cb_y_title=False, cb_top_title_pad=None,
                  x_cb_top_title=0, cb_vmin=None, cb_vmax=None, cb_hard_bounds=False,
                  cb_outline_width=None, cb_tick_number=5, cb_ticklabelsize=10,
                  cb_tick_ndecimal=None, plot_label=None, legend=False, legend_loc='upper right',
                  legend_bbox_to_anchor=None, legend_size=13, legend_weight='normal',
                  legend_style='normal', legend_handleheight=None, legend_ncol=1, show=False,
                  zorder=None, filename=None, dpi=None, suppress=True)

```

Bases: `mpl_plotter.two_d.methods.plot`

`plot()`

`mock()`

`method_rule()`



```

class fill_area (x=None, y=None, z=None, between=False, below=False, above=False, color=None,
                 cmap='RdBu_r', alpha=None, norm=None, backend='Qt5Agg', font='serif',
                 math_font='dejavuserif', font_color='black', font_size_increase=0, fig=None, ax=None,
                 figsize=None, shape_and_position=111, resize_axes=True, scale=None, aspect=1,
                 workspace_color=None, workspace_color2=None, background_color_figure='white',
                 background_color_plot='white', background_alpha=1, style=None, light=None,
                 dark=None, spine_color=None, spines_removed=(0, 0, 1, 1), x_upper_bound=None,
                 x_lower_bound=None, y_upper_bound=None, y_lower_bound=None, x_bounds=None,
                 y_bounds=None, demo_pad_plot=False, x_upper_resize_pad=0, x_lower_resize_pad=0,
                 y_upper_resize_pad=0, y_lower_resize_pad=0, grid=True, grid_color='lightgrey',
                 grid_lines='-', title=None, title_size=12, title_y=1.025, title_weight=None,
                 title_font=None, title_color=None, x_label=None, x_label_size=12, x_label_pad=10,
                 x_label_rotation=None, x_label_weight=None, y_label=None, y_label_size=12,
                 y_label_pad=10, y_label_rotation=None, y_label_weight=None, x_tick_number=5,
                 y_tick_number=5, x_label_coords=None, y_label_coords=None, tick_color=None,
                 tick_label_pad=5, ticks_where=(1, 1, 0, 0), tick_label_size=10, x_tick_label_size=None,
                 y_tick_label_size=None, x_custom_tick_locations=None, y_custom_tick_locations=None,
                 fine_tick_locations=True, x_custom_tick_labels=None, y_custom_tick_labels=None,
                 x_date_tick_labels=False, date_format='%Y-%m-%d', tick_ndecimal=1,
                 x_tick_ndecimal=None, y_tick_ndecimal=None, x_tick_rotation=None,
                 y_tick_rotation=None, tick_labels_where=(1, 1, 0, 0), color_bar=False, cb_pad=0.2,
                 cb_axis_labelpad=10, shrink=0.75, extend='neither', cb_title=None,
                 cb_orientation='vertical', cb_title_rotation=None, cb_title_style='normal',
                 cb_title_size=10, cb_top_title_y=1, cb_ytitle_labelpad=10, cb_title_weight='normal',
                 cb_top_title=False, cb_y_title=False, cb_top_title_pad=None, x_cb_top_title=0,
                 cb_vmin=None, cb_vmax=None, cb_hard_bounds=False, cb_outline_width=None,
                 cb_tick_number=5, cb_ticklabelsize=10, cb_tick_ndecimal=None, plot_label=None,
                 legend=False, legend_loc='upper right', legend_bbox_to_anchor=None, legend_size=13,
                 legend_weight='normal', legend_style='normal', legend_handleheight=None,
                 legend_ncol=1, show=False, zorder=None, filename=None, dpi=None, suppress=True)

```

Bases: `mpl_plotter.two_d.methods.plot`

plot()

Fill the region below the intersection of S and Z

i_below()

i_above()

intersection()

mock()

```

floating_text (ax, text, font='serif', x=0.5, y=0.5, size=20, weight='normal', color='darkred')

```



1.3 Placeholders

class MockData

Bases: object

filled_julia (*xyz_2d=False, xyz_3d=False, df=False*)

spirograph ()

sinewave ()

waterdrop ()

boltzman (*x, xmid, tau*)

Evaluate the boltzman function with midpoint *xmid* and time constant *tau* over *x*

1.4 Panes

panes (*x, y, f=None, fig=None, show=False, rows=1, top=None, bottom=None, left=None, right=None, wspace=None, hspace=None, **kwargs*)

Inputs

The table below displays the supported numerical input combinations, where:

- array: List or NumPy array with numerical values
- [...]: List containing ...
- result: <panes><curves per pane>

Arguments

Arguments are internally classified as FIGURE arguments, PLURAL arguments and CURVE arguments, namely:

- **Figure arguments** Select few arguments which may be input only once in the plotting process, so as to avoid conflicts. Ieg: passing *grid=True* twice (*plt.grid(...)*) will result in no grid being drawn. These are removed from the keyword arguments and used in the last *comparison* call.
- **Special arguments** Select few arguments (ieg: *plot_labels*), which satisfy the condition of being

lists with a length different to that of y

and which, for aesthetic purposes, must be applied only once.

In the case of *plot_labels*, if *plot_labels* is a list of length different to that of *y*, it is assumed that

- The *n*th curve of each pane shares a label with the *n*th curve of all other panes

and so a legend displaying the labels of the last pane will be displayed.



- **Plural arguments** Arguments with a keyword equal to any of the arguments which can be passed to the

line

2D plotter, in plural tense. The line plotter is chosen as it shares all general arguments with the other 2D plotter functions. The plural arguments are assumed to be

lists of length equal to the number of panes

and thus modify each pane. Ieg: `x_tick_labels=[1, 2, 3]` will set the tick labels of the x axes to 1, 2 and 3 respectively in a 3-pane plot.

- **Curve arguments** Curve arguments are passed as plurals to the comparison function, as they are

lists with a length different to that of y

(thus they can't apply to each pane) and they are assumed to have a length equal to the number of curves in each plot.

2.1 Plotting Methods

class canvas

Bases: object

method_backend()

method_fonts()

Fonts Reference:

- <https://matplotlib.org/2.0.2/users/customizing.html>

Pyplot method: `plt.rcParams['<category>.<item>'] = <>`

method_figure()

method_setup()

method_grid()

method_pane_fill()

class attributes

Bases: object

method_background_color()

method_workspace_style()

method_legend()

method_resize_axes()

method_title()

method_axis_labels()

method_spines()

method_ticks()

method_remove_axes()



```
    method_scale()

class plot
    Bases: mpl_plotter.three_d.methods.canvas, mpl_plotter.three_d.methods.attributes

    init()
    run()
    main()
    finish()
    method_save()
    method_show()

class color
    Bases: object
    method_cb()

class surf
    Bases: mpl_plotter.three_d.methods.color

    custom()
    method_lighting()
    method_edges_to_rgba()
```



```
class line (x=None, y=None, z=None, line_width=5, color='darkred', cmap='RdBu_r', alpha=1,
            x_scale=None, y_scale=None, z_scale=None, backend='Qt5Agg', font='serif',
            math_font='dejavuserif', font_color='black', font_size_increase=0, fig=None, ax=None,
            figsize=(5, 4), shape_and_position=111, azimuth=-138, elev=19, remove_axis=None,
            prune=None, resize_axes=True, aspect_equal=False, box_to_plot_pad=10, spines_juggled=(1,
            0, 2), spine_color=None, blend_edges=False, workspace_color=None, workspace_color2=None,
            background_color_figure='white', background_color_plot='white', background_alpha=1,
            style=None, light=None, dark=None, pane_fill=None, x_upper_bound=None,
            x_lower_bound=None, y_upper_bound=None, y_lower_bound=None, z_upper_bound=None,
            z_lower_bound=None, x_bounds=None, y_bounds=None, z_bounds=None,
            demo_pad_plot=False, x_upper_resize_pad=0, x_lower_resize_pad=0, y_upper_resize_pad=0,
            y_lower_resize_pad=0, z_upper_resize_pad=0, z_lower_resize_pad=0, show_axes=True,
            grid=True, grid_color='lightgrey', grid_lines='-.', title=None, title_weight='normal',
            title_size=12, title_y=1.025, title_color=None, title_font=None, x_label='x',
            x_label_weight='normal', x_label_size=12, x_label_pad=7, x_label_rotation=None, y_label='y',
            y_label_weight='normal', y_label_size=12, y_label_pad=7, y_label_rotation=None, z_label='z',
            z_label_weight='normal', z_label_size=12, z_label_pad=7, z_label_rotation=None,
            x_tick_number=5, x_tick_labels=None, x_custom_tick_labels=None,
            x_custom_tick_locations=None, y_tick_number=5, y_tick_labels=None,
            y_custom_tick_labels=None, y_custom_tick_locations=None, z_tick_number=5,
            z_tick_labels=None, z_custom_tick_labels=None, z_custom_tick_locations=None,
            x_tick_rotation=None, y_tick_rotation=None, z_tick_rotation=None, tick_color=None,
            x_tick_label_pad=4, y_tick_label_pad=4, z_tick_label_pad=4, x_tick_ndecimal=1,
            y_tick_ndecimal=1, z_tick_ndecimal=1, tick_label_size=10, x_tick_label_size=None,
            y_tick_label_size=None, z_tick_label_size=None, plot_label=None, legend=False,
            legend_loc='upper right', legend_size=13, legend_weight='normal', legend_style='normal',
            legend_handleheight=None, legend_ncol=1, show=False, newplot=False, filename=None,
            dpi=None, suppress=True)
```

Bases: `mpl_plotter.three_d.methods.plot`

plot ()

mock ()



```

class scatter (x=None, y=None, z=None, point_size=30, marker='o', facecolors=None, alpha=1,
               color='darkred', cmap='RdBu_r', color_rule=None, color_bar=False, cb_pad=0.1,
               extend='neither', cb_title=None, cb_orientation='vertical', cb_axis_labelpad=10,
               cb_tick_number=5, cb_tick_ndecimals=5, shrink=0.75, cb_outline_width=None,
               cb_title_rotation=None, cb_title_style='normal', cb_title_size=10, cb_top_title_y=1,
               cb_ytitle_labelpad=10, cb_title_weight='normal', cb_top_title=False, cb_y_title=False,
               cb_top_title_pad=None, x_cb_top_title=0, cb_vmin=None, cb_vmax=None,
               cb_ticklabelsize=10, cb_hard_bounds=False, x_scale=None, y_scale=None, z_scale=None,
               backend='Qt5Agg', font='serif', math_font='dejavuserif', font_color='black',
               font_size_increase=0, fig=None, ax=None, figsize=(5, 4), shape_and_position=111,
               azim=-138, elev=19, remove_axis=None, prune=None, resize_axes=True,
               aspect_equal=False, box_to_plot_pad=10, spines_juggled=(1, 0, 2), spine_color=None,
               blend_edges=False, workspace_color=None, workspace_color2=None,
               background_color_figure='white', background_color_plot='white', background_alpha=1,
               style=None, light=None, dark=None, pane_fill=None, x_upper_bound=None,
               x_lower_bound=None, y_upper_bound=None, y_lower_bound=None,
               z_upper_bound=None, z_lower_bound=None, x_bounds=None, y_bounds=None,
               z_bounds=None, demo_pad_plot=False, x_upper_resize_pad=0, x_lower_resize_pad=0,
               y_upper_resize_pad=0, y_lower_resize_pad=0, z_upper_resize_pad=0,
               z_lower_resize_pad=0, show_axes=True, grid=True, grid_color='lightgrey', grid_lines='-.',
               title=None, title_weight='normal', title_size=12, title_y=1.025, title_color=None,
               title_font=None, x_label='x', x_label_weight='normal', x_label_size=12, x_label_pad=7,
               x_label_rotation=None, y_label='y', y_label_weight='normal', y_label_size=12,
               y_label_pad=7, y_label_rotation=None, z_label='z', z_label_weight='normal',
               z_label_size=12, z_label_pad=7, z_label_rotation=None, x_tick_number=5,
               x_tick_labels=None, x_custom_tick_labels=None, x_custom_tick_locations=None,
               y_tick_number=5, y_tick_labels=None, y_custom_tick_labels=None,
               y_custom_tick_locations=None, z_tick_number=5, z_tick_labels=None,
               z_custom_tick_labels=None, z_custom_tick_locations=None, x_tick_rotation=None,
               y_tick_rotation=None, z_tick_rotation=None, tick_color=None, x_tick_label_pad=4,
               y_tick_label_pad=4, z_tick_label_pad=4, x_tick_ndecimals=1, y_tick_ndecimals=1,
               z_tick_ndecimals=1, tick_label_size=10, x_tick_label_size=None, y_tick_label_size=None,
               z_tick_label_size=None, plot_label=None, legend=False, legend_loc='upper right',
               legend_size=13, legend_weight='normal', legend_style='normal',
               legend_handleheight=None, legend_ncol=1, show=False, newplot=False, filename=None,
               dpi=None, suppress=True)

Bases: mpl_plotter.three_d.methods.plot, mpl_plotter.three_d.methods.
color

plot ()

mock ()

```



```

class surface (x=None, y=None, z=None, rstride=1, cstride=1, line_width=0.1, lighting=False,
               antialiased=False, shade=False, cmap='RdBu_r', cmap_lighting=None, color_rule=None,
               norm=None, color=None, color_bar=False, cb_pad=0.1, extend='neither', cb_title=None,
               cb_orientation='vertical', cb_axis_labelpad=10, cb_tick_number=5, cb_tick_ndecimals=5,
               shrink=0.75, cb_outline_width=None, cb_title_rotation=None, cb_title_style='normal',
               cb_title_size=10, cb_top_title_y=1, cb_ytitle_labelpad=10, cb_title_weight='normal',
               cb_top_title=False, cb_y_title=False, cb_top_title_pad=None, x_cb_top_title=0,
               cb_vmin=None, cb_vmax=None, cb_ticklabelsize=10, cb_hard_bounds=False, alpha=1,
               edge_color='black', edges_to_rgba=False, x_scale=None, y_scale=None, z_scale=None,
               backend='Qt5Agg', font='serif', math_font='dejavuserif', font_color='black',
               font_size_increase=0, fig=None, ax=None, figsize=(5, 4), shape_and_position=111,
               azim=-138, elev=19, remove_axis=None, prune=None, resize_axes=True,
               aspect_equal=False, box_to_plot_pad=10, spines_juggled=(1, 0, 2), spine_color=None,
               blend_edges=False, workspace_color=None, workspace_color2=None,
               background_color_figure='white', background_color_plot='white', background_alpha=1,
               style=None, light=None, dark=None, pane_fill=None, x_upper_bound=None,
               x_lower_bound=None, y_upper_bound=None, y_lower_bound=None,
               z_upper_bound=None, z_lower_bound=None, x_bounds=None, y_bounds=None,
               z_bounds=None, demo_pad_plot=False, x_upper_resize_pad=0, x_lower_resize_pad=0,
               y_upper_resize_pad=0, y_lower_resize_pad=0, z_upper_resize_pad=0,
               z_lower_resize_pad=0, show_axes=True, grid=True, grid_color='lightgrey', grid_lines='-.',
               title=None, title_weight='normal', title_size=12, title_y=1.025, title_color=None,
               title_font=None, x_label='x', x_label_weight='normal', x_label_size=12, x_label_pad=7,
               x_label_rotation=None, y_label='y', y_label_weight='normal', y_label_size=12,
               y_label_pad=7, y_label_rotation=None, z_label='z', z_label_weight='normal',
               z_label_size=12, z_label_pad=7, z_label_rotation=None, x_tick_number=5,
               x_tick_labels=None, x_custom_tick_labels=None, x_custom_tick_locations=None,
               y_tick_number=5, y_tick_labels=None, y_custom_tick_labels=None,
               y_custom_tick_locations=None, z_tick_number=5, z_tick_labels=None,
               z_custom_tick_labels=None, z_custom_tick_locations=None, x_tick_rotation=None,
               y_tick_rotation=None, z_tick_rotation=None, tick_color=None, x_tick_label_pad=4,
               y_tick_label_pad=4, z_tick_label_pad=4, x_tick_ndecimals=1, y_tick_ndecimals=1,
               z_tick_ndecimals=1, tick_label_size=10, x_tick_label_size=None, y_tick_label_size=None,
               z_tick_label_size=None, plot_label=None, legend=False, legend_loc='upper right',
               legend_size=13, legend_weight='normal', legend_style='normal',
               legend_handleheight=None, legend_ncol=1, show=False, newplot=False, filename=None,
               dpi=None, suppress=True)

Bases: mpl_plotter.three_d.methods.plot, mpl_plotter.three_d.methods.
surf

plot ()

mock ()

floating_text (ax, text, font, x, y, z, size=20, weight='normal', color='darkred')

```



2.2 Placeholders

```
class MockData
    Bases: object

    waterdrop3d()

    random3d()

    hill()
```

3.1 Methods

complementary (*color*, *fmt*='hex')

Return complementary of [R, G, B] or hex color.

Parameters **fmt** (*string*) – Output format: ‘hex’ or ‘rgb’.

delta (*color*, *factor*, *fmt*='hex')

Darker or lighten the input color by a percentage of <factor> ([-1, 1]) of the color spectrum (0-255).

Parameters

- **fmt** (*string*) – Output format: ‘hex’ or ‘rgb’.
- **factor** (*float*) – [-1, 1] Measure in which the color will be modified.

mapstack (*maps*, *fractions*=None, *ranges*=None)

Create a colormap stacking an arbitrary number of conventional Matplotlib colormaps.

Parameters

- **maps** (*list of str*) – List of colormap NAMES
- **fractions** (*list of float*) – For each original colormap, the fraction it'll take of the merged colormap. [0<fr_0<1, ...]
- **ranges** (*list of tuple*) – For each original colormap, the range taken. [(0=<min<1, 0<max<=1)_0, ...]

Returns `mpl.colors.LinearSegmentedColormap`



3.2 Color Schemes

`colorscheme_one()`

`custom (red, green, blue, name='coolheat', n=1024)`

Parameters

- **red** – List of (red fraction, y0, y1) tuples
- **green** – List of (red fraction, y0, y1)
- **blue** – List of (red fraction, y0, y1)
- **name** – Colormap name
- **n** – RGB quantization levels

Returns Colormap

4.1 Custom

```
class two_d(preset=None, preset_dir="", preset_name='preset_2d')
    Bases: object

    class line(x=None, y=None, **kwargs)
        Bases: mpl_plotter.two_d.methods.line

    class scatter(x=None, y=None, **kwargs)
        Bases: mpl_plotter.two_d.methods.scatter

    class heatmap(x=None, y=None, z=None, **kwargs)
        Bases: mpl_plotter.two_d.methods.heatmap

    class quiver(x=None, y=None, u=None, v=None, **kwargs)
        Bases: mpl_plotter.two_d.methods.quiver

    class streamline(x=None, y=None, u=None, v=None, **kwargs)
        Bases: mpl_plotter.two_d.methods.streamline

    class fill_area(x=None, y=None, z=None, **kwargs)
        Bases: mpl_plotter.two_d.methods.fill_area

class three_d(preset_dir="", preset_name='preset_3d', preset=None)
    Bases: object

    class line(x=None, y=None, z=None, **kwargs)
        Bases: mpl_plotter.three_d.methods.line

    class scatter(x=None, y=None, z=None, **kwargs)
        Bases: mpl_plotter.three_d.methods.scatter

    class surface(x=None, y=None, z=None, **kwargs)
        Bases: mpl_plotter.three_d.methods.surface

find_preset(dest, preset_name)

make_preset_directory(preset_dest, preset_name)

generate_preset_2d(preset_dest="", overwrite=False, disable_warning=False, preset_name='preset_2d')
```



Parameters

- **preset_dest** – Preset destination directory
- **overwrite** – Overwrite found presets automatically
- **disable_warning** – Disable overwriting warning
- **preset_name** – Name of preset to be created

Returns None

```
generate_preset_3d(preset_dest="", overwrite=False, disable_warning=False, preset_name='preset_3d')
```

Parameters

- **preset_dest** – Preset destination directory
- **overwrite** – Overwrite found presets automatically
- **disable_warning** – Disable overwriting warning
- **preset_name** – Name of preset to be created

Returns None

4.2 Precision

4.3 Publication

PYTHON MODULE INDEX

C

`mpl_plotter.color`, [17](#)
`mpl_plotter.color.functions`, [18](#)
`mpl_plotter.color.schemes`, [18](#)

p

`mpl_plotter.presets`, [19](#)
`mpl_plotter.presets.custom`, [20](#)
`mpl_plotter.presets.data`, [21](#)
`mpl_plotter.presets.data.precision`,
 [21](#)
`mpl_plotter.presets.data.publica-`
 `tion`, [21](#)
`mpl_plotter.presets.precision`, [21](#)
`mpl_plotter.presets.publication`, [21](#)

t

`mpl_plotter.three_d`, [11](#)
`mpl_plotter.three_d.methods`, [12](#)
`mpl_plotter.three_d.mock`, [16](#)
`mpl_plotter.two_d`, [1](#)
`mpl_plotter.two_d.comparison`, [2](#)
`mpl_plotter.two_d.methods`, [3](#)
`mpl_plotter.two_d.mock`, [9](#)
`mpl_plotter.two_d.panes`, [10](#)

A

`attributes` (class in `mpl_plotter.three_d.methods`), 12

`attributes` (class in `mpl_plotter.two_d.methods`), 3

B

`boltzman` () (*MockData method*), 10

C

`canvas` (class in `mpl_plotter.three_d.methods`), 12

`canvas` (class in `mpl_plotter.two_d.methods`), 3

`color` (class in `mpl_plotter.three_d.methods`), 13

`colorscheme_one` () (in module `mpl_plotter.color.schemes`), 19

`comparison` () (in module `mpl_plotter.two_d.comparison`), 2

`complementary` () (in module `mpl_plotter.color.functions`), 18

`custom` () (in module `mpl_plotter.color.schemes`), 19

`custom` () (*surf method*), 13

D

`delta` () (in module `mpl_plotter.color.functions`), 18

F

`fill_area` (class in `mpl_plotter.two_d.methods`), 8

`filled_julia` () (*MockData method*), 10

`find_preset` () (in module `mpl_plotter.presets.custom`), 20

`finish` () (*plot method*), 4, 13

`floating_text` () (in module `mpl_plotter.three_d.methods`), 16

`floating_text` () (in module `mpl_plotter.two_d.methods`), 9

G

`generate_preset_2d` () (in module `mpl_plotter.presets.custom`), 20

`generate_preset_3d` () (in module `mpl_plotter.presets.custom`), 21

H

`heatmap` (class in `mpl_plotter.two_d.methods`), 5

`hill` () (*MockData method*), 17

I

`i_above` () (*fill_area method*), 9

`i_below` () (*fill_area method*), 9

`init` () (*plot method*), 4, 13

`intersection` () (*fill_area method*), 9

L

`line` (class in `mpl_plotter.three_d.methods`), 13

`line` (class in `mpl_plotter.two_d.methods`), 4

M

`main` () (*plot method*), 4, 13

`make_preset_directory` () (in module `mpl_plotter.presets.custom`), 20

`mapstack` () (in module `mpl_plotter.color.functions`), 18

`method_axis_labels` () (*attributes method*), 3, 12

`method_backend` () (*canvas method*), 3, 12

`method_background_color` () (*attributes method*), 3, 12

`method_cb` () (*attributes method*), 3

`method_cb` () (*color method*), 13

`method_edges_to_rgba` () (*surf method*), 13

`method_figure` () (*canvas method*), 3, 12

`method_fonts` () (*canvas method*), 3, 12

`method_grid` () (*canvas method*), 3, 12

`method_legend` () (*attributes method*), 3, 12

`method_lighting` () (*surf method*), 13

`method_pane_fill` () (*canvas method*), 12



`method_remove_axes()` (*attributes method*), 12
`method_resize_axes()` (*attributes method*), 3, 12
`method_rule()` (*quiver method*), 7
`method_rule()` (*streamline method*), 8
`method_save()` (*plot method*), 4, 13
`method_scale()` (*attributes method*), 12
`method_setup()` (*canvas method*), 3, 12
`method_show()` (*plot method*), 4, 13
`method_spines()` (*attributes method*), 3, 12
`method_ticks()` (*attributes method*), 3, 12
`method_title()` (*attributes method*), 3, 12
`method_workspace_style()` (*attributes method*), 3, 12
`mock()` (*fill_area method*), 9
`mock()` (*heatmap method*), 6
`mock()` (*line method*), 4, 14
`mock()` (*quiver method*), 7
`mock()` (*scatter method*), 5, 15
`mock()` (*streamline method*), 8
`mock()` (*surface method*), 16
`MockData` (*class in mpl_plotter.three_d.mock*), 17
`MockData` (*class in mpl_plotter.two_d.mock*), 10
module
 `mpl_plotter.color`, 17
 `mpl_plotter.color.functions`, 18
 `mpl_plotter.color.schemes`, 18
 `mpl_plotter.presets`, 19
 `mpl_plotter.presets.custom`, 20
 `mpl_plotter.presets.data`, 21
 `mpl_plotter.presets.data.precision`, 21
 `mpl_plotter.presets.data.publication`, 21
 `mpl_plotter.presets.precision`, 21
 `mpl_plotter.presets.publication`, 21
 `mpl_plotter.three_d`, 11
 `mpl_plotter.three_d.methods`, 12
 `mpl_plotter.three_d.mock`, 16
 `mpl_plotter.two_d`, 1
 `mpl_plotter.two_d.comparison`, 2
 `mpl_plotter.two_d.methods`, 3
 `mpl_plotter.two_d.mock`, 9
 `mpl_plotter.two_d.panes`, 10
`mpl_plotter.color`
 module, 17
 `mpl_plotter.color.functions`
 module, 18
 `mpl_plotter.color.schemes`
 module, 18
 `mpl_plotter.presets`
 module, 19
 `mpl_plotter.presets.custom`
 module, 20
 `mpl_plotter.presets.data`
 module, 21
 `mpl_plotter.presets.data.precision`
 module, 21
 `mpl_plotter.presets.data.publication`
 module, 21
 `mpl_plotter.presets.precision`
 module, 21
 `mpl_plotter.presets.publication`
 module, 21
 `mpl_plotter.three_d`
 module, 11
 `mpl_plotter.three_d.methods`
 module, 12
 `mpl_plotter.three_d.mock`
 module, 16
 `mpl_plotter.two_d`
 module, 1
 `mpl_plotter.two_d.comparison`
 module, 2
 `mpl_plotter.two_d.methods`
 module, 3
 `mpl_plotter.two_d.mock`
 module, 9
 `mpl_plotter.two_d.panes`
 module, 10

P

`panes()` (*in module mpl_plotter.two_d.panes*), 10
 `plot` (*class in mpl_plotter.three_d.methods*), 13
 `plot` (*class in mpl_plotter.two_d.methods*), 4
 `plot()` (*fill_area method*), 9
 `plot()` (*heatmap method*), 6
 `plot()` (*line method*), 4, 14
 `plot()` (*quiver method*), 7
 `plot()` (*scatter method*), 5, 15
 `plot()` (*streamline method*), 8
 `plot()` (*surface method*), 16



Q

`quiver` (class in `mpl_plotter.two_d.methods`), 6

R

`random3d()` (*MockData method*), 17

`run()` (*plot method*), 4, 13

S

`scatter` (class in `mpl_plotter.three_d.methods`), 14

`scatter` (class in `mpl_plotter.two_d.methods`), 5

`sinewave()` (*MockData method*), 10

`spirograph()` (*MockData method*), 10

`streamline` (class in `mpl_plotter.two_d.methods`), 7

`surf` (class in `mpl_plotter.three_d.methods`), 13

`surface` (class in `mpl_plotter.three_d.methods`), 15

T

`three_d` (class in `mpl_plotter.presets.custom`), 20

`three_d.line` (class in `mpl_plotter.presets.custom`),
20

`three_d.scatter` (class in `mpl_plotter.presets.custom`), 20

`three_d.surface` (class in `mpl_plotter.presets.custom`), 20

`two_d` (class in `mpl_plotter.presets.custom`), 20

`two_d.fill_area` (class in `mpl_plotter.presets.custom`), 20

`two_d.heatmap` (class in `mpl_plotter.presets.custom`), 20

`two_d.line` (class in `mpl_plotter.presets.custom`), 20

`two_d.quiver` (class in `mpl_plotter.presets.custom`),
20

`two_d.scatter` (class in `mpl_plotter.presets.custom`), 20

`two_d.streamline` (class in `mpl_plotter.presets.custom`), 20

W

`waterdrop()` (*MockData method*), 10

`waterdrop3d()` (*MockData method*), 17