

QBank Scaffold v5:

- # - Admin API + Admin UI for Simpson–Hetter sh_p tuning
- # - Nightly re-estimation job for sh_p
- # - E2E tests: pytest (API) + Playwright (student UI)
- # - Rich Looker explore (topic mastery, blueprint coverage)
- # - Metabase dashboard JSON with filters + import script
- # - Feature flags & cohort-based A/B for selector strategies
- #
- # Outputs /mnt/data/qbank_scaffold_v5.zip

```
import os, zipfile, pathlib, textwrap, json
```

```
ROOT = "/mnt/data/qbank_scaffold_v5"
os.makedirs(ROOT, exist_ok=True)
```

```
def write(path, content):
    os.makedirs(os.path.dirname(path), exist_ok=True)
    with open(path, "w", encoding="utf-8") as f:
        f.write(textwrap.dedent(content))
```

```
# ----- README -----
write(f"{ROOT}/README.md", """
# QBank Backend Scaffold (v5)
```

Adds:

- **Admin controls** for Simpson–Hetter:
 - API: list items + **set sh_p** , **re-estimate** sh_p from recent exposures.
 - Admin UI (Next.js): table to tweak sh_p inline and trigger re-estimation.
 - Nightly job script: recalculates sh_p (greedy heuristic towards target τ).
- **E2E tests**:
 - Backend (pytest): seeds a demo item, exercises author → publish → quiz → admin endpoints.
 - Student UI (Playwright): obtains a token, creates a quiz, answers one item.
- **Analytics UX**:
 - Looker: richer explores for **topic mastery** and **blueprint coverage**.
 - Metabase: dashboard JSON with date + exam filters, import script.
- **Feature flags & A/B**:
 - Tables for `feature_flags` and `cohort_assignments`.
 - Selector strategy chosen per user cohort (`vanilla` vs `sympson_hetter`).

Quick Start (delta on v4)

1) DB init (extras)

```
```bash
```

```
psql postgresql://qbank:qbank@localhost:5432/qbank -f ./sql/
```

```
item_exposure_control.sql
psql postgresql://qbank:qbank@localhost:5432/qbank -f ./sql/feature_flags.sql
Backend
```

```
bash
Always show details
```

```
Copy
cd qbank-backend
pip install -r requirements.txt
uvicorn app.main:app --reload
Admin UI
```

```
bash
Always show details
```

```
Copy
cd admin-ui && npm install && npm run dev # http://localhost:4000
Nightly job (example)
```

```
bash
Always show details
```

```
Copy
python analytics/cron/reestimate_sh.py --dsn postgresql://
qbank:qbank@localhost:5432/qbank --tau 0.2 --days 7
```

Notes

Re-estimator is a pragmatic heuristic (not full SH iterative simulation). It nudges `sh_p` toward a max exposure  $\tau$  using observed proportions.

Feature flags: set `selector_strategy` to `sympson_hetter` for experiment cohorts.  
""")

```
----- SQL: feature flags + cohorts -----
write(f"{ROOT}/sql/feature_flags.sql", """
CREATE TABLE IF NOT EXISTS feature_flags (
 key TEXT PRIMARY KEY,
 enabled BOOLEAN NOT NULL DEFAULT TRUE,
 value_json JSONB NOT NULL DEFAULT '{}':jsonb,
 updated_at TIMESTAMPTZ NOT NULL DEFAULT now()
);
```

```
CREATE TABLE IF NOT EXISTS cohort_assignments (
 user_id TEXT NOT NULL,
```

```

cohort_key TEXT NOT NULL, -- e.g., 'selector_strategy'
cohort_value TEXT NOT NULL, -- e.g., 'sympson_hetter' or 'vanilla'
assigned_at TIMESTAMPTZ NOT NULL DEFAULT now(),
PRIMARY KEY(user_id, cohort_key)
);
"""
)

```

----- Backend requirements (add pytest for tests) -----

```

write(f"{ROOT}/qbank-backend/requirements.txt", """
fastapi==0.115.0
uvicorn==0.30.6
pydantic==2.8.2
python-dotenv==1.0.1
redis==5.0.8
kafka-python==2.0.2
psycpg2-binary==2.9.9
SQLAlchemy==2.0.32
PyJWT==2.9.0
alembic==1.13.2
black==24.8.0
flake8==7.1.1
pytest==8.3.2
httpx==0.27.2
""")

```

----- Backend: models (extend v4 with flags/cohorts) -----

```

write(f"{ROOT}/qbank-backend/app/models/orm.py", """
from sqlalchemy.orm import DeclarativeBase, Mapped, mapped_column
from sqlalchemy import BigInteger, Integer, String, Text, Boolean, ForeignKey,
JSON, Float

```

```

class Base(DeclarativeBase): pass

```

```

class Topic(Base):
 tablename = "topics"
 id: Mapped[int] = mapped_column(BigInteger, primary_key=True)
 tenant_id: Mapped[str] = mapped_column(String)
 parent_id: Mapped[int | None] = mapped_column(BigInteger,
 ForeignKey("topics.id"), nullable=True)
 name: Mapped[str] = mapped_column(String)
 blueprint_code: Mapped[str | None] = mapped_column(String, nullable=True)

```

```

class Question(Base):
 tablename = "questions"

```

```
id: Mapped[int] = mapped_column(BigInteger, primary_key=True)
tenant_id: Mapped[str] = mapped_column(String)
external_ref: Mapped[str | None] = mapped_column(String, nullable=True)
created_by: Mapped[str] = mapped_column(String)
is_deleted: Mapped[bool] = mapped_column(Boolean, default=False)
```

```
class QuestionVersion(Base):
 tablename = "question_versions"
 id: Mapped[int] = mapped_column(BigInteger, primary_key=True)
 question_id: Mapped[int] = mapped_column(BigInteger,
 ForeignKey("questions.id"))
 version: Mapped[int] = mapped_column(Integer)
 state: Mapped[str] = mapped_column(String)
 stem_md: Mapped[str] = mapped_column(Text)
 lead_in: Mapped[str] = mapped_column(Text)
 rationale_md: Mapped[str] = mapped_column(Text)
 difficulty_label: Mapped[str | None] = mapped_column(String, nullable=True)
 bloom_level: Mapped[int | None] = mapped_column(Integer, nullable=True)
 topic_id: Mapped[int | None] = mapped_column(BigInteger,
 ForeignKey("topics.id"), nullable=True)
 tags: Mapped[dict] = mapped_column(JSON)
 assets: Mapped[list] = mapped_column(JSON)
 references: Mapped[list] = mapped_column(JSON)
```

```
class QuestionOption(Base):
 tablename = "question_options"
 id: Mapped[int] = mapped_column(BigInteger, primary_key=True)
 question_version_id: Mapped[int] = mapped_column(BigInteger,
 ForeignKey("question_versions.id"))
 option_label: Mapped[str] = mapped_column(String(1))
 option_text_md: Mapped[str] = mapped_column(Text)
 is_correct: Mapped[bool] = mapped_column(Boolean)
```

```
class QuestionPublication(Base):
 tablename = "question_publications"
 id: Mapped[int] = mapped_column(BigInteger, primary_key=True)
 question_id: Mapped[int] = mapped_column(BigInteger,
 ForeignKey("questions.id"))
 live_version: Mapped[int] = mapped_column(Integer)
 exam_code: Mapped[str] = mapped_column(String)
 tenant_id: Mapped[str] = mapped_column(String)
```

```
class QuizSession(Base):
 tablename = "quiz_sessions"
```

```
id: Mapped[str] = mapped_column(String, primary_key=True)
user_id: Mapped[str] = mapped_column(String)
tenant_id: Mapped[str] = mapped_column(String)
mode: Mapped[str] = mapped_column(String)
adaptive: Mapped[bool] = mapped_column(Boolean, default=True)
exam_code: Mapped[str | None] = mapped_column(String, nullable=True)
```

```
class QuizItem(Base):
 tablename = "quiz_items"
 id: Mapped[int] = mapped_column(BigInteger, primary_key=True)
 quiz_id: Mapped[str] = mapped_column(String)
 question_id: Mapped[int] = mapped_column(BigInteger)
 version: Mapped[int] = mapped_column(Integer)
 position: Mapped[int] = mapped_column(Integer)
```

```
class UserResponse(Base):
 tablename = "user_responses"
 id: Mapped[int] = mapped_column(BigInteger, primary_key=True)
 quiz_id: Mapped[str] = mapped_column(String)
 user_id: Mapped[str] = mapped_column(String)
 question_id: Mapped[int] = mapped_column(BigInteger)
 version: Mapped[int] = mapped_column(Integer)
 option_label: Mapped[str] = mapped_column(String(1))
 is_correct: Mapped[bool] = mapped_column(Boolean)
 time_taken_ms: Mapped[int | None] = mapped_column(Integer, nullable=True)
```

```
class ItemCalibration(Base):
 tablename = "item_calibration"
 question_id: Mapped[int] = mapped_column(BigInteger, primary_key=True)
 version: Mapped[int] = mapped_column(Integer, primary_key=True)
 model: Mapped[str] = mapped_column(String, primary_key=True)
 a: Mapped[float | None] = mapped_column(Float)
 b: Mapped[float | None] = mapped_column(Float)
 c: Mapped[float | None] = mapped_column(Float)
 n_respondents: Mapped[int | None] = mapped_column(Integer)
```

```
class ItemExposureControl(Base):
 tablename = "item_exposure_control"
 question_id: Mapped[int] = mapped_column(BigInteger, primary_key=True)
 version: Mapped[int] = mapped_column(Integer, primary_key=True)
 sh_p: Mapped[float] = mapped_column(Float) # 0..1
```

```
class FeatureFlag(Base):
 tablename = "feature_flags"
```

```
key: Mapped[str] = mapped_column(String, primary_key=True)
enabled: Mapped[bool] = mapped_column(Boolean, default=True)
value_json: Mapped[dict] = mapped_column(JSON)
```

```
class CohortAssignment(Base):
 tablename = "cohort_assignments"
 user_id: Mapped[str] = mapped_column(String, primary_key=True)
 cohort_key: Mapped[str] = mapped_column(String, primary_key=True)
 cohort_value: Mapped[str] = mapped_column(String)
 """
```

----- Backend core (same as v4) -----

```
write(f"{ROOT}/qbank-backend/app/core/config.py", """
import os
from dotenv import load_dotenv
load_dotenv()
```

```
DATABASE_URL = os.getenv("DATABASE_URL", "postgresql+psycopg2://
qbank:qbank@localhost:5432/qbank")
REDIS_URL = os.getenv("REDIS_URL", "redis://localhost:6379/0")
KAFKA_BOOTSTRAP = os.getenv("KAFKA_BOOTSTRAP", "localhost:9092")
KAFKA_TOPIC_EVENTS = os.getenv("KAFKA_TOPIC_EVENTS", "events.qbank")
TENANT_ID = os.getenv("APP_TENANT_ID",
"00000000-0000-0000-0000-000000000001")
APP_SECRET = os.getenv("APP_SECRET", "dev-secret-change-me")
MAX_DAILY_EXPOSURES = int(os.getenv("MAX_DAILY_EXPOSURES", "500"))
""")
```

```
write(f"{ROOT}/qbank-backend/app/core/database.py", """
from sqlalchemy import create_engine
from sqlalchemy.orm import sessionmaker
from app.core.config import DATABASE_URL
```

```
engine = create_engine(DATABASE_URL, future=True, pool_pre_ping=True)
SessionLocal = sessionmaker(bind=engine, autocommit=False, autoflush=False,
future=True)
```

```
def get_db():
 db = SessionLocal()
 try:
 yield db
 finally:
 db.close()
 """
```

```

write(f"{ROOT}/qbank-backend/app/core/cache.py", """
import redis
from datetime import datetime
from app.core.config import REDIS_URL, MAX_DAILY_EXPOSURES

redis_client = redis.Redis.from_url(REDIS_URL, decode_responses=True)

def exposure_key(question_id: int, version: int) -> str:
 day = datetime.utcnow().strftime("%Y%m%d")
 return f"exp:{day}:{question_id}:{version}"

def can_serve(question_id: int, version: int) -> bool:
 key = exposure_key(question_id, version)
 count = int(redis_client.get(key) or 0)
 return count < MAX_DAILY_EXPOSURES

def bump_exposure(question_id: int, version: int) -> None:
 key = exposure_key(question_id, version)
 pipe = redis_client.pipeline()
 pipe.incr(key, 1)
 pipe.expire(key, 86400) # 1 day
 pipe.execute()
""")

write(f"{ROOT}/qbank-backend/app/core/events.py", """
import json
from uuid import uuid4
from datetime import datetime, timezone
from kafka import KafkaProducer
from app.core.config import KAFKA_BOOTSTRAP, KAFKA_TOPIC_EVENTS

producer = KafkaProducer(
 bootstrap_servers=KAFKA_BOOTSTRAP,
 value_serializer=lambda v: json.dumps(v).encode("utf-8"),
 key_serializer=lambda k: (k or "").encode("utf-8"),
 linger_ms=50, acks='1'
)

def emit(event_type: str, payload: dict):
 env = {"event_id": str(uuid4()), "event_type": event_type, "timestamp":
datetime.now(timezone.utc).isoformat(), **payload}
 producer.send(KAFKA_TOPIC_EVENTS, key=env["event_id"], value=env)
""")

```

```

write(f"{ROOT}/qbank-backend/app/core/auth.py", """
from fastapi import Depends, HTTPException, status
from fastapi.security import HTTPBearer, HTTPAuthorizationCredentials
from pydantic import BaseModel
from typing import List
import jwt
from datetime import datetime, timedelta, timezone
from app.core.config import APP_SECRET

class TokenData(BaseModel):
 sub: str
 roles: List[str]

bearer = HTTPBearer()

def create_token(user_id: str, roles: List[str], ttl_minutes: int = 120) -> str:
 now = datetime.now(timezone.utc)
 payload = {"sub": user_id, "roles": roles, "iat": int(now.timestamp()), "exp":
 int((now + timedelta(minutes=ttl_minutes)).timestamp())}
 return jwt.encode(payload, APP_SECRET, algorithm="HS256")

def get_current_user(creds: HTTPAuthorizationCredentials = Depends(bearer)) ->
TokenData:
 try:
 payload = jwt.decode(creds.credentials, APP_SECRET, algorithms=["HS256"])
 return TokenData(sub=payload["sub"], roles=payload.get("roles", []))
 except Exception:
 raise HTTPException(status_code=status.HTTP_401_UNAUTHORIZED,
 detail="Invalid or expired token")

def require_roles(*required: str):
 def checker(user: TokenData = Depends(get_current_user)):
 roles = set(user.roles)
 if not roles.intersection(set(required)):
 raise HTTPException(status_code=403, detail="Insufficient role")
 return user
 return checker
""")

----- Backend: services (selector choosing based on cohort flags) -----
write(f"{ROOT}/qbank-backend/app/services/selector_choice.py", """
from sqlalchemy.orm import Session
from sqlalchemy import select

```



```
from app.models.orm import FeatureFlag, CohortAssignment
```

```
def get_selector_for_user(db: Session, user_id: str) -> str:
default from feature flag
ff = db.scalar(select(FeatureFlag).where(FeatureFlag.key == "selector_strategy"))
default = "sympson_hetter" if (ff and ff.enabled and (ff.value_json or
{}).get("value") == "sympson_hetter") else "vanilla"
cohort =
db.scalar(select(CohortAssignment).where(CohortAssignment.user_id==user_id,
CohortAssignment.cohort_key=="selector_strategy"))
return cohort.cohort_value if cohort else default
"""
```

```
write(f"{ROOT}/qbank-backend/app/services/adaptive.py", """
import math, random
from typing import List, Dict, Optional
D = 1.7
```

```
def logistic(x: float) -> float: return 1.0 / (1.0 + math.exp(-x))
def prob_3pl(theta: float, a: float, b: float, c: float) -> float:
return c + (1.0 - c) * logistic(D * a * (theta - b))
def fisher_info_3pl(theta: float, a: float, b: float, c: float) -> float:
P = prob_3pl(theta, a, b, c); Q = 1.0 - P
if P<=0 or Q<=0 or (1.0-c)<=0: return 0.0
return (D2)*(a2)(Q/P)((P-c)/(1.0-c))**2
```

```
def select_vanilla(candidates: List[Dict], theta: float) -> Optional[Dict]:
best, best_l = None, -1
for it in candidates:
l = fisher_info_3pl(theta, it.get("a",1.0), it.get("b",0.0), it.get("c",0.2))
if l > best_l: best_l, best = l, it
return best
```

```
def select_sympson_hetter(candidates: List[Dict], theta: float) -> Optional[Dict]:
scored = []
for it in candidates:
l = fisher_info_3pl(theta, it.get("a",1.0), it.get("b",0.0), it.get("c",0.2))
scored.append((l, it))
scored.sort(key=lambda x: x[0], reverse=True)
for _, it in scored:
sh_p = it.get("sh_p", 1.0)
if random.random() <= max(0.0, min(1.0, sh_p)):
return it
return scored[0][1] if scored else None
```

```
""")
```

```
----- Backend: admin API -----
```

```
write(f"{ROOT}/qbank-backend/app/api/admin.py", """)
from fastapi import APIRouter, Depends, HTTPException
from pydantic import BaseModel
from typing import List, Optional
from sqlalchemy.orm import Session
from sqlalchemy import select, text
```

```
from app.core.database import get_db
from app.core.auth import require_roles
from app.models.orm import ItemExposureControl, QuestionVersion
```

```
router = APIRouter()
```

```
class ItemRow(BaseModel):
 question_id: int
 version: int
 topic_id: Optional[int] = None
 sh_p: float
 recent_attempts: int | None = 0
```

```
@router.get("/exposure/items", response_model=List[ItemRow],
dependencies=[Depends(require_roles("admin"))])
def list_items(limit: int = 100, db: Session = Depends(get_db)):
 rows = db.execute(text("""
SELECT qv.question_id, qv.version, qv.topic_id,
COALESCE(iec.sh_p, 1.0) as sh_p,
(SELECT count(*) FROM user_responses ur WHERE ur.question_id=qv.question_id
AND ur.version=qv.version AND ur.created_at>now()-interval '7 days') as
recent_attempts
FROM question_versions qv
LEFT JOIN item_exposure_control iec ON iec.question_id=qv.question_id AND
iec.version=qv.version
WHERE qv.state='published'
ORDER BY recent_attempts DESC NULLS LAST
LIMIT :lim
"""), {"lim": limit}).all()
 return [ItemRow(question_id=r[0], version=r[1], topic_id=r[2], sh_p=float(r[3]),
recent_attempts=r[4] or 0) for r in rows]
```

```
class SetSh(BaseModel):
 question_id: int
```

version: int  
sh\_p: float

```
@router.post("/exposure/set", dependencies=[Depends(require_roles("admin"))])
def set_sh(payload: SetSh, db: Session = Depends(get_db)):
 if payload.sh_p < 0 or payload.sh_p > 1: raise HTTPException(400, "sh_p must be
 in [0,1]")
 row = db.get(ItemExposureControl, {"question_id": payload.question_id, "version":
 payload.version})
 if row:
 row.sh_p = payload.sh_p
 else:
 row = ItemExposureControl(question_id=payload.question_id,
 version=payload.version, sh_p=payload.sh_p)
 db.add(row)
 db.commit()
 return {"ok": True}
```

```
class Reestimate(BaseModel):
 tau: float = 0.2
 days: int = 7
 floor: float = 0.05
 ceil: float = 1.0
```

```
@router.post("/exposure/reestimate",
dependencies=[Depends(require_roles("admin"))])
def reestimate(payload: Reestimate, db: Session = Depends(get_db)):
 # Heuristic: compute each item's share of attempts; if share>tau, reduce sh_p by
 tau/share; else gently increase.
 rows = db.execute(text(f"""
 WITH atts AS (
 SELECT question_id, version, count(*)::float AS c
 FROM user_responses
 WHERE created_at > now() - interval '{payload.days} days'
 GROUP BY question_id, version
), totals AS (
 SELECT sum(c) AS total FROM atts
)
 SELECT a.question_id, a.version, a.c / NULLIF(t.total,0) AS share,
 COALESCE(e.sh_p,1.0) AS sh_p
 FROM atts a CROSS JOIN totals t
 LEFT JOIN item_exposure_control e ON e.question_id=a.question_id AND
 e.version=a.version
 """)).all()
```

matlab

Always show details

Copy

```
updates = []
for qid, ver, share, sh in rows:
 share = float(share or 0.0); sh = float(sh or 1.0)
 if share == 0.0: continue
 if share > payload.tau:
 factor = max(payload.floor, min(payload.ceil, sh * (payload.tau / share)))
 else:
 factor = min(payload.ceil, sh * (1.0 + (payload.tau - share) * 0.25))
 updates.append((qid, ver, factor))

for qid, ver, newp in updates:
 row = db.get(ItemExposureControl, {"question_id": qid, "version": ver})
 if row: row.sh_p = newp
 else: db.add(ItemExposureControl(question_id=qid, version=ver, sh_p=newp))
db.commit()
return {"updated": len(updates)}
"""
```

----- Backend: bind everything in main & quizzes use selector\_choice  
-----

```
write(f"{ROOT}/qbank-backend/app/api/quizzes.py", """
from fastapi import APIRouter, HTTPException, Depends
from pydantic import BaseModel, Field, constr
from typing import List, Optional, Literal, Dict
from uuid import uuid4
from datetime import datetime, timedelta
import json
from sqlalchemy.orm import Session
from sqlalchemy import select
from app.core.cache import redis_client, bump_exposure
from app.core.events import emit
from app.core.database import get_db
from app.core.auth import require_roles, TokenData
from app.models.orm import QuestionVersion, QuestionOption,
QuestionPublication, ItemCalibration, ItemExposureControl
from app.services.selector_choice import get_selector_for_user
from app.services.adaptive import select_vanilla, select_sympson_hetter

router = APIRouter()
```

```
class QuizFilters(BaseModel):
 topics: Optional[List[str]] = None
 difficulty: Optional[List[Literal["easy","medium","hard"]]] = None
 num_questions: int = Field(ge=1, le=120, default=40)
 mode: Literal["tutor","exam"] = "tutor"
 exam_code: Optional[str] = "DEMO-EXAM"
```

```
class QuizCreate(BaseModel):
 tenant_id: constr(min_length=8)
 filters: QuizFilters
 adaptive: bool = True
 blueprint_quota: Optional[Dict[str,int]] = None # topic_id -> count
```

```
class QuizCreated(BaseModel):
 quiz_id: str
 question_ids: List[int]
 expires_at: datetime
 mode: Literal["tutor","exam"]
```

```
class NextQuestion(BaseModel):
 question_id: int
 version: int
 payload: dict
```

```
class AnswerSubmit(BaseModel):
 question_id: int
 selected: constr(min_length=1, max_length=1)
 time_taken_ms: Optional[int] = 0
 client_latency_ms: Optional[int] = 0
```

```
class AnswerResult(BaseModel):
 correct: bool
 correct_option: constr(min_length=1, max_length=1)
 explanation: dict
 difficulty: float
```

```
def _rk(qid: str, suf: str) -> str: return f"quiz:{qid}:{suf}"
```

```
@router.post("", response_model=QuizCreated, status_code=201,
dependencies=[Depends(require_roles("student","admin"))])
def create_quiz(payload: QuizCreate, user: TokenData =
Depends(require_roles("student","admin")), db: Session = Depends(get_db)):
 quiz_id = str(uuid4()); mode = payload.filters.mode
```

```
expires_at = datetime.utcnow() + timedelta(hours=2)
```

```
stmt = select(QuestionPublication, QuestionVersion).join(
 QuestionVersion,
 (QuestionVersion.question_id == QuestionPublication.question_id) &
 (QuestionVersion.version == QuestionPublication.live_version)
).where(QuestionPublication.exam_code == (payload.filters.exam_code or "DEMO-EXAM"), QuestionVersion.state == "published")
rows = db.execute(stmt).all()
versions = [r[1] for r in rows]
```

```
vcache = [{"q": v.question_id, "v": v.version, "t": v.topic_id, "d": v.difficulty_label}
for v in versions]
redis_client.set(_rk(quiz_id, "versions"), json.dumps(vcache), ex=7200)
redis_client.set(_rk(quiz_id, "cursor"), 0, ex=7200)
redis_client.set(_rk(quiz_id, "mode"), mode, ex=7200)
redis_client.set(_rk(quiz_id, "user"), user.sub, ex=7200)
```

```
store the selector choice per-quiz for deterministic runs
selector = get_selector_for_user(db, user.sub)
redis_client.set(_rk(quiz_id, "selector"), selector, ex=7200)
```

```
emit("quiz_started", {"quiz_id": quiz_id, "user_id": user.sub, "tenant_id":
payload.tenant_id, "mode": mode, "filters": payload.filters.model_dump(),
"selector": selector})
qids = list({v["q"] for v in vcache}[:payload.filters.num_questions])
return QuizCreated(quiz_id=quiz_id, question_ids=qids, expires_at=expires_at,
mode=mode)
```

```
@router.get("/{quiz_id}/next", response_model=NextQuestion,
dependencies=[Depends(require_roles("student","admin"))])
def next_question(quiz_id: str, db: Session = Depends(get_db)):
 raw = redis_client.get(_rk(quiz_id,"versions"))
 if not raw: raise HTTPException(404, "Quiz not found or expired")
 versions = json.loads(raw)
 selector = redis_client.get(_rk(quiz_id,"selector")) or "vanilla"
```

```
 curk = _rk(quiz_id, "cursor")
 cur = int(redis_client.get(curk) or 0)
 if cur >= len(versions): raise HTTPException(404, "No more questions")
```

```
 window = versions[cur : min(cur+20, len(versions))]
 candidates = []
 for w in window:
```

```

ic = db.scalar(select(ItemCalibration).where(ItemCalibration.question_id==w["q"],
ItemCalibration.version==w["v"]).limit(1))
exp =
db.scalar(select(ItemExposureControl).where(ItemExposureControl.question_id==
w["q"], ItemExposureControl.version==w["v"]).limit(1))
a = (ic.a if ic and ic.a is not None else 1.0) if ic else 1.0
b = (ic.b if ic and ic.b is not None else 0.0) if ic else 0.0
c = (ic.c if ic and ic.c is not None else 0.2) if ic else 0.2
sh_p = exp.sh_p if exp else 1.0
candidates.append({"question_id": w["q"], "version": w["v"], "topic_id": w["t"],
"a": a, "b": b, "c": c, "sh_p": sh_p})

if selector == "sympson_hetter":
best = select_sympson_hetter(candidates, theta=0.0) or candidates[0]
else:
best = select_vanilla(candidates, theta=0.0) or candidates[0]

redis_client.set(curk, cur+1)

qv =
db.scalar(select(QuestionVersion).where(QuestionVersion.question_id==best["que
stion_id"], QuestionVersion.version==best["version"]))
if not qv: raise HTTPException(500, "Item not found")
opts =
db.execute(select(QuestionOption).where(QuestionOption.question_version_id==
qv.id)).scalars().all()
bump_exposure(best["question_id"], best["version"])

payload = {"stem_md": qv.stem_md, "lead_in": qv.lead_in, "options": [{"label":
o.option_label, "text": o.option_text_md} for o in opts]}
emit("question_served", {"quiz_id": quiz_id, "question_id": best["question_id"],
"version": best["version"], "selector": selector})
return NextQuestion(question_id=best["question_id"], version=best["version"],
payload=payload)

@router.post("/{quiz_id}/answers", response_model=AnswerResult,
dependencies=[Depends(require_roles("student","admin"))])
def submit_answer(quiz_id: str, payload: AnswerSubmit, db: Session =
Depends(get_db)):
qv =
db.scalar(select(QuestionVersion).where(QuestionVersion.question_id==payload.q
uestion_id).order_by(QuestionVersion.version.desc()))
if not qv: raise HTTPException(404, "Question not found")
opts =

```

```

db.execute(select(QuestionOption).where(QuestionOption.question_version_id==
qv.id)).scalars().all()
correct = next((o.option_label for o in opts if o.is_correct), None)
if not correct: raise HTTPException(500, "No correct option set")
ok = (payload.selected.upper() == correct)
emit("answer_submitted", {"quiz_id": quiz_id, "question_id": payload.question_id,
"version": qv.version, "selected": payload.selected, "is_correct": ok,
"time_taken_ms": payload.time_taken_ms or 0})
return AnswerResult(correct=ok, correct_option=correct,
explanation={"rationale_md": qv.rationale_md}, difficulty=0.5)
"""

```

----- Backend: author + auth + main -----

```

write(f"{ROOT}/qbank-backend/app/api/author.py", """
from fastapi import APIRouter, Depends, HTTPException
from pydantic import BaseModel, constr
from typing import List, Optional
from sqlalchemy.orm import Session
from sqlalchemy import select, func

from app.core.database import get_db
from app.core.config import TENANT_ID
from app.core.auth import require_roles, TokenData
from app.models.orm import Topic, Question, QuestionVersion, QuestionOption,
QuestionPublication

```

```

router = APIRouter()

```

```

class OptionIn(BaseModel):
 label: constr(min_length=1, max_length=1)
 text_md: str
 is_correct: bool

```

```

class QuestionCreate(BaseModel):
 external_ref: Optional[str] = None
 topic_name: str
 exam_code: str = "DEMO-EXAM"
 stem_md: str
 lead_in: str
 rationale_md: str
 difficulty_label: Optional[str] = "medium"
 options: List[OptionIn]

```

```

@router.post("/questions",

```



```

dependencies=[Depends(require_roles("author","admin"))])
def create_question(payload: QuestionCreate, user: TokenData =
Depends(require_roles("author","admin")), db: Session = Depends(get_db)):
 t = db.scalar(select(Topic).where(Topic.name == payload.topic_name))
 if not t:
 t = Topic(tenant_id=TENANT_ID, parent_id=None, name=payload.topic_name,
blueprint_code=None)
 db.add(t); db.flush()

```

python  
Always show details

Copy

```

q = Question(tenant_id=TENANT_ID, external_ref=payload.external_ref,
created_by=user.sub, is_deleted=False)
db.add(q); db.flush()

```

```

next_v = (db.scalar(select(func.coalesce(func.max(QuestionVersion.version),
0)).where(QuestionVersion.question_id == q.id)) or 0) + 1
qv = QuestionVersion(
 question_id=q.id, version=next_v, state="published",
 stem_md=payload.stem_md, lead_in=payload.lead_in,
rationale_md=payload.rationale_md,
 difficulty_label=payload.difficulty_label, topic_id=t.id, tags={}, assets=[],
references=[]
)
db.add(qv); db.flush()

```

```

for o in payload.options:
 db.add(QuestionOption(question_version_id=qv.id,
option_label=o.label.upper(), option_text_md=o.text_md,
is_correct=o.is_correct))

```

```

db.add(QuestionPublication(question_id=q.id, live_version=next_v,
exam_code=payload.exam_code, tenant_id=TENANT_ID))
db.commit()
return {"question_id": q.id, "version": next_v, "topic_id": t.id}
@router.post("/publish/{question_id}",
dependencies=[Depends(require_roles("publisher","admin"))])
def publish(question_id: int, exam_code: str = "DEMO-EXAM", db: Session =
Depends(get_db)):
 qv = db.scalar(select(QuestionVersion).where(QuestionVersion.question_id ==
question_id).order_by(QuestionVersion.version.desc()))
 if not qv:

```

```

raise HTTPException(404, "Question not found")
pub = QuestionPublication(question_id=question_id, live_version=qv.version,
exam_code=exam_code, tenant_id=TENANT_ID)
db.add(pub); db.commit()
return {"published": True, "question_id": question_id, "version": qv.version,
"exam_code": exam_code}
"""
)

```

```

write(f"{ROOT}/qbank-backend/app/api/auth.py", """
from fastapi import APIRouter
from pydantic import BaseModel
from typing import List
from app.core.auth import create_token

```

```

router = APIRouter()

```

```

class MockLogin(BaseModel):
user_id: str
roles: List[str]

```

```

@router.post("/mock-login")
def mock_login(payload: MockLogin):
token = create_token(payload.user_id, payload.roles)
return {"access_token": token, "token_type": "bearer", "roles": payload.roles}
"""
)

```

```

write(f"{ROOT}/qbank-backend/app/main.py", """
from fastapi import FastAPI
from fastapi.middleware.cors import CORSMiddleware
from app.api.quizzes import router as quizzes_router
from app.api.author import router as author_router
from app.api.auth import router as auth_router
from app.api.admin import router as admin_router

```

```

app = FastAPI(title="QBank API v5", version="5.0.0")
app.add_middleware(CORSMiddleware, allow_origins=[""],
allow_credentials=True, allow_methods=["*"], allow_headers=["*"])

```

```

app.include_router(auth_router, prefix="/v1/auth", tags=["auth"])
app.include_router(quizzes_router, prefix="/v1/quizzes", tags=["quizzes"])
app.include_router(author_router, prefix="/v1/author", tags=["authoring"])
app.include_router(admin_router, prefix="/v1/admin", tags=["admin"])

```

```

@app.get("/health")

```

```
def health(): return {"status": "ok"}
"""
```

----- Nightly job -----

```
write(f"{ROOT}/analytics/cron/reestimate_sh.py", """
import argparse, psycopg2
```

```
SQL = '''
WITH atts AS (
SELECT question_id, version, count(*)::float AS c
FROM user_responses
WHERE created_at > now() - interval %s
GROUP BY question_id, version
), totals AS (
SELECT sum(c) AS total FROM atts
)
SELECT a.question_id, a.version, a.c / NULLIF(t.total,0) AS share,
COALESCE(e.sh_p,1.0) AS sh_p
FROM atts a CROSS JOIN totals t
LEFT JOIN item_exposure_control e ON e.question_id=a.question_id AND
e.version=a.version
'''
```

```
UPSERT = '''
INSERT INTO item_exposure_control(question_id, version, sh_p)
VALUES (%s,%s,%s)
ON CONFLICT (question_id,version) DO UPDATE SET sh_p=EXCLUDED.sh_p,
updated_at=now()
'''
```

```
def main():
ap = argparse.ArgumentParser()
ap.add_argument("--dsn", required=True, help="postgresql://
user:pass@host:port/dbname")
ap.add_argument("--tau", type=float, default=0.2)
ap.add_argument("--days", type=int, default=7)
ap.add_argument("--floor", type=float, default=0.05)
ap.add_argument("--ceil", type=float, default=1.0)
args = ap.parse_args()
interval = f"{args.days} days"
```

lua

Always show details

Copy

```
conn = psycopg2.connect(args.dsn)
cur = conn.cursor()
cur.execute(SQL, (interval,))
rows = cur.fetchall()
```

```
updates = 0
for qid, ver, share, sh in rows:
 share = float(share or 0.0); sh = float(sh or 1.0)
 if share == 0.0: continue
 if share > args.tau:
 newp = max(args.floor, min(args.ceil, sh * (args.tau / share)))
 else:
 newp = min(args.ceil, sh * (1.0 + (args.tau - share) * 0.25))
 cur.execute(UPSERT, (qid, ver, newp)); updates += 1
```

```
conn.commit(); cur.close(); conn.close()
print(f"updated={updates}")
if name == "main":
 main()
""")
```

----- Admin UI (Next.js) -----

```
write(f"{ROOT}/admin-ui/package.json", """)
{
 "name": "admin-ui",
 "private": true,
 "version": "0.1.0",
 "scripts": { "dev": "next dev -p 4000", "build": "next build", "start": "next start -p 4000" },
 "dependencies": { "next": "14.2.5", "react": "18.2.0", "react-dom": "18.2.0" }
}
""")
write(f"{ROOT}/admin-ui/next.config.js", "module.exports = { reactStrictMode:
true };\\n")
write(f"{ROOT}/admin-ui/.env.local", "NEXT_PUBLIC_API=http://localhost:8000\\n")

write(f"{ROOT}/admin-ui/pages/index.tsx", """)
import { useEffect, useState } from 'react';

const API = process.env.NEXT_PUBLIC_API || 'http://localhost:8000';
```

```
type ItemRow = { question_id:number; version:number; topic_id?:number;
```

```
sh_p:number; recent_attempts:number };
```

```
export default function Admin() {
 const [token, setToken] = useState('');
 const [items, setItems] = useState<ItemRow[]>([]);
 const headers = { 'Content-Type':'application/json', 'Authorization': Bearer $
 {token} };
```

```
 const fetchItems = async () => {
 const r = await fetch(`${API}/v1/admin/exposure/items?limit=200, { headers }`);
 setItems(await r.json());
 };
```

```
 const setSh = async (qid:number, ver:number, sh_p:number) => {
 await fetch(`${API}/v1/admin/exposure/set, { method:'POST', headers, body:
 JSON.stringify({ question_id: qid, version: ver, sh_p })`);
 await fetchItems();
 };
```

```
 const reestimate = async () => {
 await fetch(`${API}/v1/admin/exposure/reestimate, { method:'POST', headers, body:
 JSON.stringify({ tau: 0.2, days: 7 })`);
 await fetchItems();
 };
```

```
 return (
 <main style={{padding:24}}>
 <h1>Admin: Sympson–Hetter Control</h1>
 <p>Paste an admin JWT from <code>/v1/auth/mock-login</code></p>
 <textarea value={token} onChange={(e)=>setToken(e.target.value)} rows={4}
 style={{width:'100%'}} />
 <div style={{marginTop:12}}>
 <button onClick={fetchItems}>Load Items</button>
 <button onClick={reestimate} style={{marginLeft:8}}>Re-estimate (7d, $\tau=0.2$)</button>
 </div>
 <table style={{marginTop:16, width:'100%', borderCollapse:'collapse'}}>
 <thead><tr><th>Question</th><th>Ver</th><th>Topic</th><th>sh_p</th><th>Attempts(7d)</th><th>Update</th></tr></thead>
 <tbody>
 {items.map(it => (
 <tr key={`-${it.question_id}-${it.version}`} style={{borderTop:'1px solid #eee'}}>
 <td>{it.question_id}</td><td>{it.version}</td><td>{it.topic_id ?? ''}</td>
 <td><input type="number" min="0" max="1" step="0.05" defaultValue={it.sh_p}</td>
```

```

onBlur={e=>setSh(it.question_id, it.version, parseFloat(e.target.value))} /></td>
<td>{it.recent_attempts}</td>
<td><button onClick={()=>setSh(it.question_id, it.version, it.sh_p)}>Save</
button></td>
</tr>
)}}
</tbody>
</table>
</main>
);
}
""")

```

----- Student UI E2E (Playwright) -----

```

write(f"{ROOT}/student-ui/playwright.config.ts", "")
import { defineConfig, devices } from '@playwright/test';

```

```

export default defineConfig({
 testDir: './tests',
 timeout: 60000,
 use: { baseURL: 'http://localhost:3000' },
 projects: [{ name: 'chromium', use: { ...devices['Desktop Chrome'] } }]
});
""")

```

```

write(f"{ROOT}/student-ui/tests/e2e.spec.ts", "")
import { test, expect } from '@playwright/test';

```

```

const API = process.env.API || 'http://localhost:8000';

```

```

test('can load and start quiz', async ({ page, request }) => {
 // get a token
 const resp = await request.post(`${API}/v1/auth/mock-login`, { data: { user_id: 'e2e-
user', roles: ['student','author','publisher','admin'] } });
 const data = await resp.json(); const token = data.access_token;

```

```

 await page.goto('/');
 await page.fill('textarea', token);
 await page.fill('input[aria-label="Tenant ID:"]',
 '00000000-0000-0000-0000-000000000001');
 await page.fill('input[aria-label="Exam Code:"]', 'DEMO-EXAM');
 await page.click('text=Start Quiz');

```

```

 await expect(page.getByText('Quiz')).toBeVisible();
});

```

```
""")
```

----- Backend pytest -----

```
write(f"{ROOT}/qbank-backend/tests/test_api_e2e.py", """
```

```
import pytest
```

```
from httpx import Client
```

```
BASE = "http://localhost:8000"
```

```
@pytest.fixture(scope="session")
```

```
def token():
```

```
 r = Client().post(f"{BASE}/v1/auth/mock-login", json={"user_id": "tester", "roles":
 ["author", "publisher", "student", "admin"]})
```

```
 return r.json()["access_token"]
```

```
def auth(hdrs, token): hdrs["Authorization"] = f"Bearer {token}"; return hdrs
```

```
def test_seed_and_quiz_flow(token):
```

```
 s = Client()
```

```
 # create + publish question
```

```
 payload = {
```

```
 "external_ref": "E2E-1",
```

```
 "topic_name": "Cardiology",
```

```
 "exam_code": "DEMO-EXAM",
```

```
 "stem_md": "E2E stem",
```

```
 "lead_in": "Pick one",
```

```
 "rationale_md": "Because tests",
```

```
 "difficulty_label": "medium",
```

```
 "options": [
```

```
 {"label": "A", "text_md": "Alpha", "is_correct": True},
```

```
 {"label": "B", "text_md": "Bravo", "is_correct": False}
```

```
]
```

```
 }
```

```
 r = s.post(f"{BASE}/v1/author/questions", headers=auth({"Content-
 Type": "application/json"}, token), json=payload)
```

```
 assert r.status_code == 200, r.text
```

```
 qid = r.json()["question_id"]
```

```
 r = s.post(f"{BASE}/v1/author/publish/{qid}", headers=auth({}, token)); assert
 r.status_code == 200
```

pgsql

Always show details

Copy

```

create quiz
r = s.post(f"{BASE}/v1/quizzes", headers=auth({"Content-Type":"application/
json"}, token), json={

"tenant_id":"00000000-0000-0000-0000-000000000001","adaptive":True,"filter
s":{"num_questions":1,"mode":"tutor","exam_code":"DEMO-EXAM"}
})
assert r.status_code == 201, r.text
quiz_id = r.json()["quiz_id"]

next question
r = s.get(f"{BASE}/v1/quizzes/{quiz_id}/next", headers=auth({}, token))
assert r.status_code == 200, r.text
question_id = r.json()["question_id"]

submit answer
r = s.post(f"{BASE}/v1/quizzes/{quiz_id}/answers", headers=auth({"Content-
Type":"application/json"}, token), json={
 "question_id": question_id, "selected":"A", "time_taken_ms":5000
})
assert r.status_code == 200, r.text

admin list + set + reestimate
r = s.get(f"{BASE}/v1/admin/exposure/items", headers=auth({}, token)); assert
r.status_code == 200
r = s.post(f"{BASE}/v1/admin/exposure/set", headers=auth({"Content-
Type":"application/json"}, token), json={"question_id":qid,"version":1,"sh_p":0.4})
assert r.status_code == 200, r.text
r = s.post(f"{BASE}/v1/admin/exposure/reestimate", headers=auth({"Content-
Type":"application/json"}, token), json={"tau":0.2,"days":7})
assert r.status_code == 200, r.text
""")

----- Looker richer explores -----
write(f"{ROOT}/looker/qbank.model.lkml", ""
connection: "qbank_postgres"

include: "views/*.view.lkml"

explore: topic_mastery {
 joins: [topics]
}

explore: blueprint_coverage {

```



```
joins: [topics]
}
""")
```

```
write(f"{ROOT}/looker/views/topics.view.lkml", ""
view: topics {
sql_table_name: public.topics ;;
dimension: topic_id { primary_key: yes; type: number; sql: ${TABLE}.id ;; }
dimension: topic_name { type: string; sql: ${TABLE}.name ;; }
}
""")
```

```
write(f"{ROOT}/looker/views/topic_mastery.view.lkml", ""
view: topic_mastery {
sql_table_name: (SELECT ur.user_id, qv.topic_id, ur.created_at as ts, ur.is_correct,
ur.time_taken_ms
FROM public.user_responses ur
JOIN public.question_versions qv ON qv.question_id=ur.question_id AND
qv.version=ur.version) ;;
```

```
dimension: user_id { type: string; sql: ${TABLE}.user_id ;; }
dimension: topic_id { type: number; sql: ${TABLE}.topic_id ;; }
dimension_group: ts { type: time; timeframes: [date, week, month, year]; sql: $
${TABLE}.ts ;; }
measure: attempts { type: count ;; }
measure: accuracy { type: average; sql: CASE WHEN ${TABLE}.is_correct THEN 1
ELSE 0 END ;; value_format_name: "percent_2" }
measure: avg_time_ms { type: average; sql: ${TABLE}.time_taken_ms ;; }
}
""")
```

```
write(f"{ROOT}/looker/views/blueprint_coverage.view.lkml", ""
view: blueprint_coverage {
sql_table_name: (SELECT qv.topic_id, qv.difficulty_label, count(*) as items
FROM public.question_versions qv
WHERE qv.state='published'
GROUP BY 1,2) ;;
```

```
dimension: topic_id { type: number; sql: ${TABLE}.topic_id ;; }
dimension: difficulty { type: string; sql: ${TABLE}.difficulty_label ;; }
measure: items { type: sum; sql: ${TABLE}.items ;; }
}
""")
```

----- Metabase: dashboard JSON + import script -----

```
dashboard_json = {
 "name": "QBank Overview",
 "parameters": [
 {"name": "Date range", "type": "date/all-options", "slug": "date"},
 {"name": "Exam Code", "type": "category", "slug": "exam"}
],
 "cards": [
 {
 "name": "Accuracy by Day",
 "dataset_query": {
 "type": "native",
 "native": {"query": "select created_at::date as day, avg(case when is_correct then 1 else 0 end) as accuracy from public.user_responses [[where {{date}}]] group by 1 order by 1"},
 "database": 2
 },
 "display": "line"
 },
 {
 "name": "Attempts by Topic",
 "dataset_query": {
 "type": "native",
 "native": {"query": "select qv.topic_id, count(*) attempts from public.user_responses ur join public.question_versions qv on qv.question_id=ur.question_id and qv.version=ur.version [[where {{date}}]] group by 1 order by 2 desc limit 20"},
 "database": 2
 },
 "display": "bar"
 }
]
}

write(f"{ROOT}/metabase/dashboard.json", json.dumps(dashboard_json,
indent=2))
```

```
write(f"{ROOT}/metabase/import.sh", """
#!/usr/bin/env bash
set -euo pipefail
if [-z "${MB_URL:-}"] || [-z "${MB_USER:-}"] || [-z "${MB_PASS:-}"] || [-z "${MB_DB_ID:-}"]; then
echo "Set MB_URL, MB_USER, MB_PASS, MB_DB_ID"; exit 1; fi
TOKEN=$(curl -s -X POST "$MB_URL/api/session" -H "Content-Type: application/
```

```
json" -d '{"username":"$MB_USER","password":"$MB_PASS"}' | jq -r .id)
DASH_JSON=$(cat dashboard.json | jq
".cards[].dataset_query.database=$MB_DB_ID")
curl -s -X POST "$MB_URL/api/dashboard" -H "Content-Type: application/json" -H
"X-Metabase-Session: $TOKEN" -d "$DASH_JSON" >/dev/null
echo "Dashboard imported."
""")
```

```
----- CI: backend (pytest) & student-ui (playwright) -----
write(f"{ROOT}/.github/workflows/backend.yml", ""
name: backend-ci
on:
push: { paths: ["qbank-backend/", ".github/workflows/backend.yml", "sql/"] }
pull_request: { paths: ["qbank-backend/", ".github/workflows/backend.yml",
"sql/"] }
jobs:
api:
runs-on: ubuntu-latest
services:
postgres:
image: postgres:16-alpine
env:
POSTGRES_USER: qbank
POSTGRES_PASSWORD: qbank
POSTGRES_DB: qbank
ports: ["5432:5432"]
options: >-
--health-cmd="pg_isready -U qbank" --health-interval=10s --health-timeout=5s
--health-retries=5
redis:
image: redis:7-alpine
ports: ["6379:6379"]
env:
DATABASE_URL: postgresql+psycopg2://qbank:qbank@localhost:5432/qbank
REDIS_URL: redis://localhost:6379/0
APP_SECRET: ci-secret
steps:
- uses: actions/checkout@v4
- name: Setup Python
uses: actions/setup-python@v5
with: { python-version: "3.11" }
- name: Install deps
run: pip install -r qbank-backend/requirements.txt
- name: Init DB schema
```

```

run: |
psql postgresql://qbank:qbank@localhost:5432/qbank -f sql/content_ddl.sql
psql postgresql://qbank:qbank@localhost:5432/qbank -f sql/delivery_ddl.sql
psql postgresql://qbank:qbank@localhost:5432/qbank -f sql/analytics_ddl.sql
psql postgresql://qbank:qbank@localhost:5432/qbank -f sql/indexes.sql
psql postgresql://qbank:qbank@localhost:5432/qbank -f sql/
item_exposure_control.sql
psql postgresql://qbank:qbank@localhost:5432/qbank -f sql/feature_flags.sql
- name: Launch API
run: |
nohup python -m uvicorn qbank-backend.app.main:app --host 0.0.0.0 --port 8000
&
sleep 3
- name: Pytest
run: pytest -q qbank-backend/tests/test_api_e2e.py
""")

```

```

write(f"{ROOT}/.github/workflows/student-ui.yml", """
name: student-ui-e2e
on:
push: { paths: ["student-ui/", ".github/workflows/student-ui.yml"] }
pull_request: { paths: ["student-ui/", ".github/workflows/student-ui.yml"] }
jobs:
e2e:
runs-on: ubuntu-latest
services:
postgres:
image: postgres:16-alpine
env:
PGUSER: qbank
PGPASSWORD: qbank
PGDATABASE: qbank
ports: ["5432:5432"]
redis:
image: redis:7-alpine
ports: ["6379:6379"]
env:
DATABASE_URL: postgresql+psycopg2://qbank:qbank@localhost:5432/qbank
REDIS_URL: redis://localhost:6379/0
APP_SECRET: e2e-secret
steps:
- uses: actions/checkout@v4
- uses: actions/setup-python@v5
with: { python-version: "3.11" }

```

- name: Backend deps & DB

run: |

```
pip install -r qbank-backend/requirements.txt
```

```
psql postgresql://qbank:qbank@localhost:5432/qbank -f sql/content_ddl.sql
```

```
psql postgresql://qbank:qbank@localhost:5432/qbank -f sql/delivery_ddl.sql
```

```
psql postgresql://qbank:qbank@localhost:5432/qbank -f sql/analytics_ddl.sql
```

```
psql postgresql://qbank:qbank@localhost:5432/qbank -f sql/indexes.sql
```

```
psql postgresql://qbank:qbank@localhost:5432/qbank -f sql/
```

```
item_exposure_control.sql
```

```
psql postgresql://qbank:qbank@localhost:5432/qbank -f sql/feature_flags.sql
```

```
nohup python -m uvicorn qbank-backend.app.main:app --host 0.0.0.0 --port 8000
```

&

sleep 3

- name: Seed 1 demo item

run: |

```
TOKEN=$(curl -s -X POST http://localhost:8000/v1/auth/mock-login -H 'Content-Type: application/json' -d '{"user_id":"seed","roles":
```

```
["author","publisher","student","admin"]}' | python -c "import sys, json; print(json.load(sys.stdin)['access_token'])")
```

```
curl -s -X POST http://localhost:8000/v1/author/questions -H "Authorization: Bearer $TOKEN" -H "Content-Type: application/json" -d '{"external_ref":"DEMO-UI","topic_name":"Cardiology","exam_code":"DEMO-EXAM","stem_md":"Demo stem","lead_in":"Pick
```

```
one","rationale_md":"Because","difficulty_label":"medium","options":
```

```
[{"label":"A","text_md":"Alpha","is_correct":true},
```

```
{"label":"B","text_md":"Bravo","is_correct":false}]}' >/dev/null
```

- uses: actions/setup-node@v4

with: { node-version: "20" }

- name: Install & build student UI

working-directory: student-ui

run: |

```
npm ci || npm install
```

```
npm run build
```

- name: Start student UI

working-directory: student-ui

run: |

```
nohup npm start &
```

sleep 3

- name: Install Playwright

run: npx playwright install --with-deps

- name: Run Playwright tests

working-directory: student-ui

env: { API: "http://localhost:8000" }

run: npx playwright test --reporter=dot

```
""")
```

```
----- Zip -----
```

```
zip_path = "/mnt/data/qbank_scaffold_v5.zip"
```

```
with zipfile.ZipFile(zip_path, "w", zipfile.ZIP_DEFLATED) as z:
```

```
for p in pathlib.Path(ROOT).rglob("*"):
```

```
z.write(p, p.relative_to(ROOT))
```

```
zip_path
```