

4.60" 320*960 IPS ST7701S 262K 18 Bit RGB FPC Connector 40 Pin



- ST7701S is driven with 18 bit color depth.
- LCD can display 262K Colors (6R:6G:6B).
 - 18 Bit RGB Interface(VS, HS, DOTCLK, ENABLE, DB[17:0], Sync and DE mode)
- ST7701S has Lower Power Consumption.
- Display Colors (Color Mode)
 - Reduced color mode: 262K colors.
 - Reduced color mode: 65K colors.
 - Idle Mode: 8-color, RGB=(111).
- Programmable Pixel Color Format (Color Depth) for Various Display Data input Format
 - 18-bit/pixel: RGB=(666)
 - 16-bit/pixel: RGB=(565)
- Display Features
 - Programmable Partial Display Duty.
 - CABC for saving current consumption.
 - Color enhancement.
- SPI + RGB interface
 - Supports SPI for registers
- Normally black.
- IPS, all view direction.
- Power Supply
 - VDD: 2.5V - 3.6V
- Brightness: 300 cd/m².
- FPC Connector.



Ordering &
Details



Support &
Community



Technical
Documentation

1 General Specifications

Feature		Specifications
Display Spec.	LCD type	4.58 inch
	Resolution (H*V)	320H x 960V
	Technology Type	a-Si TFT
	Pixel Configuration	R.G.B. Vertical Stripe
	Display Mode	Normally Black
	Viewing Direction	ALL
	Gray Scale Inversion Direction	ALL
Mechanical Characteristics	Outline Dimensions (W x H x T) (mm)	41.57 x 118.8 x 2.5
	Active Area(mm)	36.768 x 110.304
	CTP View Area(mm)	/
	With /Without Touch screen	Without CTP
	Connector Type	Connector
	Backlight Type	LED
	With /Without TSP	Without TSP
	LED Numbers	8 LED
	Weight (g)	TBD
Electrical Characteristics	Display Interface	3SPI+18Bits RGB
	Touch Interface	I2C
	Number of color	262K
	Display Driver IC	-
	Touch Driver IC	-

Note 1: Viewing direction is following the data which measured by optics equipment.

Note 2: Requirements on Environmental Protection: RoHS

Note 3: LCM weight tolerance: +/- 5%

2 Electrical Characteristics

2.1 Absolute Maximum Ratings

Parameter	Symbol	Min.	Max.	Unit
Power Supply Voltage	V_{DD}	-0.3	4.6	V
Operation Temperature	T_{opr}	-20	70	°C
Storage Temperature	T_{stg}	-30	80	°C

2.2 Driving TFT LCD Panel

Parameter	Symbol	Min.	Typ.	Max.	Unit
Operating Voltage	V_{DD}	3.0	3.3	3.6	V
VDD Input Voltage Level	V_{IH}	$0.7 \cdot V_{DD}$	-	V_{DD}	V
	V_{IL}	0	-	$0.3 \cdot V_{DD}$	V
VDD Output Voltage Level	V_{OH}	$0.8 \cdot V_{DD}$	-	-	V
	V_{OL}	0	-	-	V

2.3 Backlight Unit


Parameter	Symbol	Min.	Typ.	Max.	Unit
Voltage for LED backlight	V_F	11.2	12.0	12.8	V
Current for LED backlight	I_F	--	40	-	mA
Connection Mode		-	4S2P	--	
LED number		/	8	-	pcs
Power Consumption	P_L		480		mW
LED Life Time	W_{BL}	25000			Hr

Note 1: There are 4 x 2 Groups LED.

Note 2: $T_a = 25^\circ\text{C}$.

Note 3: Brightness to be decreased to 50% of the initial value.

3 Mechanical Drawing



4 Pin Definition

Pin no.	Symbol	Description
1	LEDA	Backlight LED anode.
2	LEDK1	Backlight LED cathode.
3	LEDK2	Backlight LED cathode.
4	GND	Ground pin.
5	VDD	Power supply.
6	RESET	Reset signal. Active Low.
7	VDDIO	Power Supply for interface logic.
8	GND	Ground pin.
9	SDA	SPI data signal.
10	SCK	SPI clock signal.
11	CS	SPI chip select signal. Active Low.
12	PCLK	RGB dot clock signal.
13	DE	RGB data enable signal.
14	VS	RGB frame synchronizing signal.
15	HS	RGB line synchronizing signal.
16-33	DB0-DB17	(RGB data signal). RGB data signal(DB0:BLUE LSB; DB5:BLUE MSB; DB6:GREEN LSB; DB11: GREEN, MSB; DB12:RED LSB; DB17:RED MSB).
34	GND	Ground pin.
35	NC	No connection.
36	NC	No connection.
37	NC	No connection.
38	NC	No connection.
39	NC	No connection.
40	GND	Ground pin.

Note 1:SPI+RGB interface

5 Optical Characteristics

Item	Symbol	Measuring Conditions	Min.	Typ.	Max.	Unit	Remark
Viewing Angle	θ_T	Center CR \geq 10	-	80	-	Degree	Note 2
	θ_B		-	80	-		
	θ_L		-	80	-		
	θ_R		-	80	-		
Contrast Ratio	CR	$\Phi=0^\circ$	1000	1200	-	-	Note 1 Note 3
Response Time	T _{ON}	25°C	-	25	35	mS	Note 1 Note 4
	T _{OFF}			25	35		
Uniformity	U	-	80	-	-	%	Note 1 Note 6
NTSC	-	-	-	50	-	%	Note 5
Luminance	L		260	300	-	cd/m ²	Note 1 Note 7

Test Conditions:


1. IF= 20mA (one channel),the ambient temperature is 25°C.

2. The test systems refer to Note 1 and Note 2.

Notes:

1. Definition of optical measurement system.

The optical characteristics should be measured in dark room. After 5 minutes operation, the optical properties are measured at the center point of the LCD screen. All input terminals LCD panel must be ground when measuring the center area of the panel.



2. Definition of Viewing Angle:

viewing angle is measured at the center point of the LCD by CONOSCOPE(ergo-80).




Fig. 1 Definition of viewing angle

3. Definition of Contrast Ratio (CR): measured at the center point of panel

$$Contrast\ Ratio\ (CR)=\frac{Luminance\ measured\ when\ LCD\ is\ on\ the\ White\ state}{Luminance\ measured\ when\ LCD\ is\ on\ the\ Black\ state}$$


“White state “:The state is that the LCD should be driven by V_{white}.

“Black state”: The state is that the LCD should be driven by V_{black}.

V_{white}: To be determined V_{black}: To be determined.

4. Definition of Response Time:

The response time is defined as the LCD optical switching time interval between “White” state and “Black” state. Rise time (TON) is the time between photo detector output intensity changed from 90% to 10%. And fall time (TOFF) is the time between photo detector output intensity changed from 10% to 90%.



5. Definition of color chromaticity (CIE1931)
Color coordinates measured at center point of LCD.
6. Definition of Luminance Uniformity
Active area is divided into 9 measuring areas (Refer Fig. 2). Every measuring point is placed at the center of each measuring area.

$$\text{Luminance Uniformity}(U) = \frac{L_{min}}{L_{max}}$$

L=Active area length W=Active area width




Fig. 2 Definition of uniformity

L_{max} : The measured maximum luminance of all measurement position.

L_{min} : The measured minimum luminance of all measurement position.

7. Definition of Luminance:
Measure the luminance of white state at center point.

6 Environmental / Reliability Test

No.	Item	Condition	Time	Assessment
1	High temp. Storage	80°C	240 hrs	Note 1 IEC60068-2-2, GB2423. 2-89
2	High temp. Operating	70°C	240 hrs	Note 2 IEC60068-2-1 GB2423.1-89
3	Low temp. Storage	-30°C	240 hrs	IEC60068-2-2 GB2423. 2-89
4	Low temp. Operating	-20°C	240 hrs	IEC60068-2-1 GB/T2423.1-89
5	Humidity	60°C / 90%RH Max:	160 hrs	IEC60068-2-3 GB/T2423.3-2006
6	Thermal Shock(Non-operation)	-30°C ← 80°C (0.5 hour → 0.5 hour) Change time: 5min	30 Cycle	Start with cold temperature, end with high temperature IEC60068-2-14, GB2423.22-87
7	Electro Static Discharge (Operation)	C=150pF, R=330 Ω, 5 points/panel Air:±8KV, 5 times; Contact: ±4KV, 5 times; (Environment: 15°C ~ 35°C, 30% ~ 60%, 86Kpa ~ 106Kpa)	-	IEC61000-4-2 GB/T17626.2-1998
8	Vibration (Non-operation)	Frequency range: 10~55Hz, Stroke: 1mm Sweep: 10Hz~55Hz~10Hz 2 hours for each direction of X,Y, Z. (package condition)	-	IEC60068-2-6 GB/T2423.5-1995
9	Shock (Non-operation)	60G, ± X, ±Y, ± Z 3 times for each direction	6 mS	IEC60068-2-27 GB/T2423.5-1995
10	Package Drop Test	Height: 80 cm, 1 corner, 3 edges, 6 surfaces	-	IEC60068-2-32 GB/T2423.8-1995

Note:

1. TS is the temperature of panel's surface.

2. Ta is the ambient temperature of sample.

Remark:

1.The test samples should be applied to only one test item.

2.Sample size for each test item is 1~10pcs.

3.In case of malfunction defect caused by ESD damage, if it would be recovered to normal state after resetting, it would be judged as a good part.

7 Precautions For Use of LCD Modules

7.1 Handling Precautions

- The display panel is made of glass. Do not subject it to a mechanical shock by dropping it from a high place, etc.
- If the display panel is damaged and the liquid crystal substance inside it leaks out, be sure not to get any in your mouth, if the substance comes into contact with your skin or clothes, promptly wash it off using soap and water.
- Do not apply excessive force to the display surface or the adjoining areas since this may cause the color tone to vary.
- The polarizer covering the display surface of the LCD module is soft and easily scratched. Handle this polarizer carefully.
- If the display surface is contaminated, breathe on the surface and gently wipe it with a soft dry cloth. If still not completely clear, moisten cloth with one of the following solvents:
 - Isopropyl alcohol
 - Ethyl alcohol

Solvents other than those mentioned above may damage the polarizer. Especially, do not use the following:

- Water
- Ketone
- Aromatic solvents
- Do not attempt to disassemble the LCD Module.
- If the logic circuit power is off, do not apply the input signals.
- To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.
- Be sure to ground the body when handling the LCD Modules.
- Tools required for assembly, such as soldering irons, must be properly ground.
- To reduce the amount of static electricity generated, do not conduct assembly and other work under dry conditions.
- The LCD Module is coated with a film to protect the display surface. Be careful when peeling off the protective film since static electricity may be generated.

7.2 Storage precautions

- When storing the LCD modules, avoid exposure to direct sunlight or to the light of fluorescent lamps.
- The LCD modules should be stored under the storage temperature range. If the LCD modules will be stored for a long time, the recommend condition is:
- The LCD modules should be stored in the room without acid, alkali and harmful gas.

7.3 Transportation Precautions

The LCD modules should be no falling and violent shocking during transportation, and also should avoid excessive press, water, damp and sunshine.

8 Revision History

Revision	Details
1.0	Initial Release - 01.01.2023

Find Us Online



IMPORTANT NOTICE AND DISCLAIMER

AE PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with AE products. You are solely responsible for (1) selecting the appropriate AE products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. AE grants you permission to use these resources only for development of an application that uses the AE products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other AE intellectual property right or to any third party intellectual property right. AE disclaims responsibility for, and you will fully indemnify AE and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

AE's products are provided subject to AE's Terms of Sale or other applicable terms available either on alpelectronix.com or provided in conjunction with such AE products. AE's provision of these resources does not expand or otherwise alter AE's applicable warranties or warranty disclaimers for AE products.

AE objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Alp Electronix, Sjöhogvägen 6A, Västerås 721 32, Sweden
Copyright © 2023, Alptron AB