

DBC-2

Heading dbc-2 2405 V6 yuk uzak shield yok
Meas Type
Equipment under Test
Manufacturer enko
OP Condition p
Operator g.aktas
Test Spec J

Settings

Scan Start	150.000000000 kHz	Preamp State	Off
Scan Stop	30.000000000 MHz	Preamp Value	0.0 dB
RBW	9.0 kHz	Input Selection	INP1
IF RBW	10.0 kHz	Input Coupling	AC
Meas Time	1.0 s	Scan Type	TD Scan
RF Att	10.0 dB	Transducer	ENV432 ENKO.TDF

Scan Table

Scan Start	150.000000000 kHz
Scan Stop	30.000000000 MHz
Scan Type	TD Scan
Transducer	ENV432 ENKO.TDF
Detector	Trace 1: Max Peak Trace 2: Average

Start Frequency	Stop Frequency	Step Size	RBW	Meas Time	RF Atten	Preamp	Input
150.000 kHz	30.000 MHz	2.250 kHz	9.0 kHz	100.0 ms	10.0 dB	0.0 dB	INPUT1

Peak List

Margin	6.0 dB				
Peaks	25				
Trace	Frequency	Level (dB μ V)	Phase	Detector	Delta Limit/dB
1	11.157000000 MHz	55.42	L1	Positive Peak	-4.58

Final Results

Meas Time	1.0 s				
Margin	6.0 dB				
Peaks	25				
Trace	Frequency	Level (dB μ V)	Phase	Detector	Delta Limit/dB
1	11.157000000 MHz	48.85	L1	Quasi Peak	-11.15

Heading dbc-2 2405 V6 yuk uzak shield yok
Meas Type
Equipment under Test
Manufacturer enko
OP Condition p
Operator g.aktas
Test Spec J

Scan Diagram

