

sens

Heading dbc2 150W 2905
Meas Type
Equipment under Test
Manufacturer enko
OP Condition p
Operator g.aktas
Test Spec J

Settings

Scan Start	150.000000000 kHz	Preamplifier State	Off
Scan Stop	30.000000000 MHz	Preamplifier Value	0.0 dB
RBW	9.0 kHz	Input Selection	INP1
IF RBW	10.0 kHz	Input Coupling	AC
Meas Time	1.0 s	Scan Type	TD Scan
RF Att	10.0 dB	Transducer	ENV432 ENKO.TDF

Scan Table

Scan Start	150.000000000 kHz
Scan Stop	30.000000000 MHz
Scan Type	TD Scan
Transducer	ENV432 ENKO.TDF
Detector	Trace 1: Max Peak Trace 2: Average

Start Frequency	Stop Frequency	Step Size	RBW	Meas Time	RF Atten	Preamplifier	Input
150.000 kHz	30.000 MHz	2.250 kHz	9.0 kHz	10.0 ms	10.0 dB	0.0 dB	INPUT1

Peak List

Margin 6.0 dB
 Peaks 25

Trace	Frequency	Level (dBμV)	Phase	Detector	Delta Limit/dB
1	161.250000000 kHz	60.32	L1	Positive Peak	-5.08
2	163.500000000 kHz	50.37	L1	Average	-4.91
2	1.214250000 MHz	41.72	L1	Average	-4.28

Final Results

Meas Time 1.0 s
 Margin 6.0 dB
 Peaks 25

Trace	Frequency	Level (dBμV)	Phase	Detector	Delta Limit/dB
1	161.250000000 kHz	59.39	N	Quasi Peak	-6.01
2	163.500000000 kHz	48.53	N	CISPR AV	-6.75
2	1.214250000 MHz	40.94	L1	CISPR AV	-5.06

Heading dbc2 150W 2905
Meas Type
Equipment under Test
Manufacturer enko
OP Condition p
Operator g.aktas
Test Spec J

Scan Diagram

