

DBC2

Heading DBC2-150W-7-1510
Meas Type
Equipment under Test DBC2
Manufacturer ENKO
OP Condition p
Operator C.U.
Test Spec J

Settings

Scan Start	150.000000000 kHz	Preamplifier State	Off
Scan Stop	30.000000000 MHz	Preamplifier Value	0.0 dB
RBW	9.0 kHz	Input Selection	INP1
IF RBW	10.0 kHz	Input Coupling	AC
Meas Time	1.0 s	Scan Type	TD Scan
RF Att	10.0 dB	Transducer	ENV432 ENKO.TDF

Scan Table

Scan Start 150.000000000 kHz
 Scan Stop 30.000000000 MHz
 Scan Type TD Scan
 Transducer ENV432 ENKO.TDF
 Detector Trace 1: Max Peak Trace 2: Average

Start Frequency	Stop Frequency	Step Size	RBW	Meas Time	RF Atten	Preamplifier	Input
150.000 kHz	30.000 MHz	2.250 kHz	9.0 kHz	10.0 ms	10.0 dB	0.0 dB	INPUT1

Peak List

Margin 6.0 dB
 Peaks 25

Trace	Frequency	Level (dBμV)	Phase	Detector	Delta Limit/dB
1	186.000000000 kHz	59.29	L1	Positive Peak	-4.92
1	3.358500000 MHz	50.55	L1	Positive Peak	-5.45
2	13.002000000 MHz	44.09	L1	Average	-5.91
1	13.384500000 MHz	56.01	L1	Positive Peak	-3.99
1	16.836000000 MHz	57.40	L1	Positive Peak	-2.60
2	17.009250000 MHz	44.44	N	Average	-5.56

Final Results

Meas Time 1.0 s
 Margin 6.0 dB
 Peaks 25

Trace	Frequency	Level (dBμV)	Phase	Detector	Delta Limit/dB
1	186.000000000 kHz	57.42	L1	Quasi Peak	-6.79
1	3.358500000 MHz	45.27	L1	Quasi Peak	-10.73
2	13.002000000 MHz	42.95	L1	CISPR AV	-7.05
1	13.384500000 MHz	49.52	L1	Quasi Peak	-10.48
1	16.836000000 MHz	51.17	N	Quasi Peak	-8.83
2	17.009250000 MHz	43.87	N	CISPR AV	-6.13

Heading DBC2-150W-7-1510
Meas Type
Equipment under Test DBC2
Manufacturer ENKO
OP Condition p
Operator C.U.
Test Spec J

Scan Diagram

