

DBC2

Heading DBC2-150W-8-1510
Meas Type
Equipment under Test DBC2
Manufacturer ENKO
OP Condition p
Operator C.U.
Test Spec J

Settings

Scan Start	150.000000000 kHz	Preamp State	Off
Scan Stop	30.000000000 MHz	Preamp Value	0.0 dB
RBW	9.0 kHz	Input Selection	INP1
IF RBW	10.0 kHz	Input Coupling	AC
Meas Time	1.0 s	Scan Type	TD Scan
RF Att	10.0 dB	Transducer	ENV432 ENKO.TDF

Scan Table

Scan Start 150.000000000 kHz
 Scan Stop 30.000000000 MHz
 Scan Type TD Scan
 Transducer ENV432 ENKO.TDF
 Detector Trace 1: Max Peak Trace 2: Average

Start Frequency	Stop Frequency	Step Size	RBW	Meas Time	RF Atten	Preamp	Input
150.000 kHz	30.000 MHz	2.250 kHz	9.0 kHz	10.0 ms	10.0 dB	0.0 dB	INPUT1

Peak List

Margin 6.0 dB
 Peaks 25

Trace	Frequency	Level (dBμV)	Phase	Detector	Delta Limit/dB
1	188.250000000 kHz	58.54	L1	Positive Peak	-5.57
1	3.554250000 MHz	50.17	L1	Positive Peak	-5.83
1	12.117750000 MHz	54.35	L1	Positive Peak	-5.65
2	13.053750000 MHz	44.12	L1	Average	-5.88
1	13.056000000 MHz	55.76	L1	Positive Peak	-4.24
1	16.809000000 MHz	55.41	N	Positive Peak	-4.59
2	16.908000000 MHz	44.03	L1	Average	-5.97

Final Results

Meas Time 1.0 s
 Margin 6.0 dB
 Peaks 25

Trace	Frequency	Level (dBμV)	Phase	Detector	Delta Limit/dB
1	188.250000000 kHz	56.95	L1	Quasi Peak	-7.16
1	3.554250000 MHz	46.07	L1	Quasi Peak	-9.93
1	12.117750000 MHz	47.19	L1	Quasi Peak	-12.81
2	13.053750000 MHz	43.54	L1	CISPR AV	-6.46
1	13.056000000 MHz	49.14	L1	Quasi Peak	-10.86
1	16.809000000 MHz	49.86	N	Quasi Peak	-10.14
2	16.908000000 MHz	41.36	L1	CISPR AV	-8.64

Heading DBC2-150W-8-1510
Meas Type
Equipment under Test DBC2
Manufacturer ENKO
OP Condition p
Operator C.U.
Test Spec J

Scan Diagram

