

String decoder

Stability: 2 - Stable

Source Code: [lib/string_decoder.js](#)

The `node:string_decoder` module provides an API for decoding `Buffer` objects into strings in a manner that preserves encoded multi-byte UTF-8 and UTF-16 characters. It can be accessed using:

```
const { StringDecoder } = require('node:string_decoder'); copy
```

The following example shows the basic use of the `StringDecoder` class.

```
const { StringDecoder } = require('node:string_decoder');
const decoder = new StringDecoder('utf8');

const cent = Buffer.from([0xC2, 0xA2]);
console.log(decoder.write(cent)); // Prints: ¢

const euro = Buffer.from([0xE2, 0x82, 0xAC]);
console.log(decoder.write(euro)); // Prints: € copy
```

When a `Buffer` instance is written to the `StringDecoder` instance, an internal buffer is used to ensure that the decoded string does not contain any incomplete multibyte characters. These are held in the buffer until the next call to `stringDecoder.write()` or until `stringDecoder.end()` is called.

In the following example, the three UTF-8 encoded bytes of the European Euro symbol (€) are written over three separate operations:

```
const { StringDecoder } = require('node:string_decoder');
const decoder = new StringDecoder('utf8');

decoder.write(Buffer.from([0xE2]));
decoder.write(Buffer.from([0x82]));
console.log(decoder.end(Buffer.from([0xAC]))); // Prints: € copy
```

Class: `StringDecoder`

```
new StringDecoder([encoding])
```

- `encoding` <string> The character encoding the `StringDecoder` will use. **Default:** `'utf8'` .

Added in: v0.1.99

Creates a new `StringDecoder` instance.

```
stringDecoder.end([buffer])
```

- `buffer` [<string>](#) | [<Buffer>](#) | [<TypedArray>](#) | [<DataView>](#) The bytes to decode.
- Returns: [<string>](#)

Added in: v0.9.3

Returns any remaining input stored in the internal buffer as a string. Bytes representing incomplete UTF-8 and UTF-16 characters will be replaced with substitution characters appropriate for the character encoding.

If the `buffer` argument is provided, one final call to `stringDecoder.write()` is performed before returning the remaining input. After `end()` is called, the `stringDecoder` object can be reused for new input.

```
stringDecoder.write(buffer)
```

- `buffer` [<string>](#) | [<Buffer>](#) | [<TypedArray>](#) | [<DataView>](#) The bytes to decode.
- Returns: [<string>](#)

► History

Returns a decoded string, ensuring that any incomplete multibyte characters at the end of the `Buffer`, or `TypedArray`, or `DataView` are omitted from the returned string and stored in an internal buffer for the next call to `stringDecoder.write()` or `stringDecoder.end()`.

© Joyent, Inc. and other Node contributors

Licensed under the MIT License.

Node.js is a trademark of Joyent, Inc. and is used with its permission.

We are not endorsed by or affiliated with Joyent.

https://nodejs.org/dist/latest-v20.x/docs/api/string_decoder.html

Exported from DevDocs — <https://devdocs.io>