

## Query string

Stability: 2 - Stable

**Source Code:** [lib/querystring.js](#)

The `node:querystring` module provides utilities for parsing and formatting URL query strings. It can be accessed using:

```
const querystring = require('node:querystring'); copy
```

`querystring` is more performant than [<URLSearchParams>](#) but is not a standardized API. Use [<URLSearchParams>](#) when performance is not critical or when compatibility with browser code is desirable.

`querystring.decode()`

The `querystring.decode()` function is an alias for `querystring.parse()` .

Added in: v0.1.99

`querystring.encode()`

The `querystring.encode()` function is an alias for `querystring.stringify()` .

Added in: v0.1.99

`querystring.escape(str)`

- `str` [<string>](#)

Added in: v0.1.25

The `querystring.escape()` method performs URL percent-encoding on the given `str` in a manner that is optimized for the specific requirements of URL query strings.

The `querystring.escape()` method is used by `querystring.stringify()` and is generally not expected to be used directly. It is exported primarily to allow application code to provide a replacement percent-encoding implementation if necessary by assigning `querystring.escape` to an alternative function.

`querystring.parse(str[, sep[, eq[, options]]])`

- `str` [<string>](#) The URL query string to parse
- `sep` [<string>](#) The substring used to delimit key and value pairs in the query string. **Default:** `'&'` .
- `eq` [<string>](#) . The substring used to delimit keys and values in the query string. **Default:** `'='` .
- `options` [<Object>](#)
  - `decodeURIComponent` [<Function>](#) The function to use when decoding percent-encoded characters in the query string. **Default:** `querystring.unescape()` .

► History

- `maxKeys` <number> Specifies the maximum number of keys to parse. Specify `0` to remove key counting limitations. **Default:** `1000` .

The `querystring.parse()` method parses a URL query string ( `str` ) into a collection of key and value pairs.

For example, the query string `'foo=bar&abc=xyz&abc=123'` is parsed into:

```
{
  "foo": "bar",
  "abc": ["xyz", "123"]
} copy
```

The object returned by the `querystring.parse()` method *does not* prototypically inherit from the JavaScript `Object` . This means that typical `Object` methods such as `obj.toString()` , `obj.hasOwnProperty()` , and others are not defined and *will not work*.

By default, percent-encoded characters within the query string will be assumed to use UTF-8 encoding. If an alternative character encoding is used, then an alternative `decodeURIComponent` option will need to be specified:

```
// Assuming gbkDecodeURIComponent function already exists...

querystring.parse('w=%D6%D0%CE%C4&foo=bar', null, null,
  { decodeURIComponent: gbkDecodeURIComponent }); copy
```

```
querystring.stringify(obj[, sep[, eq[, options]])
```

- `obj` <Object> The object to serialize into a URL query string Added in: v0.1.25
- `sep` <string> The substring used to delimit key and value pairs in the query string. **Default:** `'&'` .
- `eq` <string> . The substring used to delimit keys and values in the query string. **Default:** `'='` .
- `options`
  - `encodeURIComponent` <Function> The function to use when converting URL-unsafe characters to percent-encoding in the query string. **Default:** `querystring.escape()` .

The `querystring.stringify()` method produces a URL query string from a given `obj` by iterating through the object's "own properties".

It serializes the following types of values passed in `obj` : <string> | <number> | <bigint> | <boolean> | <string[]> | <number[]> | <bigint[]> | <boolean[]> . The numeric values must be finite. Any other input values will be coerced to empty strings.

```
querystring.stringify({ foo: 'bar', baz: ['qux', 'quux'], corge: '' });
// Returns 'foo=bar&baz=qux&baz=quux&corge='

querystring.stringify({ foo: 'bar', baz: 'qux' }, ';', ':');
// Returns 'foo:bar;baz:qux' copy
```

By default, characters requiring percent-encoding within the query string will be encoded as UTF-8. If an alternative encoding is required, then an alternative `encodeURIComponent` option will need to be specified:

```
// Assuming gbkEncodeURIComponent function already exists,  
  
querystring.stringify({ w: '中文', foo: 'bar' }, null, null,  
    { encodeURIComponent: gbkEncodeURIComponent }); copy
```

```
querystring.unescape(str)
```

- `str` [<string>](#)

Added in: v0.1.25

The `querystring.unescape()` method performs decoding of URL percent-encoded characters on the given `str`.

The `querystring.unescape()` method is used by `querystring.parse()` and is generally not expected to be used directly. It is exported primarily to allow application code to provide a replacement decoding implementation if necessary by assigning `querystring.unescape` to an alternative function.

By default, the `querystring.unescape()` method will attempt to use the JavaScript built-in `decodeURIComponent()` method to decode. If that fails, a safer equivalent that does not throw on malformed URLs will be used.

© Joyent, Inc. and other Node contributors

Licensed under the MIT License.

Node.js is a trademark of Joyent, Inc. and is used with its permission.

We are not endorsed by or affiliated with Joyent.

<https://nodejs.org/dist/latest-v20.x/docs/api/querystring.html>

Exported from DevDocs — <https://devdocs.io>