

Spenso

Typed tensors, symbolic structures, and executable tensor networks

1 Overview

Spenso represents and evaluates tensors with abstract indices. It separates a tensor's structure—representations, slots, dimensions, names, and index order—from its stored data. Dense and sparse storage, symbolic and parametric values, automatic index matching, and network execution build on that separation.

Two questions, two layers

Tensor structure answers “which indices and representations does this object carry?” Tensor data answers “which values occupy that structure?” Contraction first matches compatible slots, then combines data. Keep these phases distinct when diagnosing a shape, duality, or contraction error.

1.1 Choose a task

- To verify slot duality with one numerical contraction, follow the [first-contraction tutorial](#) and the exact `Contract` reference.
- To assemble and execute several tensor/scalar nodes, use the [tensor-network guide](#) with the `Network` reference.
- To construct tensors or execute a network from Python, follow the [Python tensor-workflow guide](#) with the exact `TensorNetwork` reference.
- To parse symbolic tensor functions or apply Dirac/color identities, review the [feature and interface guide](#), then continue with `Idenso` for representation-aware rewrites.

1.2 From tensors to networks

The core package supports three related levels of work:

- tensor structures describe slots and abstract indices;
- dense, sparse, numeric, symbolic, and parametric tensors attach data to those structures;
- tensor networks represent a collection of tensors and choose an execution or contraction strategy.

Networks can be assembled directly. With the shadowing feature, they can also be inferred from Symbolica expressions whose functions carry recognizable tensor structure. Parsing is not mere string conversion: representation initialization, index variance, names, and the tensor library determine the inferred network.

```
[dependencies]  
spenso = "0.6"
```

Enable shadowing only when Symbolica-backed parsing or symbolic operations are needed. It pulls in the Symbolica integration and corresponding Linnet support. The default core remains useful for typed tensors and contractions without that layer.

1.3 Companion packages

Component ownership

`spenso` owns the tensor model and execution engine. `spenso-macros` owns the `SimpleRepresentation` derive used to declare custom index representations. `spenso-hep-lib` owns concrete high-energy-physics tensor-

library data such as gamma matrices and projectors. The `spynso3` adapter owns the Python community module. Their versions and feature gates are independent, so select and upgrade each component explicitly.

Spenso uses `Linnet` for the underlying network graph. `Idenso` is the symbolic-identity layer for Spenso-formatted Symbolica expressions. `GammaLoop` consumes these components inside a broader collider workflow.

The [interface guide](#) and generated Rust/Python references list the public modules, traits, feature gates, and import paths.

Contributors changing structures, contraction, parsing, storage, or network scheduling should also read the source-audited [Spenso implementation architecture](#).

2 Tutorial

This tutorial performs one concrete tensor contraction in Rust. The example makes the tensor structure, dual index matching, storage, and numerical result visible—the same layers that a larger Spenso network coordinates automatically.

2.1 Prerequisites

Use Rust 1.85 or newer (Spenso uses Rust 2024 edition), then create a binary project:

```
cargo new spenso-first-contraction
cd spenso-first-contraction
cargo add spenso@0.6
```

This first contraction uses dense integer tensors and needs neither Symbolica nor the shadowing feature.

2.2 Contract one shared index

Replace `src/main.rs` with:

```
use spenso::{
    contraction::Contract,
    structure::{
        OrderedStructure, PermutedStructure,
        representation::{LibraryRep, Lorentz, RepName},
        slot::{DualSlotTo, IsAbstractSlot},
    },
    tensors::data::{DenseTensor, GetTensorData, SetTensorData},
};

fn main() {
    let rep = Lorentz {};
    let left_free = rep.new_slot(2, 0).to_lib();
    let right_free = rep.new_slot(2, 2).to_lib();
    let shared = rep.new_slot(2, 10).to_lib();

    let left_structure: OrderedStructure<LibraryRep> =
        PermutedStructure::from_iter([left_free, shared]).structure;
    let right_structure: OrderedStructure<LibraryRep> =
        PermutedStructure::from_iter([right_free, shared.dual()]).structure;

    let mut left = DenseTensor::<i32, _>::zero(left_structure);
    let mut right = DenseTensor::<i32, _>::zero(right_structure);
    left.set(&[0, 1], 2).unwrap();
    right.set(&[0, 1], 5).unwrap();
```

```

let result = left.contract(&right).unwrap();
assert_eq!(*result.get_ref([0, 0]).unwrap(), 10);
println!("result structure: {}", result.structure);
println!("result data: {:?}", result.data);
}

```

Run `cargo run`. Success means the assertion passes and the printed result contains 10 at the component selected by the two remaining free indices. Spenso matched `shared` with `shared.dual()`, summed that axis, and preserved `left_free` and `right_free` in the output structure. The contraction follows index identity and duality, not merely equal dimensions.

Verification scope and cost

The docs harness compiles and runs this Rust program; it syntax-checks the setup commands without creating a project or using the network. Success is the asserted component value 10 with two free output indices. The contraction is tiny; a clean external Cargo build can take minutes, while the program itself should finish in well under a second.

Structure is part of the value

The data vectors alone do not say which axes may contract. Preserve the `OrderedStructure` with the tensor, and inspect the resulting structure before interpreting a flat component offset. A dimension match with unrelated abstract indices produces an exterior product, not the contraction shown above.

2.3 From two tensors to a network

Pairwise Contract is the clearest first success. For a larger expression, place tensors in a `Network`, inspect its graph, choose or benchmark a contraction strategy, and execute it. Use `DataTensor` when individual nodes may be dense or sparse. Enable shadowing only when the network must mix concrete data with Symbolica-backed parametric tensors.

2.4 Troubleshooting and next steps

- If contract leaves both shared-looking axes free, print their slots and check that one is the dual of the other; dimensions alone are insufficient.
- If set rejects a component, compare the coordinate count and each coordinate with the structure's rank and dimensions.
- If a sparse contraction reports an empty input, distinguish an intentionally zero tensor from a tensor whose nonzero entries were never populated.
- Continue with the tensor-structures and networks manual before selecting an automatic contraction strategy.

3 Tensor data, contraction, and network execution

Spenso keeps tensor structure and tensor data separate so the same structural operations work with dense, sparse, symbolic, or parametric storage. A structure supplies ordered slots, representations, dimensions, and abstract indices. Data supplies values and a storage-specific access strategy. Contraction first establishes structural compatibility and only then chooses a data operation.

3.1 Dense, sparse, and parametric data

Dense storage is appropriate when most components are populated and a predictable contiguous layout matters. Sparse storage is appropriate when zero structure dominates, but contraction cost depends on index overlap and lookup behavior rather than only the number of stored values. Parametric and symbolic tensors defer numeric substitution; keep their parameter environment with the tensor when serializing or moving a calculation between stages.

Conversions must preserve the structure's slot order. A tensor with the same dimensions but a different representation or variance is not interchangeable until an explicit structural operation establishes that relationship.

3.2 Contraction and planning

Pairwise contraction matches compatible dual slots, determines the output structure, and then contracts the selected data backends. A tensor network generalizes this to many nodes connected through abstract indices. Planning selects a contraction order; execution applies that plan to the current data.

The cheapest-looking local pair is not always the cheapest complete plan. Intermediate tensor dimensions, sparsity, symbolic expression growth, and reusable subexpressions can dominate. Record the planner/configuration with performance results and invalidate a stored plan when the network structure changes.

Plan structure, execute data

A plan is meaningful for the network structure it was derived from. Replacing values without changing slots can reuse it; adding a tensor, changing a representation, or rewiring an index requires validation or replanning.

3.3 Execute a small tensor/scalar network

This self-contained network computes $2a + 3b$ for two equally structured tensors. The dummy libraries make the execution boundary explicit: every tensor is already concrete and any unresolved function key is an error.

```
use spenso::{
    network::{
        ExecutionResult, Network, Sequential, SmallestDegree,
        library::{DummyKey, DummyLibrary, DummyLibraryTensor, panicing::ErroringLibrary},
        store::NetworkStore,
    },
    structure::{
        OrderedStructure,
        representation::{Euclidean, RepName},
    },
    tensors::data::DenseTensor,
};

fn main() {
    type Tensor = DenseTensor<f64, OrderedStructure<Euclidean>>;
    type Store = NetworkStore<Tensor, f64>;
    type Net = Network<Store, DummyKey, DummyKey>;
    type LibraryTensor = DummyLibraryTensor<Tensor>;

    let structure = OrderedStructure::new(vec![Euclidean {}.new_slot(2, 1)]).structure;
    let a = DenseTensor::from_data(vec![1.0, 2.0], structure.clone()).unwrap();
    let b = DenseTensor::from_data(vec![3.0, 4.0], structure).unwrap();
    let tensors = DummyLibrary::new();
    let functions = ErroringLibrary::new();

    let mut network =
        Net::from_scalar(2.0) * Net::from_tensor(a) + Net::from_scalar(3.0) *
        Net::from_tensor(b);
    network
        .execute:::<Sequential, SmallestDegree, LibraryTensor, _, _>(&tensors, &functions)
        .unwrap();

    let ExecutionResult::Val(result) = network.result_tensor:::<LibraryTensor,
    _>(&tensors).unwrap()
    else {
```

```
    panic!("expected a concrete tensor result");
};
assert_eq!(result.data, vec![11.0, 16.0]);
}
```

The output invariant is the component vector `[11.0, 16.0]`; the original rank-one structure must also remain attached to the result. The documentation harness compiles the complete program; run it to execute the assertion in a provisioned Symbolica environment. See the exact `Network`, `DenseTensor`, and `pairwise contraction` references.

Interpret execution failures by layer

`from_data` errors are rank/dimension or storage-length mismatches. An unresolved function-key error means the network contains a symbolic library node despite the concrete-only setup. A different value with the same shape points to scalar placement or node arithmetic; a different shape points to changed slots or unintended contraction, which requires replanning.

3.4 Symbolica shadowing

With shadowing, Spenso recognizes registered tensor functions inside Symbolica expressions and builds a network whose nodes shadow those subexpressions. Initialization of representations and the tensor library must happen before parsing. Unknown functions remain symbolic rather than silently acquiring tensor semantics.

Shadowing is useful for extracting a contraction problem while retaining a reversible link to the source expression. Keep the replacement map until the computed result has been substituted back. For rewrite identities and index cooking, use `Idenso` Spenso itself owns storage, contraction, and execution.

The implementation handoff from symbolic syntax into network nodes is traced in the Spenso parsing flow. The Symbolica syntax and rewrite guide records the contributor-facing matching and replacement conventions.

3.5 Custom representations and the HEP library

`SimpleRepresentation` derives the repetitive representation plumbing for a user enum. The derive input still defines domain semantics: duality, dimension, slot compatibility, and any Symbolica tags must agree. The resulting representations implement the ordinary Rust traits used by the rest of Spenso; the `spenso-macros` API reference lists the supported derive attributes.

`spenso-hep-lib` registers concrete high-energy-physics structures such as gamma matrices and projectors. Treat that library as shared domain data. `GammaLoop` uses the same definitions.

Graph and tensor ownership

`Linnet` owns connectivity, cuts, cycles, and graph mutation. Spenso owns which connected slots contract and how a plan is executed. Keeping that boundary explicit prevents a graph rewrite from being mistaken for a tensor-algebra identity.

4 Python tensor workflows

Spenso's Python interface is a native adapter over the same tensor structures, libraries, and network executor as the Rust crates. Use the generated reference for exact signatures and this guide for the object boundaries and execution sequence that those signatures do not explain.

4.1 Availability and version boundary

A Symbolica community module

Import Spenso as `symbolica.community.spenso`; there is no standalone `spenso` wheel. The installed Symbolica assembly determines whether the module is present and which Spenso API it contains. A source checkout or generated `.pyi` file does not add the native module to an existing Python environment.

Check the environment before building a workflow:

```
python -c "import symbolica.community.spenso as spenso; print(spenso.__name__)"
```

When a provider's Symbolica package does not include Spenso, build it through the `community-module` assembly. Record the Symbolica assembly version with reproducible results; it is a more useful Python compatibility fact than the version of an unrelated local Rust checkout.

4.2 Choose the right object

- Representation and Slot define dimensions, duality, and abstract indices.
- TensorIndices carries concrete abstract indices; TensorStructure describes a reusable shape whose indices can be assigned later.
- Tensor owns ordinary dense or sparse data. LibraryTensor is the named form registered in a TensorLibrary for reuse by symbolic networks.
- TensorNetwork owns an expression graph. ExecutionMode selects the rewrite strategy: one smallest-degree rewrite per step, scalar work only, or the general smallest-degree strategy. Use `n_steps`, not the mode, to bound how many execution steps run.
- TensorEvaluator substitutes repeated numerical parameter batches into a symbolic tensor; its compiled counterpart owns the generated native evaluator.

The generated `Representation`, `Tensor`, and `TensorNetwork` entries are the exact versioned contracts. Do not infer index compatibility from two equal dimensions: names, representations, and duality remain part of the value.

4.3 Construct and inspect concrete data

This complete source creates a named rank-two tensor, verifies one component, and converts its storage in place. The documentation harness compiles the Python source without importing the native module.

```
from symbolica.community.spenso import Representation, Tensor, TensorIndices

rep = Representation.euc(2)
i = rep("i")
j = rep("j")
indices = TensorIndices(i, j)
matrix = Tensor.dense(indices, [1.0, 0.0, 0.0, 1.0])

assert len(matrix) == 4
assert matrix[0, 0] == 1.0
matrix.to_sparse()
assert matrix[1, 1] == 1.0
```

`Tensor.dense` requires row-major data whose length is the product of the structure dimensions. `Tensor.sparse` instead needs the element type and starts empty. `to_dense()` and `to_sparse()` mutate the storage representation; they do not change slots or re-index the tensor. See the `dense` constructor and `conversion` contract.

Diagnose structure before storage

A constructor failure usually means the data length and dimensions disagree. An unexpected contraction or

exterior product is instead an index/duality problem. Print the structure and slots before changing dense/sparse storage, because a storage conversion cannot repair a structural mismatch.

4.4 Register data and execute a network

A symbolic network resolves named tensors through a library. Register the data first, construct the expression with the same name and compatible slots, then execute and request the result:

```
from symbolica.community.spenso import (
    ExecutionMode,
    LibraryTensor,
    Representation,
    TensorLibrary,
    TensorName,
    TensorNetwork,
    TensorStructure,
)

rep = Representation.euc(2)
A = TensorName("A")
structure = TensorStructure(rep, rep, name=A)
library = TensorLibrary()
library.register(LibraryTensor.dense(structure, [1.0, 0.0, 0.0, 1.0]))

network = TensorNetwork(A(rep("i"), rep("j")), library=library)
network.execute(library=library, mode=ExecutionMode.All)
result = network.result_tensor(library=library)
assert len(result) == 4
```

`ExecutionMode.Single` selects the smallest-degree single-rewrite strategy, but execution still continues while work remains unless it is bounded; use `n_steps=1` to inspect exactly one step. `Scalar` processes scalar work while retaining tensor structure, and `All` attempts the complete available execution. A successful `execute()` does not make `result_scalar()` appropriate for a tensor result; choose `result_tensor()` or `result_scalar()` according to the remaining structure. Exact behavior is linked from `execute`, `result_tensor`, and `ExecutionMode`.

Interpret a network failure by ownership

A missing-library error means a symbolic tensor name has no registered data. A result-kind error means the graph still has tensor structure when a scalar was requested, or vice versa. A changed network structure invalidates assumptions about contraction order; replacing only values with the same registered structure does not.

4.5 Repeated symbolic evaluation

Use `Tensor.evaluator()` when the tensor structure stays fixed and only symbolic parameters change across batches. Supply constants, custom functions, and parameters explicitly. Call `evaluate()` for real inputs and `evaluate_complex()` when coefficients or inputs are complex. `compile()` creates source and a shared library, so treat its filenames, compiler, architecture, and optimization level as reproducibility inputs rather than incidental arguments.

Control Symbolica-backed Rayon work with `SymbolicParallelism`: `Serial` keeps work on the calling thread, `Auto` checks license capability and applies workload heuristics, and `Parallel` forces Rayon without that safety choice. Configure the policy before benchmarking; otherwise a threading-policy change can be mistaken for an algorithmic improvement.

For exact parameters and defaults, use the [evaluator reference](#) and [symbolic parallelism reference](#). The implementation starts in the [Spenso Python adapter](#).

5 Rust, macros, and Python APIs

5.1 Core Rust package

The `spenso` crate organizes its public surface into structure, tensors, contraction, network, iterators, and algebra. The important abstractions form a progression:

- `TensorStructure` and related traits describe slots, names, and contraction compatibility;
- `DenseTensor`, `SparseTensor`, and the heterogeneous tensor enums own storage;
- contraction traits perform pairwise or multi-tensor operations;
- network stores and libraries bind symbolic tensor names to concrete data and execute a graph.

Trait implementations and generic constraints determine which combinations of structure and data support an operation. Consult the [curated Rust API](#) when a method is unavailable for a particular tensor type, then follow its Rustdoc link for exhaustive generic detail. The shadowing API and symbolic parallelism controls require their corresponding Cargo features.

5.2 Proc macros and HEP data

`spenso-macros` is a separate proc-macro crate. Its `SimpleRepresentation` derive generates the representation and duality boilerplate used by Spenso index types. A declaration supplies a symbolic name and chooses either `self_dual` or a `dual_name`:

```
use spenso_macros::SimpleRepresentation;
use spenso::structure::representation::RepName;

#[derive(SimpleRepresentation)]
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash, PartialOrd, Ord, Default)]
#[representation(name = "flavor", dual_name = "AntiFlavor")]
struct Flavor {}
```

The `spenso-macros` card in the [Rust reference](#) lists the derive's helper attributes, allowed targets, and feature conditions. Macro expansion happens at compile time and produces ordinary Rust implementations.

`spenso-hep-lib` supplies domain data and tensor-library construction for high-energy physics. It is intentionally separate from the generic core. Users who need gamma matrices or physics projectors add that package; generic Spenso users do not inherit those conventions implicitly.

5.3 Python community module

An adapter, not a Spenso wheel

Python users import `symbolica.community.spenso`. The implementation is the `spynso3` Rust adapter and is distributed through the Symbolica community-module mechanism. Enabling Spenso's Rust python feature only enables conversion interoperability; it does not create a standalone importable `spenso` Python distribution.

For a released Python assembly that includes Spenso, install the provider's Symbolica distribution with `python -m pip install symbolica`, then verify `python -c "import symbolica.community.spenso"`. Module availability follows the Symbolica assembly version; a local Spenso source checkout does not add the module to an installed wheel. Source embedders must add `spynso3` to the external `symbolica-community` assembly and invoke its `SymbolicaCommunityModule` registration while building that extension; building the Rust crate alone does not inject the module into another Symbolica wheel.

```
from symbolica.community.spenso import (
    Representation,
```

```

    Tensor,
    TensorIndices,
)

rep = Representation.euc(2)
indices = TensorIndices(rep("i"), rep("j"))
identity = Tensor.dense(indices, [1.0, 0.0, 0.0, 1.0])

```

The Python `tensor-workflow` guide connects construction, libraries, network execution, evaluators, and symbolic-parallelism policy. Use it with the structured Python reference, whose exact signatures can differ from the generic Rust API because `spynso3` provides Python-specific conversions and defaults.

Source starting points are the [core crate](#), the [derive crate](#), the [HEP library](#), and the [Python adapter](#).

6 Version history

History coverage

This version of Spenso is 0.6.0, but the published changelog currently ends at 0.5.6. Release notes for 0.6.0 are not yet available, so the history below is incomplete for that version. `spenso-macros`, `spenso-hep-lib`, and `spynso3` have independent versions and changelogs.

6.1 Available histories

- [Spenso core versions](#)
- [Spenso macros versions](#)
- [Spenso HEP library versions](#)
- [Spynso3 Python-adapter versions](#)

When upgrading, inspect the history for tensor structure, contraction, network parsing, Symbolica integration, and Python API or signature changes. Also check each companion component used by the application: a core Spenso release does not imply a release of the macro, HEP, or Python adapter package.

6.2 Upgrade checklist

Compare tensor structure and contraction behavior, network parsing, Symbolica integration, feature flags, and Python signatures for every component used by the application.

6.3 Reproducibility record

For reproducible upgrades, record the versions of Spenso and every companion component used by the application. Do not assume that changes between 0.5.6 and 0.6.0 are fully represented in the available notes.

7 Spenso versions

This page renders the canonical Spenso changelog source as part of the Spenso website, navigation, and search.

All notable changes to this project will be documented in this file.

The format is based on [Keep a Changelog](#), and this project adheres to [Semantic Versioning](#).

8.1 Unreleased

8.2 0.5.6 - 2026-01-08

8.2.1 Fixed

- fix python_stub_gen feature
- fix metric initialization and update to symbolica 1.2

8.2.2 Other

- update linnet

8.3 0.5.5 - 2025-12-15

8.3.1 Fixed

- fix canonization in presence of duals
- fix sum normalization in network parsing
- fix warnings
- fix overflowing slot order
- fix add_assign with sparse tensors

8.3.2 Other

- Update symbolica to 1.1.0
- update linnet
- add depth to parser, to stop at first mul
- remove more prints
- remove prints
- update linnet
- add readmes
- formatting and add ref for parametric
- update to 0.17 pyo3_stub_gen
- update linnet and make classattr to classmethods
- Release spenso-macros 0.3
- update to symbolica 1.0
- update sympolica to 0.20
- Properly precontract scalars
- Add back pyo3-stub-gen-derive
- Updated spenso with minor canonical string update for symbolica f2eb0c1ddcc61c342f2ff9616c2d129141d433dc
- Refactor coefficient conversions to support generic float types
- update to current dev symbolica and add pattern for pslash + m conjugate
- update to linnet 0.13.1
- working canonize (up to functions) and dirac adjoint
- spenso canonize buggy
- robust_conj but with lots of gamma_0s
- first try conj
- update python api
- working pow and fun execution
- working pow execution with wrapping
- support for executing pow and functions on tensors
- implement function library trait
- add function generic key

8.4 0.5.3 - 2025-08-18

8.4.1 Other

- update linnet to crates
- all tests pass
- Fix Multiple Heads Bug
- implement ExportNumber for `spenso::Complex`
- to Atom for ExpandedIndex
- remove printouts
- update linnet
- update linnet
- update linnet
- add infinite loop error test
- update parse problem and add `spenso::` to all symbols
- remove expand

8.5 0.5.2 - 2025-07-15

8.5.1 Other

- remove printout

8.6 0.5.1 - 2025-07-15

8.6.1 Fixed

- fix gamma algebra $\approx$

8.6.2 Other

- allow arbitrary arguments for to dots

9 Spenso macros versions

The procedural macros are versioned independently from Spenso. Their canonical version history remains the [spenso-macros changelog](#) source. This rendered copy integrates it with the manual, navigation, search, and product PDF.

All notable changes to this project will be documented in this file.

The format is based on [Keep a Changelog](#), and this project adheres to [Semantic Versioning](#).

10.1 Unreleased

10.2 0.3.2 - 2026-01-08

10.2.1 Fixed

- fix metric initialization and update to symbolica 1.2

10.2.2 Other

- update linnet

10.3 0.3.1 - 2025-12-15

10.3.1 Other

- Update symbolica to 1.1.0
- update linnet
- update linnet
- add readmes
- update linnet and make classattr to classmethods

10.4 0.2.1 - 2025-08-18

10.4.1 Other

- update linnet to crates
- update linnet
- update linnet
- update linnet

11 Spenso HEP library versions

The HEP helper library is versioned independently from Spenso. Its canonical version history remains the [spenso-hep-lib changelog](#) source. This rendered copy integrates it with the manual, navigation, search, and product PDF.

All notable changes to this project will be documented in this file.

The format is based on [Keep a Changelog](#), and this project adheres to [Semantic Versioning](#).

12.1 Unreleased

12.2 0.1.7 - 2026-01-14

12.2.1 Other

- update versions

12.3 0.1.6 - 2026-01-08

12.3.1 Fixed

- fix python_stub_gen feature
- fix metric initialization and update to symbolica 1.2

12.4 0.1.5 - 2025-12-15

12.4.1 Fixed

- fix warnings
- fix add_assign with sparse tensors

12.4.2 Other

- Update symbolica to 1.1.0
- update linnet
- add readmes

- Release spenso-macros 0.3
- update to symbolica 1.0
- update sympolica to 0.20
- Properly precontract scalars
- Refactor coefficient conversions to support generic float types
- working pow and fun execution
- working pow execution with wrapping
- add function generic key

12.5 0.1.3 - 2025-08-18

12.5.1 Other

- all tests pass
- update linnet

12.6 0.1.2 - 2025-07-15

12.6.1 Fixed

- fix gamma algebra again

12.6.2 Other

- update versions

12.7 0.1.1 - 2025-07-15

12.7.1 Fixed

- fix gamma algebra $\approx$

12.7.2 Other

- update release action
- allow arbitrary arguments for to dots

13 Spynso3 versions

The Python adapter is versioned independently from Spenso. Its canonical version history remains the [spynso3 changelog](#) source. This rendered copy integrates it with the manual, navigation, search, and product PDF.

All notable changes to this project will be documented in this file.

The format is based on [Keep a Changelog](#), and this project adheres to [Semantic Versioning](#).

14.1 Unreleased

14.2 0.1.2 - 2026-01-14

14.2.1 Other

- update versions

14.3 0.1.1 - 2025-12-15

14.3.1 Fixed

- fix sum normalization in network parsing
- fix warnings
- fix add_assign with sparse tensors
- fix projp
- fix param docs and iter return type
- fix pyo3_stubs

14.3.2 Other

- Update implementation to pyo3-stub-gen 0.17
- Update symbolica to 1.1.0
- update linnet
- add readmes
- update to 0.17 pyo3_stub_gen
- update linnet and make classattr to classmethods
- move initialize to api
- Release spenso-macros 0.3
- update to symbolica 1.0
- update sympolica to 0.20
- Properly precontract scalars
- Add back pyo3-stub-gen-derive
- update to current dev symbolica and add pattern for pslash + m conjugate
- first try conj
- update python api
- add function generic key
- again
- return any because python is dumb
- update __iter__ method
- use numpy doc format
- add overloaded pyi stub gen

API reference

The packages available in this version are listed below. Follow an item link for its complete language reference.

spenso

Spensor's supported tensor and network API. The scope is *intentionally* ordered so foundational tensor types precede planning and execution.

Tensor structure

Describes ordered slots, dimensions, representations, and contraction compatibility independently of data.

Describes ordered slots, dimensions, representations, and contraction compatibility independently of data.

```
pub trait TensorStructure {}
```

Reference feature matrix: shadowing (item is available without an additional gate)

Supported usage

```
fn accepts_structure<S: spenso::structure::TensorStructure>(_structure: &S) {}
```

Slot

Kind: AssociatedType

```
type Slot : IsAbstractSlot + DualSlotTo < Dual = Self :: Slot > ;
```

Abstract slot type used for the structure's external indices.

Indexed

Kind: AssociatedType

```
type Indexed : TensorStructure < Indexed = Self :: Indexed, Slot = Self :: Slot > ;
```

Structure type produced after assigning new abstract indices.

reindex

Kind: Method

```
fn reindex(self, indices : & [< Self :: Slot as IsAbstractSlot > :: Aind],) ->  
Result < PermutedStructure < Self :: Indexed > , StructureError >;
```

Replaces the slot indices in order and records any resulting permutations.

dual

Kind: Method

```
fn dual(self) -> Self;
```

Returns this structure with every external slot dualized.

string_rep

Kind: Method

```
fn string_rep(& self) -> String { ... }
```

Concatenates the display representation of all external slots.

external_structure_iter

Kind: Method

```
fn external_structure_iter(& self) -> impl Iterator < Item = Self :: Slot >;
```

Iterates over external slots in structure order.

external_dims_iter

Kind: Method

```
fn external_dims_iter(& self) -> impl Iterator < Item = Dimension >;
```

Iterates over the dimensions of external slots in structure order.

external_reps_iter

Kind: Method

```
fn external_reps_iter(& self,) -> impl Iterator < Item = Representation < < Self :: Slot as IsAbstractSlot > :: R > >;
```

Iterates over the representations of external slots in structure order.

external_indices_iter

Kind: Method

```
fn external_indices_iter(& self) -> impl Iterator < Item = < Self :: Slot as IsAbstractSlot > :: Aind >;
```

Iterates over the abstract indices of external slots in structure order.

get_aind

Kind: Method

```
fn get_aind(& self, i : impl Into < SlotIndex >) -> Option < < Self :: Slot as IsAbstractSlot > :: Aind >;
```

Returns the abstract index at a slot position, if it exists.

get_rep

Kind: Method

```
fn get_rep(& self, i : impl Into < SlotIndex > ,) -> Option < Representation < < Self :: Slot as IsAbstractSlot > :: R > >;
```

Returns the representation at a slot position, if it exists.

get_dim

Kind: Method

```
fn get_dim(& self, i : impl Into < SlotIndex >) -> Option < Dimension >;
```

Returns the dimension at a slot position, if it exists.

get_slot

Kind: Method

```
fn get_slot(& self, i : impl Into < SlotIndex >) -> Option < Self :: Slot >;
```

Returns the external slot at a position, if it exists.

order

Kind: Method

```
fn order(& self) -> usize;
```

Returns the number of external slots.

external_structure

Kind: Method

```
fn external_structure(& self) -> Vec < Self :: Slot > { ... }
```

returns the list of slots that are the external indices of the tensor

to_shell

Kind: Method

```
fn to_shell(self) -> TensorShell < Self > where Self : Sized, { ... }
```

Wraps this structure as a data-free tensor shell.

contains_matching

Kind: Method

```
fn contains_matching(& self, slot : & Self :: Slot) -> bool { ... }
```

Reports whether an external slot matches the supplied slot.

external_reps

Kind: Method

```
fn external_reps(& self) -> Vec < Representation < < Self :: Slot as  
IsAbstractSlot > :: R > > { ... }
```

Collects the external representations in structure order.

external_indices

Kind: Method

```
fn external_indices(& self) -> Vec < < Self :: Slot as IsAbstractSlot > ::  
Aind > { ... }
```

Collects the external abstract indices in structure order.

same_content

Kind: Method

```
fn same_content(& self, other : & Self) -> bool { ... }
```

checks if the tensor has the same exact structure as another tensor

match_index

Kind: Method

```
fn match_index(& self, other : & Self) -> Option < (bool, usize, usize) > { ... }
```

Given two [`TensorStructure``]'s, returns the index of the first matching slot in each external index list, along with a boolean indicating if there is a single match

match_indices

Kind: Method

```
fn match_indices(& self, other : & Self) -> Option <  
(Permutation, Vec < bool > , Vec < bool >) > { ... }
```

Given two [`TensorStructure``]'s, returns the index of the first matching slot in each external index list

traces

Kind: Method

```
fn traces(& self) -> Vec < [usize; 2] > { ... }
```

Identify the repeated slots in the external index list

shape

Kind: Method

```
fn shape(& self) -> Vec < Dimension > { ... }
```

yields the (outwards facing) shape of the tensor as a list of dimensions

reps

Kind: Method

```
fn reps(& self) -> Vec < Representation < < Self :: Slot as IsAbstractSlot >
:: R > > { ... }
```

Collects the external representations in structure order.

same_external

Kind: Method

```
fn same_external(& self, other : & Self) -> bool { ... }
```

checks if externally, the two tensors are the same

find_permutation

Kind: Method

```
fn find_permutation(& self, other : & Self) -> Result < Permutation > { ... }
```

find the permutation of the external indices that would make the two tensors the same. Applying the permutation to other should make it the same as self

strides_column_major

Kind: Method

```
fn strides_column_major(& self) -> Result < Vec < usize > > { ... }
```

yields the strides of the tensor in column major order

strides_row_major

Kind: Method

```
fn strides_row_major(& self) -> Result < Vec < usize > > { ... }
```

yields the strides of the tensor in row major order

strides

Kind: Method

```
fn strides(& self) -> Result < Vec < usize > > { ... }
```

By default, the strides are row major

verify_indices

Kind: Method

```
fn verify_indices < C : AsRef < [ConcreteIndex] > > (& self, indices : C) ->
Result < () > { ... }
```

Verifies that the list of indices provided are valid for the tensor

Errors

`Mismatched order` = if the length of the indices is different from the order of the tensor,

`Index out of bounds` = if the index is out of bounds for the dimension of that index

flat_index

Kind: Method

```
fn flat_index < C : AsRef < [ConcreteIndex] > > (& self, indices : C) ->  
Result < FlatIndex > { ... }
```

yields the flat index of the tensor given a list of indices

Errors

Same as [`Self::verify_indices`]

expanded_index

Kind: Method

```
fn expanded_index(& self, flat_index : FlatIndex) -> Result < ExpandedIndex > { ... }
```

yields the expanded index of the tensor given a flat index

Errors

`Index out of bounds` = if the flat index is out of bounds for the tensor

co_expanded_index

Kind: Method

```
fn co_expanded_index(& self, flat_index : FlatIndex) -> Result <  
DualConciousExpandedIndex > { ... }
```

Expands a flat index while retaining each representation's dual orientation.

index_iter

Kind: Method

```
fn index_iter(& self) -> TensorStructureIndexIterator < '_, Self > where Self  
: Sized, { ... }
```

yields an iterator over the indices of the tensor

is_scalar

Kind: Method

```
fn is_scalar(& self) -> bool { ... }
```

if the tensor has no (external) indices, it is a scalar

is_fully_self_dual

Kind: Method

```
fn is_fully_self_dual(& self) -> bool;
```

Reports whether every external representation is self-dual.

size

Kind: Method

```
fn size(& self) -> Result < usize > { ... }
```

yields the size of the tensor, i.e. the product of the dimensions. This is the length of the vector of the data in a dense tensor

[Exhaustive reference](#) · [Source](#)

Dense tensor

Stores every tensor component in structure-defined flat order.

Stores every tensor component in structure-defined flat order.

```
pub struct DenseTensor < T, S = OrderedStructure > {}
```

Reference feature matrix: shadowing (item is available without an additional gate)

Supported usage

```
use spenso::tensors::data::DenseTensor;
```

data

Kind: Field

Vec < T >

Components in the flat order defined by `structure`.

structure

Kind: Field

S

Tensor structure that maps external slots to flat component indices.

[Exhaustive reference](#) · [Source](#)

Sparse tensor

Stores only explicit tensor components keyed by flat index.

Sparse data tensor, generic on storage type `T`, and structure type `I`.

Stores data in a hashmap of usize, using ahash's hashmap.

The usize key is the flattened index of the corresponding position in the dense tensor

```
pub struct SparseTensor < T, I = OrderedStructure > {}
```

Reference feature matrix: shadowing (item is available without an additional gate)

Supported usage

```
use spenso::tensors::data::SparseTensor;
```

elements

Kind: Field

```
std :: collections :: HashMap < FlatIndex, T >
```

Explicitly stored components keyed by their flat indices.

zero

Kind: Field

T

Value used for components absent from `elements`.

structure

Kind: Field

I

Tensor structure that maps external slots to flat component indices.

[Exhaustive reference](#) · [Source](#)

Pairwise contraction

Defines pairwise tensor contraction with an explicit settings type and output.

Defines pairwise tensor contraction with an explicit settings type and output.

```
pub trait Contract < T = Self, Settings = () > {}
```

Reference feature matrix: shadowing (item is available without an additional gate)

Supported usage

```
fn can_contract<T: spenso::contraction::Contract>(_tensor: &T) {}
```

LCM

Kind: AssociatedType

type LCM;

Result type produced by contracting with `T`.

contract

Kind: Method

```
fn contract(& self, other : & T) -> Result < Self :: LCM, ContractionError >;
```

Contracts matching dual slots with `other` and returns the resulting tensor.

[Exhaustive reference](#) · [Source](#)

Tensor network

Binds symbolic tensor expressions to libraries and an executable contraction graph.

Binds symbolic tensor expressions to libraries and an executable contraction graph.

```
pub struct Network < S, LibKey, FunKey, Aind = AbstractIndex > {}
```

Reference feature matrix: shadowing (item is available without an additional gate)

Supported usage

```
use spenso::network::Network;
```

graph

Kind: Field

```
NetworkGraph < LibKey, FunKey, Aind >
```

Expression and contraction topology whose leaves reference stored values.

store

Kind: Field

S

Backing tensor and scalar storage referenced by graph leaves.

state

Kind: Field

NetworkState

Classification of the network result as scalar or tensor, including self-duality.

[Exhaustive reference](#) · [Source](#)

Network contraction strategy

Defines how a ready network operation is contracted and whether product subgraphs can be rewritten incrementally.

Defines how a ready network operation is contracted and whether product subgraphs can be rewritten incrementally.

```
pub trait ContractionStrategy < E, L, K, FK, Aind > : Sized {}
```

Reference feature matrix: shadowing (item is available without an additional gate)

Supported usage

```
use spenso::network::ContractionStrategy;
```

SUPPORTS_PARTIAL_GRAPH_REWRITE

Kind: AssociatedConst

```
const SUPPORTS_PARTIAL_GRAPH_REWRITE : bool = ...;
```

Whether this strategy can incrementally rewrite a ready product subgraph in place.

contract

Kind: AssociatedFunction

```
fn
contract(executor : & mut E, graph : & NetworkGraph < K, FK, Aind > ,
operation : & NetworkOperation < FK > , lib : & L,) -> Result < NetworkLeaf <
K, Aind > , TensorNetworkError < K, FK > > where K : Display, FK : Display;
```

Contracts one ready network operation into its replacement leaf.

contract_product_in_place

Kind: AssociatedFunction

```
fn
contract_product_in_place(executor : & mut E, graph : & mut NetworkGraph < K,
FK, Aind > , operation : & NetworkOperation < FK > , lib : & L, ignored : &
mut SuBitGraph,) -> Result < bool, TensorNetworkError < K, FK > > where K :
Display + Debug, FK : Display + Debug, Aind : AbsInd, { ... }
```

Attempts an in-place product rewrite and reports whether it made progress.

[Exhaustive reference](#) · [Source](#)

Network execution strategy

Defines how an executor repeatedly applies a selected contraction strategy until the strategy's stopping condition is reached.

Defines how an executor repeatedly applies a selected contraction strategy until the strategy's stopping condition is reached.

```
pub trait ExecutionStrategy < E, FL, L, K, FK, Aind > where E : ExecuteOp <
FL, L, K, FK, Aind > , {}
```

Reference feature matrix: shadowing (item is available without an additional gate)

Supported usage

```
use spenso::network::ExecutionStrategy;
```

execute_all

Kind: AssociatedFunction

```
fn execute_all < C : ContractionStrategy < E, L, K, FK, Aind > >
(executor : & mut E, graph : & mut NetworkGraph < K, FK, Aind > , lib : & L,
fnlib : & FL,) -> Result < (), TensorNetworkError < K, FK > > where K :
Display, FK : Display;
```

Run the entire contraction to one leaf.

[Exhaustive reference](#) · [Source](#)

Network execution mode

Enumerates sequential, parallel, borrowed-reference, and extracting execution modes.

Enumerates sequential, parallel, borrowed-reference, and extracting execution modes.

```
pub enum ExecutionMode {}
```

Reference feature matrix: shadowing (item is available without an additional gate)

Supported usage

```
use spenso::network::ExecutionMode;
```

Sequential

Kind: Variant

Executes ready operations serially against the original graph.

Parallel

Kind: Variant

Requests concurrent execution of independent ready operations with Rayon.

Execution falls back to the sequential path when Rayon is unavailable or partial graph rewriting requires it.

SequentialRef

Kind: Variant

Executes serially after locating ready operations through borrowed graph views.

SequentialExtract

Kind: Variant

Executes serially by extracting each ready operation's owned subgraph.

[Exhaustive reference](#) · [Source](#)

Network execution result

Represents a completed network as the multiplicative identity, the additive identity, or a concrete value.

Represents a completed network as the multiplicative identity, the additive identity, or a concrete value.

```
pub enum ExecutionResult < T > {}
```

Reference feature matrix: shadowing (item is available without an additional gate)

Supported usage

```
use spenso::network::ExecutionResult;
```

One

Kind: Variant

Multiplicative identity produced by an empty product.

Zero

Kind: Variant

Additive identity produced by an empty sum.

Val

Kind: Variant

Concrete scalar, tensor, or library-key result.

0

Kind: Field

T

Exhaustive reference · Source

Tensor-network error

Classifies invalid topology, contraction, library, structure, I/O, and result-shape failures during network processing.

Classifies invalid topology, contraction, library, structure, I/O, and result-shape failures during network processing.

```
pub enum TensorNetworkError < K : Display, FK : Display > {}
```

Reference feature matrix: shadowing (item is available without an additional gate)

Supported usage

```
use spenso::network::TensorNetworkError;
```

SlotEdgeToProdNode

Kind: Variant

A tensor-slot edge terminated at a product operation.

SlotEdgeToScalarNode

Kind: Variant

A tensor-slot edge terminated at a scalar node.

MoreThanOneNeg

Kind: Variant

A negation operation did not have exactly one child.

ChildlessNeg

Kind: Variant

A unary operation had no executable leaf child.

ContractionError**Kind:** Variant

Tensor contraction failed with the attached contraction error.

0**Kind:** Field

ContractionError

ScalarSlotEdge**Kind:** Variant

A scalar leaf was connected through a tensor-slot edge.

StructErr**Kind:** Variant

Tensor-structure validation or manipulation failed.

0**Kind:** Field

StructureError

LibErr**Kind:** Variant

Resolving a tensor through the tensor library failed.

0**Kind:** Field

LibraryError < K >

FunLibErr**Kind:** Variant

Applying a registered tensor function failed.

0**Kind:** Field

FunctionLibraryError < FK >

NonTensorNodePresent**Kind:** Variant

A tensor-only graph operation encountered another node kind.

NegativeExponentNonScalar**Kind:** Variant

A negative exponent was applied to a non-scalar result.

0**Kind:** Field

String

TooManyArgsFunction**Kind:** Variant

A function received an unsupported number of tensor arguments.

0**Kind:** Field

String

InvalidDotFunction**Kind:** Variant

A ``dot`` expression did not have exactly two arguments.

0**Kind:** Field

String

NonSelfDualTensorPower**Kind:** Variant

An integer power was applied to a non-self-dual tensor.

0**Kind:** Field

String

InvalidResultNode**Kind:** Variant

Execution produced a node that cannot represent a final result.

0**Kind:** Field

NetworkNode < DummyKey, FK >

InternalEdgePresent**Kind:** Variant

A final graph still contained an internal edge requiring contraction.

UncontractedScalar**Kind:** Variant

A scalar factor remained uncontracted in the final graph.

CannotContractEdgeBetween**Kind:** Variant

No contraction rule exists for the two endpoint node kinds.

0**Kind:** Field

String

1

Kind: Field

String

NoNodes

Kind: Variant

A result was requested from an empty graph.

NoScalar

Kind: Variant

A scalar result was requested but no scalar value was available.

MoreThanOneNode

Kind: Variant

A single result was requested from a graph with multiple nodes.

NotScalarOutput

Kind: Variant

A scalar result was requested from a non-scalar network.

FailedScalarMul

Kind: Variant

Multiplying scalar values failed to produce a result.

ScalarFieldEmpty

Kind: Variant

Scalar storage was unexpectedly empty.

NotAllScalars

Kind: Variant

A scalar-only operation encountered one or more tensor values.

0

Kind: Field

String

ScalarLibSum

Kind: Variant

A sum attempted to combine a scalar with a library tensor.

0

Kind: Field

String

SumScalarTensor

Kind: Variant

A sum attempted to combine a scalar with a materialized tensor.

0

Kind: Field

String

IncompatibleSummand

Kind: Variant

Summands had incompatible tensor structures or result states.

0

Kind: Field

String

FailedContract

Kind: Variant

A contraction operation failed.

0

Kind: Field

ContractionError

NegativeExponent

Kind: Variant

The requested negative exponent is not supported.

FailedContractMsg

Kind: Variant

A contraction operation failed with additional context.

0

Kind: Field

String

Other

Kind: Variant

An uncategorized network operation failed.

0

Kind: Field

eyre :: Error

InOut

Kind: Variant

Reading or writing network data failed.

0

Kind: Field

std :: io :: Error

Infallible

Kind: Variant

Marks the impossible conversion from an infallible error.

[Exhaustive reference](#) · [Source](#)

Network parsing settings

Controls scalar precontraction, depth limits, shorthand expansion and inference, scalar-leaf handling, and tensor-head recognition.

Controls scalar precontraction, depth limits, shorthand expansion and inference, scalar-leaf handling, and tensor-head recognition.

```
pub struct ParseSettings {}
```

Requires features: shadowing

Supported usage

```
let settings = spenso::network::parsing::ParseSettings::default();
```

precontract_scalars

Kind: Field

bool

Fold factors that parse as pure scalars into one scalar factor while parsing a product.

This keeps scalar-only subexpressions out of the tensor graph when they cannot affect contraction topology. Disable it when the caller needs every product factor to remain represented separately in the network.

take_first_term_from_sum

Kind: Field

bool

Parse only the first summand of an addition.

This is meant for structure discovery paths where all summands are expected to have the same external structure, for example listing dangling indices without building a full sum network.

depth_limit

Kind: Field

Option < usize >

Stop recursive parsing once the current parse depth reaches this value.

At the limit, the current expression is handed to the opaque tensor expression boundary as a leaf. `None` means there is no depth limit.

depth_is_product_depth

Kind: Field

bool

Selects what contributes to `depth\_limit`.

When true, only product nesting increments parse depth. When false,

additions and powers also increment depth before their children are parsed.

shorthand_parsing

Kind: Field

ShorthandParsing

Selects how shorthand notation is represented in the parsed network.

``Expand`` turns the selected shorthand families into explicit graph structure. Fresh dummies created by this lowering are local to the expansion.

``Opaque`` keeps shorthand as a leaf tensor or scalar. Its inference mode controls whether the exposed structure comes from a fast syntactic walk or from expanding the shorthand and reading the resulting dangling slots.

parse_composite_scalars_as_tensors

Kind: Field

bool

Allow parser implementations to treat composite scalar expressions as scalar-structured tensors.

Depth-limited additive or multiplicative scalar composites use this to stay represented as scalar-structured tensor leaves, so recursive contraction passes can inspect their internals instead of storing them as pure scalars.

strict_tensor_filter

Kind: Field

StrictTensorFilter

Controls which ordinary function heads are eligible tensor leaves.

Parser-owned syntax such as slots, representations, ``chain``, ``trace``, ``dot``, metric heads, and transparent brackets keeps its fixed meaning. This setting decides how strict the parser is for ordinary tensor heads: require tensor tags, require tensor tags plus visible representation arguments, or accept untagged heads that contain representation syntax.

Exhaustive reference · Source

Symbolic network parsing

Converts Symbolica atoms and atom views into parametric tensor networks under explicit parsing settings.

Converts Symbolica atoms and atom views into parametric tensor networks under explicit parsing settings.

pub trait NetworkParse {}

Requires features: shadowing

Supported usage

`use` `spenso::network::parsing::NetworkParse;`

parse_to_atom_net

Kind: Method

```
fn parse_to_atom_net < Aind : AbsInd + DummyAind + ParseableAind >
(& self, settings : & ParseSettings,) -> Result < ParamNet < Aind > ,
TensorNetworkError < DummyKey, Symbol > >;
```

Parses this symbolic expression into a parameterized tensor network using `settings`.

[Exhaustive reference](#) · [Source](#)

Symbolic parallelism policy

Chooses automatic license-aware, serial, or forced-parallel Rayon behavior for operations over Symbolica atoms.

Policy used to configure Rayon for operations that manipulate Symbolica atoms.

```
pub enum SymbolicParallelism {}
```

Requires features: shadowing

Supported usage

```
use spenso::symbolic_parallelism::SymbolicParallelism;
```

Auto

Kind: Variant

Permit Rayon when licensed and use workload heuristics where available.

Serial

Kind: Variant

Keep symbolic operations on the calling thread.

Parallel

Kind: Variant

Force Rayon without `Auto`'s Symbolica license safety check.

[Exhaustive reference](#) · [Source](#)

Parametric tensor

Stores tensor components as parameter-dependent symbolic coefficients.

Stores tensor components as parameter-dependent symbolic coefficients.

```
pub struct ParamTensor < S = OrderedStructure > {}
```

Requires features: shadowing

Supported usage

```
use spenso::tensors::parametric::ParamTensor;
```

tensor

Kind: Field

```
DataTensor < Atom, S >
```

Dense or sparse symbolic components together with their tensor structure.

param_type

Kind: Field

ParamOrComposite

Whether the components are primitive parameters or composite expressions.

[Exhaustive reference](#) · [Source](#)

spenso-macros

Spenso's exported procedural macros. Expansion details remain in the exhaustive Rustdoc sidecar.

SimpleRepresentation derive

Derives representation naming and duality boilerplate from the representation helper attribute.

Derives representation naming and duality boilerplate from the representation helper attribute.

```
#[derive(SimpleRepresentation)]
fn derive_simple_representation(input : TokenStream) -> TokenStream
```

Reference feature matrix: shadowing (item is available without an additional gate)

Supported usage

```
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash, PartialOrd, Ord, Default,
spenso_macros::SimpleRepresentation)] #[representation(name = "flavor", self_dual)]
struct Flavor;
```

[Exhaustive reference](#) · [Source](#)

spenso-hep-lib

Spenso's high-energy-physics companion library. These entries *complement* the tensor concepts owned by the main Spenso documentation.

HEP tensor library

Constructs the standard high-energy-physics tensor library for a chosen scalar data type.

Constructs the standard high-energy-physics tensor library for a chosen scalar data type.

```
fn hep_lib < Aind : AbsInd, T : TensorLibraryData + Clone + Default >
(one : T, zero : T,) -> TensorLibrary < MixedTensor < T, ExplicitKey < Aind >
> , Aind >
```

Parameter	Type
one	T
zero	T

Returns: TensorLibrary < MixedTensor < T, ExplicitKey < Aind > > , Aind >

Supported usage

```
use spenso_hep_lib::hep_lib;
```

[Exhaustive reference](#) · [Source](#)

Dirac gamma data

Creates sparse Dirac-basis gamma-matrix data for the supplied tensor structure.

Creates sparse Dirac-basis gamma-matrix data for the supplied tensor structure.

```
fn gamma_data_dirac < T, N > (structure : N, one : T, zero : T) ->
SparseTensor < Complex < T > , N > where T : Clone + Neg < Output = T > , N :
TensorStructure,
```

Parameter	Type
structure	N
one	T
zero	T

Returns: SparseTensor < Complex < T > , N >

Supported usage

```
use spenso_hep_lib::gamma_data_dirac;
```

Exhaustive reference · Source

SU(3) generator data

Creates the standard sparse SU(3) fundamental-generator tensor.

Fundamental SU(3) generators in the normalization $\text{Tr}(T^a T^b) = 1/2 \delta^{ab}$.

The index order follows `CS.t_strct`: adjoint, fundamental, anti-fundamental.

```
fn su3_generator_data < N > (structure : N) -> SparseTensor < Complex < f64 >
, N > where N : TensorStructure,
```

Parameter	Type
structure	N

Returns: SparseTensor < Complex < f64 > , N >

Supported usage

```
use spenso_hep_lib::su3_generator_data;
```

Exhaustive reference · Source

spynso3

Exports registered by spynso3.

CompiledTensorEvaluator

A compiled and optimized evaluator for maximum performance tensor evaluation.

A compiled and optimized evaluator for maximum performance tensor evaluation.

This class wraps a compiled C++ shared library for extremely fast numerical evaluation of tensor expressions. It only supports complex-valued evaluation as this is the most general case.

A compiled and optimized evaluator for maximum performance tensor evaluation.

This class wraps a compiled C++ shared library for extremely fast numerical evaluation of tensor expressions. It only supports complex-valued evaluation as this is the most general case.

Create instances using the `TensorEvaluator.compile()` method.

Examples

```
-----
>>> compiled = evaluator.compile("eval_func", "code.cpp", "lib")
>>> results = compiled.evaluate_complex(large_input_batch)

class CompiledTensorEvaluator:
```

Requires features: python_stubgen

evaluate_complex

Kind: Method

```
def evaluate_complex(self, inputs: Sequence[Sequence[complex]]) -> list[Tensor]:
```

Evaluate the tensor expression for multiple complex-valued parameter inputs.

Uses the compiled C++ code for maximum performance evaluation with complex numbers.

Parameters

```
-----
inputs : list of list of complex
    List of parameter value lists, where each inner list contains
    complex values for all parameters in the same order as specified
    when creating the original evaluator
```

Returns

```
-----
list of Tensor
    List of evaluated tensors, one for each input parameter set
```

Examples

```
-----
>>> complex_inputs = [
...     [1.0+2.0j, 3.0+0.0j],
...     [0.0+1.0j, 2.0+1.0j]
... ]
>>> results = compiled_evaluator.evaluate_complex(complex_inputs)
```

inputs

Kind: Parameter

Sequence[Sequence[complex]]

List of parameter value lists, where each inner list contains complex values for all parameters in the same order as specified when creating the original evaluator

Exhaustive reference · Source

LibraryTensor

A library tensor class optimized for use in tensor libraries and networks.

A library tensor class optimized for use in tensor libraries and networks.

Library tensors are similar to regular tensors but use explicit keys for efficient lookup and storage in tensor libraries. They can be either dense or sparse and store data as floats, complex numbers, or symbolic expressions.

LibraryTensors are designed for:

- Registration in TensorLibrary instances
- Use in tensor networks where structure reuse is important
- Efficient symbolic manipulation and pattern matching

Examples

```
>>> from symbolica.community.spenso import LibraryTensor, TensorStructure,
Representation
>>> rep = Representation.euc(3)
>>> structure = TensorStructure(rep, rep, name="T")
>>> data = [1.0, 0.0, 0.0, 0.0, 1.0, 0.0, 0.0, 0.0, 1.0]
>>> tensor = LibraryTensor.dense(structure, data)
>>> sparse_tensor = LibraryTensor.sparse(structure, float)
```

```
class LibraryTensor:
```

Requires features: python_stubgen

structure

Kind: Method

```
def structure(self) -> TensorStructure:
```

sparse

Kind: AssociatedFunction

```
def sparse(structure: TensorStructure | list[Representation] | list[int], type_info:
type) -> LibraryTensor:
```

Create a new sparse empty library tensor with the given structure and data type.

Creates a sparse tensor that initially contains no non-zero elements.
Elements can be set individually using indexing operations.

Parameters

structure : TensorStructure, list of Representations, or list of int
The tensor structure defining shape and index properties
type_info : type
The data type - either `float` or `Expression` class

Returns

LibraryTensor

A new sparse library tensor with all elements initially zero

Examples

```
>>> import symbolica as sp
>>> from symbolica.community.spenso import LibraryTensor, TensorStructure,
Representation
>>> rep = Representation.euc(3)
>>> structure = TensorStructure(rep, rep)
>>> sparse_float = LibraryTensor.sparse(structure, float)
>>> sparse_sym = LibraryTensor.sparse(structure, sp.Expression)
>>> sparse_float[0, 0] = 1.0
>>> sparse_float[1, 1] = 2.0
```

structure

Kind: Parameter

TensorStructure | list[Representation] | list[int]

The tensor structure defining shape and index properties

type_info

Kind: Parameter

type

The data type - either `float` or `Expression` class

dense

Kind: AssociatedFunction

```
def dense(structure: TensorStructure | list[Representation] | list[int], data:
Sequence[Expression] | Sequence[float] | Sequence[complex]) -> LibraryTensor:
```

Create a new dense library tensor with the given structure and data.

Dense tensors store all elements explicitly in row-major order. The structure defines the tensor's shape and indexing properties.

Parameters

structure : TensorStructure, list of Representations, or list of int
 The tensor structure defining shape and index properties
data : list of float, complex, or Expression
 The tensor data in row-major order

Returns

LibraryTensor

 A new dense library tensor with the specified data

Examples

```
>>> from symbolica import S
>>> from symbolica.community.spensio import LibraryTensor, TensorStructure,
Representation
>>> rep = Representation.euc(2)
>>> sigma = S("sigma")
>>> structure = TensorStructure(rep, rep, name=sigma)
>>> data = [0.0, 1.0, 1.0, 0.0]
>>> tensor = LibraryTensor.dense(structure, data)
>>> x, y = S("x", "y")
>>> sym_data = [x, y, -y, x]
>>> sym_tensor = LibraryTensor.dense(structure, sym_data)
```

structure

Kind: Parameter

TensorStructure | list[Representation] | list[int]

The tensor structure defining shape and index properties

data

Kind: Parameter

Sequence[Expression] | Sequence[float] | Sequence[complex]

The tensor data in row-major order

one

Kind: AssociatedFunction

```
def one() -> LibraryTensor:
```

Create a scalar library tensor with value 1.0.

Returns

LibraryTensor

A scalar library tensor containing the value 1.0

Examples

```
>>> from symbolica.community.spenso import LibraryTensor
```

```
>>> one = LibraryTensor.one()
```

zero

Kind: AssociatedFunction

```
def zero() -> LibraryTensor:
```

Create a scalar library tensor with value 0.0.

Returns

LibraryTensor

A scalar library tensor containing the value 0.0

Examples

```
>>> from symbolica.community.spenso import LibraryTensor
```

```
>>> zero = LibraryTensor.zero()
```

to_dense

Kind: Method

```
def to_dense(self) -> None:
```

Convert this library tensor to dense storage format.

Converts sparse tensors to dense format in-place. Dense tensors are unchanged.
This allocates memory for all tensor elements.

Examples:

```
```python
```

```
from symbolica.community.spenso import LibraryTensor, TensorStructure, Representation
```

```
rep = Representation.cof(2)
```

```
structure = TensorStructure([rep, rep])
```

```
tensor = LibraryTensor.sparse(structure, float)
```

```
tensor[0, 0] = 1.0
```

```
tensor.to_dense() # Now stores all 4 elements explicitly
```

```
```
```

to_sparse

Kind: Method

```
def to_sparse(self) -> None:
```

Convert this library tensor to sparse storage format.

Converts dense tensors to sparse format in-place, only storing non-zero elements. This can save memory for tensors with many zero elements.

Examples:

```
```python
from symbolica.community.spenso import LibraryTensor, TensorStructure, Representation

rep = Representation.euc(2)
structure = TensorStructure(rep, rep)
data = [1.0, 0.0, 0.0, 2.0]
tensor = LibraryTensor.dense(structure, data)
tensor.to_sparse() # Now only stores 2 non-zero elements
```
```

__repr__

Kind: Method

```
def __repr__(self) -> str:
```

__str__

Kind: Method

```
def __str__(self) -> str:
```

__len__

Kind: Method

```
def __len__(self) -> int:
```

__getitem__

Kind: Method

__getitem__

Kind: Overload

```
def __getitem__(self, item: slice | int | list[int]) -> Any:
```

item

Kind: Parameter

slice | int | list[int]

__getitem__

Kind: Overload

```
def __getitem__(self, item: slice) -> list[Expression | complex | float]:
```

Get library tensor elements at the specified range of indices.

Parameters

item : slice

 Slice object defining the range of indices

Returns

list of float, complex, or Expression
The tensor elements at the specified range

item

Kind: Parameter

slice

Slice object defining the range of indices

__getitem__

Kind: Overload

```
def __getitem__(self, item: Sequence[int] | int) -> Expression | complex | float:
```

Get library tensor element at the specified index or indices.

Parameters

item : int or list of int

Index specification (int for flat index, list of int for coordinates)

Returns

float, complex, or Expression

The tensor element at the specified index

item

Kind: Parameter

Sequence[int] | int

Index specification (int for flat index, list of int for coordinates)

__setitem__

Kind: Method

__setitem__

Kind: Overload

```
def __setitem__(self, item: Any, value: Any) -> None:
```

Set library tensor element(s) at the specified index or indices.

Parameters

item : int or list of int

Index specification (int for flat index, list of int for coordinates)

value : float, complex, or Expression

The value to set

Examples

```
>>> from symbolica.community.spenso import LibraryTensor, TensorStructure, Representation
>>> rep = Representation.euc(2)
>>> structure = TensorStructure(rep, rep)
>>> tensor = LibraryTensor.sparse(structure, float)
>>> tensor[0] = 1.0
>>> tensor[1, 1] = 2.0
```

item

Kind: Parameter

Any

Index specification (int for flat index, list of int for coordinates)

value

Kind: Parameter

Any

The value to set

__setitem__

Kind: Overload

```
def __setitem__(self, item: Sequence[int] | int, value: Expression | complex | float)
-> None:
```

Set library tensor element(s) at the specified index or indices.

Parameters

item : int or list of int

Index specification (int for flat index, list of int for coordinates)

value : float, complex, or Expression

The value to set

Examples

```
>>> from symbolica.community.spenso import LibraryTensor, TensorStructure,
Representation
```

```
>>> rep = Representation.euc(2)
```

```
>>> structure = TensorStructure(rep, rep)
```

```
>>> tensor = LibraryTensor.sparse(structure, float)
```

```
>>> tensor[0] = 1.0
```

```
>>> tensor[1, 1] = 2.0
```

item

Kind: Parameter

Sequence[int] | int

Index specification (int for flat index, list of int for coordinates)

value

Kind: Parameter

Expression | complex | float

The value to set

scalar

Kind: Method

```
def scalar(self) -> Expression:
```

Extract the scalar value from a rank-0 (scalar) library tensor.

Returns

Expression

The scalar expression contained in this tensor

Raises

RuntimeError

If the tensor is not a scalar

Examples

```
>>> from symbolica.community.spenso import LibraryTensor
>>> scalar_tensor = LibraryTensor.one()
>>> value = scalar_tensor.scalar()
```

Exhaustive reference · Source

Representation

A representation in the sense of group representation theory for tensor indices.

A representation in the sense of group representation theory for tensor indices.

Representations define the transformation properties of tensor indices under group operations.

They specify the dimension and duality structure, determining which indices can contract.

Key concepts:

- **Self-dual**: Indices can contract with other indices of the same representation
- **Dualizable**: Indices can only contract with their dual representation
- **Dimension**: Size of the representation space

Predefined representations are available as class methods:

- `Representation.euc(d)`: Euclidean space (self-dual)
- `Representation.mink(d)`: Minkowski space (self-dual)
- `Representation.bis(d)`: Bispinor (self-dual)
- `Representation.cof(d)`: Color fundamental (dualizable)
- `Representation.coad(d)`: Color adjoint (self-dual)
- `Representation.cos(d)`: Color sextet (dualizable)

Examples:

```
```python
from symbolica.community.spenso import Representation

Standard representations
euclidean = Representation.euc(4) # 4D Euclidean
lorentz = Representation.mink(4) # 4D Minkowski
color = Representation.cof(3) # SU(3) fundamental
adjoint = Representation.coad(8) # SU(3) adjoint

Custom representation
custom = Representation("MyRep", 5, is_self_dual=True)

Create slots with indices
mu_slot = euclidean('mu') # Euclidean index μ
a_slot = color('a') # Color index a

Generate metric tensors
```

```
metric = euclidean.g('mu', 'nu') # gμν
...
```

class Representation:

**Requires features:** python\_stubgen

**\_\_call\_\_**

**Kind:** Method

**\_\_call\_\_**

**Kind:** Overload

```
def __call__(self, aind: int | Expression | str) -> Slot:
```

Create a slot from this representation, by specifying an index.

Parameters

-----

aind : int, str, or Symbol  
    The index specification

Returns

-----

Slot

    A new Slot object with the specified index

Examples

-----

```
>>> from symbolica.community.spenso import Representation
>>> import symbolica as sp
>>> rep = Representation.euc(3)
>>> slot1 = rep('mu')
>>> slot2 = rep(1)
>>> slot3 = rep(sp.S('nu'))
```

**aind**

**Kind:** Parameter

int | Expression | str

The index specification

**\_\_call\_\_**

**Kind:** Overload

```
def __call__(self, aind: Expression) -> Expression | Slot:
```

Create a slot or symbolic expression from this representation.

Parameters

-----

aind : Expression  
    The index specification (Expression creates symbolic representation)

Returns

-----

Expression

    A symbolic expression representing this representation

## Examples

-----

```
>>> from symbolica.community.spenso import Representation
>>> import symbolica as sp
>>> rep = Representation.euc(3)
>>> expr = rep(sp.E("cos(x)"))
```

### **aind**

**Kind:** Parameter

Expression

The index specification (Expression creates symbolic representation)

### **\_\_new\_\_**

**Kind:** AssociatedFunction

```
def __new__(cls, name: str, dimension: int | Expression | str, is_self_dual: bool
= ...) -> Representation:
```

Create and register a new representation with specified properties.

# Parameters:

- name: String name for the representation
- dimension: Size of the representation (int or symbolic)
- is\_self\_dual: If True, creates self-dual representation; if False, creates dualizable pair

# Examples:

```
```python
```

```
from symbolica.community.spenso import Representation
import symbolica as sp
```

```
# Self-dual representation (indices contract with themselves)
euclidean = Representation("Euclidean", 4, is_self_dual=True)
```

```
# Dualizable representation (needs dual partner for contraction)
vector_up = Representation("VectorUp", 4, is_self_dual=False)
```

```
# Symbolic dimension
```

```
n = sp.S('n')
```

```
general = Representation("General", n, is_self_dual=True)
```

```
```
```

### **name**

**Kind:** Parameter

str

### **dimension**

**Kind:** Parameter

int | Expression | str

### **is\_self\_dual**

**Kind:** Parameter

bool

**Default:** ...

## **dual**

**Kind:** Method

```
def dual(self) -> Representation:
```

## **g**

**Kind:** Method

```
def g(self, i: int | Expression | str, j: int | Expression | str) -> TensorIndices:
```

Create a metric tensor for this representation.

# Parameters:

- i: First index
- j: Second index

# Examples:

```
```python
rep = Representation.mink(4)
metric = rep.g('mu', 'nu') # Minkowski metric  $g_{\mu\nu}$ 
```
```

## **i**

**Kind:** Parameter

int | Expression | str

## **j**

**Kind:** Parameter

int | Expression | str

## **flat**

**Kind:** Method

```
def flat(self, i: int | Expression | str, j: int | Expression | str) ->
TensorIndices:
```

Create a musical isomorphism tensor for this representation.

# Parameters:

- i: First index
- j: Second index

# Examples:

```
```python
rep = Representation.mink(4)
flat = rep.flat('mu', 'nu') # Flat isomorphism  $b_{\mu\nu}$ 
```
```

## **i**

**Kind:** Parameter

int | Expression | str

## **j**

**Kind:** Parameter

int | Expression | str

## **id**

**Kind:** Method

def id(self, i: int | Expression | str, j: int | Expression | str) -> TensorIndices:  
Create an identity tensor for this representation.

# Parameters:

- i: First index
- j: Second index

# Examples:

```
```python  
rep = Representation.cof(3)  
identity = rep.id('a', 'b') # Color identity  $\delta_{ab}$   
```
```

## **i**

**Kind:** Parameter

int | Expression | str

## **j**

**Kind:** Parameter

int | Expression | str

## **\_\_repr\_\_**

**Kind:** Method

def \_\_repr\_\_(self) -> str:

## **\_\_str\_\_**

**Kind:** Method

def \_\_str\_\_(self) -> str:

## **to\_expression**

**Kind:** Method

def to\_expression(self) -> Expression:  
Convert the representation to a symbolic expression.

## **bis**

**Kind:** AssociatedFunction

def bis(dimension: int | Expression | str) -> Representation:  
Create a bispinor representation.

# Parameters:

- dimension: The dimension of the bispinor space

## **dimension**

**Kind:** Parameter

int | Expression | str

## **euc**

**Kind:** AssociatedFunction

```
def euc(dimension: int | Expression | str) -> Representation:
```

```
Create a Euclidean space representation.
```

```
Parameters:
```

```
- dimension: The dimension of the Euclidean space
```

```
dimension
```

```
Kind: Parameter
```

```
int | Expression | str
```

```
mink
```

```
Kind: AssociatedFunction
```

```
def mink(dimension: int | Expression | str) -> Representation:
```

```
Create a Minkowski space representation.
```

```
Parameters:
```

```
- dimension: The dimension of the Minkowski space
```

```
dimension
```

```
Kind: Parameter
```

```
int | Expression | str
```

```
cof
```

```
Kind: AssociatedFunction
```

```
def cof(dimension: int | Expression | str) -> Representation:
```

```
Create a color fundamental representation.
```

```
Parameters:
```

```
- dimension: The dimension of the color group (e.g., 3 for SU(3))
```

```
dimension
```

```
Kind: Parameter
```

```
int | Expression | str
```

```
coad
```

```
Kind: AssociatedFunction
```

```
def coad(dimension: int | Expression | str) -> Representation:
```

```
Create a color adjoint representation.
```

```
Parameters:
```

```
- dimension: The dimension of the adjoint representation (e.g., 8 for SU(3))
```

```
dimension
```

```
Kind: Parameter
```

```
int | Expression | str
```

```
cos
```

```
Kind: AssociatedFunction
```

```
def cos(dimension: int | Expression | str) -> Representation:
```

Create a color sextet representation.

# Parameters:

- dimension: The dimension of the sextet representation (e.g., 6 for SU(3))

**dimension**

**Kind:** Parameter

int | Expression | str

[Exhaustive reference](#) · [Source](#)

**Slot**

A tensor index slot combining a representation with an abstract index.

A tensor index slot combining a representation with an abstract index.

Slots are the building blocks for tensor structures, pairing a representation (which defines transformation properties) with an abstract index identifier. Slots with matching representations and indices can be contracted.

# Examples:

```
```python
from symbolica.community.spenso import Slot, Representation
import symbolica as sp
```

Create representation and slots

```
rep = Representation.euc(3)
slot1 = rep('mu')          # Slot with string index
slot2 = rep(1)              # Slot with integer index
slot3 = rep(sp.S('nu'))    # Slot with symbolic index
```

Create custom slot

```
custom_slot = Slot("MyRep", 4, 'alpha', dual=False)
```

Use in tensor structures

```
from symbolica.community.spenso import TensorIndices
tensor_structure = TensorIndices(slot1, slot2)
```
```

class Slot:

**Requires features:** python\_stubgen

**\_\_repr\_\_**

**Kind:** Method

```
def __repr__(self) -> str:
```

**\_\_str\_\_**

**Kind:** Method

```
def __str__(self) -> str:
```

**dual**

**Kind:** Method

```
def dual(self) -> Slot:
```

## **\_\_new\_\_**

**Kind:** AssociatedFunction

```
def __new__(cls, name: str, dimension: int, aind: int | Expression | str, dual: bool = ...) -> Slot:
```

Create a new slot with a custom representation and index.

# Parameters:

- name: String name for the representation
- dimension: Size of the representation space
- aind: The abstract index (int, str, or Symbol)
- dual: If True, creates dualizable representation; if False, self-dual

# Examples:

```
```python
from symbolica.community.spenso import Slot
import symbolica as sp

# Self-dual slot
euclidean_slot = Slot("Euclidean", 4, 'mu', dual=False)

# Dualizable slot
vector_slot = Slot("Vector", 4, 'nu', dual=True)

# With symbolic index
sym_index = sp.S('alpha')
symbolic_slot = Slot("Custom", 3, sym_index, dual=False)
```
```

## **name**

**Kind:** Parameter

str

## **dimension**

**Kind:** Parameter

int

## **aind**

**Kind:** Parameter

int | Expression | str

## **dual**

**Kind:** Parameter

bool

**Default:** ...

## **to\_expression**

**Kind:** Method

```
def to_expression(self) -> Expression:
```

Convert the slot to a symbolic expression.

# Examples:

```

```python
rep = Representation.euc(3)
slot = rep('mu')
expr = slot.to_expression() # Symbolic representation of the slot
```

```

Exhaustive reference · Source

## Tensor

A tensor class that can be either dense or sparse with flexible data types.

A tensor class that can be either dense or sparse with flexible data types.

The tensor can store data as floats, complex numbers, or symbolic expressions.

Tensors have an associated structure that defines their shape and index properties.

Examples

```

>>> from symbolica.community.spenso import Tensor, TensorIndices, Representation
>>> structure = TensorIndices(Representation.euc(4)(1))
>>> data = [1.0, 2.0, 3.0, 4.0]
>>> tensor = Tensor.dense(structure, data)
>>> sparse_tensor = Tensor.sparse(structure, float)

```

class Tensor:

**Requires features:** python\_stubgen

### structure

**Kind:** Method

def structure(self) -> TensorIndices:

### sparse

**Kind:** AssociatedFunction

def sparse(structure: TensorIndices | list[Slot], type\_info: type) -> Tensor:

Create a new sparse empty tensor with the given structure and data type.

Parameters

```

structure : TensorIndices or list of Slots
 The tensor structure defining shape and index properties
type_info : type
 The data type - either `float` or `Expression` class

```

Returns

```

Tensor
 A new sparse tensor with all elements initially zero

```

Examples

```

>>> from symbolica.community.spenso import Tensor, TensorIndices, Representation as R
>>> structure = TensorIndices(R.euc(3)(1), R.euc(3)(2))
>>> sparse_float = Tensor.sparse(structure, float)
>>> sparse_sym = Tensor.sparse(structure, symbolica.Expression)

```

## **structure**

**Kind:** Parameter

TensorIndices | list[Slot]

The tensor structure defining shape and index properties

## **type\_info**

**Kind:** Parameter

type

The data type - either `float` or `Expression` class

## **dense**

**Kind:** AssociatedFunction

```
def dense(structure: TensorIndices | list[Slot], data: Sequence[Expression] |
Sequence[float] | Sequence[complex]) -> Tensor:
```

Create a new dense tensor with the given structure and data.

Parameters

-----

structure : TensorIndices or list of Slots

The tensor structure defining shape and index properties

data : list of float, complex, or Expression

The tensor data in row-major order

Returns

-----

Tensor

A new dense tensor with the specified data

Examples

-----

```
>>> from symbolica import S
>>> from symbolica.community.spenso import Tensor, TensorIndices, Representation as R
>>> structure = TensorIndices(R.euc(2)(1), R.euc(2)(2))
>>> data = [1.0, 2.0, 3.0, 4.0]
>>> tensor = Tensor.dense(structure, data)
>>> x, y = S("x", "y")
>>> sym_data = [x, y, x * y, x + y]
>>> sym_tensor = Tensor.dense(structure, sym_data)
```

## **structure**

**Kind:** Parameter

TensorIndices | list[Slot]

The tensor structure defining shape and index properties

## **data**

**Kind:** Parameter

Sequence[Expression] | Sequence[float] | Sequence[complex]

The tensor data in row-major order

## **one**

**Kind:** AssociatedFunction

```
def one() -> Tensor:
```

Create a scalar tensor with value 1.0.

Returns

-----

Tensor

A scalar tensor containing the value 1.0

Examples

-----

```
>>> from symbolica.community.spenso import Tensor
>>> one = Tensor.one()
```

### **zero**

**Kind:** AssociatedFunction

```
def zero() -> Tensor:
```

Create a scalar tensor with value 0.0.

Returns

-----

Tensor

A scalar tensor containing the value 0.0

Examples

-----

```
>>> from symbolica.community.spenso import Tensor
>>> zero = Tensor.zero()
```

### **to\_dense**

**Kind:** Method

```
def to_dense(self) -> None:
```

Convert this tensor to dense storage format.

Converts sparse tensors to dense format in-place. Dense tensors are unchanged.  
This allocates memory for all tensor elements.

Examples

-----

```
>>> from symbolica.community.spenso import Tensor, TensorIndices, Representation as R
>>> structure = TensorIndices(R.euc(4)(2))
>>> tensor = Tensor.sparse(structure, float)
>>> tensor[0] = 1.0
>>> tensor.to_dense()
```

### **to\_sparse**

**Kind:** Method

```
def to_sparse(self) -> None:
```

Convert this tensor to sparse storage format.

Converts dense tensors to sparse format in-place, only storing non-zero elements.  
This can save memory for tensors with many zero elements.

Examples

```

>>> from symbolica.community.spenso import Tensor, TensorIndices, Representation as R
>>> structure = TensorIndices(R.euc(2)(2), R.euc(2)(1))
>>> data = [1.0, 0.0, 0.0, 2.0]
>>> tensor = Tensor.dense(structure, data)
>>> tensor.to_sparse()

```

**\_\_repr\_\_**

**Kind:** Method

```
def __repr__(self) -> str:
```

**\_\_str\_\_**

**Kind:** Method

```
def __str__(self) -> str:
```

**\_\_len\_\_**

**Kind:** Method

```
def __len__(self) -> int:
```

**\_\_getitem\_\_**

**Kind:** Method

**\_\_getitem\_\_**

**Kind:** Overload

```
def __getitem__(self, item: slice | int | list[int]) -> Any:
```

**item**

**Kind:** Parameter

slice | int | list[int]

**\_\_getitem\_\_**

**Kind:** Overload

```
def __getitem__(self, item: slice) -> list[Expression | complex | float]:
```

Get tensor elements at the specified range of indices.

Parameters

-----

**item** : slice

Slice object defining the range of indices

Returns

-----

list of float, complex, or Expression

The tensor elements at the specified range

**item**

**Kind:** Parameter

slice

Slice object defining the range of indices

### **\_\_getitem\_\_**

**Kind:** Overload

```
def __getitem__(self, item: Sequence[int] | int) -> Expression | complex | float:
```

Get tensor element at the specified index or indices.

Parameters

-----

**item** : int or list of int

Index specification (int for flat index, list of int for coordinates)

Returns

-----

float, complex, or Expression

The tensor element at the specified index

**item**

**Kind:** Parameter

Sequence[int] | int

Index specification (int for flat index, list of int for coordinates)

### **\_\_setitem\_\_**

**Kind:** Method

### **\_\_setitem\_\_**

**Kind:** Overload

```
def __setitem__(self, item: Any, value: Any) -> None:
```

Set tensor element(s) at the specified index or indices.

Parameters

-----

**item** : int or list of int

Index specification (int for flat index, list of int for coordinates)

**value** : float, complex, or Expression

The value to set

Examples

-----

```
>>> from symbolica.community.spenso import Tensor, TensorIndices, Representation as R
>>> structure = TensorIndices(R.euc(2)(2), R.euc(2)(1))
>>> tensor = Tensor.sparse(structure, float)
>>> tensor[0] = 4.0
>>> tensor[1, 1] = 1.0
```

**item**

**Kind:** Parameter

Any

Index specification (int for flat index, list of int for coordinates)

**value**

**Kind:** Parameter

Any

The value to set

### **\_\_setitem\_\_**

**Kind:** Overload

```
def __setitem__(self, item: int | Sequence[int], value: Expression | complex | float)
-> None:
```

Set tensor element at the specified index.

#### Parameters

-----

**item** : int or list of int

Index specification (int for flat index, list of int for coordinates)

**value** : float, complex, or Expression

The value to set

#### Examples

-----

```
>>> from symbolica.community.spenso import Tensor, TensorIndices, Representation
>>> rep = Representation.euc(2)
>>> structure = TensorIndices(rep(1), rep(2))
>>> tensor = Tensor.sparse(structure, float)
>>> tensor[0] = 1.0
>>> tensor[1, 1] = 2.0
```

### **item**

**Kind:** Parameter

int | Sequence[int]

Index specification (int for flat index, list of int for coordinates)

### **value**

**Kind:** Parameter

Expression | complex | float

The value to set

### **evaluator**

**Kind:** Method

```
def evaluator(self, constants: Mapping[Expression, Expression], funs:
Mapping[tuple[Expression, str, Sequence[Expression]], Expression], params:
Sequence[Expression], iterations: int = ..., n_cores: int = ..., verbose: bool = ...)
-> TensorEvaluator:
```

Create an optimized evaluator for symbolic tensor expressions.

Compiles the symbolic expressions in this tensor into an optimized evaluation tree that can efficiently compute numerical values for different parameter inputs.

#### Parameters

-----

**constants** : dict

Dict mapping symbolic expressions to their constant numerical values

**funs** : dict

Dict mapping function signatures to their symbolic definitions

**params** : list of Expression

List of symbolic parameters that will be varied during evaluation  
iterations : int, optional  
    Number of optimization iterations for Horner scheme (default: 100)  
n\_cores : int, optional  
    Number of CPU cores to use for optimization (default: 4)  
verbose : bool, optional  
    Whether to print optimization progress (default: False)

Returns

-----

TensorEvaluator

    An optimized evaluator for efficient numerical evaluation

Examples

-----

```
>>> from symbolica import S
>>> from symbolica.community.spenso import Tensor, TensorIndices, Representation as R
>>> x, y = S("x", "y")
>>> structure = TensorIndices(R.euc(2)(1))
>>> tensor = Tensor.dense(structure, [x * y, x + y])
>>> evaluator = tensor.evaluator(constants={}, funcs={}, params=[x, y], iterations=50)
>>> results = evaluator.evaluate_complex([[1.0, 2.0], [3.0, 4.0]])
```

**constants**

**Kind:** Parameter

Mapping[Expression, Expression]

Dict mapping symbolic expressions to their constant numerical values

**funcs**

**Kind:** Parameter

Mapping[tuple[Expression, str, Sequence[Expression]], Expression]

Dict mapping function signatures to their symbolic definitions

**params**

**Kind:** Parameter

Sequence[Expression]

List of symbolic parameters that will be varied during evaluation

**iterations**

**Kind:** Parameter

int

**Default:** ...

Number of optimization iterations for Horner scheme (default: 100)

**n\_cores**

**Kind:** Parameter

int

**Default:** ...

Number of CPU cores to use for optimization (default: 4)

## **verbose**

**Kind:** Parameter

bool

**Default:** ...

Whether to print optimization progress (default: False)

## **scalar**

**Kind:** Method

def scalar(self) -> Expression:

Extract the scalar value from a rank-0 (scalar) tensor.

Returns

-----

Expression

The scalar expression contained in this tensor

Raises

-----

RuntimeError

If the tensor is not a scalar

Examples

-----

```
>>> from symbolica.community.spenso import Tensor
```

```
>>> scalar_tensor = Tensor.one()
```

```
>>> value = scalar_tensor.scalar()
```

## **\_\_iter\_\_**

**Kind:** Method

def \_\_iter\_\_(self) -> Iterator[Any]:

Iterator

Exhaustive reference · Source

## **TensorEvaluator**

An optimized evaluator for symbolic tensor expressions.

An optimized evaluator for symbolic tensor expressions.

This class provides efficient numerical evaluation of symbolic tensor expressions after optimization. It supports both real and complex-valued evaluations.

Create instances using the ``Tensor.evaluator()`` method rather than directly.

Examples

-----

```
>>> evaluator = my_tensor.evaluator(constants={}, funs={}, params=[x, y])
```

```
>>> results = evaluator.evaluate([[1.0, 2.0], [3.0, 4.0]])
```

```
class TensorEvaluator:
```

**Requires features:** python\_stubgen

## **evaluate**

**Kind:** Method

```
def evaluate(self, inputs: Sequence[Sequence[float]]) -> list[Tensor]:
```

Evaluate the tensor expression for multiple real-valued parameter inputs.

Parameters

-----

**inputs** : list of list of float

List of parameter value lists, where each inner list contains numerical values for all parameters in the same order as specified when creating the evaluator

Returns

-----

list of Tensor

List of evaluated tensors, one for each input parameter set

Raises

-----

ValueError

If the evaluator contains complex coefficients

Examples

-----

```
>>> results = evaluator.evaluate([[1.0, 2.0], [3.0, 4.0]])
```

## **inputs**

**Kind:** Parameter

Sequence[Sequence[float]]

List of parameter value lists, where each inner list contains numerical values for all parameters in the same order as specified when creating the evaluator

## **evaluate\_complex**

**Kind:** Method

```
def evaluate_complex(self, inputs: Sequence[Sequence[complex]]) -> list[Tensor]:
```

Evaluate the expression for multiple inputs and return the results.

## **inputs**

**Kind:** Parameter

Sequence[Sequence[complex]]

## **compile**

**Kind:** Method

```
def compile(self, function_name: str, filename: str, library_name: str, inline_asm: str = ..., optimization_level: int = ..., compiler_path: Optional[str] = None, custom_header: Optional[str] = None) -> CompiledTensorEvaluator:
```

Compile the evaluator to a shared library using C++ for maximum performance.

Generates optimized C++ code with optional inline assembly and compiles it into a shared library that can be loaded for extremely fast evaluation.

## Parameters

-----

**function\_name** : str

Name for the generated C++ function

**filename** : str

Path for the generated C++ source file

**library\_name** : str

Name for the compiled shared library

**inline\_asm** : str, optional

Type of inline assembly optimization ("default", "x64", "aarch64", "none")

**optimization\_level** : int, optional

Compiler optimization level 0-3 (default: 3)

**compiler\_path** : str, optional

Path to specific C++ compiler (default: system default)

**custom\_header** : str, optional

Additional C++ header code to include

## Returns

-----

**CompiledTensorEvaluator**

A compiled evaluator for maximum performance evaluation

## Examples

-----

```
>>> compiled = evaluator.compile(
... function_name="fast_eval",
... filename="tensor_eval.cpp",
... library_name="tensor_lib",
... optimization_level=3,
...)
>>> results = compiled.evaluate_complex([[1.0, 2.0], [3.0, 4.0]])
```

### **function\_name**

**Kind:** Parameter

str

Name for the generated C++ function

### **filename**

**Kind:** Parameter

str

Path for the generated C++ source file

### **library\_name**

**Kind:** Parameter

str

Name for the compiled shared library

### **inline\_asm**

**Kind:** Parameter

str

**Default:** ...

Type of inline assembly optimization ("default", "x64", "aarch64", "none")

### **optimization\_level**

**Kind:** Parameter

int

**Default:** ...

Compiler optimization level 0-3 (default: 3)

### **compiler\_path**

**Kind:** Parameter

Optional[str]

**Default:** None

Path to specific C++ compiler (default: system default)

### **custom\_header**

**Kind:** Parameter

Optional[str]

**Default:** None

Additional C++ header code to include

Exhaustive reference · Source

## **TensorIndices**

A tensor structure with abstract indices for symbolic tensor operations.

A tensor structure with abstract indices for symbolic tensor operations.

TensorIndices represents the index structure of tensors with named abstract indices that can be contracted, manipulated symbolically, and converted to expressions. It maintains both the representation structure and index assignments.

Examples

-----

```
>>> from symbolica.community.spenso import TensorIndices, Representation, TensorName
>>> rep = Representation.euc(3)
>>> mu = rep('mu')
>>> nu = rep('nu')
>>> indices = TensorIndices(mu, nu)
>>> T = TensorName("T")
>>> named_indices = T(mu, nu)
>>> expr = named_indices.to_expression()
```

```
class TensorIndices:
```

**Requires features:** python\_stubgen

### **set\_name**

**Kind:** Method

```
def set_name(self, name: TensorName | str | Expression) -> None:
```

Set the tensor name for this structure.

## Parameters

-----

**name** : `TensorName`

The tensor name to assign

## Examples

-----

```
>>> from symbolica.community.spenso import TensorIndices, TensorName, Representation
>>> rep = Representation.euc(3)
>>> structure = TensorIndices(rep('mu'), rep('nu'))
>>> T = TensorName("T")
>>> structure.set_name(T)
```

### **name**

**Kind:** Parameter

`TensorName` | `str` | `Expression`

The tensor name to assign

### **get\_name**

**Kind:** Method

`def get_name(self) -> Optional[TensorName]:`

Get the tensor name of this structure.

### Returns

-----

`TensorName` or `None`

The tensor name if set, `None` otherwise

## Examples

-----

```
>>> name = structure.get_name()
```

### **\_\_repr\_\_**

**Kind:** Method

`def __repr__(self) -> str:`

### **\_\_str\_\_**

**Kind:** Method

`def __str__(self) -> str:`

### **to\_expression**

**Kind:** Method

`def to_expression(self) -> Expression:`

Convert the tensor indices to a symbolic expression.

Creates a symbolic representation of the tensor with its indices that can be used in algebraic manipulations and pattern matching.

### Returns

-----

`Expression`

A symbolic `Expression` representing this indexed tensor

Raises

-----

RuntimeError

If the tensor structure has no name

Examples

-----

```
>>> from symbolica.community.spenso import TensorName, Representation
>>> T = TensorName("T")
>>> rep = Representation.euc(3)
>>> mu = rep('mu')
>>> nu = rep('nu')
>>> indices = T(mu, nu)
>>> expr = indices.to_expression()
```

**`__len__`**

**Kind:** Method

```
def __len__(self) -> int:
```

**`__add__`**

**Kind:** Method

```
def __add__(self, rhs: Expression | int | str | float | complex | TensorIndices |
Expression) -> Expression:
```

Add this expression to `other`, returning the result.

**rhs**

**Kind:** Parameter

Expression | int | str | float | complex | TensorIndices | Expression

**`__radd__`**

**Kind:** Method

```
def __radd__(self, rhs: Expression | int | str | float | complex | TensorIndices |
Expression) -> Expression:
```

Add this expression to `other`, returning the result.

**rhs**

**Kind:** Parameter

Expression | int | str | float | complex | TensorIndices | Expression

**`__sub__`**

**Kind:** Method

```
def __sub__(self, rhs: Expression | int | str | float | complex | TensorIndices |
Expression) -> Expression:
```

Subtract `other` from this expression, returning the result.

**rhs**

**Kind:** Parameter

Expression | int | str | float | complex | TensorIndices | Expression

**\_\_rsub\_\_**

**Kind:** Method

```
def __rsub__(self, rhs: Expression | int | str | float | complex | TensorIndices |
Expression) -> Expression:
```

Subtract this expression from `other`, returning the result.

**rhs**

**Kind:** Parameter

Expression | int | str | float | complex | TensorIndices | Expression

**\_\_mul\_\_**

**Kind:** Method

```
def __mul__(self, rhs: Expression | int | str | float | complex | TensorIndices |
Expression) -> Expression:
```

Add this expression to `other`, returning the result.

**rhs**

**Kind:** Parameter

Expression | int | str | float | complex | TensorIndices | Expression

**\_\_rmul\_\_**

**Kind:** Method

```
def __rmul__(self, rhs: Expression | int | str | float | complex | TensorIndices |
Expression) -> Expression:
```

Add this expression to `other`, returning the result.

**rhs**

**Kind:** Parameter

Expression | int | str | float | complex | TensorIndices | Expression

**\_\_new\_\_**

**Kind:** AssociatedFunction

```
def __new__(cls, *slots: TensorIndices | list[Slot], name: TensorName | str |
Expression | None = None) -> TensorIndices:
```

Create tensor structure from slots and optional arguments.

Parameters

-----

**\*additional\_args** : Slot or Expression

Mixed arguments (Slot objects and Expressions for additional arguments)

**name** : TensorName, optional

Optional tensor name to assign to the structure

Returns

-----

TensorIndices

A new TensorIndices object

Examples

-----

```

>>> from symbolica import S
>>> from symbolica.community.spenso import TensorIndices, Representation, TensorName
>>> rep = Representation.euc(3)
>>> mu = rep('mu')
>>> nu = rep('nu')
>>> structure = TensorIndices(mu, nu)
>>> x = S('x')
>>> structure_with_args = TensorIndices(mu, nu, x)
>>> T = TensorName("T")
>>> named_structure = TensorIndices(mu, nu, name=T)

```

### slots

**Kind:** Parameter

TensorIndices | list[Slot]

### name

**Kind:** Parameter

TensorName | str | Expression | None

**Default:** None

Optional tensor name to assign to the structure

### \_\_getitem\_\_

**Kind:** Method

### \_\_getitem\_\_

**Kind:** Overload

```
def __getitem__(self, item: slice) -> list[Expression | complex | float]:
```

Get expanded indices at the specified range of flattened indices.

Parameters

-----

item : slice

Slice object defining the range of indices

Returns

-----

list of list of int

List of expanded indices

### item

**Kind:** Parameter

slice

Slice object defining the range of indices

### \_\_getitem\_\_

**Kind:** Overload

```
def __getitem__(self, item: Sequence[int]) -> Expression | complex | float:
```

Get flattened index associated to this expanded index.

Parameters

-----

item : list of int  
Multi-dimensional index coordinates

Returns

-----

int  
The flat index

**item**

**Kind:** Parameter

Sequence[int]

Multi-dimensional index coordinates

**\_\_getitem\_\_**

**Kind:** Overload

def \_\_getitem\_\_(self, item: int) -> Expression | complex | float:

Get expanded index associated to this flat index.

Parameters

-----

item : int  
Flat index into the tensor

Returns

-----

list of int  
Multi-dimensional index coordinates

**item**

**Kind:** Parameter

int

Flat index into the tensor

Exhaustive reference · Source

## TensorLibrary

A library for registering and managing tensor templates and structures.

A library for registering and managing tensor templates and structures.

The TensorLibrary provides a centralized registry for tensor definitions that can be reused across tensor networks and expressions. It manages tensor structures with their associated names and can resolve symbolic references to registered tensors.

```
```python
import symbolica
from symbolica.community.spenso import TensorLibrary, LibraryTensor, TensorStructure, Representation
```

```
lib = TensorLibrary()
rep = Representation.euc(3)
name = symbolica.S("my_tensor")
structure = TensorStructure(rep, rep, name=name)
```

```

tensor = LibraryTensor.dense(structure, [1.0, 0.0, 0.0, 1.0, 0.0, 0.0, 1.0, 0.0,
0.0])
lib.register(tensor)
tensor_ref = lib[name]
```

```

```

class TensorLibrary:

```

**Requires features:** python\_stubgen

**\_\_new\_\_**

**Kind:** AssociatedFunction

```

def __new__(cls) -> TensorLibrary:

```

Create a new empty tensor library.

Initializes an empty library ready for registering tensor structures.  
The library automatically manages internal tensor IDs.

Returns

-----

TensorLibrary

A new empty tensor library

Examples

-----

```

>>> from symbolica.community.spenso import TensorLibrary

```

```

>>> lib = TensorLibrary()

```

**construct**

**Kind:** AssociatedFunction

```

def construct() -> TensorLibrary:

```

Create a new empty tensor library (static method).

Initializes an empty library ready for registering tensor structures.  
The library automatically manages internal tensor IDs.

Returns

-----

TensorLibrary

A new empty tensor library

Examples

-----

```

>>> from symbolica.community.spenso import TensorLibrary

```

```

>>> lib = TensorLibrary.construct()

```

**register**

**Kind:** Method

```

def register(self, tensor: Tensor | LibraryTensor) -> None:

```

Register a tensor in the library.

Adds a tensor template to the library that can be referenced by name  
in tensor networks and symbolic expressions. The tensor must have a name  
set in its structure.

## Parameters

-----

tensor : LibraryTensor or Tensor

The tensor to register - can be a LibraryTensor or regular Tensor

## Examples

-----

```
>>> import symbolica
>>> from symbolica.community.spenso import TensorLibrary, LibraryTensor,
TensorStructure, Representation
>>> lib = TensorLibrary()
>>> rep = Representation.euc(3)
>>> name = symbolica.S("my_tensor")
>>> structure = TensorStructure(rep, rep, name=name)
>>> tensor = LibraryTensor.dense(structure, [1.0, 0.0, 0.0, 1.0, 0.0, 0.0, 1.0, 0.0,
0.0])
>>> lib.register(tensor)
>>> tensor_ref = lib[name]
```

## tensor

**Kind:** Parameter

Tensor | LibraryTensor

The tensor to register - can be a LibraryTensor or regular Tensor

## \_\_getitem\_\_

**Kind:** Method

```
def __getitem__(self, key: Expression | int | str | float | complex | str) ->
TensorStructure:
```

Retrieve a registered tensor structure by name.

Looks up a previously registered tensor by its name and returns  
a reference structure that can be used to create new tensor instances.

## Parameters

-----

key : str or Expression

The tensor name - can be a string or symbolic expression

## Returns

-----

TensorStructure

A TensorStructure representing the registered tensor template

## Raises

-----

RuntimeError

If the tensor name is not found in the library

## Examples

-----

```
>>> structure = lib["T"]
```

**key**

**Kind:** Parameter

Expression | int | str | float | complex | str

The tensor name - can be a string or symbolic expression

**hep\_lib**

**Kind:** AssociatedFunction

```
def hep_lib() -> TensorLibrary:
```

Create a library pre-loaded with High Energy Physics tensor definitions.

Returns a library containing standard HEP tensors such as gamma matrices, color generators, metric tensors, and other commonly used structures in particle physics calculations. They are floating point tensors with f64 precision.

Returns

-----

TensorLibrary

A TensorLibrary pre-populated with HEP tensor definitions

Examples

-----

```
>>> import symbolica
>>> from symbolica.community.spenso import TensorLibrary, TensorName
>>> hep_lib = TensorLibrary.hep_lib()
>>> gamma_structure = hep_lib[symbolica.S("spenso::gamma")]
```

**hep\_lib\_atom**

**Kind:** AssociatedFunction

```
def hep_lib_atom() -> TensorLibrary:
```

Create a library pre-loaded with High Energy Physics tensor definitions.

Returns a library containing standard HEP tensors such as gamma matrices, color generators, metric tensors, and other commonly used structures in particle physics calculations. They are tensors with atom numeric entries.

Returns

-----

TensorLibrary

A TensorLibrary pre-populated with HEP tensor definitions

Examples

-----

```
>>> import symbolica
>>> from symbolica.community.spenso import TensorLibrary, TensorName
>>> hep_lib = TensorLibrary.hep_lib_atom()
>>> gamma_structure = hep_lib[symbolica.S("spenso::gamma")]
```

Exhaustive reference · Source

**TensorName**

A symbolic name for tensor functions and structures.

A symbolic name for tensor functions and structures.

TensorName represents named tensor functions that can be called with indices and arguments to create tensor structures. Names can have various mathematical properties like symmetry, antisymmetry, and custom normalization or printing behavior.

#### Examples

```

>>> from symbolica.community.spenso import TensorName, Slot, Representation
>>> T = TensorName("T")
>>> symmetric_T = TensorName("S", is_symmetric=True)
>>> antisymmetric_T = TensorName("A", is_antisymmetric=True)
>>> rep = Representation.cof(3)
>>> mu = rep('mu')
>>> nu = rep('nu')
>>> tensor_structure = T(mu, nu)

class TensorName:
```

**Requires features:** python\_stubgen

#### \_\_new\_\_

**Kind:** AssociatedFunction

```
def __new__(cls, name: str, is_symmetric: Optional[bool] = None, is_antisymmetric:
Optional[bool] = None, is_cyclesymmetric: Optional[bool] = None, is_linear:
Optional[bool] = None, custom_normalization: Optional[Transformer] = None) ->
TensorName:
```

Create a new tensor name with optional mathematical properties.

#### Parameters

```

name : str
 The string name for the tensor function
is_symmetric : bool, optional
 If True, tensor is symmetric under index permutation
is_antisymmetric : bool, optional
 If True, tensor is antisymmetric under index permutation
is_cyclesymmetric : bool, optional
 If True, tensor is symmetric under cyclic permutations
is_linear : bool, optional
 If True, tensor is linear in its arguments
custom_normalization : Transformer, optional
 Custom normalization function (advanced)
```

#### Returns

```

TensorName
 A new TensorName with the specified properties
```

#### Examples

```

>>> from symbolica.community.spenso import TensorName
>>> T = TensorName("T")
>>> g = TensorName("g", is_symmetric=True)
>>> F = TensorName("F", is_antisymmetric=True)
>>> D = TensorName("D", is_linear=True)
```

**name**

**Kind:** Parameter

str

The string name for the tensor function

**is\_symmetric**

**Kind:** Parameter

Optional[bool]

**Default:** None

If True, tensor is symmetric under index permutation

**is\_antisymmetric**

**Kind:** Parameter

Optional[bool]

**Default:** None

If True, tensor is antisymmetric under index permutation

**is\_cyclesymmetric**

**Kind:** Parameter

Optional[bool]

**Default:** None

If True, tensor is symmetric under cyclic permutations

**is\_linear**

**Kind:** Parameter

Optional[bool]

**Default:** None

If True, tensor is linear in its arguments

**custom\_normalization**

**Kind:** Parameter

Optional[Transformer]

**Default:** None

Custom normalization function (advanced)

**\_\_repr\_\_**

**Kind:** Method

```
def __repr__(self) -> str:
```

**\_\_str\_\_**

**Kind:** Method

```
def __str__(self) -> str:
```

### **to\_expression**

**Kind:** Method

```
def to_expression(self) -> Expression:
```

Convert the tensor name to a symbolic expression.

Returns

-----

Expression

A symbolic Expression representing this tensor name

Examples

-----

```
>>> T = TensorName("T")
```

```
>>> expr = T.to_expression()
```

### **g**

**Kind:** AssociatedFunction

```
def g() -> TensorName:
```

Predefined metric tensor name.

### **flat**

**Kind:** AssociatedFunction

```
def flat() -> TensorName:
```

Predefined musical isomorphism tensor name. This enables dualizing self dual indices.

### **gamma**

**Kind:** AssociatedFunction

```
def gamma() -> TensorName:
```

Predefined gamma matrix name.

### **gamma5**

**Kind:** AssociatedFunction

```
def gamma5() -> TensorName:
```

Predefined gamma5 matrix name.

### **projm**

**Kind:** AssociatedFunction

```
def projm() -> TensorName:
```

Predefined left chiral projector name.

### **projp**

**Kind:** AssociatedFunction

```
def projp() -> TensorName:
```

Predefined right chiral projector name.

### **sigma**

**Kind:** AssociatedFunction

```
def sigma() -> TensorName:
```

Predefined sigma matrix name.

**f**

**Kind:** AssociatedFunction

def f() -> TensorName:

Predefined color structure constant name.

**t**

**Kind:** AssociatedFunction

def t() -> TensorName:

Predefined color generator name.

**\_\_call\_\_**

**Kind:** Method

**\_\_call\_\_**

**Kind:** Overload

def \_\_call\_\_(self, \*args: Slot | Expression | int | str | float | complex) -> TensorIndices:

Call the tensor name with arguments to create tensor structures.

Accepts a mix of slots and symbolic expressions (for additional arguments).

Parameters

-----

\*args : Slot or Expression

Slot objects and Expressions for additional arguments

Returns

-----

TensorIndices

A new TensorIndices object

Examples

-----

```
>>> from symbolica.community.spenso import TensorName, Slot, Representation
```

```
>>> import symbolica as sp
```

```
>>> T = TensorName("T")
```

```
>>> rep = Representation.euc(3)
```

```
>>> mu = rep("mu")
```

```
>>> nu = rep("nu")
```

```
>>> indexed_tensor = T(mu, nu)
```

**args**

**Kind:** Parameter

Slot | Expression | int | str | float | complex

**\_\_call\_\_**

**Kind:** Overload

def \_\_call\_\_(self, \*args: Representation | Expression) -> TensorStructure:

Call the tensor name with arguments to create a TensorStructure.

Accepts a mix of representations and symbolic expressions (for additional arguments).

Parameters

-----

\*args : Representation or Expression

Representation objects and Expressions for additional arguments

Returns

-----

TensorStructure

A new TensorStructure object

Examples

-----

```
>>> from symbolica.community.spenso import TensorName, Slot, Representation
```

```
>>> import symbolica as sp
```

```
>>> T = TensorName("T")
```

```
>>> rep = Representation.euc(3)
```

```
>>> structure_tensor = T(rep, rep)
```

**args**

**Kind:** Parameter

Representation | Expression

[Exhaustive reference](#) · [Source](#)

## TensorNetwork

A tensor network representing computational graphs of tensor operations.

A tensor network representing computational graphs of tensor operations.

A tensor network is a graph-based representation of tensor computations where nodes represent tensors and operations, edges represent tensor contractions and data flow, and the network can be optimized and executed to compute results.

Tensor networks are particularly useful for symbolic manipulation of complex tensor expressions, optimization of tensor contraction orders, efficient evaluation of large tensor computations, and physics calculations involving many-body systems.

Examples

-----

```
>>> import symbolica as sp
```

```
>>> from symbolica.community.spenso import TensorNetwork, Tensor, TensorIndices
```

```
>>> x = sp.symbol('x')
```

```
>>> expr = x * sp.symbol('T')(sp.symbol('mu'), sp.symbol('nu'))
```

```
>>> network = TensorNetwork(expr)
```

```
>>> network.execute()
```

```
>>> result = network.result_tensor()
```

```
class TensorNetwork:
```

**Requires features:** python\_stubgen

**\_\_new\_\_**

**Kind:** AssociatedFunction

```
def __new__(cls, expr: Expression | int | str | float | complex | TensorIndices |
Expression, library: Optional[TensorLibrary] = None) -> TensorNetwork:
```

Create a tensor network by parsing an arithmetic expression.

Parses symbolic expressions containing tensor operations and converts them into an optimizable computational graph representation.

Parameters

-----

**expr** : ArithmeticStructure

The arithmetic expression or tensor structure to parse

**library** : TensorLibrary, optional

Optional tensor library for resolving named tensor references

Returns

-----

TensorNetwork

A new TensorNetwork representing the parsed expression

**expr**

**Kind:** Parameter

Expression | int | str | float | complex | TensorIndices | Expression

The arithmetic expression or tensor structure to parse

**library**

**Kind:** Parameter

Optional[TensorLibrary]

**Default:** None

Optional tensor library for resolving named tensor references

**one**

**Kind:** AssociatedFunction

```
def one() -> TensorNetwork:
```

Create a tensor network representing the scalar value 1.

Returns

-----

TensorNetwork

A TensorNetwork containing only the scalar 1

Examples

-----

```
>>> from symbolica.community.spenso import TensorNetwork
```

```
>>> one_net = TensorNetwork.one()
```

```
>>> result = one_net.result_scalar()
```

**bracket**

**Kind:** AssociatedFunction

```
def bracket() -> Expression:
```

## **broadcast**

**Kind:** AssociatedFunction

```
def broadcast(str: str) -> Expression:
```

**str**

**Kind:** Parameter

str

## **zero**

**Kind:** AssociatedFunction

```
def zero() -> TensorNetwork:
```

Create a tensor network representing the scalar value 0.

Returns

-----

TensorNetwork

A TensorNetwork containing only the scalar 0

Examples

-----

```
>>> from symbolica.community.spenso import TensorNetwork
>>> zero_net = TensorNetwork.zero()
>>> result = zero_net.result_scalar()
```

## **replace**

**Kind:** Method

```
def replace(self, pattern: Expression | int | str | float | complex, rhs: Expression
| int | str | float | complex | HeldExpression | Callable[[dict[Expression,
Expression]], Expression] | int | float | complex | decimal.Decimal, _cond:
Optional[PatternRestriction | Condition] = None, non_greedy_wildcards:
Optional[Sequence[Expression]] = None, level_range: Optional[tuple[int,
Optional[int]]] = None, level_is_tree_depth: Optional[bool] = None,
allow_new_wildcards_on_rhs: Optional[bool] = None, rhs_cache_size: Optional[int] =
None, repeat: Optional[bool] = None) -> TensorNetwork:
```

Replace patterns in the tensor network using symbolic pattern matching.

Applies pattern-based transformations to the network structure, allowing for symbolic simplifications, substitutions, and algebraic manipulations.

Parameters

-----

pattern : Expression

The symbolic pattern to match against

rhs : Expression

The replacement expression or pattern

non\_greedy\_wildcards : list of Expression, optional

List of wildcard symbols to match non-greedily

level\_range : tuple of int, optional

Tuple specifying depth range for pattern matching

level\_is\_tree\_depth : bool, optional

Whether level refers to tree depth or expression depth

allow\_new\_wildcards\_on\_rhs : bool, optional

Allow new wildcards in replacement pattern

`rhs_cache_size : int, optional`  
Size of cache for replacement pattern compilation  
`repeat : bool, optional`  
Whether to repeatedly apply the replacement until no more matches

Returns

-----

`TensorNetwork`  
A new `TensorNetwork` with the replacements applied

### **pattern**

**Kind:** Parameter

`Expression | int | str | float | complex`

The symbolic pattern to match against

### **rhs**

**Kind:** Parameter

`Expression | int | str | float | complex | HeldExpression |`  
`Callable[[dict[Expression, Expression]], Expression] | int | float | complex |`  
`decimal.Decimal`

The replacement expression or pattern

### **\_cond**

**Kind:** Parameter

`Optional[PatternRestriction | Condition]`

**Default:** None

### **non\_greedy\_wildcards**

**Kind:** Parameter

`Optional[Sequence[Expression]]`

**Default:** None

List of wildcard symbols to match non-greedily

### **level\_range**

**Kind:** Parameter

`Optional[tuple[int, Optional[int]]]`

**Default:** None

Tuple specifying depth range for pattern matching

### **level\_is\_tree\_depth**

**Kind:** Parameter

`Optional[bool]`

**Default:** None

Whether level refers to tree depth or expression depth

### **allow\_new\_wildcards\_on\_rhs**

**Kind:** Parameter

Optional[bool]

**Default:** None

Allow new wildcards in replacement pattern

**rhs\_cache\_size**

**Kind:** Parameter

Optional[int]

**Default:** None

Size of cache for replacement pattern compilation

**repeat**

**Kind:** Parameter

Optional[bool]

**Default:** None

Whether to repeatedly apply the replacement until no more matches

**evaluate**

**Kind:** Method

```
def evaluate(self, constants: Mapping[Expression, float], functions:
Mapping[Expression, Any]) -> TensorNetwork:
```

Evaluate symbolic expressions in the network with numerical values.

Substitutes symbolic constants and functions with numerical values,  
converting symbolic parts of the network to concrete numerical tensors.

Parameters

-----

constants : dict

Dict mapping symbolic expressions to their numerical values

functions : dict

Dict mapping function symbols to Python callable objects

Returns

-----

TensorNetwork

A new TensorNetwork with symbolic expressions evaluated

**constants**

**Kind:** Parameter

Mapping[Expression, float]

Dict mapping symbolic expressions to their numerical values

**functions**

**Kind:** Parameter

Mapping[Expression, Any]

Dict mapping function symbols to Python callable objects

## **execute**

**Kind:** Method

```
def execute(self, library: Optional[TensorLibrary] = None, function_library: None = None, n_steps: Optional[int] = None, mode: ExecutionMode = ...) -> None:
```

Execute the tensor network to perform tensor contractions and simplifications.

Processes the computational graph by executing tensor operations such as contractions, additions, and multiplications. The execution can be controlled by mode and step limits.

### Parameters

-----

**library** : TensorLibrary, optional

Optional tensor library for resolving tensor operations

**function\_library** : None, optional

Reserved for an internally supplied function library

**n\_steps** : int, optional

Maximum number of execution steps (None for complete execution)

**mode** : ExecutionMode, optional

Execution strategy. ExecutionMode.Single selects one smallest-degree rewrite per step; use n\_steps to bound how many steps run.

### Examples

-----

```
>>> from symbolica.community.spenso import TensorNetwork, ExecutionMode, TensorLibrary
>>> network = TensorNetwork(some_expression)
>>> network.execute()
>>> network.execute(n_steps=5)
>>> network.execute(mode=ExecutionMode.Scalar)
>>> lib = TensorLibrary.hep_lib()
>>> network.execute(library=lib)
```

## **library**

**Kind:** Parameter

Optional[TensorLibrary]

**Default:** None

Optional tensor library for resolving tensor operations

## **function\_library**

**Kind:** Parameter

None

**Default:** None

Reserved for an internally supplied function library

## **n\_steps**

**Kind:** Parameter

Optional[int]

**Default:** None

Maximum number of execution steps (None for complete execution)

### **mode**

**Kind:** Parameter

ExecutionMode

**Default:** ...

Execution strategy. ExecutionMode.Single selects one smallest-degree rewrite per step; use n\_steps to bound how many steps run.

### **result\_tensor**

**Kind:** Method

```
def result_tensor(self, library: Optional[TensorLibrary] = None) -> Tensor:
```

Extract the final tensor result from the executed network.

After network execution, retrieves the computed tensor result. The network should be executed before calling this method.

Parameters

-----

library : TensorLibrary, optional  
Optional tensor library for resolving tensor structures

Returns

-----

Tensor  
The computed tensor result

Raises

-----

RuntimeError  
If the network execution resulted in an error

Examples

-----

```
>>> from symbolica.community.spenso import TensorNetwork, TensorLibrary
>>> network = TensorNetwork(tensor_expression)
>>> network.execute()
>>> result = network.result_tensor()
>>> lib = TensorLibrary.hep_lib()
>>> result_with_lib = network.result_tensor(library=lib)
```

### **library**

**Kind:** Parameter

Optional[TensorLibrary]

**Default:** None

Optional tensor library for resolving tensor structures

### **result\_scalar**

**Kind:** Method

```
def result_scalar(self) -> Expression:
```

Extract the final scalar result from the executed network.

For networks that evaluate to scalar expressions, retrieves the computed scalar value. The network should be executed before calling this method.

Returns

-----

Expression

The computed scalar expression

Raises

-----

RuntimeError

If the network execution resulted in an error

Examples

-----

```
>>> from symbolica.community.spenso import TensorNetwork
>>> network = TensorNetwork(scalar_expression)
>>> network.execute()
>>> scalar_result = network.result_scalar()
```

**`__str__`**

**Kind:** Method

```
def __str__(self) -> str:
```

Return a string representation of the network structure.

Generates a DOT format representation of the computational graph that can be visualized using graphviz or similar tools.

**`__add__`**

**Kind:** Method

```
def __add__(self, rhs: Expression | int | str | float | complex | TensorIndices |
Expression | TensorNetwork | Tensor) -> TensorNetwork:
```

Add two tensor networks element-wise.

Parameters

-----

rhs : TensorNetwork

The tensor network to add (right-hand side)

Returns

-----

TensorNetwork

A new TensorNetwork representing the sum

Examples

-----

```
>>> net1 = TensorNetwork(expr1)
>>> net2 = TensorNetwork(expr2)
>>> sum_net = net1 + net2
```

**rhs**

**Kind:** Parameter

Expression | int | str | float | complex | TensorIndices | Expression | TensorNetwork  
| Tensor

The tensor network to add (right-hand side)

**\_\_radd\_\_**

**Kind:** Method

```
def __radd__(self, rhs: Expression | int | str | float | complex | TensorIndices |
Expression | TensorNetwork | Tensor) -> TensorNetwork:
```

Add two tensor networks element-wise (right-hand addition).

**rhs**

**Kind:** Parameter

Expression | int | str | float | complex | TensorIndices | Expression | TensorNetwork  
| Tensor

**\_\_sub\_\_**

**Kind:** Method

```
def __sub__(self, rhs: Expression | int | str | float | complex | TensorIndices |
Expression | TensorNetwork | Tensor) -> TensorNetwork:
```

Subtract one tensor network from another element-wise.

Parameters

-----

rhs : TensorNetwork

The tensor network to subtract (right-hand side)

Returns

-----

TensorNetwork

A new TensorNetwork representing the difference

Examples

-----

```
>>> net1 = TensorNetwork(expr1)
```

```
>>> net2 = TensorNetwork(expr2)
```

```
>>> diff_net = net1 - net2
```

**rhs**

**Kind:** Parameter

Expression | int | str | float | complex | TensorIndices | Expression | TensorNetwork  
| Tensor

The tensor network to subtract (right-hand side)

**\_\_rsub\_\_**

**Kind:** Method

```
def __rsub__(self, rhs: Expression | int | str | float | complex | TensorIndices |
Expression | TensorNetwork | Tensor) -> TensorNetwork:
```

Subtract one tensor network from another (right-hand subtraction).

**rhs**

**Kind:** Parameter

Expression | int | str | float | complex | TensorIndices | Expression | TensorNetwork  
| Tensor

**`__mul__`**

**Kind:** Method

```
def __mul__(self, rhs: Expression | int | str | float | complex | TensorIndices |
Expression | TensorNetwork | Tensor) -> TensorNetwork:
```

Multiply two tensor networks.

Parameters

-----

**rhs** : TensorNetwork

The tensor network to multiply with (right-hand side)

Returns

-----

TensorNetwork

A new TensorNetwork representing the product

Examples

-----

```
>>> net1 = TensorNetwork(expr1)
```

```
>>> net2 = TensorNetwork(expr2)
```

```
>>> product_net = net1 * net2
```

**rhs**

**Kind:** Parameter

Expression | int | str | float | complex | TensorIndices | Expression | TensorNetwork  
| Tensor

The tensor network to multiply with (right-hand side)

**`__rmul__`**

**Kind:** Method

```
def __rmul__(self, rhs: Expression | int | str | float | complex | TensorIndices |
Expression | TensorNetwork | Tensor) -> TensorNetwork:
```

Multiply two tensor networks (right-hand multiplication).

**rhs**

**Kind:** Parameter

Expression | int | str | float | complex | TensorIndices | Expression | TensorNetwork  
| Tensor

Exhaustive reference · Source

## TensorStructure

A tensor structure without abstract indices, defined purely by representations.

A tensor structure without abstract indices, defined purely by representations.

TensorStructure represents the shape and representation structure of tensors without specific index assignments. It's used for defining tensor templates in libraries and for creating indexless tensor computations.

# Examples:

```

```python
from symbolica.community.spenso import TensorStructure, Representation, TensorName

# Create from representations
rep = Representation.euc(3)
structure = TensorStructure(rep, rep) # 3x3 matrix structure

# With name for library registration
T = TensorName("T")
named_structure = TensorStructure(rep, rep, name=T)

# Use to create indexed tensor
indices = structure.index('mu', 'nu') # Assign specific indices

# Create symbolic expression
expr = structure.symbolic('a', 'b') # T(a, b)
```

```

```

class TensorStructure:

```

**Requires features:** python\_stubgen

**set\_name**

**Kind:** Method

```

def set_name(self, name: TensorName | str | Expression) -> None:

```

**name**

**Kind:** Parameter

```

TensorName | str | Expression

```

**get\_name**

**Kind:** Method

```

def get_name(self) -> Optional[TensorName]:

```

**\_\_repr\_\_**

**Kind:** Method

```

def __repr__(self) -> str:

```

**\_\_str\_\_**

**Kind:** Method

```

def __str__(self) -> str:

```

**\_\_len\_\_**

**Kind:** Method

```

def __len__(self) -> int:

```

**\_\_new\_\_**

**Kind:** AssociatedFunction

```

def __new__(cls, *reps_and_additional_args: TensorIndices | list[Slot], name:
TensorName | str | Expression | None = None) -> TensorStructure:

```

Construct a new TensorStructure with the given representations.

## Parameters

-----

**\*reps\_and\_additional\_args** : Representation or Expression

Mixed arguments (Representation objects and Expressions for additional arguments)

**name** : TensorName, optional

Optional tensor name to assign to the structure

## Returns

-----

TensorStructure

A new TensorStructure object

## Examples

-----

```
>>> from symbolica import S
```

```
>>> from symbolica.community.spenso import TensorStructure, Representation,
TensorName
```

```
>>> rep = Representation.euc(3)
```

```
>>> structure = TensorStructure(rep, rep)
```

```
>>> x = S('x')
```

```
>>> structure_with_args = TensorStructure(rep, rep, x)
```

```
>>> T = TensorName("T")
```

```
>>> named_structure = TensorStructure(rep, rep, name=T)
```

## **reps\_and\_additional\_args**

**Kind:** Parameter

TensorIndices | list[Slot]

## **name**

**Kind:** Parameter

TensorName | str | Expression | None

**Default:** None

Optional tensor name to assign to the structure

## **\_\_getitem\_\_**

**Kind:** Method

## **\_\_getitem\_\_**

**Kind:** Overload

```
def __getitem__(self, item: slice) -> list[Expression | complex | float]:
```

Get expanded indices at the specified range of flattened indices.

## Parameters

-----

**item** : slice

Slice object defining the range of indices

## Returns

-----

list of list of int

List of expanded indices

**item**

**Kind:** Parameter

slice

Slice object defining the range of indices

**\_\_getitem\_\_**

**Kind:** Overload

```
def __getitem__(self, item: Sequence[int]) -> Expression | complex | float:
```

Get flattened index associated to this expanded index.

Parameters

-----

item : list of int

Multi-dimensional index coordinates

Returns

-----

int

The flat index

**item**

**Kind:** Parameter

Sequence[int]

Multi-dimensional index coordinates

**\_\_getitem\_\_**

**Kind:** Overload

```
def __getitem__(self, item: int) -> Expression | complex | float:
```

Get expanded index associated to this flat index.

Parameters

-----

item : int

Flat index into the tensor

Returns

-----

list of int

Multi-dimensional index coordinates

**item**

**Kind:** Parameter

int

Flat index into the tensor

**\_\_call\_\_**

**Kind:** Method

```
def __call__(self, *args: int | Expression | str, extra_args: Sequence[Expression |
int | str | float | complex] | None = None) -> Expression:
```

Convenience method for creating symbolic expressions.

This is a shorthand for calling ``symbolic(*args, extra_args=extra_args)``.  
Creates a symbolic Expression representing this tensor structure.

Parameters

-----

`*args` : int, str, Symbol, or Expression  
Positional arguments (indices and additional args)  
`extra_args` : list of Expression, optional  
Optional list of additional non-tensorial arguments

Returns

-----

Expression

A symbolic Expression representing the tensor

Examples

-----

```
>>> structure = TensorStructure(rep, rep, name="T")
>>> expr = structure('mu', 'nu')
```

**args**

**Kind:** Parameter

int | Expression | str

**extra\_args**

**Kind:** Parameter

Sequence[Expression | int | str | float | complex] | None

**Default:** None

Optional list of additional non-tensorial arguments

**symbolic**

**Kind:** Method

```
def symbolic(self, *args: int | Expression | str, extra_args: Sequence[Expression |
int | str | float | complex] | None = None) -> Expression:
```

Create a symbolic expression representing this tensor structure.

Builds a symbolic tensor expression with the specified indices. Arguments can be separated using a semicolon (';') to distinguish between additional arguments and tensor indices.

Parameters

-----

`*args` : int, str, Symbol, Expression, or ';'
Positional arguments (int, str, Symbol, Expression for indices, ';' for separator)
`extra_args` : list of Expression, optional
Optional list of additional non-tensorial arguments

Returns

-----

Expression

A symbolic Expression representing the tensor with indices

#### Examples

-----

```
>>> import symbolica as sp
>>> from symbolica.community.spenso import TensorStructure, Representation,
TensorName
>>> rep = Representation.euc(3)
>>> T = TensorName("T")
>>> structure = TensorStructure([rep, rep], name=T)
>>> expr = structure.symbolic('mu', 'nu')
>>> x = sp.S('x')
>>> expr = structure.symbolic(x, ';', 'mu', 'nu')
>>> expr = structure.symbolic('mu', 'nu', extra_args=[x])
```

#### args

**Kind:** Parameter

int | Expression | str

#### extra\_args

**Kind:** Parameter

Sequence[Expression | int | str | float | complex] | None

**Default:** None

Optional list of additional non-tensorial arguments

#### index

**Kind:** Method

```
def index(self, *args: int | Expression | str, extra_args: Sequence[Expression] |
None = None, cook_indices: bool = False) -> TensorIndices:
```

Create an indexed tensor (TensorIndices) from this structure.

Converts this structure template into a concrete indexed tensor by assigning specific abstract indices to each representation slot.

#### Parameters

-----

**\*args** : int, str, Symbol, Expression, or ';'.

Positional arguments (indices and ';' separator between additional args and indices)

**extra\_args** : list of Expression, optional

Optional list of additional non-tensorial arguments

**cook\_indices** : bool, optional

If True, attempt to convert expressions to valid indices

#### Returns

-----

TensorIndices

A TensorIndices object with concrete index assignments

#### Examples

-----

```
>>> import symbolica as sp
>>> from symbolica.community.spenso import TensorStructure, Representation,
```

```

TensorName
>>> rep = Representation.cof(3)
>>> T = TensorName("T")
>>> structure = TensorStructure([rep, rep], name=T)
>>> indices = structure.index('mu', 'nu')
>>> x = sp.S('x')
>>> indices = structure.index(x, ';', 'mu', 'nu')

```

### args

**Kind:** Parameter

int | Expression | str

### extra\_args

**Kind:** Parameter

Sequence[Expression] | None

**Default:** None

Optional list of additional non-tensorial arguments

### cook\_indices

**Kind:** Parameter

bool

**Default:** False

If True, attempt to convert expressions to valid indices

Exhaustive reference · Source

### ExecutionMode

Execution modes for tensor network evaluation.

Execution modes for tensor network evaluation.

Controls how the tensor network execution engine processes the computational graph.

Variants

-----

Single : Select one smallest-degree rewrite per step; without `n\_steps`, continue until no work remains

Scalar : Only contract scalar operations, leaving tensor structure intact

All : Execute all possible contractions for complete evaluation

```
class ExecutionMode(enum.Enum):
```

**Requires features:** python\_stubgen

### Single

**Kind:** Variant

Select one smallest-degree rewrite per step; without `n\_steps`, continue until no work remains

### Scalar

**Kind:** Variant

Only contract scalar operations, leaving tensor structure intact

## **All**

**Kind:** Variant

Execute all possible contractions for complete evaluation

Exhaustive reference · Source

## **SymbolicParallelism**

Policy for Rayon operations that manipulate Symbolica expressions.

Policy for Rayon operations that manipulate Symbolica expressions.

```
class SymbolicParallelism(enum.Enum):
```

**Requires features:** python\_stubgen

## **Auto**

**Kind:** Variant

Permit Rayon when licensed and use workload heuristics where available.

## **Serial**

**Kind:** Variant

Keep symbolic operations on the calling thread.

## **Parallel**

**Kind:** Variant

Force Rayon without `Auto`'s Symbolica license safety check.

Exhaustive reference · Source

## **set\_symbolica\_rayon\_enabled**

Configure whether Spenso may use Rayon for Symbolica operations.

Configure whether Spenso may use Rayon for Symbolica operations.

`Auto` checks the Symbolica license once during this call. When licensed, operations may use Rayon and apply workload heuristics where available; when unlicensed, symbolic operations remain serial. The returned boolean reports whether the resolved policy permits Rayon, not whether every operation will use it.

```
def set_symbolica_rayon_enabled(policy: SymbolicParallelism) -> bool:
```

**Requires features:** python\_stubgen

Exhaustive reference · Source

## Version information

Save these identifiers with published results and include them in issue reports so that collaborators can reproduce the same software environment.

- **Documentation channel:** latest
- **Documentation route:** /products/spenso/latest/
- **Source revision:** cbfc3a5827679de14e9373edd6b332e6b9b28a55

## Package versions and enabled features

- gammaloop/gammalooprs — 0.3.4 (no optional features)
- gammaloop/gammaloop-api — 0.1.0 (features: cli)
- gammaloop/gammaloop — 0.3.4 (features: python\_api, python\_abi, python\_stubgen)
- linnet/linnet — 0.17.0 (features: nodestore-vec, serde, bincode, drawing, symbolica)
- linnet/linnet-py — 0.1.0 (features: extension-module, abi3-py310)
- spenso/spenso — 0.6.0 (features: shadowing)
- spenso/spenso-macros — 0.3.2 (features: shadowing)
- spenso/spenso-hep-lib — 0.1.7 (no optional features)
- spenso/spynso3 — 0.1.2 (features: python\_stubgen)
- idenso/idenso — 0.3.0 (features: bincode, reference-cases)
- idenso/idenso — 0.3.0 (features: python, python\_stubgen)
- vakint/vakint — 0.1.2 (no optional features)
- vakint/vakint — 0.1.2 (features: symbolica\_community\_module, python\_stubgen)