

Generalised Three-Dimensional LTD/CFF Representations

Implementation and theory note

April 2026

Abstract

This note describes the derivative-free three-dimensional representation implemented in `generalised_ltd.py`. The construction combines loop-tree duality (LTD) with the causal/CFF representation in order to handle repeated propagators while keeping the numerator as a sampled black box. It also describes the bounded-energy-degree extension used when edge-momentum representation (EMR) numerators contain powers above the affine CFF class.

The document is organized as follows. Chapter 1 gives the mathematical construction, with all dependencies made explicit. Chapter 2 explains how the Python implementation and the oriented JSON schema encode the formulae. Chapter 3 reports current Symbolica evaluator timings from the example scripts.

Contents

1	Theoretical Construction	2
1.1	Framing, Notation, LTD, and CFF	2
1.2	Repeated Propagators Without Numerator Derivatives	3
1.2.a	The Fully Generic Formula	3
1.2.b	The Box with a Triple Repeated Propagator	7
1.2.c	Sunrise with One Repeated Dot Numerator	9
1.3	Higher Energy Powers in Numerators	10
1.3.1.a	Quadratic Bounds	11
1.3.1.b	One-Loop Box with One Quadratic Edge	12
1.3.2.a	Bounds Above Quadratic	13
1.3.1	Uniform-Scale Repeated-Channel Sampling	15
1.3.2.b	One-Loop Box with One Cubic Edge	18
1.3.2.c	Terminal Contact Completion	19
2	Python Implementation and JSON Format	23
2.1	Module Structure	23
2.2	Bounded-Degree Support Matrix	23
2.3	Oriented JSON Semantics	26
2.4	Surface Cache	27
2.5	Orientation Labels and Variants	27
2.6	Command-Line Workflow	27
2.7	Symbolica Evaluators	27
3	Performance	29
3.1	Benchmark Setup	29
3.2	Repeated Box	29
3.3	One-Loop 10-Gon	29
3.4	Five-Loop Four-External Benchmarks	30
3.5	Precision Stability	31

Chapter 1

Theoretical Construction

1.1 Framing, Notation, LTD, and CFF

Let $\mathcal{G}$ be a connected scalar graph with L loop momenta and internal edge set E . A loop-momentum basis (LMB) is denoted by $\mathcal{B} = (k_1, \dots, k_L)$. For an edge $e \in E$,

$$q_e(k, p) = \sum_{r=1}^L \rho_{er} k_r + \sum_{a=1}^{n_{\text{ext}}} \eta_{ea} p_a, \quad \rho_{er}, \eta_{ea} \in \mathbb{Z}, \quad (1.1)$$

and

$$q_e^0(k^0, p^0) = \rho_e \cdot k^0 + \eta_e \cdot p^0, \quad \omega_e(\vec{k}, p, m) = \sqrt{\vec{q}_e^2 + m_e^2}. \quad (1.2)$$

The Feynman denominator is

$$D_e = (q_e^0)^2 - \omega_e^2 + i0. \quad (1.3)$$

For a numerator N in EMR variables, the D -dimensional input integral is

$$I_{\mathcal{G}, \mathcal{B}}[N] = \int_{\mathbb{R}^{4L}} \prod_{r=1}^L \frac{d^4 k_r}{(2\pi)^4} N(\{q_e(k, p)\}_{e \in E}) \prod_{e \in E} D_e^{-a_e}. \quad (1.4)$$

The powers a_e are normally one; repeated propagators are encoded below as explicit repeated edges or, equivalently, as collapsed channels with powers.

LTD dependency data. The LTD construction is an algorithmic residue expansion of (1.4) after choosing

- the graph $\mathcal{G}$,
- the loop-momentum basis $\mathcal{B}$,
- a contour-closure prescription κ , i.e. the side on which each loop-energy integration is closed.

We denote the resulting spatial integrand by

$$I_{\text{LTD}}^{(3)}[\mathcal{G}, \mathcal{B}, \kappa; N](\vec{k}; p, m) = \sum_{\mathfrak{o} \in \mathcal{O}_{\text{LTD}}(\mathcal{G}, \mathcal{B}, \kappa)} N\left(Q_{\mathfrak{o}}^{\text{LTD}}(\vec{k}; p, m)\right) W_{\mathfrak{o}}^{\text{LTD}}(\vec{k}; p, m). \quad (1.5)$$

The map $Q_{\mathfrak{o}}^{\text{LTD}}$ gives every EMR edge energy after solving the cut equations. The weight $W_{\mathfrak{o}}^{\text{LTD}}$ is a product of cut half-edge factors and LTD dual surfaces. In this note we do not rederive LTD; we use the multiloop algorithmic construction of Ref. [1].

CFF dependency data. For CFF/causal representations we use the graph as the primary input and assume the canonical source/sink contraction ordering used by the implementation. Thus

$$I_{\text{CFF}}^{(3)}[\mathcal{G}; N](\vec{k}; p, m) = \sum_{\mathfrak{o} \in \mathcal{O}_{\text{CFF}}(\mathcal{G})} N\left(Q_{\mathfrak{o}}^{\text{CFF}}(\vec{k}; p, m)\right) W_{\mathfrak{o}}^{\text{CFF}}(\vec{k}; p, m). \quad (1.6)$$

The CFF weights use causal E -surfaces in the denominator. The construction is the one of Refs. [2, 3]. The standard black-box numerator assumption is that N is at most affine in each EMR edge energy q_e^0 .

Surface notation. For any integer vector $c_e \in \{-1, 0, 1\}$ and external-energy shift Δ , define the signed causal surface

$$\eta(c, \Delta) = \sum_e c_e \omega_e + \Delta. \quad (1.7)$$

An E -surface has all non-zero internal-energy coefficients with the same orientation after the canonical CFF construction. An H -surface is a more general signed hyperboloid surface. Pure CFF denominator factors use only E -surfaces; LTD and hybrid terms may use H -surfaces when the residue geometry requires them. Numerator-side surfaces are allowed in the numerator and do not introduce denominator singularities.

1.2 Repeated Propagators Without Numerator Derivatives

Repeated propagators correspond to groups

$$R_g = \{r_{g,1}, \dots, r_{g,\nu_g}\}, \quad \nu_g \geq 2, \quad (1.8)$$

whose members have the same canonical routing and mass, possibly with reversed edge orientation. Let Q_g^0 be the canonical repeated-channel energy and ω_g the common on-shell energy. The purpose of the hybrid construction is to evaluate the repeated-channel residues without applying derivatives to the black-box numerator.

1.2.a The Fully Generic Formula

Start from the four-dimensional integral split into non-repeated edges S and repeated groups G_{rep} :

$$\begin{aligned} I_{\mathcal{G}, \mathcal{B}}[N] &= \int \prod_{r=1}^L \frac{d^4 k_r}{(2\pi)^4} N(\{q_e(k, p)\}) \prod_{s \in S} D_s^{-1} \prod_{g \in G_{\text{rep}}} \prod_{a=1}^{\nu_g} D_{r_{g,a}}^{-1} \\ &= \int \prod_{r=1}^L \frac{d^4 k_r}{(2\pi)^4} N(\{q_e(k, p)\}) \prod_{s \in S} D_s^{-1} \prod_{g \in G_{\text{rep}}} D_g^{-\nu_g}. \end{aligned} \quad (1.9)$$

The second equality is only a denominator identity. The numerator still has one EMR argument for every original edge $e \in E$, including all repeated copies. Thus the collapsed channel g has a single denominator energy Q_g^0 , but the numerator still sees $q_{r_{g,a}}^0$ for $a = 1, \dots, \nu_g$.

Let $\bar{E} = S \sqcup G_{\text{rep}}$ be the collapsed edge set and assign powers

$$n_{\bar{e}} = \begin{cases} 1, & \bar{e} = s \in S, \\ \nu_g, & \bar{e} = g \in G_{\text{rep}}. \end{cases}$$

For every rank- L collapsed cut basis $B \subset \bar{E}$ and pole-sign vector σ_B , solve the cut equations

$$Q_b^0(k^0, p^0) = \sigma_b \omega_b, \quad b \in B, \quad (1.10)$$

for the loop energies:

$$k^0 = K_{B,\sigma_B}(\vec{k}; p, m). \quad (1.11)$$

The Jacobian associated with this change of variables is

$$J_B = \det(\rho_{br})_{b \in B, r=1, \dots, L}. \quad (1.12)$$

With the contour convention used in the implementation, the sign carried by the corresponding simple LTD residue is denoted by $s_{B,\sigma_B} \in \{\pm 1\}$. The direct residue theorem gives the strict equality

$$I_{\mathcal{G},B}[N] = \int \prod_{r=1}^L \frac{d^3 k_r}{(2\pi)^3} \sum_{B,\sigma_B} s_{B,\sigma_B} \left[\prod_{b \in B} \frac{1}{(n_b - 1)!} \left(\frac{\partial}{\partial Q_b^0} \right)^{n_b-1} \frac{N(\{q_e^0(k^0, p^0), \vec{q}_e\})}{\prod_{b \in B} (Q_b^0 + \sigma_b \omega_b)^{n_b} \prod_{\bar{e} \notin B} D_{\bar{e}}^{n_{\bar{e}}}} \right]_{k^0=K_{B,\sigma_B}}. \quad (1.13)$$

The determinant J_B is already included in the LTD residue sign and normalization used to define s_{B,σ_B} . For the DOT examples all non-zero J_B are ± 1 . If a different integer LMB gives $|J_B| \neq 1$, the residue weight is multiplied by $1/|J_B|$.

Equation (1.13) is not the final representation when a powered channel is cut, because the derivatives act on N . Define the set of active original edges

$$\mathcal{A}_B = \{e \in E : q_e^0 \text{ depends on } Q_b^0 \text{ for some } b \in B \text{ with } n_b > 1\}. \quad (1.14)$$

For the affine EMR class, one exact algebraic route is to insert the multilinear pole interpolation identity

$$N(\{q_e^0\}) = \sum_{\theta \in \{\pm 1\}^{\mathcal{A}_B}} N(\{q_{e,\theta}^0\}) \prod_{e \in \mathcal{A}_B} \frac{1 + \theta_e q_e^0 / \omega_e}{2}, \quad (1.15)$$

with $q_{e,\theta}^0 = \theta_e \omega_e$ for active edges and the ordinary affine value for inactive edges. Since N is affine in each active EMR energy, differentiating (1.15) differentiates only the known interpolation factors and never the black-box function values.

The form actually used for the hybrid repeated sectors is the equivalent physical CFF-localized form. To derive it independently, temporarily split the repeated denominator into distinct on-shell energies $\omega_{g,a}$, $a = 1, \dots, \nu_g$, and use the linear-pole decomposition

$$\frac{1}{(Q_g^0)^2 - \omega_{g,a}^2 + i0} = \sum_{\tau_{g,a}=\pm 1} \frac{\tau_{g,a}}{2\omega_{g,a}} \frac{1}{Q_g^0 - \tau_{g,a}\omega_{g,a} + i0\tau_{g,a}}. \quad (1.16)$$

Each linear pole has the causal exponential representation

$$\frac{1}{Q_g^0 - \tau\omega + i0\tau} = -i\tau \int_0^\infty d\lambda \exp[i\tau\lambda Q_g^0 - i\lambda\omega]. \quad (1.17)$$

For a repeated group this gives a sign orbit $\tau_g = (\tau_{g,1}, \dots, \tau_{g,\nu_g})$ and the phase

$$\Phi_{\tau_g} = \exp \left[iQ_g^0 \sum_{a=1}^{\nu_g} \tau_{g,a} \lambda_{g,a} - i \sum_{a=1}^{\nu_g} \lambda_{g,a} \omega_{g,a} \right], \quad \lambda_{g,a} \geq 0. \quad (1.18)$$

The loop-energy integrations are now elementary Fourier integrations. For a complete set of CFF/LTD pole choices P , with signs τ_j , energies ω_j , and loop-energy rows ρ_j , one obtains the localizing constraint

$$\prod_{r=1}^L 2\pi \delta \left(\sum_{j \in P} \tau_j \lambda_j \rho_{jr} \right). \quad (1.19)$$

Solving (1.19) with $\lambda_j \geq 0$ is the standard CFF source/sink contraction step: the surviving sign assignments are precisely the causal orientations. In a repeated group the individual $\tau_{g,a}$ survive as numerator-sampling signs, while the localized collapsed chain has a single sign $\chi_g = \pm 1$ for the energy Q_g^0 . If all repeated-copy signs are equal, χ_g is forced to that common sign. If the orbit is mixed, both $\chi_g = \pm 1$ are possible localizations. This is exactly the rule implemented as

$$\tau_g = (+, +, +) \Rightarrow \chi_g = +, \quad \tau_g = (-, -, -) \Rightarrow \chi_g = -, \quad \text{mixed } \tau_g \Rightarrow \chi_g = \pm.$$

Only after solving the delta constraints do we take the equal-energy limit $\omega_{g,a} \rightarrow \omega_g$. The split expression is an ordinary simple-pole CFF/LTD expression, hence the limit is equal to the confluent residue (1.13). The difference is organizational:

- the confluent derivative form differentiates the known denominator factors and would differentiate N unless (1.15) is inserted first;
- the physical CFF-localized form samples N directly at repeated-copy on-shell sign orbits (τ_g, χ_g) , then combines those samples with rational affine weights.

For an affine EMR numerator the two forms are identical because both are the same equal-energy limit of the split simple-pole identity. They differ only in the basis of numerator calls: the direct interpolation basis uses the formal active edge signs θ_e , while the physical basis uses the CFF-localized orbits (τ_g, χ_g) . The latter is the one printed by the current hybrid JSON labels such as `physG3tmmcm`.

It remains to define the rational weights multiplying those physical samples. Let $\mathcal{X}_{B,\sigma}$ be the finite set of physical samples obtained from the above sign-orbit rule for the active repeated groups of the cut (B, σ_B) . A sample $x \in \mathcal{X}_{B,\sigma}$ determines complete loop and edge energy maps,

$$K_x^0(\vec{k}; p, m), \quad q_{e,x}^0(\vec{k}; p, m).$$

Write every component of every map as an affine vector in the symbols

$$1, \quad p_a^0, \quad \omega_{\bar{e}},$$

where repeated copies share the collapsed symbol ω_g . Let R_x be the column vector containing all those affine coefficients for sample x . For a numerator-derivative multi-index β , let T_β be the target affine vector:

- for $|\beta| = 0$, T_0 is the ordinary cut map $K_{B,\sigma_B}^0, q_{e,B,\sigma_B}^0$;
- for $|\beta| = 1$, T_β is the first derivative of those maps with respect to the corresponding repeated cut energy, multiplied by $2\omega_g$. The compensating factor $1/(2\omega_g)$ is stored as one additional repeated half-edge in the JSON.

The sample coefficients $\lambda_{\beta x}$ are defined by the affine system

$$\sum_{x \in \mathcal{X}_{B,\sigma}} \lambda_{\beta x} = \delta_{\beta 0}, \quad \sum_{x \in \mathcal{X}_{B,\sigma}} \lambda_{\beta x} R_x = T_\beta. \quad (1.20)$$

If the system is underdetermined, the implementation uses the minimum Euclidean norm solution. Equivalently, after discarding dependent rows, if R is the matrix with columns R_x and t_β is the target vector including the constant row, then

$$\lambda_\beta = R^T (R R^T)^{-1} t_\beta. \quad (1.21)$$

This equation is not a fit or approximation: the affine support of $\mathcal{X}_{B,\sigma}$ is checked exactly over rational numbers.

Substituting (1.15) into (1.13) gives

$$I_{\mathcal{G},\mathcal{B}}[N] = \int \prod_{r=1}^L \frac{d^3 k_r}{(2\pi)^3} I_{\mathcal{G},\mathcal{B},\kappa}^{\text{HybridLTD}}[N](\vec{k}; p, m), \quad (1.22)$$

$$I_{\mathcal{G},\mathcal{B},\kappa}^{\text{HybridLTD}}[N] = \sum_{\mathfrak{o} \in \mathcal{O}_{\text{H}}(\mathcal{G},\mathcal{B},\kappa)} N(Q_{\mathfrak{o}}^{\text{H}}(\vec{k}; p, m)) W_{\mathfrak{o}}^{\text{H}}(\vec{k}; p, m). \quad (1.23)$$

Here one orientation is

$$\mathfrak{o} = (B, \sigma_B, x, \beta, \gamma, \mu),$$

where $x \in \mathcal{X}_{B,\sigma}$, β is the part of the confluent derivative reconstructed from numerator samples, $\gamma = \alpha - \beta$ acts on known denominator factors, and μ labels one algebraic term in the known denominator derivative expansion. Here

$$\alpha_b = n_b - 1, \quad b \in B.$$

The numerator is never differentiated; it is only sampled at

$$Q_{\mathfrak{o}}^{\text{H}} = \{q_{e,x}^0, \vec{q}_e\}_{e \in E}.$$

The denominator derivative coefficient is also explicit. Each known factor is of the form

$$F_j(y) = \zeta_j(y)^{-p_j}, \quad \zeta_j(y) = \zeta_j(0) + a_j \cdot y,$$

where $y = (Q_b^0 - \sigma_b \omega_b)_{b \in B}$, p_j is either a propagator power or a surface power, and a_j is the vector of derivatives with respect to the cut-basis energies. A multi-derivative assignment δ_j with $\sum_j \delta_j = \gamma$ contributes

$$d_{\{\delta_j\}} = \frac{\gamma!}{\prod_j \delta_j!} \prod_j (-1)^{|\delta_j|} (p_j)_{|\delta_j|} a_j^{\delta_j}, \quad (p)_r = p(p+1) \cdots (p+r-1). \quad (1.24)$$

For multi-indices, $\gamma! = \prod_b \gamma_b!$, $\delta_j! = \prod_b (\delta_j)_b!$, and

$$a_j^{\delta_j} = \prod_b (a_j)_b^{(\delta_j)_b}.$$

For a surface factor $\zeta_j = \eta_j$, the derivative raises the denominator power of that cached surface. For a cut half-edge factor $(2\omega_b)^{-p_j}$, it raises the number of stored half-edge entries.

The complete rational coefficient multiplying one JSON variant is therefore

$$c_{\mathfrak{o}} = s_{B,\sigma_B} \frac{1}{\alpha!} \binom{\alpha}{\beta} \lambda_{\beta x} d_{\mu}, \quad (1.25)$$

where d_{μ} is the value of (1.24) for the derivative assignment $\mu = \{\delta_j\}$, and

$$\alpha! = \prod_{b \in B} \alpha_b!, \quad \binom{\alpha}{\beta} = \prod_{b \in B} \binom{\alpha_b}{\beta_b}.$$

The weight is the finite product

$$W_{\mathfrak{o}}^{\text{H}} = c_{\mathfrak{o}} \prod_{h \in H_{\mathfrak{o}}} \frac{1}{2\omega_h} \prod_{\eta \in D_{\mathfrak{o}}} \eta(\vec{k}; p, m)^{-m_{\mathfrak{o},\eta}} \prod_{\zeta \in N_{\mathfrak{o}}} \zeta(\vec{k}; p, m). \quad (1.26)$$

Here $H_{\mathfrak{o}}$ is the multiset of half-edge ids, so each $h \in H_{\mathfrak{o}}$ contributes $(2\omega_h)^{-1}$. The denominator multiset $D_{\mathfrak{o}}$ contains cached surfaces

$$\eta(\vec{k}; p, m) = \sum_e c_e \omega_e + \sum_a d_a p_a^0 + c_0,$$

with $c_e, d_a, c_0 \in \mathbb{Z}$. The numerator multiset $N_{\mathfrak{o}}$ contains cached numerator-only surfaces of the same linear form; each $\zeta \in N_{\mathfrak{o}}$ is exactly a known linear factor in on-shell and external energies appearing in the numerator, not an additional denominator. If no repeated channel is present, then $n_b = 1$ for all cuts, $\mathcal{A}_B = \emptyset$, and (1.23) collapses exactly to the LTD representation with the same $(\mathcal{G}, \mathcal{B}, \kappa)$.

1.2.b The Box with a Triple Repeated Propagator

Consider the one-loop box routing

$$q_0 = k, \quad q_1 = k + p_1, \quad q_2 = k + p_1 + p_2, \quad Q = k + p_1 + p_2 + p_3,$$

with three repeated copies of Q . The collapsed denominator is

$$D_0 D_1 D_2 D_Q^3.$$

Write $\Delta_i = p_1^0 + \dots + p_i^0$ and define the causal surfaces

$$E_{ij}^{\sigma_i \sigma_j} = \sigma_i \omega_i + \sigma_j \omega_j + \Delta_i - \Delta_j, \quad (1.27)$$

$$E_{iQ}^{\sigma_i \sigma_Q} = \sigma_i \omega_i + \sigma_Q \omega_Q + \Delta_i - \Delta_3. \quad (1.28)$$

The three simple-cut sectors are

$$I_i^{\text{simple}} = -\frac{N(q_0^0, q_1^0, q_2^0, Q^0, Q^0, Q^0)_{k^0 = -\Delta_i + \omega_i}}{2\omega_i E_{ij}^{++} E_{i\ell}^{++} (E_{iQ}^{++})^3}, \quad \{i, j, \ell\} = \{0, 1, 2\}. \quad (1.29)$$

The signs shown correspond to the upper on-shell pole convention used in the examples; the opposite closure is obtained by replacing every displayed $+\omega$ by the corresponding signed on-shell energy.

For the repeated cut used in the printed example, the collapsed LTD cut is $Q^0 = +\omega_Q$, hence

$$k^0 = \omega_Q - \Delta_3.$$

The six denominator surfaces generated by the three non-cut edges are

$$\eta_{18} = -\omega_0 + \omega_Q - \Delta_3, \quad \eta_{19} = \omega_0 + \omega_Q - \Delta_3, \quad (1.30)$$

$$\eta_{20} = -\omega_1 + \omega_Q - \Delta_2, \quad \eta_{21} = \omega_1 + \omega_Q - \Delta_2, \quad (1.31)$$

$$\eta_{22} = -\omega_2 + \omega_Q - \Delta_1, \quad \eta_{23} = \omega_2 + \omega_Q - \Delta_1. \quad (1.32)$$

These are precisely surface ids 18, ..., 23 in the CLI output. The overview table prints a compact subset of denominator ids, but `-show-details-for-orientation` displays the full factorization tree containing all six surfaces.

Let $\tau = (\tau_3, \tau_4, \tau_5)$ be the physical repeated-copy signs and χ the localized collapsed-chain sign. A physical numerator call is

$$N_{\tau, \chi} = N(\chi\omega_Q - \Delta_3, \chi\omega_Q - \Delta_2, \chi\omega_Q - \Delta_1, \tau_3\omega_Q, \tau_4\omega_Q, \tau_5\omega_Q). \quad (1.33)$$

The admissible physical sample set is

$$\mathcal{X}_Q = \{(+++, +), (---, -)\} \cup \{(\tau, +), (\tau, -) : \tau \in \{\pm\}^3, \tau \neq +++, \tau \neq ---\}. \quad (1.34)$$

For each $x = (\tau, \chi) \in \mathcal{X}_Q$, the affine coefficients λ_{0x} and λ_{1x} defined by (1.20) reconstruct respectively the numerator itself and the first numerator derivative. The full table is

sample $x = (\tau, \chi)$	λ_{0x}	λ_{1x}
(+ + +, +)	43/112	5/8
(- - -, -)	-27/112	-5/8
(- - +, -)	-3/56	-1/4
(- - +, +)	1/112	-1/8
(- + -, -)	-3/56	-1/4
(- + -, +)	1/112	-1/8
(- + +, -)	15/112	1/8
(- + +, +)	11/56	1/4
(+ - -, -)	-3/56	-1/4
(+ - -, +)	1/112	-1/8
(+ - +, -)	15/112	1/8
(+ - +, +)	11/56	1/4
(+ + -, -)	15/112	1/8
(+ + -, +)	11/56	1/4

The first column sums to one and reconstructs the base affine numerator map. The second column sums to zero and reconstructs the derivative map, with one extra factor $1/(2\omega_Q)$.

For the repeated box, $\alpha = 2$. Hence $\beta = 0, \gamma = 2$ or $\beta = 1, \gamma = 1$. Define

$$P = \prod_{i=18}^{23} \eta_i^{-1}, \quad h_r = \sum_{18 \leq i_1 \leq \dots \leq i_r \leq 23} \eta_{i_1}^{-1} \dots \eta_{i_r}^{-1}, \quad h_0 = 1.$$

The denominator derivative terms are

$$\gamma = 2: \quad 2 \frac{Ph_2}{(2\omega_Q)^3} + 6 \frac{Ph_1}{(2\omega_Q)^4} + 12 \frac{P}{(2\omega_Q)^5}, \quad (1.35)$$

$$\gamma = 1: \quad - \frac{Ph_1}{(2\omega_Q)^3} - 3 \frac{P}{(2\omega_Q)^4}. \quad (1.36)$$

These equations are exactly the two factorization trees printed in the JSON: Ph_2 is the large tree with all weakly ordered pairs of surfaces, Ph_1 is the smaller tree, and P is the single chain [18, 19, 20, 21, 22, 23].

The complete repeated-cut contribution is therefore

$$I_Q^{\text{rep}} = \sum_{x \in \mathcal{X}_Q} N_x \left[-\frac{\lambda_{0x}}{2} \left(2 \frac{Ph_2}{(2\omega_Q)^3} + 6 \frac{Ph_1}{(2\omega_Q)^4} + 12 \frac{P}{(2\omega_Q)^5} \right) - \lambda_{1x} \left(-\frac{Ph_1}{(2\omega_Q)^4} - 3 \frac{P}{(2\omega_Q)^5} \right) \right]. \quad (1.37)$$

The overall minus sign is the one-loop LTD residue sign for the Q -cut in this routing. Equation (1.37) contains no undefined coefficient: every rational number is either one of the affine weights in the table or one of the derivative factors in (1.35)–(1.36).

For the concrete orientation requested in the CLI output,

$$x = (- - -, -), \quad N_x = N_{---, -}.$$

The coefficients are

$$\lambda_{0x} = -\frac{27}{112}, \quad \lambda_{1x} = -\frac{5}{8}.$$

Using (1.25), the $\beta = 0, \gamma = 2$ variants are

$$-\frac{1}{2} \lambda_{0x} (2, 6, 12) = \left(\frac{27}{112}, \frac{81}{112}, \frac{81}{56} \right),$$

with half-edge powers 3, 4, 5. The $\beta = 1, \gamma = 1$ variants include the extra numerator-derivative half-edge and have

$$-\lambda_{1x}(-1, -3) = \left(-\frac{5}{8}, -\frac{15}{8}\right),$$

with half-edge powers 4, 5. These five numbers are exactly

variant label	prefactor	half-edge multiset
B3 b0 g2 n0:physG3tmmcm	27/112	[3, 3, 3]
B3 b0 g2 n0:physG3tmmcm	81/112	[3, 3, 3, 3]
B3 b0 g2 n0:physG3tmmcm	81/56	[3, 3, 3, 3, 3]
B3 b1 g1 nD0phys:physG3tmmcm	-5/8	[3, 3, 3, 3]
B3 b1 g1 nD0phys:physG3tmmcm	-15/8	[3, 3, 3, 3, 3].

The label **tmmcm** means $\tau = (-, -, -)$ and $\chi = -$; **b0/g2** means $\beta = 0, \gamma = 2$, and **b1/g1** means $\beta = 1, \gamma = 1$. The repeated edge signs in the orientation are all minus because the numerator sample uses the physical repeated-copy signs $\tau = (-, -, -)$, even though the denominator tree is the derivative expansion around the collapsed $Q^0 = +\omega_Q$ cut.

The final boxed formula is

$$I_{\square(3)}^{\text{HybridLTD}} = I_0^{\text{simple}} + I_1^{\text{simple}} + I_2^{\text{simple}} + I_Q^{\text{rep}}.$$

1.2.c Sunrise with One Repeated Dot Numerator

The file `examples/graphs/sunrise_pow4.dot` gives a compact multiloop example where the same repeated-channel mechanism is used in a two-loop LMB. Its internal EMR momenta are

$$q_0 = -k_1 - k_2 + p_1, \quad q_1 = k_1, \quad q_2 = q_3 = q_4 = q_5 = k_2,$$

with masses $m_1, m_2, m_3, m_3, m_3, m_3$. The repeated group is

$$R = \{2, 3, 4, 5\}, \quad \nu_R = 4, \quad Q_R^0 = k_2^0, \quad \omega_R = \omega_2 = \omega_3 = \omega_4 = \omega_5.$$

Consider the numerator

$$N(q) = q_2 \cdot p_1 = q_2^0 p_1^0 - \vec{q}_2 \cdot \vec{p}_1,$$

which is affine in the repeated energy. The command-line shorthand

```
-energy-degree-bounds 2:1 -numerator-expr auto
==> dot(edges[2], ext[0])
```

generates exactly (1.2).

There are two types of rank-two cut bases in the collapsed graph. The first type cuts the two non-repeated edges $\{0, 1\}$. Since the repeated channel is not cut, $n_0 = n_1 = 1$, $\alpha = 0$, and the hybrid term is just the LTD term with the ordinary numerator map. In the pretty output this is the orientation with variant

$$\text{B0,1|b00|g00|n0:phys0.}$$

The second type cuts one non-repeated edge and the repeated channel,

$$B = \{a, R\}, \quad a \in \{0, 1\}.$$

For definiteness take $B = \{0, R\}$. The cut equations are

$$-k_1^0 - k_2^0 + p_1^0 = \sigma_0 \omega_0, \quad k_2^0 = \chi \omega_R,$$

so

$$k_2^0 = \chi \omega_R, \quad k_1^0 = p_1^0 - \sigma_0 \omega_0 - \chi \omega_R.$$

The repeated physical sample has

$$\tau_R = (\tau_2, \tau_3, \tau_4, \tau_5) \in \{\pm 1\}^4,$$

and the CFF-localized sign χ obeys the same rule as before: all equal orbits force χ to the common sign, while mixed orbits allow both $\chi = \pm 1$. The numerator call for (1.2) is therefore

$$N_{\tau, \chi}^{\text{sun}} = \tau_2 \omega_R p_1^0 - \vec{k}_2 \cdot \vec{p}_1. \quad (1.38)$$

The other repeated signs τ_3, τ_4, τ_5 do not enter this particular dot numerator, but they are still part of the representation-level numerator energy map stored in the JSON. This is deliberate: the JSON describes a representation valid for any numerator respecting the bound, not only for the single displayed dot.

Because $\nu_R = 4$, the confluent derivative order is

$$\alpha_R = \nu_R - 1 = 3.$$

For an affine repeated numerator, only $\beta_R = 0$ and $\beta_R = 1$ appear. Consequently the repeated-cut contribution for any fixed non-repeated cut sign σ_0 has the form

$$I_{0,R}^{\text{sun}} = \sum_{x=(\tau, \chi) \in \mathcal{X}_R} N_x^{\text{sun}} \sum_{\beta=0}^1 \sum_{\mu: |\mu|=3-\beta} s_{0,R,\sigma_0,\chi} \frac{1}{3!} \binom{3}{\beta} \lambda_{\beta x} d_\mu \prod_{h \in H_{\beta,\mu}} \frac{1}{2\omega_h} \prod_{\eta \in D_\mu} \eta^{-1}. \quad (1.39)$$

Here $\mathcal{X}_R$ is the four-copy version of (1.34), $\lambda_{\beta x}$ is obtained from the same rational affine system (1.20), and d_μ is the explicit denominator-derivative coefficient of (1.24). For $\beta = 0$ the half-edge multiset contains four copies of the repeated edge before additional derivatives are distributed; for $\beta = 1$ it contains five copies because the numerator derivative reconstruction stores one extra factor $(2\omega_R)^{-1}$.

In the actual pretty table the first repeated-channel rows have labels such as

$$\text{-x++++} \quad \text{B0,2|b00|g03|n0:physG2tppppcp}.$$

This means:

$$\begin{aligned} \text{-x++++} : & \quad q_0^0 = -\omega_0, \quad q_1^0 \text{ is the solved affine map of (1.2), } q_2^0 = q_3^0 = q_4^0 = q_5^0 = +\omega_R, \\ \text{B0,2} : & \quad \text{the collapsed cut basis is edge 0 and the repeated representative 2,} \\ \text{b00|g03} : & \quad \beta = (0, 0), \quad \gamma = (0, 3), \\ \text{physG2tppppcp} : & \quad \tau_R = (+, +, +, +), \quad \chi = +. \end{aligned}$$

For a mixed sign row such as **physG2tmmmpcm**, the four letters after **t** are $\tau_2, \tau_3, \tau_4, \tau_5$, and the final **c m** gives $\chi = -$. Substituting those signs into (1.38), and the corresponding $\lambda_{\beta x}$ into (1.39), reproduces the prefactors and half-edge powers printed in the JSON.

1.3 Higher Energy Powers in Numerators

The CFF construction is naturally compatible with numerators affine in each EMR edge energy. When a user supplies a bound d_e for the highest power of each edge energy in N , the implementation first checks loop-energy UV convergence. In every loop-energy direction v , the degree of the numerator minus twice the number of denominators depending on that direction must be strictly smaller than -1 . If this check fails, finite pole data are not enough and the command refuses to build a representation.

1.3.1.a Quadratic Bounds

Let $x = q_e^0$, $\omega = \omega_e$, and suppose N has degree at most two in x , while all other EMR edge energies are held fixed. There is an exact polynomial division

$$N(x) = R_e N(x) + (x^2 - \omega^2) C_e N, \quad (1.40)$$

where the pole-safe affine remainder is

$$R_e N(x) = \frac{x + \omega}{2\omega} N(+\omega) + \frac{\omega - x}{2\omega} N(-\omega), \quad (1.41)$$

and the contact quotient is

$$C_e N = \frac{N(+\omega) - 2N(0) + N(-\omega)}{2\omega^2}. \quad (1.42)$$

Therefore

$$\frac{N}{D_e \prod_{f \neq e} D_f} = \frac{R_e N}{D_e \prod_{f \neq e} D_f} + \frac{C_e N}{\prod_{f \neq e} D_f}. \quad (1.43)$$

The first term is affine in q_e^0 and can be handled by ordinary CFF. The second term is a pinched graph with edge e removed, also handled by CFF. Consequently the pure CFF denominator remains E -surface only. The non-trivial part is to lift the CFF expression of the deleted graph back to an orientation of the original graph. The lift is completely mechanical:

1. Delete the pinched edge set P from the denominator graph and build a CFF representation of the lower graph $\mathcal{G} \setminus P$. If the lower graph factorizes into independent loop-energy components, build one CFF factor per component and multiply the component representations.
2. Every lower-sector CFF term fixes loop energies $K_t^{0, \mathcal{G} \setminus P}$ in the original LMB. If component CFF factors were built separately, the global loop-energy map is reconstructed by solving the full-rank linear system defined by the union of component basis edges.
3. For every original edge, including each deleted edge, compute the lifted EMR energy

$$\hat{q}_{e,t}^0 = \rho_e \cdot K_t^{0, \mathcal{G} \setminus P} + \eta_e \cdot p^0. \quad (1.44)$$

This number is used only for known polynomial factors. It is not automatically the numerator sample value of a deleted edge.

4. The numerator sample value of a deleted quadratic edge is one of $+\omega_e, 0, -\omega_e$, because $C_e N$ in (1.42) depends on those three black-box samples. The JSON orientation therefore assigns $q_e^0 = +\omega_e, 0$, or $-\omega_e$ to the deleted edge and records the corresponding orientation character $+$, 0 , or $-$.
5. Any lifted factor $\hat{q}_{e,t}^0$ that remains outside the black-box numerator is stored as a numerator-side surface. In the strictly quadratic contact quotient no such q -factor is needed; for cubic and higher bounds it is needed.
6. The lower-sector CFF denominator surfaces are copied into the original surface cache after replacing every lower-sector edge id by its original edge id. No denominator surface involving a deleted edge is introduced.

The rational coefficients in the JSON follow directly from (1.42). Since half-edge lists encode $(2\omega_e)^{-1}$, the factor $1/(2\omega_e^2)$ is represented as

$$\frac{1}{2\omega_e^2} = \frac{2}{(2\omega_e)^2}.$$

The three samples $N(+\omega_e)$, $N(0)$, $N(-\omega_e)$ therefore carry raw half-edge prefactors 2, -4 , 2. A one-edge CFF pinch contributes one additional sign (-1) in the implementation's CFF orientation convention, so the printed pinched quadratic prefactors are -2 , $+4$, -2 .

In hybrid mode, the same division is applied to non-affine edge energies before or inside the repeated-channel residue expansion. For non-repeated edges this is identical to the pure CFF lift above. For repeated edges the division is combined with the repeated-channel sample set $\mathcal{X}_{B,\sigma}$. The black-box numerator is still sampled only at the explicit finite set of energies supplied by the JSON orientation map.

1.3.1.b One-Loop Box with One Quadratic Edge

For a non-repeated one-loop box with denominators $D_0 D_1 D_2 D_3$, assume the only non-affine dependence is $d_0 = 2$. Use the routing

$$q_0 = k, \quad q_1 = k + p_1, \quad q_2 = k + p_1 + p_2, \quad q_3 = k + p_1 + p_2 + p_3,$$

and set $\Delta_i = p_1^0 + \dots + p_i^0$. Equations (1.40)–(1.43) give

$$I_{\square}^{\text{CFF}}[N] = I_{\text{CFF}}[\square; R_0 N] + I_{\text{CFF}}[\square/0; C_0 N], \quad (1.45)$$

where $\square/0$ is the triangle obtained by deleting propagator 0. More explicitly,

$$I_{\text{CFF}}[\square; R_0 N] = \sum_{\mathfrak{o} \in \mathcal{O}_{\text{CFF}}(\square)} \left[\frac{q_0^0(\mathfrak{o}) + \omega_0}{2\omega_0} N(q_0^0 = +\omega_0) + \frac{\omega_0 - q_0^0(\mathfrak{o})}{2\omega_0} N(q_0^0 = -\omega_0) \right] W_{\mathfrak{o}}^{\text{CFF}}, \quad (1.46)$$

$$I_{\text{CFF}}[\square/0; C_0 N] = \sum_{\mathfrak{t} \in \mathcal{O}_{\text{CFF}}(\square/0)} \frac{N(+\omega_0) - 2N(0) + N(-\omega_0)}{2\omega_0^2} W_{\mathfrak{t}}^{\text{CFF}}. \quad (1.47)$$

Both $W_{\mathfrak{o}}^{\text{CFF}}$ and $W_{\mathfrak{t}}^{\text{CFF}}$ contain only E -surface denominators.

The lifted triangle terms make the orientation structure concrete. If the triangle CFF term cuts edge $j \in \{1, 2, 3\}$ with sign σ_j , then

$$k^0 = \sigma_j \omega_j - \Delta_j, \quad \widehat{q}_0^0 = \sigma_j \omega_j - \Delta_j.$$

However, in the contact numerator call the deleted edge energy is not $\widehat{q}_0^0$; it is one of the three interpolation samples

$$q_0^0 = +\omega_0, \quad q_0^0 = 0, \quad q_0^0 = -\omega_0.$$

For example, the lower triangle orientation with original signs $(-++)$ on edges 1, 2, 3 contributes three lifted original-box orientations

$$+ - ++, \quad 0 - ++, \quad - - ++,$$

where the first character is the assigned numerator value of the deleted edge. The printed coefficients are

orientation	variant	prefactor	half-edge multiset
$+ - ++$	<code>pinch[0] e0=+</code>	-2	$[0, 0, 1, 2, 3]$
$0 - ++$	<code>pinch[0] e0=0</code>	4	$[0, 0, 1, 2, 3]$
$- - ++$	<code>pinch[0] e0=-</code>	-2	$[0, 0, 1, 2, 3]$.

The denominator surfaces of that lower triangle are the ordinary CFF surfaces among edges 1, 2, 3; in the CLI table they appear, for this orientation, as ids $[4, 5]$. The two extra half-edge entries 0, 0 encode the factor $(2\omega_0)^{-2}$. No denominator singularity associated with edge 0 remains because D_0 has been cancelled by the contact quotient. This is why the final JSON is still a normal orientation of the original box: all four numerator edge energies are specified, but only the lower triangle denominator surfaces are present.

1.3.2.a Bounds Above Quadratic

For $d_e > 2$, the same idea works but the contact quotient is no longer a constant in the deleted edge energy. Let $a_1, \dots, a_{d_e-1}$ be non-pole interpolation nodes with $a_j \neq \pm 1$, and write

$$u = \frac{q_e^0}{\omega_e}.$$

The implementation uses the deterministic node list

$$0, 2, -2, 3, -3, \dots$$

truncated to $d_e - 1$ nodes. The Lagrange basis polynomial associated with node a_j is

$$L_j(u) = \prod_{\ell \neq j} \frac{u - a_\ell}{a_j - a_\ell}. \quad (1.48)$$

It is characterized by $L_j(a_i) = \delta_{ij}$. The pole remainder is still the affine interpolation at $u = \pm 1$, and the contact quotient is reconstructed from black-box samples by

$$C_e N(q_e^0) = \sum_j \frac{L_j(q_e^0/\omega_e)}{(a_j^2 - 1)\omega_e^2} \left[N(a_j\omega_e) - \frac{a_j + 1}{2} N(+\omega_e) - \frac{1 - a_j}{2} N(-\omega_e) \right]. \quad (1.49)$$

The quotient $C_e N$ is now a known polynomial in the lifted deleted-edge energy $\hat{q}_{e,t}^0$ of (1.44). Expanding each $L_j(u)$ gives

$$L_j(u) = \sum_{r=0}^{d_e-2} \ell_{jr} u^r.$$

A monomial contribution is therefore

$$\ell_{jr} \frac{(\hat{q}_{e,t}^0)^r}{(a_j^2 - 1)\omega_e^{r+2}} \left[N(a_j\omega_e) - \frac{a_j + 1}{2} N(+\omega_e) - \frac{1 - a_j}{2} N(-\omega_e) \right]. \quad (1.50)$$

In JSON this becomes:

- $r + 2$ entries of edge e in `half_edges`, because $\omega_e^{-(r+2)} = 2^{r+2}(2\omega_e)^{-(r+2)}$;
- r numerator-side copies of the lifted surface $\hat{q}_{e,t}^0$, unless that linear form is zero;
- one numerator map with $q_e^0 = a_j\omega_e, +\omega_e$, or $-\omega_e$, depending on the black-box sample in the bracket.

For several higher-power edges, (1.50) suggests a recursive construction: pick an active edge, split its contribution into the pole remainder and the contact sector, then repeat the operation on the remaining bounded edges of the same graph or lower graph. Once a cubic or higher contact has been taken, the lower graph carries known polynomial factors

$$\prod_s (\hat{q}_{e_s,t}^0)^{r_s}.$$

If a second non-affine edge is then contacted, those known factors and the black-box numerator samples no longer separate into independent edge-wise finite-pole divisions. The completion is obtained by reducing those known polynomial factors against the remaining quadratic denominators, as described in Sec. 1.3.2.c below. Algebraically this is the lower-sector contact/infinity completion of the finite-pole recursion. In JSON it is still encoded with the same ingredients: ordinary E -surface denominator trees, half-edge factors, numerator-only linear factors, and one black-box numerator map per orientation. The only grammar extension is that a denominator tree may now contain a unit node, represented by a node with no surfaces and no children. Such a node evaluates to 1 and represents a terminal tadpole or unit lower-sector contact.

The implementation exposes the following pure-CFF higher-power cases:

1. arbitrary quadratic-or-lower caps $d_e \leq 2$, on one-loop, multiloop, split-mass, and repeated-signature graphs, provided the loop-energy UV check is satisfied;
2. arbitrary UV-convergent higher caps on non-repeated edges, using the recursive lower-contact completion described below;
3. arbitrary UV-convergent higher caps on repeated-signature channels, using a channel normal form before any individual copy is deleted.

In all accepted pure-CFF cases every denominator tree is built only from E -surfaces. Numerator-side cached factors may be E - or H -type linear forms, but the JSON marks them as numerator-only and the evaluator multiplies them in the numerator.

The repeated-channel case needs one extra algebraic step. Let

$$C = \{e_1, \dots, e_\nu\}$$

be a repeated channel with common canonical energy y_C , on-shell energy ω_C , and denominator $D_C = y_C^2 - \omega_C^2$. If the user-supplied edge bounds in this channel are d_{e_a} , the black-box numerator is known to have total channel degree at most

$$d_C = \sum_{a=1}^{\nu} d_{e_a}.$$

Choose the deterministic interpolation nodes

$$\mathcal{X}_{d_C} = (1, -1, 0, 2, -2, 3, -3, \dots)$$

truncated to $d_C + 1$ entries. The Lagrange polynomial for node a is

$$L_a(u) = \prod_{\substack{b \in \mathcal{X}_{d_C} \\ b \neq a}} \frac{u - b}{a - b}, \quad u = \frac{y_C}{\omega_C}.$$

For any black-box numerator, with all channel-copy EMR energies sampled at their signed values $q_{e_a}^0 = s_{e_a} a \omega_{e_a}$, where $s_{e_a} = \pm 1$ is the sign of the copy relative to the canonical channel,

$$N(y_C, \dots) = \sum_{a \in \mathcal{X}_{d_C}} L_a(y_C/\omega_C) N(q_{e_a}^0 = s_{e_a} a \omega_{e_a}, \dots).$$

Now write

$$L_a(u) = \sum_{r=0}^{d_C} \ell_{a,r} u^r, \quad r = 2b + p, \quad p \in \{0, 1\}.$$

The normal form of each monomial is

$$\frac{u^{2b+p}}{D_C^\nu} = \sum_{j=0}^b \binom{b}{j} \frac{y_C^p D_C^j}{\omega_C^{2j+p} D_C^\nu}. \quad (1.51)$$

If $j < \nu$, the term keeps $\nu - j$ explicit copies of the repeated denominator and deletes the other j copies. In JSON it contributes:

- coefficient $2^{2j+p} \ell_{a,2b+p} \binom{b}{j}$, because $\omega_C^{-(2j+p)} = 2^{2j+p} (2\omega_C)^{-(2j+p)}$;
- $2j + p$ entries of the representative channel edge in **half_edges**;
- one numerator-only surface for y_C if $p = 1$;

- a lower CFF denominator graph with exactly $\nu - j$ copies of the channel still present.

If $j \geq \nu$, no denominator copy of C remains. The extra $D_C^{j-\nu}$ is serialized as numerator-only factors

$$(y_C - \omega_C)^{j-\nu} (y_C + \omega_C)^{j-\nu},$$

again expressed through cached surface keys. The lower denominator is then the CFF expression of the graph with the whole repeated channel deleted. This is still an E -surface-only denominator representation; the additional factors are explicitly numerator-side objects.

This channel normal form is the reason pure CFF can now handle high powers on repeated propagators without ever invoking LTD contact denominators. It also makes the ordinary finite-pole/contact recursion a limiting case: for $\nu = 1$, (1.51) is precisely the division of a single higher-power edge into a pole remainder and a lower contact sector.

1.3.1 Uniform-Scale Repeated-Channel Sampling

The default interpolation variable in (1.3) is $u_C = y_C/\omega_C$. This is compact and is kept as the default implementation because it produces the smallest coefficients for the ordinary repeated-channel formula. However, after (1.51), high-degree monomials can generate explicit inverse powers of ω_C . These inverse powers are artificial interpolation factors: the complete orientation sum is independent of the normalization used for the interpolation nodes. They are not physical propagator singularities, and for a massless representative edge they can make individual terms unnecessarily sensitive to a soft limit before the term sum is formed.

The implementation therefore also supports a user-provided non-zero scale M . Let

$$\mathcal{X}_d = (1, -1, 0, 2, -2, \dots)$$

be the deterministic integer node list. In uniform-scale mode the pure CFF channel interpolant is

$$N(y_C, \dots) = \sum_{a \in \mathcal{X}_{d_C}} L_a(y_C/M) N(q_{e_b}^0 = s_{e_b} a M, \dots), \quad (1.52)$$

where $s_{e_b} = \pm 1$ is the sign of member e_b relative to the channel representative. The Lagrange polynomial is the same polynomial in its dimensionless argument:

$$L_a(v) = \sum_{r=0}^{d_C} \ell_{a,r} v^r, \quad v = y_C/M.$$

For a monomial $r = 2b + p$, $p \in \{0, 1\}$, the normal form becomes

$$\frac{(y_C/M)^{2b+p}}{D_C^\nu} = \sum_{j=0}^b \binom{b}{j} \frac{y_C^p \omega_C^{2(b-j)} D_C^j}{M^{2b+p} D_C^\nu}. \quad (1.53)$$

Compared with (1.51), the inverse scale is now $M^{-(2b+p)}$, while positive powers of ω_C are numerator-side known factors. If $j < \nu$, the denominator keeps $\nu - j$ channel copies. If $j \geq \nu$, the excess $D_C^{j-\nu}$ is again serialized as numerator factors $(y_C - \omega_C)^{j-\nu} (y_C + \omega_C)^{j-\nu}$. Hence the denominator surfaces are unchanged CFF causal surfaces; only the numerator map and variant prefactor gain explicit dependence on M .

For hybrid LTD/CFF, the same idea is applied around the localized LTD pole. If a repeated basis edge has sign $\sigma = \pm 1$, the finite-difference samples are

$$q_C^0 = \sigma \omega_C + aM, \quad a \in \mathcal{X}_d, \quad (1.54)$$

and the finite-difference weights carry $M^{-|\beta|}$ for a multi-derivative index β . This replaces the default $(2\omega_C)^{-|\beta|}$ factors without changing the final summed value.

The CLI exposes three policies:

none	use ω_C normalization everywhere (default),
beyond-quadratic	use M only when the repeated-channel bound is $d_C > 2$,
all	use M for every repeated-channel bound $d_C > 1$.

The second policy keeps the quadratic case in the original compact ω_C -normalized form; the third is useful when one wants all repeated finite-difference samples to have the same external normalization. The runtime evaluator rejects $M = 0$. Real evaluators accept positive or negative real M . Complex-valued Symbolica evaluators also accept complex M ; real-valued Symbolica evaluators reject it.

For the two-loop `sunrise_pow4.dot` graph, the repeated channel is

$$C = \{2, 3, 4, 5\}, \quad y_C = k_2^0, \quad \nu = 4.$$

With

$$\text{-energy-degree-bounds } 2:5$$

the channel degree is $d_C = 5$, so

$$\mathcal{X}_5 = (1, -1, 0, 2, -2, 3).$$

The JSON samples the black-box numerator at the six maps

$$q_2^0 = a \omega_2, \quad q_3^0 = a \omega_3, \quad q_4^0 = a \omega_4, \quad q_5^0 = a \omega_5, \quad a \in \mathcal{X}_5,$$

where $\omega_2 = \omega_3 = \omega_4 = \omega_5$ numerically because the repeated copy masses and spatial routings are equal. For a monomial check,

$$\frac{(y_C)^5}{D_C^4} = \frac{\omega_C^4 y_C}{D_C^4} + 2 \frac{\omega_C^2 y_C}{D_C^3} + \frac{y_C}{D_C^2}.$$

The serialized black-box formula does not assume this monomial; it emits the six Lagrange sample maps above and the rational coefficients obtained from (1.3)–(1.51). The three denominator powers in (1.3.1) correspond to JSON variants keeping four, three, and two repeated denominator copies, respectively. Every such variant has only CFF E -surfaces in the denominator and, when $p = 1$, one numerator-only surface representing y_C . The tests compare this pure-CFF value with the hybrid value and with the split-mass LTD limiting proxy.

How the JSON rows are obtained. The oriented JSON does not store the polynomial (1.3) symbolically. It stores the fully expanded terms of

$$L_a(u) D_C^{-\nu}$$

after applying (1.51). For each interpolation node a and each monomial u^{2b+p} in L_a , the builder emits one variant for each $j = 0, \dots, b$. The row data are

$$\begin{aligned} \text{sample} &= a, \\ \text{remaining_power} &= \max(0, \nu - j), \\ \text{parity} &= p, \\ \text{cancelled_power} &= \max(0, j - \nu), \\ \text{inverse_ose_power} &= 2j + p, \\ \text{coefficient} &= \ell_{a, 2b+p} \binom{b}{j}. \end{aligned}$$

The JSON prefactor of that variant is this coefficient multiplied by 2^{2j+p} and by the ordinary lower CFF prefactor of the denominator graph with $\max(0, \nu - j)$ channel copies retained. The

ordinary CFF half-edge list of that lower graph is then appended with $2j + p$ copies of the representative channel edge. If $p = 1$, the numerator-surface list gets one cached copy of the canonical channel energy y_C . This construction is purely mechanical and is what the evaluator uses directly.

For `box_pow3.dot` with

`-energy-degree-bounds 3:4,`

the repeated channel is $C = \{3, 4, 5\}$, $\nu = 3$, $d_C = 4$, and $\mathcal{X}_4 = (1, -1, 0, 2, -2)$. The first numerator map printed by `build -family cff -pretty` has orientation label `-++++`. For its sample $a = 1$, the actual variants are:

pref	remaining_power	p	inverse_ose_power	half_edges	num_surfaces
$-8/3$	1	0	4	$[0, 1, 2, 3, 3, 3, 3]$	$\square$
$-4/3$	2	0	2	$[0, 1, 2, 3, 3, 3, 4]$	$\square$
$4/3$	2	1	3	$[0, 1, 2, 3, 3, 3, 3, 4]$	[19]
$1/2$	3	0	0	$[0, 1, 2, 3, 4, 5]$	$\square$
1	3	1	1	$[0, 1, 2, 3, 3, 4, 5]$	[19].

Here surface 19 is numerator-only and is the cached linear form for the canonical repeated energy y_C in that orientation. The denominator surfaces referenced by the factorization trees are all E -surfaces.

For the mixed box command

`-energy-degree-bounds 0:1,1:1,2:0,3:4,`

the same channel reduction is performed first. The affine powers on edges 0 and 1 do not require new black-box calls. They become known linear factors whenever a lower contact sector leaves them outside the sampled black-box numerator, so the same orientation label can have additional variants with extra numerator surfaces, for example surfaces 20, 21, 22 in the current output. These variants are still grouped under the same `edge_q0` map; this is the invariant that one orientation equals one black-box numerator call.

For `sunrise_pow4.dot` with

`-energy-degree-bounds 2:5,`

the repeated channel is $C = \{2, 3, 4, 5\}$, $\nu = 4$, $d_C = 5$, and $\mathcal{X}_5 = (1, -1, 0, 2, -2, 3)$. The first numerator map has orientation label `+++++`. For sample $a = 1$, the variants are:

pref	remaining_power	p	inverse_ose_power	half_edges	num_surfaces
$-8/3$	2	0	4	$[0, 1, 2, 2, 2, 2, 2, 3]$	$\square$
$8/3$	2	1	5	$[0, 1, 2, 2, 2, 2, 2, 2, 3]$	[5]
$-4/3$	3	0	2	$[0, 1, 2, 2, 2, 3, 4]$	$\square$
$10/3$	3	1	3	$[0, 1, 2, 2, 2, 2, 3, 4]$	[5]
$1/2$	4	0	0	$[0, 1, 2, 3, 4, 5]$	$\square$
1	4	1	1	$[0, 1, 2, 2, 3, 4, 5]$	[5].

Surface 5 is numerator-only and represents the lifted canonical channel energy

$$y_C = -\omega_0 - \omega_1 + p_1^0$$

for this orientation. Its sign-flipped companion appears as surface 6 in the `-++++` orientation. These two surfaces are marked (e) in pretty output because they occur only in the numerator.

If the same sunrise graph is built with

`-energy-degree-bounds 2:3,3:3,`

the channel degree is $d_C = 6$, because both powered repeated copies belong to the same denominator channel. The node set is $\mathcal{X}_6 = (1, -1, 0, 2, -2, 3, -3)$. The first printed numerator map has seven variants for sample $a = 1$; the leading channel-reduction metadata are

pref	remaining_power	p	inverse_ose_power	coefficient
$-4/3$	1	0	6	$1/48$
$-10/3$	2	0	4	$-5/24$
$2/3$	2	1	5	$1/48$
$-13/12$	3	0	2	$13/48$

The remaining three variants are the same expansion continued to `remaining_power` = 3, 4, 4. The important point is that the JSON does not distinguish which copy originally carried which cubic cap once the copies are identified as a repeated channel; it only needs the total channel degree $d_C = 6$ and the individual numerator sample map for every original edge copy.

Pure CFF does not need a separate repeated-pole derivative construction: repeated propagators are repeated denominator factors in the CFF contour integral. The channel normal form above simply performs the finite polynomial division at the level of the repeated denominator power before CFF denominator trees are generated. The hybrid formula remains useful for the LTD-like repeated-channel organization, but it is not needed to make the pure-CFF higher-power lift well-defined.

Hybrid mode has a different status. The hybrid repeated-channel formula is not constrained to keep pure-CFF denominator trees E -only: H -surfaces are allowed because the non-repeated part is LTD-like and CFF is used only to localize repeated channels. With `-energy-degree-bounds`, numerator derivatives in the repeated-channel residue are replaced by tensor-product finite-difference samples in the repeated basis coordinates. For a derivative multiindex β , the degree used along basis direction b is

$$D_b = \sum_e d_e \mathbf{1}\{\partial q_e^0 / \partial z_b \neq 0\},$$

where z_b is the repeated basis energy. The finite-difference stencil is the node set $0, 1, -1, 2, -2, \dots$ truncated to $D_b + 1$ nodes, with weights fixed by exact polynomial interpolation. Therefore the numerator is still a black box: the JSON only asks for samples at explicit EMR energy maps.

The implemented hybrid path is validated for arbitrary user-provided caps subject to the same loop-energy UV check and practical expression size. The test suite covers cubic, quartic, and quintic caps on repeated box, sunrise, kite, mercedes, and iterated-bubble examples by comparing the hybrid value to the split-mass LTD limiting proxy. In the absence of repeated propagators, hybrid collapses exactly to LTD for any accepted bound vector.

1.3.2.b One-Loop Box with One Cubic Edge

For the same one-loop box, take $d_0 = 3$. The implementation chooses the two non-pole nodes

$$a_0 = 0, \quad a_1 = 2.$$

The Lagrange basis is

$$L_0(u) = 1 - \frac{u}{2}, \quad L_1(u) = \frac{u}{2}. \quad (1.55)$$

Substituting these two polynomials into (1.49) gives

$$\begin{aligned} C_0 N(q_0^0) = & -\frac{1 - u/2}{\omega_0^2} \left[N(0) - \frac{1}{2}N(+\omega_0) - \frac{1}{2}N(-\omega_0) \right] \\ & + \frac{u/2}{3\omega_0^2} \left[N(2\omega_0) - \frac{3}{2}N(+\omega_0) + \frac{1}{2}N(-\omega_0) \right], \quad u = \frac{\hat{q}_0^0}{\omega_0}. \end{aligned} \quad (1.56)$$

For a lower triangle orientation $\mathbf{t}$, the lifted deleted energy is

$$\widehat{q}_{0,\mathbf{t}}^0 = \rho_0 \cdot K_{\mathbf{t}}^{0,\square/0}.$$

For instance, if the triangle cut is edge 1 with sign $-$, then

$$\widehat{q}_{0,\mathbf{t}}^0 = -\omega_1 - p_1^0,$$

which appears in the surface cache as a numerator-only E -surface. If the cut is edge 1 with sign $+$, the lifted surface is $\omega_1 - p_1^0$. These are the numerator-only surfaces printed as (e) in the cubic box output.

The monomial coefficients of (1.56) map directly to JSON variants. Before the one-edge CFF pinch sign, the finite-pole contact components for edge 0 are

sample q_0^0	prefactor	half-edge multiset	numerator surface
0	-4	$[0, 0]$	$\emptyset$
0	4	$[0, 0, 0]$	$[\widehat{q}_0^0]$
$+\omega_0$	2	$[0, 0]$	$\emptyset$
$+\omega_0$	-4	$[0, 0, 0]$	$[\widehat{q}_0^0]$
$-\omega_0$	2	$[0, 0]$	$\emptyset$
$-\omega_0$	-4/3	$[0, 0, 0]$	$[\widehat{q}_0^0]$
$2\omega_0$	4/3	$[0, 0, 0]$	$[\widehat{q}_0^0]$.

The printed one-loop box CFF table includes the additional pinch sign, so the visible variants are

orientation label	variant	prefactor	meaning
0 - ++	pinch[0] e0=0	4	$-(-4) N(q_0^0 = 0)/(2\omega_0)^2$
0 - ++	pinch[0] e0=0	-4	$-(4) \widehat{q}_0^0 N(q_0^0 = 0)/(2\omega_0)^3$
x - ++	pinch[0] e0=2	-4/3	$-(4/3) \widehat{q}_0^0 N(q_0^0 = 2\omega_0)/(2\omega_0)^3$
+ - ++	pinch[0] e0=+	-2	$-(2) N(q_0^0 = +\omega_0)/(2\omega_0)^2$
+ - ++	pinch[0] e0=+	4	$-(-4) \widehat{q}_0^0 N(q_0^0 = +\omega_0)/(2\omega_0)^3$
- - ++	pinch[0] e0=-	-2	$-(2) N(q_0^0 = -\omega_0)/(2\omega_0)^2$
- - ++	pinch[0] e0=-	4/3	$-(-4/3) \widehat{q}_0^0 N(q_0^0 = -\omega_0)/(2\omega_0)^3$.

The label x in $x - ++$ indicates that the deleted edge is sampled at the non-standard finite node $q_0^0 = 2\omega_0$, so its detailed energy map must be read from the orientation details rather than from a single $+$, $-$, or 0 symbol. All denominator surfaces in these rows are the lifted triangle CFF surfaces; $\widehat{q}_0^0$ is a numerator-only surface and cannot create a denominator singularity.

This cubic box example is the first member of the higher-contact recursion. If the other box edges are affine, for example $(d_0, d_1, d_2, d_3) = (3, 1, 1, 1)$, the formula above is exact and agrees with LTD. If one spectator is quadratic, for example $(3, 1, 2, 0)$, a second contact produces the terminal tadpole derived below. The implemented command now emits that completion as an explicit unit denominator node, so the resulting pure-CFF JSON remains E -surface-only in the denominator and agrees with LTD for all UV-convergent one-loop box monomial caps through the convergence range $\sum_e d_e \leq 6$. The same higher cap is allowed on a graph that contains repeated propagators, including when the capped edge is one of the repeated copies, because pure CFF treats those copies as ordinary repeated denominator factors.

1.3.2.c Terminal Contact Completion

The recursive lower-contact completion can terminate on a sector whose remaining denominator set is smaller than the degree of the known polynomial factor carried by previous contacts. The simplest terminal sector is useful because it can be analyzed completely and because it fixes the unit-tree terms that appear in the JSON grammar.

Consider the one-loop box with edge energies

$$q_e^0 = k^0 + \Delta_e, \quad D_e = (q_e^0)^2 - \omega_e^2, \quad e = 0, 1, 2, 3,$$

where Δ_e is the external-energy shift of edge e and $\omega_e = E_e(\vec{k})$. Define

$$\delta_{ab} = \Delta_a - \Delta_b, \quad q_a^0 = q_b^0 + \delta_{ab}.$$

One representative terminal sector is

$$(d_0, d_1, d_2, d_3) = (0, 0, 3, 3), \quad N(q) = (q_2^0)^3 (q_3^0)^3.$$

For a cubic edge the finite-pole/contact division is just

$$(q_e^0)^3 = \omega_e^2 q_e^0 + D_e q_e^0. \quad (1.57)$$

The first term is the pole remainder and is handled by the finite-pole CFF samples. The second term cancels D_e and produces a contact lower sector. Taking the contact part on both cubic edges produces, among other already handled terms, the lower bubble

$$\frac{q_2^0 q_3^0}{D_0 D_1}. \quad (1.58)$$

This bubble is the first terminal sector in which the lower-contact completion produces a unit denominator tree. Writing the numerator in terms of the remaining edge 0,

$$q_2^0 = q_0^0 + \delta_{20}, \quad q_3^0 = q_0^0 + \delta_{30},$$

gives the exact identity

$$\begin{aligned} q_2^0 q_3^0 &= (q_0^0)^2 + (\delta_{20} + \delta_{30}) q_0^0 + \delta_{20} \delta_{30} \\ &= D_0 + \omega_0^2 + (\delta_{20} + \delta_{30}) q_0^0 + \delta_{20} \delta_{30}. \end{aligned} \quad (1.59)$$

Therefore

$$\frac{q_2^0 q_3^0}{D_0 D_1} = \frac{\omega_0^2 + (\delta_{20} + \delta_{30}) q_0^0 + \delta_{20} \delta_{30}}{D_0 D_1} + \frac{1}{D_1}. \quad (1.60)$$

The first term has an affine numerator in the lower bubble and is a standard CFF object. The second term is a terminal lower-sector tadpole. It has no ordinary E -surface denominator left after the half-edge factor of edge 1; in the JSON grammar it would be represented as a unit denominator tree with the half-edge list [1].

With the close-below convention used by the code, this terminal contribution has the sign of the corresponding CFF branch and evaluates to

$$-\frac{1}{2\omega_1}$$

for the sector in (1.58). The same value is obtained by comparing the serialized CFF unit-tree term against the LTD reference at high precision. For the same random kinematics used in the tests,

$$\omega_1 = 0.788665091489179\dots, \quad \frac{1}{2\omega_1} = 0.633982669444499\dots$$

The related box sectors

$$(0, 3, 0, 3), \quad (0, 3, 3, 0), \quad (2, 1, 0, 3), \quad (3, 1, 2, 0),$$

and their permutations show the same pattern: the terminal contribution is a single terminal tadpole $\pm 1/(2\omega_i)$, with i determined by the last remaining denominator in the lower sector. In

the intermediate recursion these branches are terms with no E -surface denominator chain. The schema now serializes them as a unit denominator node

`{surfaces: [], children: []},`

so the evaluator multiplies by the half-edge factors and by one. With this unit-node encoding, all UV-convergent one-loop box monomial caps satisfying $\sum_e d_e \leq 6$ agree with LTD at arbitrary precision.

The natural one-loop generalization is consequently not another finite-pole sample, but a lower-sector normal-form recursion. Let S be the set of denominators left after some contacts and let $P(q^0)$ be the known polynomial factor multiplying the black-box numerator sample. Choose $a \in S$ and divide P by

$$D_a = (q_a^0)^2 - \omega_a^2$$

after rewriting all q_e^0 in terms of q_a^0 :

$$P(q^0) = D_a Q_a(q^0) + R_a(q^0), \quad \deg_{q_a^0} R_a \leq 1. \quad (1.61)$$

Then

$$\frac{P}{\prod_{e \in S} D_e} = \frac{R_a}{D_a \prod_{e \in S \setminus \{a\}} D_e} + \frac{Q_a}{\prod_{e \in S \setminus \{a\}} D_e}. \quad (1.62)$$

The first term is again a finite-pole CFF term because its numerator is affine in the active energy. The second term is the contact completion and is recursed on the smaller denominator set. When one denominator remains, (1.62) terminates in a tadpole; when no denominator remains, UV convergence of the full sector must make the sum of such unit polynomial branches cancel across contact histories.

The same mechanism extends to multiloop contact sectors whenever the known polynomial factors reduce to the span of the denominator components that remain. The smallest diagnostic graph is the two-loop penta-denominator

$$D_0(k_1 + k_2 + p_3) D_1(k_1) D_2(k_1 + p_1) D_3(k_2) D_4(k_2 + p_2).$$

For the UV-convergent bounds

$$(d_0, d_1, d_2, d_3, d_4) = (1, 0, 3, 0, 3),$$

one contact history sets $q_2^0 = q_4^0 = q_0^0 = q_1^0 = 0$ and leaves only

$$\frac{(p_1^0)(p_2^0 - p_3^0)}{D_3(k_2)}.$$

The original graph has two loop energies, but this lower sector has rank one. It is nevertheless not ambiguous: all dependence on the unlocalized k_1^0 has disappeared into external-energy factors. The completion is therefore a single terminal tadpole,

$$\frac{p_1^0(p_2^0 - p_3^0)}{2\omega_3},$$

times the half-edge factors accumulated along the contact path. The code handles this by decomposing the remaining denominator rows into vector-matroid components, building a CFF or terminal LTD factor for each non-zero component, and solving only the localized rank directions. Free loop-energy directions are assigned the particular value zero in the derived `loop_q0` map; the EMR `edge_q0` map is the numerator map and is unchanged by that bookkeeping choice.

This gives a practical generalization of (1.61)–(1.62): recurse on active higher-power or known-polynomial edges, reduce quotient terms against the remaining denominators, decompose

the lower denominator into matroid components, and serialize terminal components as unit denominator nodes. The pure-CFF tests now include the one-loop box sectors above, repeated-signature box sectors with quartic caps on repeated copies, high-power repeated sunrise and kite sectors, two repeated channels in the iterated-bubble topology, and the two-loop rank-deficient penta sectors; in every accepted case the denominator surface set is E -only and the value agrees with LTD or, for repeated propagators, with the hybrid value and the split-mass LTD limiting proxy.

Chapter 2

Python Implementation and JSON Format

2.1 Module Structure

The implementation is organized around an evaluator-complete intermediate format.

- `graph_io.py` parses DOT graphs, extracts momentum signatures, detects repeated channels, and builds split-mass reference graphs.
- `graph_signatures.py` implements the `graph_from_signatures` command, which turns products such as `prop(k1+p1,m)` into DOT graphs.
- `orientation_bundle.py` constructs LTD, CFF, hybrid, and bounded-degree contact bundles. This is where repeated channels are collapsed, active numerator maps are enumerated, and CFF lower minors are generated.
- `structure.py` serializes bundles to schema-v6 JSON and contains the arbitrary-precision Python evaluator.
- `pretty.py` renders the JSON in a human-readable form.
- `symbolica_eval.py` compiles a fixed-numerator JSON expression to Symbolica eager and assembly-backed evaluators.

2.2 Bounded-Degree Support Matrix

The command-line option `-energy-degree-bounds` is interpreted as an upper bound d_e for the degree of the black-box numerator in each EMR edge energy q_e^0 . The builder first applies the loop-energy UV check described in Section 1.3. If the check fails, no representation is built. For the `test` and `compare` subcommands this option is common: the same bound vector is used to build the CFF expression, the hybrid expression, and the split-mass LTD reference. The `-cff-energy-degree-bounds` option is retained only for CFF-only diagnostics.

When a command both evaluates a numerator and sees `-numerator-expr auto`, the CLI replaces `auto` by a concrete black-box numerator before any representation is evaluated or compiled. The `build` command accepts the same option as metadata: it records the resolved expression in `graph.numerator_expr` while leaving the orientation structure unchanged. If the graph has n_{ext} external momentum symbols and the normalized bound vector is $d = (d_0, \dots, d_{|E|-1})$, the generated expression is

$$N_{\text{auto}}(q, p) = \prod_{e=0}^{|E|-1} \prod_{r=0}^{d_e-1} (q_e \cdot p_{(e+r) \bmod n_{\text{ext}}}). \quad (2.1)$$

Edges absent from the bound input have $d_e = 0$ and therefore contribute no factor. The external index cycle is deterministic and is chosen only to make the numerator depend on generic external energies; it has no bearing on the representation builder. For example, on `box_pow3.dot`,

```
-energy-degree-bounds 3:3,4:4 -numerator-expr auto
```

is resolved to

```
dot(edges[3], ext[0]) * dot(edges[3], ext[1]) * dot(edges[3], ext[2]) *
dot(edges[4], ext[1]) * dot(edges[4], ext[2]) * dot(edges[4], ext[0]) *
dot(edges[4], ext[1])
```

The concrete string is stored in JSON test reports and in Symbolica evaluator metadata. For `evaluate` and `compile`, `auto` reads the bound vector from `graph.energy_degree_bounds` in the input orientation JSON; for `build`, `test`, `compare`, and `test-cff-ltd`, it uses the command-line bound vector.

For repeated-channel interpolation one may additionally set

```
--uniform-numerator-sampling-scale none
--uniform-numerator-sampling-scale beyond-quadratic
--uniform-numerator-sampling-scale all
```

on `build`, `test`, or `compare`. The first value is the default. In uniform modes the JSON graph block records

```
"uniform_numerator_sampling_scale": "all",
"uniform_scale_symbol": "M"
```

and every energy map is allowed to contain an integer coefficient `"m"` multiplying the runtime scale M :

```
{"i": [[3, 1]], "x": [[0, -1]], "m": 2, "c": "0"}
```

The expression above means $\omega_3 - E_0 + 2M$. Variants also have an integer `uniform_scale_power`; a value r multiplies that variant by M^{-r} . The arbitrary-precision evaluator receives M through `evaluate -uniform-scale VALUE`. The `test` command receives comparison scales through `-uniform-scales A,B`; if omitted, it uses $M = 1.0$ and $M = 2.75$.

The surface cache stores both a compact expression and structured terms:

```
"terms": {
  "ose": [[edge_id, coeff]],
  "external_shift": [[external_id, coeff]],
  "uniform_scale": coeff,
  "constant": "0"
},
"surface_origin": "physical",
"singularity": "physical"
```

`surface_origin="helper"` is reserved for factors introduced by interpolation, known-factor reconstruction, finite-pole recursion, or terminal sectors. CFF causal surfaces emitted by the original graph or by a lower-sector CFF component are still classified as `surface_origin="physical"`, because they are genuine causal thresholds of the denominator set being evaluated. `singularity="spurious"` is an algorithmic marker for a helper factor that is not one of those causal surfaces, for example a factor containing M , a non-unit OSE coefficient, or a polynomial reconstruction factor. In pretty output the class tag adds `_h` for helper origin and `_sp` for the spurious marker, while parentheses still mean numerator-only. Thus `e` is a physical denominator E-surface and `(e_h_sp)` is a numerator-only helper factor. Pure CFF denominator trees are tested not to contain `_sp` surfaces.

After the UV check, the guaranteed support is:

family	graph class	supported bounds
<code>ltd</code>	any graph	any UV-convergent bounds; structure unchanged
<code>hybrid</code>	no repeated propagators	any UV-convergent bounds; exact LTD collapse
<code>hybrid</code>	repeated propagators	any tested UV-convergent bounds; finite-difference samples
<code>cff</code>	any graph	all $d_e \leq 2$, denominator E -surfaces only
<code>cff</code>	high-power edge caps	channel/contact normal form; denominator E -surfaces only

The last `cff` row includes one-loop and multiloop sectors with mixed cubic/quadratic and quartic-or-higher caps, including caps on repeated-signature edges, provided the loop-energy UV check succeeds. Repeated channels are reduced by (1.51); non-repeated high-power contacts are reduced by the lower-sector recursion (1.61)–(1.62). The implementation still may become impractical for very large cap vectors because the number of Lagrange samples and lower-contact sectors grows rapidly, but the JSON grammar and evaluator semantics do not require a separate fallback branch.

Production representation names. The implementation-level family names above separate the mathematical building blocks. In gammaLoop user settings the production choices are only `CFF` and `LTD`. The public `LTD` path uses the derivative-free repeated-channel construction where needed, and therefore agrees with the split-mass LTD limit without differentiating the numerator. `pure_ltd` remains a diagnostic/testing object for the 3D-representation CLI and is not the production formula for unsplit repeated propagators with non-trivial numerator dependence. The feature-gated `old_cff` object is kept only inside the `three-dimensional-reps` crate for legacy parity tests.

Uniform E -surface characterization for LU cuts. Local unitarity cut selection and threshold counterterm construction must not depend on whether the original integrand is eventually evaluated as CFF or LTD. GammaLoop therefore treats the causal E -surface groups as the representation-neutral catalogue of physical threshold and Cutkosky cut surfaces. CFF expressions expose this catalogue directly. LTD expressions may contain additional H -surfaces in intermediate dual denominators, but after the explicit sum over orientations those surfaces are spurious for the threshold problem and are not used as threshold-counterterm surfaces.

For a forward-scattering graph, initial-state cut edges are first externalized as correlated external energy shifts and external tree denominators are kept four-dimensional. GammaLoop then builds a companion CFF projection expression with the same reduced graph data and uses its canonical E -surface groups to identify raised LU cuts and left/right threshold residues. The selected residue data are mapped back to the requested representation before numerator energy maps are localized and event weights are assembled. This keeps CFF and LTD aligned at the level of event groups, individual event weights, and additional counterterm weights.

Canonicalization fixes the sign convention of a surface such as $-\omega_{i_1} - \dots - \omega_{i_r} + \Delta$ by replacing it with $\omega_{i_1} + \dots + \omega_{i_r} - \Delta$ and carrying the corresponding residue orientation in the surface map. The LTD projection also carries a Cutkosky residue bridge for simple LU cuts. GammaLoop determines this bridge from the generated graph and surface data: the selected denominator sign is the product of the positive-energy Cutkosky edge-flow orientation and the determinant sign of the resolved LU coordinate basis $(B_{\text{left}}, B_{\text{cut}}, B_{\text{right}})$ in the chosen loop-momentum basis. Simple poles also carry the orientation of the full LU surface family, defined as the product of the unit external-energy coefficients used to parametrize the generated LU-cut E -surfaces. This converts the local LTD surface variables to GammaLoop’s simultaneous positive-energy Cutkosky variables without referring to graph labels or to the number of selected cut groups as an independent rule.

Raised or confluent LU cuts do not use the simple-pole selected-variable bridge. Their selected local variable is kept in the generated LTD convention; the remaining basis factor is carried once as a residue prefactor containing the repeated-pole derivative parity and the product of the positive-energy orientations of the collapsed Cutkosky alternatives. The remaining representation bridges are global convention factors: the LTD LU loop-measure parity $(-1)^{L-1}$, with L the forward-scattering loop count after removing initial-state cut edges, and the full-source versus reduced-source CFF sign exponent used for expanded-four-dimensional UV counterterms. None of these signs depends on a graph label or on a fitted sign from tests.

Embedding in gammaLoop cross-section integrands. The gammaLoop production path always constructs the three-dimensional representation through `generate_3d_expr`. Initial-state cut edges of a forward-scattering graph are treated as external energy shifts rather than ordinary CFF/LTD denominator edges. External tree structures and pure tree graphs are likewise preserved as residual four-dimensional denominators: when the reduced source has no loop-energy variables, the energy-bound check is trivially convergent and the generated object is just the product of those residual denominators.

Local inspect parity in the cross-section tests compares three structurally different constructions: CFF with local UV counterterms from 3D expansions, CFF with local UV counterterms from expanded four-dimensional integrands, and LTD with local UV counterterms from expanded four-dimensional integrands. The only LTD-specific global bridge in this comparison is the loop-measure convention factor $(-1)^{L-1}$, where L is the forward-scattering loop count after removing initial-state cut edges; its branch-local Cutkosky residue bridge is the simultaneous-residue parity described above. CFF expanded-source UV terms instead receive the difference between the full-graph and reduced-source generalized-CFF sign exponents; this accounts for duplicate-signature excess lost or gained when a local UV source is projected out of the original graph. LTD expanded-source UV terms do not receive this reduced-source CFF exponent: their reduced source is evaluated directly in the generated dual convention, and the full LTD measure bridge is applied once when the local UV forest term is embedded back into the original graph. These signs are representation-convention factors, not graph-name patches.

The hybrid high-power tests are not pure-CFF tests. They compare the hybrid value with a split-mass LTD proxy and verify convergence as the mass split is reduced. This is the correct reference for repeated propagators because ordinary LTD on the unsplit repeated graph would require numerator derivatives, which the hybrid construction avoids.

2.3 Oriented JSON Semantics

The top-level JSON contains graph metadata, a surface cache, and a list of orientations. The central invariant is:

one orientation corresponds to one unique EMR edge-energy numerator map.

All denominator terms sharing that numerator call are stored as **variants**. Each variant has its own rational prefactor, half-edge list, numerator-surface list, and factorized denominator tree.

The evaluator uses only the JSON plus the DOT graph. It does not reconstruct a hidden LTD or CFF object. A variant contributes

$$\text{pref} \prod_{e \in \text{half_edges}} (2\omega_e)^{-1} \prod_{s \in \text{num_surfaces}} \eta_s \prod_{t \in \text{denominator tree}} \eta_t^{-1}$$

times the numerator sampled at the orientation's `edge_q0` map.

2.4 Surface Cache

Each surface cache entry records a class, coefficients of internal on-shell energies, and external-energy shifts. The class is printed as **e** or **h**. If a surface appears only in numerator factors, the entry carries `numerator_only=true` and pretty printing displays **(e)** or **(h)**. If a numerator-side surface is identical to an existing denominator surface, the same id is reused.

2.5 Orientation Labels and Variants

Compact labels use $+$, $-$, 0 , and x :

- $+$: the numerator samples that edge at $+\omega_e$;
- $-$: the numerator samples that edge at $-\omega_e$;
- 0 : the numerator samples that edge at zero energy;
- x : the edge has a non-trivial affine map, printed by `-show-details`.

The physical origin of a contribution, such as CFF, LTD, pinched contacts, or hybrid basis/interpolation data, is variant metadata rather than part of the orientation identity. This is what keeps the number of numerator calls minimal.

2.6 Command-Line Workflow

The main commands are:

```
python3 generalised_ltd.py validate --dot examples/graphs/box_pow3.dot
python3 generalised_ltd.py build --family hybrid --dot examples/graphs/box_pow3.dot --
  pretty
python3 generalised_ltd.py build --family cff --dot examples/graphs/box_pow3.dot \
  --energy-degree-bounds 3:3,4:4 --numerator-expr auto
python3 generalised_ltd.py test --dot examples/graphs/box_pow3.dot
python3 generalised_ltd.py test --dot examples/graphs/box_pow3.dot \
  --energy-degree-bounds 0:1,1:1,2:0,3:4 \
  --numerator-expr 'edges[0][0] * edges[1][0] * edges[3][0]**4'
python3 generalised_ltd.py test --dot examples/graphs/box_pow3.dot \
  --energy-degree-bounds 3:3,4:4 --numerator-expr auto
python3 generalised_ltd.py test-cff-ltd --dot examples/graphs/box.dot --energy-degree-
  bounds 0:2
python3 generalised_ltd.py compile --orientation-json demo.json --dot graph.dot --
  numerator-expr "1"
python3 generalised_ltd.py evaluate --orientation-json demo.json --dot graph.dot --
  evaluator-backend symbolica
```

The repeated-propagator three-way test compares pure CFF, hybrid, and the split-mass LTD limiting proxy. The ordinary LTD formula on an unsplit repeated graph is not a valid physics comparison because numerator derivatives are not included there.

2.7 Symbolica Evaluators

The `compile` command accepts one JSON representation and one fixed numerator expression. It reconstructs the JSON expression symbolically, introducing structured functions such as `OSE(qx,qy,qz,m)`, `etaE(i)`, `etaH(i)`, and tagged edge/loop/external momentum components. The resulting Symbolica evaluator is saved both as a shared library and as eager evaluator state.

The JSON is updated with relative paths and fingerprints tying the evaluator to the graph, numerator, value type, and orientation structure.

The `evaluate` command can use:

```
builtin, symbolica_compiled, symbolica_eager, symbolica_eager_symjit.
```

Profiling performs ten calls of a batch evaluator. The default batch size is 100, so a profile line reports one thousand repeated samples of the same input kinematics.

The same saved eager evaluator is used by `evaluate -stability`. This mode converts the generated or supplied real kinematic input to decimal precision-tracking numbers with 16 significant digits by default, evaluates with Symbolica's `Evaluator.evaluate_with_prec`, and reports the number of significant digits carried by the final decimal result. The work precision for constants and arithmetic defaults to 80 decimal digits and can be changed with `-stability-work-precision`. Non-finite outputs are assigned zero reported digits. The printed central value is diagnostic only: once the reported digit count is small, the value may have lost enough significance to be numerically meaningless.

Chapter 3

Performance

3.1 Benchmark Setup

The numbers below were generated on April 26, 2026 using the scripts in `examples/scripts`. Each timing is the per-sample time reported by `evaluate -profiling 100`, i.e. ten batch calls of size 100. The 15-external one-loop benchmark is intentionally omitted here: the LTD build is small, but the pure CFF one-loop representation has $2^{15} - 2 = 32766$ sign sectors and the CFF build is not practical for routine documentation runs.

3.2 Repeated Box

The repeated box script `examples/scripts/box_pow3_cli_showcase.sh` compares hybrid and pure CFF for the six-edge graph with a triple repeated propagator. The numerator is `dot(edges[0], ext[0]) + edges[3][0]`.

label	backend	orientations	maps	value type	per sample
hybrid	compiled	17	17	real	$0.0955\ \mu s$
hybrid	eager	17	17	real	$0.521\ \mu s$
hybrid	eager+symjit	17	17	real	$0.104\ \mu s$
hybrid	compiled	17	17	complex	$0.271\ \mu s$
hybrid	eager	17	17	complex	$0.725\ \mu s$
hybrid	eager+symjit	17	17	complex	$0.0989\ \mu s$
CFF	compiled	62	62	real	$0.162\ \mu s$
CFF	eager	62	62	real	$1.44\ \mu s$
CFF	eager+symjit	62	62	real	$0.142\ \mu s$
CFF	compiled	62	62	complex	$0.466\ \mu s$
CFF	eager	62	62	complex	$2.03\ \mu s$
CFF	eager+symjit	62	62	complex	$0.136\ \mu s$

The hybrid representation has fewer numerator maps than CFF, which explains the faster compiled real evaluator. Complex compiled evaluation is slower because the generated function propagates complex arithmetic even though the input kinematics are real. Symjit eager evaluation is competitive for this small expression because the batch is small and the expression has only 17 or 62 maps.

3.3 One-Loop 10-Gon

The script `examples/scripts/one_loop_10_external_runtime_compare.sh` compares numerator-free LTD and CFF on a true one-loop 10-gon.

family	backend	orientations	maps	per sample
LTD	compiled	10	10	$0.234\ \mu s$
LTD	eager	10	10	$0.852\ \mu s$
LTD	eager+symjit	10	10	$0.147\ \mu s$
CFF	compiled	1022	1022	$3.96\ \mu s$
CFF	eager	1022	1022	$36.6\ \mu s$
CFF	eager+symjit	1022	1022	$2.97\ \mu s$

The result is expected: the one-loop CFF orientation count grows like $2^n - 2$, while LTD has only one cut per internal edge. The CFF expression is still fast in absolute terms after compilation, but it is much larger.

3.4 Five-Loop Four-External Benchmarks

The script `examples/scripts/five_loop_symbolica_runtime_compare.sh` compares three numerator choices on a non-repeated five-loop graph and on the repeated five-loop graph. The three numerator choices are 1, one edge-external dot product per internal edge, and the same numerator with three selected edge terms squared.

case	family	maps	compiled	eager	eager+symjit
no repeats, $N = 1$	LTD	137	0.326	1.88	0.250
no repeats, $N = 1$	CFF	930	1.26	12.3	0.892
no repeats, $N = 1$	hybrid	137	0.333	1.87	0.246
no repeats, linear	LTD	137	0.481	3.29	0.379
no repeats, linear	CFF	930	1.96	17.5	1.35
no repeats, linear	hybrid	137	0.484	3.24	0.391
no repeats, squared	LTD	137	0.493	3.45	1.73
no repeats, squared	CFF	4692	18.7	45.9	13.2
no repeats, squared	hybrid	137	0.520	3.31	0.390

case	family	maps	compiled	eager	eager+symjit
repeated, $N = 1$	LTD	137	0.334	1.90	0.272
repeated, $N = 1$	CFF	930	1.26	12.5	0.899
repeated, $N = 1$	hybrid	630	0.823	4.88	0.579
repeated, linear	LTD	137	0.481	3.44	0.408
repeated, linear	CFF	930	1.88	17.4	1.32
repeated, linear	hybrid	630	21.4	37.8	12.4
repeated, squared	LTD	137	0.491	3.53	0.387
repeated, squared	CFF	see text	see text	see text	see text
repeated, squared	hybrid	115	1.84	9.47	1.11

For non-repeated graphs the hybrid family collapses to the LTD structure, so their orientation and map counts agree. CFF is slower because it has more causal sign sectors. The squared CFF no-repeat case is much larger because the bounded-degree contact completion adds pinched CFF minors.

For repeated graphs, the LTD rows are included only as runtime references. The ordinary unsplit LTD expression does not include numerator derivatives for raised propagators; the correct comparison is CFF versus hybrid versus the split-mass LTD limiting test. The repeated unit numerator shows the expected middle ground: hybrid has fewer maps than CFF but more

than LTD. The repeated linear case is slower for hybrid because the confluent interpolation creates heavier denominator variants per numerator map. In the squared repeated case, the pure CFF row now uses the recursive E -surface-only contact/minor construction rather than an LTD-contact correction; the timing table should be regenerated before quoting a stable number for that row. The bounded hybrid reduction has 115 maps for this benchmark.

3.5 Precision Stability

The following tables use `evaluate -stability` with 16 significant digits in the input and 80 decimal digits of work precision. They measure the precision carried by Symbolica’s eager precision-tracking arithmetic through the already compiled structured expression. These measurements are not identity tests; they probe numerical conditioning of the particular representation and kinematic point. When only one or two digits remain, the displayed value should be interpreted as a symptom of cancellation rather than as a trustworthy estimate.

example	family	maps	result digits	tracked value
repeated box	LTD	6	0	∞
repeated box	CFF	62	1	10^{-2}
repeated box	hybrid	17	1	-2×10^3
one-loop 10-gon	LTD	10	2	2.6×10^5
one-loop 10-gon	CFF	1022	1	10^{-1}

For the repeated box, the LTD row is again not a valid repeated-propagator formula; its singular output is a useful reminder that the unsplit LTD structure contains zero repeated-channel surfaces. CFF and hybrid have the same ordinary double value for this point, but the precision-tracking run shows that both are badly conditioned at 16 input digits, with the hybrid central value already unusable. This is consistent with the hybrid expression being a more compact but more cancellation-prone confluent combination.

five-loop case	LTD digits	CFF digits	hybrid digits
no repeats, $N = 1$	2	2	2
no repeats, linear	2	2	2
no repeats, squared	2	2	2
repeated, $N = 1$	0	2	2
repeated, linear	0	2	2
repeated, squared	0	2	2

The five-loop tables show that the tested random point is numerically delicate for all structured sums at ordinary double-like input precision. The non-repeated hybrid rows coincide with LTD, as required by construction. In the repeated graph, the invalid unsplit LTD expression produces NaN and therefore zero digits, while CFF and hybrid retain two tracked digits in all three numerator scenarios. The result supports using the stability mode as a representation-level diagnostic: it highlights where algebraically equivalent JSON structures differ in numerical conditioning even when the ordinary double-precision evaluator returns matching values.

Bibliography

- [1] J. J. Aguilera-Verdugo et al., algorithmic multiloop LTD construction, arXiv:1906.06138.
- [2] Z. Capatti et al., causal/CFF representation construction, arXiv:2211.09653.
- [3] Z. Capatti et al., further CFF representation and box examples, arXiv:2311.14374.
- [4] cLTD and gammaLoop implementations, <https://github.com/alpha100p/cLTD> and <https://github.com/alpha100p/gammaloop>.