

GammaLoop

Differential cross-sections with Local Unitarity

1 Overview

GammaLoop is alpha-stage research software that computes numerical amplitude integrands and uses Local Unitarity for differential partonic cross sections. Its current external-kinematics path uses fixed momenta and a unit PDF factor; it does not yet provide hadronic PDF convolution or a factorization scale. Begin with the [physics scope](#) and [method](#) before translating a desired collider observable into a run card.

The primary manual path is written for perturbative-QFT and collider physicists. GammaLoop is an application rather than a thin numerical library: model import, process generation, integrand construction, integration, observables, persistence, and diagnostics meet in one stateful workflow. Rust and Python details become relevant only when structured automation is needed.

Primary interface

The command-line interface is the primary user interface. A run card creates a state, executes commands, and leaves a reusable working directory. The Rust and Python APIs load the same persisted state and expose selected structured operations; they do not define a second, independent execution model.

1.1 Choose a task

- To build or install the CLI and evaluate a compact one-loop scalar graph, follow the [command-line guide](#).
- To decide whether an initial state, contribution, mass/spin choice, subtraction, and observable are supported, read [physics scope](#) and [Local Unitarity](#).
- To define momentum flow, helicity and color ownership, flux, units, and sample weights, use the [scientific conventions](#).
- To follow a maintained run card through the complete persistence lifecycle, use the [first-state tutorial](#).
- To adapt a process specification or generation filters, use the [process-generation guide](#) with the [generated generate reference](#).
- To inspect and edit a diagram before rendering it, use the live notebook in [GammaLoop DOT input](#).
- To inspect concrete cut events, selectors, and histogram snapshots without a full integration, follow the [events and observables guide](#).
- To automate a loaded state or diagnose a long run, choose the [Rust/Python interface guide](#) or [logging and diagnostics guide](#).

1.2 A stateful run

A typical source checkout is built and exercised from the repository root:

```
just build-cli-release
./gammaLoop ./examples/cli/gg_hhh/1L/gg_hhh_1L.toml
```

The run card imports a model, generates the requested process, executes its command blocks, and records the resulting state. Resume that directory explicitly for subsequent work:

```
./gammaLoop -s ./examples/cli/gg_hhh/1L/state \  
run integrate_physical -c "quit -o"
```

The persisted `run.toml` records how to replay the run. The settings files describe global and default runtime configuration, while `processes/` contains process-specific state. Ordinary runs create `gammaloop_state/` unless a different state path is supplied.

A lifecycle example is not a physics benchmark

The maintained `gg_hhh` card is useful because it exercises model loading, generation, integration settings, and persistence. It selects a fixed-helicity amplitude contribution with an explicit color projector; running it does not by itself produce an unpolarized, color-averaged cross section or validate a published observable.

1.3 Installation and external tools

For ordinary CLI use, begin with using [GammaLoop](#) from the command line. It recommends the packaged Nix application when Nix is available, but does not require it: a copy-and-paste Cargo route is provided for a standard Rust toolchain. Neither installation path requires a source checkout.

A source checkout is still needed to change [GammaLoop](#) or to work through repository-owned run cards. Its supported development path is the repository's Nix shell, or a local Rust toolchain together with `just`, a recent GNU toolchain, and Python 3.11 or newer when building bindings. FORM 4.2.1 or newer is needed for analytical integration of integrated UV counterterms. UFO model import also needs the Python `ufo-model-loader` package.

Diagram rendering is a separate concern and uses [Clinnet](#) and [Typst](#). Building the CLI does not imply that these drawing tools are installed. Use the [Clinnet DOT-rendering guide](#) for their independent versions, templates, and cache boundary.

1.4 Related crates

How the crates fit together

[Linnet](#) provides the half-edge graph model and graph algorithms. [Spenso](#) provides typed tensors, tensor structures, and network execution. [Idenso](#) handles symbolic tensor identities and algebraic simplification. [Vakint](#) matches and evaluates vacuum-integral topologies. [GammaLoop](#) combines these components into a collider-calculation workflow.

For a deeper view of how the command layer, state, integrands, and external components fit together, see the [GammaLoop implementation architecture](#).

1.5 Where to begin

- Use built-in `--help` for the CLI options supported by your installed version.
- Start with the included `gg_hhh` run card for a complete state lifecycle, not as a substitute for a physical normalization and validation plan.
- Record the method scope and every factor from the [normalization checklist](#) before launching a production run.
- Use the Rust or Python API only when a program needs structured access to loaded state or sample-evaluation results.
- Check prerequisites before starting an expensive integration; some workflows require a Symbolica license or external tools such as FORM.

2 Your first GammaLoop calculation

Generate the same scalar one-loop bubble through the interface that fits your work. Every route uses [GammaLoop](#)'s built-in scalar model, disables integrated UV generation, and evaluates the same three-dimensional loop-momentum point. The result is a compact software check rather than a normalized collider prediction.

Command line

Use the executable for run cards, interactive commands, persistent states, and complete calculations. This is the shortest route for most GammaLoop users.

Use GammaLoop from the command line →

Python

Use the stateful Python API from notebooks, scripts, or workflow automation. It drives the same command session and returns structured evaluation records.

Use GammaLoop from Python →

Rust

Embed GammaLoop when a Rust application must own the state lifecycle, issue commands, or retain typed evaluation results without crossing a Python boundary.

Use GammaLoop from Rust →

If you are unsure, begin with the [command-line guide](#). The [interface guide](#) explains the longer-term ownership and precision boundaries once the first calculation works.

3 Using GammaLoop from the command line

This guide builds one scalar one-loop topology, saves it as a GammaLoop state, and evaluates one point. It uses a built-in model and does not require a run card, a UFO model, or FORM. Once the executable is available, the example itself takes only a few seconds.

3.1 Get the CLI

Nix is recommended, not required

If you already use Nix, or want the most reproducible installation, follow the first route. Otherwise skip directly to the Cargo route below. Both routes provide the same `gamma-loop` command, and neither requires a GammaLoop source checkout.

3.1.1 Recommended: the Nix package

The repository flake exposes GammaLoop as a packaged application. Install that package directly; a source checkout and development shell are not required:

```
nix profile add github:alphal00p/gamma-loop#gamma-loop
gamma-loop --help
```

Nix downloads the package from a configured binary cache when it is available and otherwise builds the same derivation locally. The flake currently supports x86-64 and ARM64 Linux, plus Apple-silicon macOS.

To try the same packaged CLI without adding it to your profile, run:

```
nix run github:alphal00p/gamma-loop#gamma-loop -- --help
```

Use `nix run .#gamma-loop -- --help` instead when testing the package from an existing source checkout. `nix develop` followed by `just build-cli` remains useful for contributors changing GammaLoop, but it is not the normal installation path.

3.1.2 No Nix: install with Cargo

Install a stable Rust toolchain with `rustup`, then install the small set of native build tools used by GammaLoop. On Debian or Ubuntu:

```
sudo apt-get update
sudo apt-get install -y build-essential m4 diffutils
```

On macOS, install Apple's command-line build tools if they are absent:

```
xcode-select --install
```

Then install the `gamma-loop-api` crate. Its executable is named `gamma-loop`:

```
SYMBOLICA_OEM_LICENSE=SYMBOLICA_OEM_GAMMALOOP \
cargo install --locked gamma-loop-api
gamma-loop --help
```

This registry command becomes available with the first automated crates.io release. Until then, install the release candidate directly from its tested Git revision, without making a checkout:

```
SYMBOLICA_OEM_LICENSE=SYMBOLICA_OEM_GAMMALOOP \
cargo install --locked \
--git https://github.com/alphal00p/gamma-loop.git \
--rev eb1dab23c24345def88226ef10874f0dde6c4aa5 \
gamma-loop-api
```

Cargo compiles the CLI locally, so its first installation takes longer than downloading a cached Nix build. Its default build vendors the required GMP, MPFR, and MPC sources; OpenSSL, Python, FORM, and system copies of those libraries are not prerequisites for this example. On Windows, use WSL 2 and follow the Debian or Ubuntu instructions above. The `SYMBOLICA_OEM_LICENSE` value is GammaLoop's public build selector, not a private license key. Add the `ufo_support` feature and Python development headers only when external UFO model loading is needed. Symbolica's license terms still apply to both installation paths.

Cargo install is Nix-free, but it is still a source build

The current release workflow publishes crate sources and Python distributions, but not target-specific GammaLoop CLI archives or Cargo Binstall metadata. `cargo binstall` therefore cannot yet provide a supported prebuilt binary and may only fall back to a source build.

3.2 Generate a one-loop graph

Users who installed the Nix package or Cargo crate can run this command as written. Contributors using just `build-cli` in a source checkout should replace `gamma-loop` with `./gamma-loop`:

Choose a disposable state path

`--clean-state` removes and replaces the state directory passed with `-s`. Use the fresh `./gamma-loop_state/quickstart` path shown below, or substitute another path whose existing contents you are prepared to delete.

```
gamma-loop --clean-state -s ./gamma-loop_state/quickstart run -c \
'import model scalars-default.json; set global kv
global.generation.uv.generate_integrated=false; generate amp scalar_1 > scalar_1 [{1}] --
allowed-vertex-interactions V_3_SCALAR_122 -p bubble -i one_loop; display processes; quit -
o'
```

The command imports the built-in scalar model, generates one one-loop bubble amplitude, prints the process named bubble and integrand named one_loop, and writes a reusable state under gammaloop_state/quickstart/. Integrated UV generation is disabled deliberately so that this first topology does not invoke FORM.

Check the result by looking for bubble and one_loop in the process listing and for gammaloop_state/quickstart/state_manifest.toml. This graph is a compact software exercise, not a normalized collider prediction.

3.3 Evaluate one point

Load the state read-only and inspect the integrand at one loop-momentum point:

```
gammaloop --read-only-state -s ./gammaloop_state/quickstart run -c \  
'inspect -p bubble -i one_loop -x 0.1 0.2 0.3; quit'
```

A successful run prints the parameterization Jacobian and a finite complex value without changing the saved state. Continue with the [first-state tutorial](#) to use a maintained run card, inspect the complete persistence lifecycle, and prepare a calculation whose physics scope and normalization are explicit.

4 Using GammaLoop from Python

This route generates the same scalar bubble as the command-line example, but keeps the session in a Python object and returns a structured evaluation result. Use Python 3.11 or newer.

4.1 Install the Python package

Create an isolated environment. The ordinary wheel command targets the automated 0.3.4 release and newer:

```
python3.11 -m venv .venv  
. .venv/bin/activate  
python -m pip install --upgrade pip  
python -m pip install "gammaloop>=0.3.4"
```

Until that release is visible on PyPI, build the current package from a source checkout instead:

```
git clone https://github.com/alphal00p/gammaloop.git  
cd gammaloop  
python3.11 -m venv .venv  
. .venv/bin/activate  
python -m pip install .
```

The Python library does not activate the CLI's OEM license. Set SYMBOLICA_LICENSE to your user license when running Python; no OEM selector is needed to build the library.

4.2 Generate and evaluate

Save this as first_gammaloop.py:

```
from pathlib import Path  
from tempfile import TemporaryDirectory  
  
from gammaloop import GammaLoopAPI  
  
with TemporaryDirectory() as temporary:  
    api = GammaLoopAPI(state_folder=Path(temporary) / "state")  
    api.run("import model scalars-default.json")  
    api.run(  
        "set global kv "  
        "set global kv "
```

```

        "global.generation.uv.generate_integrated=false"
    )
    api.run(
        "generate amp scalar_1 > scalar_1 [{1}] "
        "--allowed-vertex-interactions V_3_SCALAR_122 "
        "-p bubble -i one_loop"
    )

    result = api.evaluate_sample(
        [0.1, 0.2, 0.3],
        process_id=0,
        integrand_name="one_loop",
    )
    print(result.integrand_result)

```

Run `python first_gammaploop.py`. A successful execution prints a finite complex value. The temporary state is deleted when the script exits; use a normal directory when the state should be persisted and explicitly execute a `save` command before closing the session.

One session owns one mutable state

`GammaLoopAPI.run` acts on the same in-memory model, settings, processes, and history as the structured methods. The object does not save automatically. Use separate instances for independent calculations, and inspect the [interface guide](#) before building a long-running workflow around mutable state.

The documentation harness syntax-checks this script. Runtime execution additionally needs the native wheel or source build and a Symbolica license mode appropriate for the user.

5 Using GammaLoop from Rust

Embed GammaLoop when a Rust program should own the state, command session, and typed evaluation result directly. This example generates the same scalar bubble as the CLI and Python routes.

5.1 Create a project

The ordinary `crates.io` command becomes available with the automated 0.3.4 release:

```

cargo new first-gammaploop
cd first-gammaploop
cargo add gammaploop-api@0.3.4 ndarray@0.17 eyre@0.6

```

Before that release, replace the `gammaploop-api` line with the tested release revision:

```

cargo add gammaploop-api \
    --git https://github.com/alphal00p/gammaploop.git \
    --rev eb1dab23c24345def88226ef10874f0dde6c4aa5
cargo add ndarray@0.17 eyre@0.6

```

5.2 Drive one state and evaluate it

Replace `src/main.rs` with:

```

use eyre::Result;
use gammaploop_api::{
    commands::evaluate_samples::{evaluate_sample, EvaluateSamples},
    state::CommandHistory,

```

```

        StateLoadOption,
    };
    use ndarray::arr2;
    use std::time::{SystemTime, UNIX_EPOCH};

    fn main() -> Result<()> {
        let nonce = SystemTime::now().duration_since(UNIX_EPOCH)?.as_nanos();
        let state_folder = std::env::temp_dir().join(format!("gammaLoop-quickstart-{}", nonce));
        let mut loaded = StateLoadOption {
            state_folder: Some(state_folder.clone()),
            ..StateLoadOption::default()
        }
        .load()?;

        for raw in [
            "import model scalars-default.json",
            "set global kv global.generation.uv.generate_integrated=false",
            concat!(
                "generate amp scalar_1 > scalar_1 [{1}] ",
                "--allowed-vertex-interactions V_3_SCALAR_122 ",
                "-p bubble -i one_loop"
            ),
        ] {
            let command = CommandHistory::from_raw_string(raw)?;
            let _ = loaded.cli_session().execute_command(command)?;
        }

        let point = arr2(&[[0.1, 0.2, 0.3]]);
        let result = evaluate_sample(
            &mut loaded.state,
            &EvaluateSamples {
                process_id: Some(0),
                integrand_name: Some("one_loop".into()),
                use_arb_prec: false,
                minimal_output: false,
                return_generated_events: None,
                momentum_space: false,
                points: point.view(),
                integrator_weights: None,
                discrete_dims: None,
                graph_names: None,
                orientations: None,
            },
        )?;

        println!("{result}");
        std::fs::remove_dir_all(state_folder)?;
        Ok(())
    }

```

Compile and run with your Symbolica user license available through `SYMBOLICA_LICENSE`. Embedding the Rust API does not activate the GammaLoop CLI's OEM license:

```
cargo run
```

The facade owns the supported embedding boundary

Prefer `StateLoadOption`, `CliSession`, and the typed request objects from `gammaLoop-api`. `gammaLoop-prs`

exposes lower-level implementation types, but their presence in Rustdoc is not a stability promise. The [interface guide](#) maps the supported workflow to the complete Rust reference.

The docs harness compiles this source against the current workspace. Running it additionally requires the native toolchain and a Symbolica license mode appropriate for the user.

6 Physics scope and Local Unitarity

GammaLoop is alpha-stage research software for perturbative quantum-field-theory calculations. Its present, demonstrable calculation path is partonic: it constructs amplitude integrands and uses Local Unitarity forward-scattering representations for differential cross sections, then evaluates or integrates selected contributions. It is not currently a general hadron-level event generator or a promise that every process allowed by a model is numerically supported.

Intended reader

This chapter is for physicists deciding whether GammaLoop is appropriate for a calculation. The command-line workflow requires no Rust knowledge. Read the [kinematics](#) and [normalization contract](#) before interpreting a value, and treat compiled loop-count limits as software bounds rather than demonstrated perturbative reach.

6.1 What Local Unitarity changes

At fixed perturbative order, a conventional calculation separates real-emission and virtual contributions even though their infrared singularities cancel only in the sum. The Local Unitarity representation uses Loop-Tree Duality for each forward-scattering graph to express those degrees of freedom on common integration variables. Contributions that approach the same soft or collinear configuration can then cancel locally, before a Monte Carlo integral relies on cancellations between separately integrated numbers.

The defining [Local Unitarity paper](#) proves this representation for processes without initial-state collinear singularities and introduces local ultraviolet counterterms. The [raised-propagator and local-renormalization paper](#) extends the formalism with distributional cutting rules and a local R-operation treatment. Those are statements about the method. A method valid at arbitrary perturbative order is not evidence that this release implements every order, process, initial state, or renormalization choice.

For one Monte Carlo point, GammaLoop can produce several cut or counterterm contributions in one or more correlated event groups. The observable layer commits the complete group list as one statistical sample. Treating the members as independent events would discard the local-cancellation relation and underestimate correlations.

6.2 Capability envelope in this release

The labels below are deliberately conservative:

- **Supported** means an explicit implementation path was identified; it does not certify every process or numerical regime.
- **Conditional or experimental** means feature-, backend-, model-, or workflow-dependent.
- **Unsupported** means the accepted value reaches a placeholder, explicit error, or panic.
- **Unverified** means the source does not justify a public scientific guarantee.

Area	Classification	Current boundary
Calculation objects	Supported, scoped	Amplitude integrands and forward-scattering cross-section integrands are generated. Numerical support must still be established for the selected topology and contribution.
Initial states and PDFs	Partonic only	The current external kinematics are fixed momenta and helicities, with a PDF factor of one. There is no PDF convolution or

Area	Classification	Current boundary
		factorization scale. The built-in flux path supports exactly one or two incoming particles.
Orders and selectors	Conditional filters	{n} constrains an amplitude graph's loops or the sum on two cut sides, while {{n}} constrains forward-graph loops. Outside the bracketed block, unpowered constraints populate the amplitude filter and powered constraints populate the cross-section filter, whose exponent is currently discarded. Bracketed named orders bound model-resolved additional cut content on the cross-section path. These mechanisms are not interchangeable and do not provide a universal LO/NLO/NNLO mapping.
Models	Conditional	Built-in Standard Model, scalar, and scalar-gravity JSON models are available; other JSON models can be imported. UFO import requires the optional Python-backed feature and its loader.
External polarizations	Scoped	Automatic sums are implemented for scalar, spinor, and vector states, with Feynman or light-like axial gauge for vectors. Higher-spin polarization replacement is unsupported.
Masses and widths	Real masses only	Real masses enter evaluation. Complex masses are unsupported. Width names are model metadata, but no finite-width or complex-mass scheme was verified.
Subtraction and renormalization	Conditional or experimental	Local UV settings and several vacuum-integral backends exist. Threshold subtraction is experimental, and the physical meaning of every exposed prescription still needs a method-author review.
Integration components	Scoped	Real and imaginary components can be integrated separately. The accepted both setting is not implemented.
Observables	Supported; requires user validation	Particle and jet quantities, selectors, histograms, and kT-family clustering are available. GammaLoop does not establish the infrared and collinear safety of an arbitrary user-defined observable.
Licenses and tools	Conditional	The Rust crates use MIT or Apache-2.0 terms, while Symbolica has separate license conditions. FORM, vacuum-integral backends, UFO import, and drawing tools have independent availability requirements.

6.3 Decide whether a calculation is in scope

Before generating graphs, write down these physics choices outside the run card:

1. Is the requested quantity partonic with fixed external kinematics, or does it require PDFs, a factorization scale, beam structure, or more than two incoming particles?
2. Is it an amplitude or a differential cross section, and which exact graph, loop, cut, and coupling-order filters define the requested contribution?
3. Does the active model use only supported external spins and real masses? If a width is physically essential, do not infer a finite-width scheme from imported metadata.
4. Which spin and color sums or averages, projectors, flux, symmetry factors, and units belong in the normalization? Record them using the [conventions checklist](#).
5. Is the observable infrared and collinear safe for the selected real/virtual combination? This is a physics precondition, not an automatic validation step.
6. What maintained limit, independent implementation, or published number will be used to validate the result and its Monte Carlo uncertainty?

Method scope versus software evidence

The first-state tutorial proves that a model, generated integrand, settings, and persisted state fit together; it does not validate a physical cross section. Use the partonic cross-section regression card and the scalar-topology targets as concrete implementation sources to inspect. The former still uses a powered selector whose exponent is not enforced, so it is not an audited perturbative-order or normalization exemplar. Publish a number only after recording its contribution definition, normalization, convergence, and an independent comparison.

7 Kinematics, normalization, and weights

This page assembles the source-verifiable scientific conventions needed to interpret a GammaLoop sample. It intentionally separates factors supplied by the runtime from factors that remain the physicist's responsibility. Where the implementation does not establish a universal convention, the text says so instead of filling the gap from customary notation.

7.1 Four-vectors and momentum flow

External four-vectors use component order (E, p_x, p_y, p_z) and metric signature $g = \text{diag}(+1, -1, -1, -1)$, so

$$p \cdot q = E_p E_q - (p_x q_x + p_y q_y + p_z q_z), \quad p^2 = E^2 - p_x^2 - p_y^2 - p_z^2.$$

Stored external momenta are physical, normally positive-energy vectors. A separate process signature marks a particle as initial or final; GammaLoop does not require the user-facing list to store every final momentum with a minus sign. When one momentum is dependent, it is reconstructed to satisfy

$$\sum_i^{\text{initial}} p_i - \sum_j^{\text{final}} p_j = 0.$$

The runtime field `e_cm` is a construction and normalization scale. If it is omitted for fixed momenta, the current fallback is the mean absolute value of their nonzero components, not a physical reconstruction of $\sqrt{s}$. Supply `e_cm` explicitly whenever its physical meaning matters.

7.2 Helicity and polarization

Fixed external helicities use `-1`, `0`, or `+1`. Zero is the physical and documented convention for a scalar card, but the current evaluator ignores rather than enforces a scalar's helicity. The automatic external-momentum generator currently assigns `+1` to every external entry; that is a fixed-polarization default, not an unpolarized calculation.

Use `summed` for a polarization sum and `summed_averaged` for the same replacement with the implemented spin-state average. The setting acts on every external entry explicitly marked that way; incoming particles are not averaged merely because they are incoming. Implemented averaging factors are `1` for a scalar, `1/2` for a spinor, `1/2` for a massless vector, and `1/3` for a massive vector. Automatic higher-spin polarization sums are unsupported.

Color is a separate normalization decision

No general automatic incoming-color average was identified. A maintained calculation may supply a color projector or global prefactor explicitly. Record that choice rather than assuming that `summed_averaged` includes color.

7.3 Flux and reporting units

With the flux factor enabled, the implemented one-incoming-particle factor is

$$F_{1 \text{ in}} = \frac{1}{2E},$$

and the implemented two-incoming-particle factor is

$$F_{2\text{ in}} = \frac{1}{4\sqrt{(p_1 \cdot p_2)^2 - m_1^2 m_2^2}}.$$

Zero or three-or-more incoming particles are not implemented by this default path. Reporting units resolve to pb, fb, ab, mb, or none; auto selects picobarns for more than one incoming particle and no conversion otherwise. The fixed factor $3.89379372171859 \times 10^8$ relative to picobarns is applied only by the two-incoming-particle flux branch. The one-incoming-particle branch returns $F_{1\text{ in}}$ without a reporting-unit conversion. Disabling the flux factor also bypasses the conversion branch.

The code describes input scales as model energy units, while the fixed picobarn conversion is the usual natural-unit form associated with GeV. Until the energy-unit premise is made an explicit model contract, do not claim that arbitrary model units convert correctly to pb.

7.4 From an integrand value to a Monte Carlo sample

For the public sample-evaluation contract, the exact weighting relation is

$$w_{\text{sample}} = I_{\text{returned}} J_{\text{parameterization}} w_{\text{MC}}.$$

`integrand_result` is the returned integrand before the parameterization Jacobian, and `integrator_weight` excludes that Jacobian. During integration, GammaLoop first multiplies by the parameterization Jacobian and then applies the Monte Carlo sample weight. For a cross section, the returned integrand already contains the enabled flux and reporting-unit factor.

An event group may retain an original contribution, threshold counterterms, and one full multiplicative factor. Its implemented reconstruction is

$$w_{\text{event}} = \left(w_{\text{Original}} + \sum_i w_{\text{CT},i} \right) w_{\text{FullMultiplicativeFactor}}.$$

All groups originating from one Monte Carlo point are combined before one statistical sample is committed to a histogram bin. They are correlated contributions, not independent events. The `events` and `observables` guide shows the corresponding Python and Rust records.

7.5 Normalization ownership checklist

Factor	Usual owner here	What to record
Polarization sum and spin average	Run card	The explicit helicity mode for every external particle and the vector gauge choice.
Color sum or average	Physicist / projector	The projector or prefactor and its normalization; do not infer a universal automatic average.
Graph multiplicity and signs	Generated graph factor	Automorphism, fermion-loop, external-ordering, and grouping contributions visible in the generated state.
Flux and output units	Runtime when enabled	Incoming momenta and masses, the selected unit, and whether the flux branch was disabled.
Parameterization Jacobian	Integration driver	The parameterization and whether a reported value is before or after its Jacobian.
Monte Carlo weight	Integrator	The sample weight, seed, component, and correlation boundary.
Subtraction contributions	Correlated event group	Original and counterterm weights, signs, and the common multiplicative factor.

Factor	Usual owner here	What to record
Overall physical normalization	Calculation definition	Any remaining coupling, projector, color, symmetry, phase-space, or conventional factor used for comparison.

Generated graph factors retain several combinatorial and fermionic contributions, but the source audit did not establish one universal statement that these plus a chosen projector form the complete physical symmetry and averaging factor for every process. Inspect the generated factor and write the full normalization used by the comparison calculation.

7.6 Scales and scheme names

Keep these settings distinct:

- `mu_r` is the renormalization scale and enters the parameter set as its square;
- `m_uv` is a UV reference mass;
- `renormalization_localization_scale` controls localization of local UV counterterms;
- MUV, PolePart, OS, IR, Unsubtracted, and VacuumLimit are accepted local-counterterm prescription names whose full physical definitions still require a method-author contract; OS, IR, and VacuumLimit reach explicit unimplemented paths in at least one current counterterm evaluator; and
- Vakint's default `MSbar` choice describes its vacuum-integral normalization and must not be used as a synonym for GammaLoop's MUV prescription.

No factorization scale belongs to the current fixed-partonic external-kinematics path.

7.7 Terms that are easy to overload

- A **GammaLoop state** is the persisted calculation workspace, not a quantum state and not an integration checkpoint.
- An **integration workspace** owns resumable Monte Carlo iterations for selected (`process`, `integrand`) slots; its summary JSON is not the authoritative checkpoint.
- An **integration coordinate** is a parameterization coordinate unless `momentum_space` is explicitly selected, in which case each loop momentum is a flattened (`p_x`, `p_y`, `p_z`) triplet.
- A **target** is a comparison value used to report a delta. It is not the relative or absolute accuracy that stops integration.
- An **event group** contains correlated contributions from one Monte Carlo point. A **graph group** is a generation-time grouping of related graphs and multiplicity/numerator factors; the two are not interchangeable.

Conventions not yet established as universal contracts

Before publishing a result, obtain an explicit calculation-level statement for all 2π , i , sign, contour, and phase-space-measure factors; overall amplitude and cross-section normalization; color sums and averages; remaining symmetry factors; powered coupling constraints; the LO/NLO meaning of graph filters; finite-width treatment; and the selected renormalization prescription. The current source does not justify silently supplying any of these from convention alone.

The `e+ e- partonic regression card` is useful for tracing implemented factors, but it is not yet a normalization exemplar: its powered selector exponent is not enforced. For any audit, record the model, contribution filters, helicities, projectors, runtime settings, observable definition, and independently reviewed perturbative-order definition.

8 Tutorial

This tutorial builds the GammaLoop command-line interface and uses the included one-loop `g g -> h h h` run card to create a state that can be inspected and resumed. Compilation and process generation can take longer than a `--help smoke` test.

For the shortest installation and first-run path, begin with [Using GammaLoop from the command line](#). Then return here to create, inspect, and resume the larger bundled example.

What this example establishes

The card selects one fixed-helicity, one-loop amplitude contribution and supplies an explicit 1/8 color projector. It demonstrates software state creation, inspection, and resumption; it is not an unpolarized, automatically color-averaged cross section. Read the [method and capability boundary and normalization conventions](#) before interpreting either integration block as a physical result.

8.1 Prerequisites

Work from a GammaLoop source checkout. The supported development environment is the repository Nix shell; without Nix you need Rust 1.85 or newer, just, a recent GNU toolchain, and the dependencies described in the root README. The bundled Standard Model used below does not need the UFO loader. A Symbolica license may be required by your build and use case.

```
nix develop
just build-cli
./gammaLoop --help
```

The last command should print the one-shot CLI options and command tree. The `./gammaLoop` wrapper selects the binary built under `target/dev-optim/`.

Verification scope and cost

The docs harness checks these shell blocks for syntax; it does not build or execute GammaLoop. Verify a clean checkout manually in `nix develop`. A cold CLI build and process generation are the high-resource path and can take tens of minutes, while reopening a valid state is normally much cheaper. The invariant for this tutorial is a resumable state with the files listed below, not a completed Monte Carlo integration.

8.2 Generate an example process

The run card declares a state folder, settings, and named command blocks. Run its generate block and persist the result on exit:

```
./gammaLoop --clean-state \
./examples/cli/gg_hhh/1L/gg_hhh_1L.toml \
run generate -c "quit -o"
```

--clean-state removes the resolved state first

Use it only for this first, reproducible run. Omit it when resuming work you want to keep. Its generated argument reference records the exact valueless-flag semantics. The example card resolves its state to `examples/cli/gg_hhh/1L/state` and requests ten worker cores; make a private copy of the card before changing either value.

The block imports `sm-default.json`, generates the selected one-loop pentagon amplitude contribution, applies the card's explicit helicity and color choices, builds its integrand, saves DOT data, and writes the state. A successful run exits without an error and leaves at least `run.toml`, `global_settings.toml`, `default_runtime_settings.toml`, and `processes/` in the state folder. `run.toml` records the commands and settings needed to replay the run; it is not merely a log file.

Use GammaLoop DOT input to inspect a diagram interactively or render the exported drawing bundle with `just draw`.

8.3 Resume the saved state

Load the saved state and ask the active session to display its processes:

```
./gammaloop -s ./examples/cli/gg_hhh/1L/state \  
run -c "display processes; quit -o"
```

Success means the display includes the generated `gg_hhh` process and the command exits while keeping the same state. You can now run the card's `integrate_euclidean` or `integrate_physical` block, but those are deliberately beyond the first-success path because they request a substantial Monte Carlo integration and require a separate normalization and validation plan.

8.4 Inspect before expensive work

Reopen the state read-only and inspect both the generated structure and the effective integrator settings before launching either integration block:

```
./gammaloop --read-only-state \  
-s ./examples/cli/gg_hhh/1L/state \  
run -c "display integrand -p gg_hhh -i 1L; display settings process -p gg_hhh -i 1L  
integrator; quit"
```

`display integrand` reports the generation backend, compiled record size, graph and graph-group counts, and detailed orientation, loop-momentum-basis, cut, and threshold tables. The settings command resolves the values attached to this generated integrand, which may differ from the current defaults. Check these records together: an unexpected graph count points back to process generation, while an unexpected sample budget, target accuracy, or seed belongs to runtime settings.

Read-only inspection is not persistence

`--read-only-state` prevents commands from writing inside the active state directory and disables file logging there. It does not make the in-memory session immutable. This command intentionally exits without `-o`; change settings in a separate writable session or in the run card that reconstructs the state.

The exact fields and selectors are kept current in the generated integrand `display` and `process-settings` references.

8.5 Troubleshooting and next steps

- If the wrapper cannot find a binary, rerun `just build-cli` and confirm that `target/dev-optim/gammaloop` exists.
- If compilation or process generation exhausts local resources, copy the card and reduce the values under `cli_settings.global.n_cores`; do not edit a state midway through generation.
- If startup reports a state fingerprint or settings mismatch, replay the card with a new state folder instead of transplanting only its `processes/` directory.
- Use `./gammaloop help generate` to inspect the flags supported by your installed version, then continue with the process-generation guide and the `generate-command` reference.

Example run card

See the complete `gg_hhh` run card before adapting the process, state location, or resource settings for your own calculation.

9 Process generation and state workflows

GammaLoop describes a calculation with a TOML run card and stores its reusable state in a directory. Start the command-line interface through the repository wrapper (`./gammaloop`) or the Cargo-built executable, then generate processes, integrands, and integration jobs within that state.

9.1 Choose a generation mode

The interactive command tree separates cross sections, amplitudes, and operations on processes already stored in the active state:

```
generate xs INITIAL > FINAL ...
generate amp INITIAL > FINAL ...
generate existing ...
generate help xs
```

`xs` constructs forward-scattering graphs and filters compatible Cutkosky cuts. `amp` constructs ordinary amplitudes. Their final-state lists therefore have different meanings even when the printed particle syntax is identical. Use the GammaLoop DOT input guide when preparing or reviewing imported graph files. Use `generate help <mode>` inside the stateful CLI to see the flags supported by your installed version.

9.2 Process specification grammar

Process specifications accept `to` or `>` between space-separated initial and final states. Braces express alternatives in a cross-section final state, while `{}` denotes an empty state:

```
e+ e- > mu+ mu-
e+ e- > { Z Z, a a, H H }
{} > {}
```

The empty-initial-state form is generation grammar, not evidence that the default cross-section flux evaluator supports a zero-incoming-particle calculation. Its implemented flux branches require exactly one or two incoming particles.

A slash vetoes particles and a vertical bar selects an allow-list. The words `veto` and `only` are equivalent forms. Outside the bracketed perturbative block, coupling constraints use the active model's coupling-order name:

```
e+ e- > d d~ g / u c QED==2 QCD>=2 QCD<=4
e+ e- > mu+ mu- | g ghG QED==2 QCD>=2
```

Powered and unpowered constraints are not interchangeable

An unpowered spelling such as `QCD==2` builds an amplitude-side coupling-order filter. A powered spelling such as `QCD^2==2` builds a cross-section-side coupling-order filter, but the parsed exponent is currently discarded. Substituting one spelling for the other changes which filter container is used and still does not define a squared amplitude or a complete cross-section order. Production work therefore needs a scientifically reviewed selector set; do not infer one from the spelling alone.

The bracketed perturbative block is intentionally distinct from ordinary flags. For `amp`, `{n}` fixes the amplitude graph's loop count; for `xs`, it fixes the sum of loop counts on the two cut sides. `{{n}}` fixes the forward graph's loop count. On a cross-section process, bracketed `QCD=n` or the shorthand `QCD` resolves the model's unresolved-particle set and permits at most the summed requested count of additional cut particles from those sets; it is not an exact graph coupling power. No corresponding amplitude-side selection effect has yet been established for that bracketed named-order spelling:

```
e+ e- > Z [ {1} {{2}} QCD=2 QED=1 ]
e+ e- > Z [ QCD ]
```

These selectors are generation filters, not universal definitions of LO, NLO, or NNLO. Record the amplitude-side loops, forward loops, unresolved-cut allowance, and coupling filters explicitly for the chosen generation mode; use the [physics-scope guide](#) to distinguish that calculation definition from the formal perturbative reach of Local Unitarity.

Resolve names through the active model

Particle names, antiparticles, coupling-order names, and allowed interactions come from the model loaded in the current state. A syntactically valid specification can still be rejected when that model does not define a requested name.

9.3 Filters, grouping, and multiplicity

Generation flags control topology filters, loop ranges, cut blobs and spectators, symmetrization, and numerator-aware grouping. These choices are physics-significant. In particular, grouping can combine graph multiplicities and numerator ratios; external-fermion symmetrization requires the caller to retain the associated ordering signs. Run `generate help <mode>` before choosing filters to see the available aliases, defaults, values, and argument counts.

The generated graph's overall factor keeps separate contributions for automorphisms, internal fermion loops, external-fermion ordering, numerator-independent symmetry grouping, and numerator-dependent grouping. It does not establish a universal incoming-color average. Persist the state and inspect that factor together with any explicit projector when auditing diagram normalization instead of replacing it with an assumed factorial; the [normalization checklist](#) assigns each factor to its owner.

9.4 A maintainable generation card

The following reduced card uses the repository's scalar model and the same one-loop bubble command exercised by the maintained scalar-topology example. Save it as `manual-bubble.toml` and run `./gammaLoop --clean-state manual-bubble.toml run generate -c "quit -o"` from the repository root.

```
commands = []

[cli_settings.state]
folder = "./gammaLoop_state/manual-bubble"
name = "manual_bubble"

[[command_blocks]]
name = "generate"
commands = [
  "import model scalars-default.json",
  "generate amp scalar_1 > scalar_1 [{1}] --allowed-vertex-interactions V_3_SCALAR_122 -p",
  "bubble -i scalar_bubble",
  "generate",
  "save state -o",
]
```

The acceptance invariant is a persisted state in which `display` processes identifies process bubble and integrand scalar_bubble; replaying the card with a clean destination must produce the same named objects. The exact command and setting semantics are linked from the [amplitude-generation reference](#), [state-persistence reference](#), and [state-folder setting](#). The full maintained source is the [scalar bubble run card](#).

Interpret the first failing stage

An unknown particle or `V_3_SCALAR_122` error means the scalar model was not imported or no longer exposes that interaction. A process with no retained diagram points to the process specification or generation filters. A generated process that disappears after restart means `save state -o` did not complete or the resumed `-s` path differs from `cli_settings.state.folder`.

9.5 From generation to evaluation

A reproducible run keeps its stages explicit:

- import or select the model before resolving a process specification;
- generate the process and inspect the retained diagrams;
- generate the requested integrand representation;
- set kinematics, sampling, stability, and subtraction settings;
- evaluate samples or run an integration command block;
- exit with persistence enabled when the state should be resumed.

9.6 Select integration slots and targets

An integration slot is one (process, integrand) pair. Repeat `-p/--process` and `-i/--integrand-name` in matching order to integrate several slots together. By default those slots train and sample a shared grid, so their sample shapes must be compatible; add `--uncorrelated` when each slot needs an independent grid.

A single `--target re im` (or `--target re,im`) applies the same known comparison value to every selected slot. Multi-slot runs can instead use one keyed value per slot:

```
integrate \  
-p bubble_no_integrated_UV -i scalar_bubble_below_thres \  
-p bubble -i scalar_bubble_below_thres \  
--target bubble_no_integrated_UV@scalar_bubble_below_thres=1.471664021721597e-2,0.0 \  
      bubble@scalar_bubble_below_thres=2.7029875684552542e-3,0.0 \  
--workspace-path ./integration/bubble-below-threshold \  
--n-cores 1
```

Targets annotate result deltas; they do not replace `integrator.target_relative_accuracy`, `integrator.target_absolute_accuracy`, or the sample-budget settings that control convergence. The maintained scalar bubble run card contains the complete settings and both below- and above-threshold target sets. The generated integration reference is authoritative for selectors, renderers, batching controls, and allowed values.

9.7 Resume or replace an integration workspace

An integration workspace is a completed-iteration checkpoint, not a second GammaLoop state. Without `--workspace-path`, writable sessions use `STATE_FOLDER/integration_workspace`; read-only sessions use `./integration_workspace_STATE_NAME` (or `./integration_workspace`) so they do not write into the active state.

- Without `--restart`, GammaLoop resumes when the workspace already contains a compatible checkpoint. Slots, shared-versus-uncorrelated sampling, effective model parameters, and generated-integrand fingerprints must match. Saved targets and non-model runtime settings win over changed values and produce a warning.
- With `--restart`, GammaLoop removes that specific workspace and starts the integration from scratch. Use it when changing slots, sampling correlation, generated integrands, or settings that should take effect. It does not mean “resume”.
- `--show-summary-only` reads the last completed result without evaluating more samples and cannot be combined with `--restart`.

The workspace root contains `manifest.json`, the latest user-facing `integration_result.json`, per-slot settings and results under `integrand`s/, and the internal resume checkpoint under `state/integration_state.bin`. Observable resume snapshots live at `state/observables/<process@integrand>/latest.json`. Configured user-

facing output is written per slot as `integrands/<process@integrand>/observables_final.json` or `integrands/<process@integrand>/observables_final.hwu`. `--write-results-for-each-iteration` additionally retains numbered result and observable history at the corresponding root or slot boundary.

Archive the right boundary

`integration_result.json` is a presentation snapshot, not the authoritative resume state. Keep the complete integration workspace when a run must be resumed, and keep the GammaLoop state/run card that produced the referenced integrands. A copied result JSON alone is suitable for analysis, not continuation.

Keep the complete state together

`run.toml` records boot settings, reusable command blocks, and top-level commands. Generated process and integrand artifacts live beside it. Resume with `-s STATE_FOLDER`; replay the run card to reconstruct the state from scratch. Copy or archive the entire state directory rather than moving a generated subdirectory on its own, because settings and fingerprints are checked together.

Contributor-facing ownership and data flow are documented in the [GammaLoop architecture](#) and the [UV renormalization architecture](#).

10 GammaLoop DOT input

GammaLoop imports Feynman graphs from Graphviz digraph files. The generic DOT syntax and parser behavior are covered in [Linnet's DOT input and graph indices](#) this page records GammaLoop's physics contract.

10.1 Explore a DOT diagram

Edit an amplitude or cross-section diagram using the same rendering pipeline as `save dot` followed by `just draw`.

The notebook loads automatically when it comes into view. The first visit downloads browser Python and its dependencies; rendering then runs locally in your browser.

The online guide includes an interactive notebook. Open the [physics rendering notebook source](#) to run the same example locally.

Try changing an internal edge's particle: `a` draws a photon wave, `g` a gluon coil, `H` a dashed scalar, and `t` a fermion with its model label. The same generated particle map and Typst callbacks control these styles in exported GammaLoop drawings.

The initial settings match ordinary `just draw`: 1200 iterations, seed 42, and momentum arrows and labels disabled. The preview draws edited DOT without importing it into a GammaLoop calculation, so it does not validate interactions or numerators against the model.

The amplitude assigns half-edge ports `5:12` and `4:15` to put the outgoing leg at vertex 5 above the leg at vertex 4. This external order allows the default layout to draw the internal cycle without crossings. The ports are global half-edge indices; the remaining indices are inferred. Reordering the DOT statements alone would not establish this order.

10.2 Graph shape and half-edges

```
digraph box {
  ext [style=invis];
  ext -> v0:0 [particle="e-"];
  v0 -> v1 [id=1, particle="a"];
  v1 -> ext [particle="e+"];
}
```

Use `digraph NAME { ... }`. DOT arrows define the underlying edge orientation. An invisible node represents an external dangling half-edge: invisible-node to vertex is incoming, and vertex to invisible-node is outgoing. An edge between two invisible nodes is invalid.

Use one shared `ext [style=invis]` node for all external legs. Each connection still creates a separate dangling half-edge. Keep the shared node otherwise attribute-free: attributes on a dangling node are merged into every external edge, so put `particle`, `num`, and other per-leg data on the edge.

Numeric ports (`vertex:0`) fix half-edge indices; an edge `id=1` fixes its edge index. These are separate index spaces. Assign only indices needed by momentum or numerator references; omitted indices are allocated automatically. Either endpoint of an internal edge can be indexed independently. Supplied indices must be unique and in range across the entire graph, including external legs. A numeric port is not a slot numbered locally within one vertex. Omitted indices follow parser order, which need not be DOT statement order; see [DOT input and graph indices](#) for the allocation rules.

Input	Drawing	GammaLoop calculation
Edge <code>id=n</code>	Names the momentum label q_n .	Identifies an edge in momentum expressions such as $Q(n, \dots)$.
Numeric port <code>vertex:h</code>	Sets initial amplitude row order and identifies half-edge debug labels.	Orders amplitude external momentum and helicity entries; also supplies tensor-index identities.
Edge <code>is_cut=k</code>	Orders cross-section rows numerically and pairs legs at the same vertical position.	Marks an initial-state cut and orders its external momentum entries; equal tags sew split legs.
Edge <code>lmb_id=k</code>	Does not rename the edge's q label.	Selects this edge as the carrier of loop momentum $K(k, \dots)$.

DOT arrow direction determines incoming versus outgoing, independently of these numbers and of `dir`, which controls the displayed or particle orientation. For an amplitude, the runtime external momentum and helicity lists follow increasing dangling half-edge index. Incoming momenta enter the conservation equation with a plus sign and outgoing momenta with a minus sign. Automatic amplitude placement uses this same half-edge order, separately for the incoming left column and outgoing right column. Gaps in the indices do not create empty rows. These are initial vertical positions that layout may adjust; explicit positions still take precedence. Moving a port index to another leg changes its kinematic-list position and its initial drawing order. See [Kinematics](#), [normalization](#), and [weights](#) for the four-vector and sign conventions.

For example, the edge and half-edge indices deliberately differ here:

```
digraph amplitude_order {
  ext [style=invis];
  ext -> v:3 [id=0, particle="H"];
  v:2 -> ext [id=1, particle="H"];
  v:1 -> ext [id=2, particle="H"];
  ext -> v:0 [id=3, particle="H"];
}
```

The incoming half-edges are 0, 3, so the left column starts with q_3 above q_0 . The outgoing half-edges are 1, 2, so the right column starts with q_2 above q_1 . The runtime external list follows half-edges 0, 1, 2, 3, belonging to edges 3, 2, 1, 0. This ordering does not renumber either collection: edge IDs continue to determine the q labels.

10.3 Cross-section cuts and drawing order

A cross-section input may describe an initial-state cut as an internal edge carrying `is_cut`, or as two dangling legs with the same `is_cut` value. In the split form, one leg must be incoming and the other outgoing. They still

have distinct edge IDs and distinct half-edge IDs. For example, these two statements in a larger graph identify one pair:

```
ext -> left:0 [id=0, is_cut=0, particle="e-"];
right:7 -> ext [id=5, is_cut=0, particle="e-"];
```

Here `ext` must be declared invisible, and the enclosing graph must have enough edges and half-edges for the explicit indices. Sharing `id=0` between the two statements would be an error; sharing `is_cut=0` is what associates them. Use one tag per initial-state pair, with consistent particle data on its two legs. A cut-tagged dangling leg without its opposite-flow partner is invalid for a `GammaLoop` calculation.

On import, `GammaLoop` sews matching legs into one edge, then sorts the cut tags numerically and moves the resulting cut edges and their incoming half-edges to leading indices `0, 1, ...`. These cut entries determine the cross-section's external momentum order. Sewing and this normalization can change other edge and half-edge indices too. Exports conventionally use the incoming cut half-edge index as the tag. On import, however, tags are non-negative integer matching and ordering values: they need not be contiguous or name an existing half-edge. The index bounds described above apply to `id` and numeric ports, not to these tags.

The notebook and `just draw render DOT` directly, without this physics import or sewing. Cross-section placement follows the same numeric `is_cut` order as the calculation: incoming legs occupy rows from top to bottom, and outgoing legs find their row through the matching tag. For example, tag 2 precedes tag 10; gaps do not create empty rows. Incoming legs go on the left and outgoing legs on the right. These cross-section rows are pinned vertically, while amplitude rows use the adjustable starting positions described above. All dangling depths are pinned to zero, and explicit horizontal and vertical placements retain precedence. An outgoing cut tag without an incoming counterpart can still be drawn, but receives no automatic row placement.

Generated momentum labels use the current drawing edge's `eid`, including on split cut legs: the example's labels are q_0 and q_5 . With edge IDs fixed, changing `is_cut`, a half-edge port, or `lmb_id` does not rename these labels. After importing and saving a graph, the labels instead reflect the edge IDs in that newly exported DOT. Do not infer kinematic-list positions from the drawing's q subscripts.

10.4 Physics attributes

Location	Fields	Meaning
Graph	<code>num</code>	Global numerator factor, default 1.
Graph	<code>overall_factor</code> , <code>projector</code> , <code>params</code> , <code>group_id</code> , <code>is_group_master</code>	Advanced imported-state and grouping metadata.
Node	<code>int_id</code>	UFO interaction identifier when incident particles do not uniquely select a rule.
Node	<code>num</code> , <code>dod</code>	Vertex numerator override and degree-of-divergence override.
Edge	<code>particle</code> , <code>pdg</code>	Model particle name or signed UFO PDG code.
Edge	<code>dir</code>	Explicit orientation; otherwise fermion orientation is derived from the signed particle.
Edge	<code>name</code> , <code>mass</code>	Optional stable name and Symbolica mass override.

Location	Fields	Meaning
Edge	<code>lmb_id</code>	Loop-momentum slot carried by this edge.
Edge	<code>num</code> , <code>is_cut</code> , <code>is_dummy</code> , <code>momtrop_edge_power</code> , <code>vakint_edge_power</code>	Numerator and evaluator controls.

For fermions, signed particles and edge orientation must give a consistent fermion flow around closed loops and along open fermion lines. External momentum labels are not a current GammaLoop physics attribute; older examples using `mom` should use edge `particle/pdg` and half-edge ports. The active model supplies propagator tensors; the legacy propagator field is not a current GammaLoop input field. `multiplicity_factor` is likewise a legacy field; current grouping uses `group_id`, `is_group_master`, and `overall_factor`.

10.5 Numerators and loop bases

A graph, vertex, or edge `num` is parsed as a Symbolica expression. Quote expressions containing punctuation or spaces. Keep vertex and edge numerators attached to their owning statement when editing an exported graph. In an edge numerator, `eid`, `source`, and `sink` refer to that edge's index and its existing endpoint indices; their function forms, such as `source(0)`, construct corresponding tensor-index identities. This local shorthand is resolved for edge numerators, not for an arbitrary graph or vertex expression.

By contrast, generated `hedge(h)` or `hedge(h, k)` expressions contain explicit tensor-index identities: `h` is not a local port number within the statement. Preserve the exported topology, indices, and numerator expressions together. Sewing can move graph records without renaming those abstract tensor identities, so changing only the printed ports or only numbers in `num` is not a safe way to renumber an exported calculation.

Edge momenta `Q(e, ...)`, loop momenta `K(k, ...)`, and external momenta `P(p, ...)` use different indices. Setting `lmb_id=k` chooses the internal edge carrying `K(k, ...)`; it does not set the edge ID or an external momentum slot. The remaining edge momenta are expressed through the chosen basis and external flows. Exports show these expressions in `lmb_rep`; they are generated routing information, not a replacement for the `lmb_id` input.

Load a DOT file after importing its model:

```
import model assets/models/json/sm/sm.json
import graphs ./my_graphs.dot
```

Save loaded graphs back to DOT with `save dot ./my_graphs_exported`. GammaLoop fills omitted names, indices, factors, and loop-momentum basis entries during import/export. The current spelling is `lmb_id`; older wiki examples may use `lmb_index`.

Keep external data on edges

A shared invisible node is deliberately compact. Put each external particle, numerator, and cut flag on its own connecting edge so those attributes do not get copied to every leg.

For PDF figures, run `just draw` from the directory written by `save dot`. See [Clinnet DOT rendering](#) for renderer configuration, or [Rendering graphs from Python](#) to build graphs with arbitrary Python data and custom drawing selectors.

11 Inspect events and observables

GammaLoop can evaluate selected points without launching a full adaptive integration. This is the shortest path for inspecting the generated cut events, testing selectors, and checking that histograms receive the expected weights. It is an investigative workflow: a few chosen points cannot establish convergence or replace the persisted result of an integration.

11.1 Start from the differential regression example

The repository contains matching Python and Rust journeys for the differential Local Unitarity process $e^+ e^- \rightarrow d \bar{d} g$. Their run cards generate the real two-graph process and configure:

- event generation and additional event weights;
- jet transverse-momentum, jet-count, and down-quark-energy quantities;
- a leading-jet selector; and
- continuous and discrete histogram observables.

What this example verifies

This is an API and event-pipeline regression fixture, not a scientifically reviewed perturbative-order or normalization benchmark. Its run card uses a powered coupling selector, but the current filter construction discards that exponent. Keep it for inspecting events and observable plumbing; define and validate production contributions independently.

The run card's `display_named_settings_examples` block lets you inspect each named object before evaluation:

```
display quantities -p #0
display quantities -p #0 leading_jet_pt
display selectors -p #0 leading_jet_pt_cut
display observables -p #0 leading_jet_pt_hist
```

Use these displays as a preflight check. A missing quantity name belongs to configuration; an empty event list belongs to event generation or selection; an unexpected histogram belongs to the quantity, phase, binning, or weights. Keeping those stages separate is more informative than debugging the final number alone.

11.2 Run the Python journey

Build the native package, then run the maintained script from the repository root. It creates a fresh state beside the script, generates the configured process, evaluates one integration-space point, evaluates a two-point batch, and evaluates one momentum-space point:

```
nix develop
uv venv .venv
source .venv/bin/activate
just build-api
python examples/api/python/epem_a_ddxg_xs_L0/inspect_events.py
```

The exact workflow is kept in the Python event-inspection script and its differential run card. The core API sequence is:

```
from pathlib import Path

import numpy as np
from gammaloop import GammaLoopAPI

example = Path("examples/api/python/epem_a_ddxg_xs_L0")
api = GammaLoopAPI(
    state_folder=example / "state",
    boot_commands_path=example / "run.toml",
    clean_state=True,
)
api.run("run display_named_settings_examples")

info = api.get_integrand_info()
assert info.kind == "cross section"
```

```

assert info.graph_count == 2
assert info.graph_group_count == len(info.graph_groups)
assert all(
    sum(graph.is_master for graph in group.graphs) == 1
    for group in info.graph_groups
)

point = [0.17, 0.31, 0.53, 0.23, 0.41, 0.67]
single = api.evaluate_sample(point, return_events=True)
assert single.parameterization_jacobian is not None
assert single.stability_results
assert single.event_groups

points = np.array([
    point,
    [0.11, 0.29, 0.47, 0.19, 0.37, 0.59],
], dtype=float)
batch = api.evaluate_samples(points, return_events=True)
assert len(batch.samples) == 2
assert all(sample.event_groups for sample in batch.samples)
assert len(batch.observables["leading_jet_pt_hist"].bins) == 8
assert len(batch.observables["jet_count_hist"].bins) == 6
assert batch.observables["leading_jet_pt_hist"].sample_count == 2
assert batch.observables["jet_count_hist"].sample_count == 2

print(single.integrand_result, single.generated_event_count)
for group in single.event_groups:
    for event in group.events:
        print(event.cut_info.graph_id, event.weight, event.outgoing_momenta)
print(batch.observables["leading_jet_pt_hist"].sample_count)

```

`return_events=True` temporarily requests returned events for that call; it does not permanently rewrite the integrand setting. Every `EventGroup` contains correlated accepted events produced by one graph group. Each event carries incoming/outgoing momenta, its primary complex weight, cut and graph identifiers, and any configured additional weights.

The `normalization` and `weight` contract defines which factors are already present in an event weight and why all contributions from one Monte Carlo point must be committed as one statistical sample.

Single and batch results have different aggregation boundaries

`evaluate_sample` returns one `EvaluationResult`: its event groups and observable snapshot belong to that sample. `evaluate_samples` returns per-row `SampleEvaluationResult` objects and one `BatchEvaluationResult.observables` dictionary merged across the whole batch. Do not read a batch histogram as if it belonged to the last row, and do not add the same batch snapshot once per sample.

The histogram values are immutable snapshots. Inspect bins, underflow/overflow, raw sums of weights and squared weights, entry counts, and the aggregate statistics before deriving a plot. Keep raw statistics when combining results; rounded rendered values are not a merge format.

11.3 Run the Rust journey

The Rust example loads the same kind of run card through `StateLoadOption`, executes the display block through a CLI session, then calls the typed evaluation functions. It is a rust-script program so its dependency revision is recorded with the example:

```
EXTRA_MACOS_LIBS_FOR_GNU_GCC=T \
SYMBOLICA_LICENSE="$SYMBOLICA_LICENSE" \
rust-script --debug examples/api/rust/epem_a_ddxg_xs_L0/inspect_events.rs
```

The documentation gate compiles the request boundary below against the workspace API. It keeps the event-return override and every required field synchronized even though the licensed process evaluation remains outside the pull-request tier:

```
use gammaloop_api::commands::evaluate_samples::EvaluateSamples;
use ndarray::arr2;

let points = arr2(&[[0.17, 0.31, 0.53, 0.23, 0.41, 0.67]]);
let request = EvaluateSamples {
    process_id: None,
    integrand_name: None,
    use_arb_prec: false,
    minimal_output: false,
    return_generated_events: Some(true),
    momentum_space: false,
    points: points.view(),
    integrator_weights: None,
    discrete_dims: None,
    graph_names: None,
    orientations: None,
};
assert_eq!(request.return_generated_events, Some(true));

let loop_momenta = arr2(&[[
    0.11, -0.07, 0.19, // k1 = (px, py, pz)
    -0.13, 0.05, 0.29, // k2 = (px, py, pz)
]]);
let momentum_request = EvaluateSamples {
    process_id: None,
    integrand_name: None,
    use_arb_prec: true,
    minimal_output: true,
    return_generated_events: None,
    momentum_space: true,
    points: loop_momenta.view(),
    integrator_weights: None,
    discrete_dims: None,
    graph_names: None,
    orientations: None,
};
assert_eq!(momentum_request.points.ncols(), 2 * 3);
```

Read the Rust event-inspection script with its run card. The ordinary EvaluateSamples path returns the cross-language f64 boundary. Rust callers that must retain the active numeric precision use EvaluateSamplesPrecise; arbitrary-precision internal evaluation does not make the ordinary result fields arbitrary-precision. use_arb_prec=true forces arbitrary-precision (Arb) internal evaluation, using the configured Arb stability level when available and a default Arb level otherwise. The sample evaluation contract defines this flattened momentum layout and the precision behavior once for CLI, Rust, and Python.

Verification and resource cost

The pull-request gate parses the commands, compiles the Python source, and type-checks the Rust request literal, but does not run process generation or native evaluation. The maintained scripts are the real acceptance path and require a built API, the repository's scientific dependencies, and an appropriate

Symbolica license. They create or replace only their example-local state directory because they opt into `clean_state=True`; remove that option before pointing at work you need to keep.

11.4 From point inspection to integration output

Selected points answer structural questions: whether events are produced, how graph/cut metadata is grouped, which selector accepts them, and which histogram bins are filled. A production result still needs an integration workspace, target-accuracy settings, iteration diagnostics, and the final observable output. Continue with the [state and integration-workspace](#) guide for resume semantics and the distinction between `integration_result.json`, `observables_final.*`, and the authoritative checkpoint.

Contributors changing progress reporting, cancellation, or terminal ownership should also read the [integration dashboard architecture](#).

The exact Python return types and fields are linked from the [interface guide](#) and generated Python API.

12 CLI, Rust, and Python APIs

12.1 Rust packages

The Rust API spans two primary packages.

- `gammalooprs` contains the physics implementation, data model, integrands, integration, observables, and lower-level algorithms.
- `gammaloop-api` provides the supported state-loading API, session/command integration, CLI assembly, and the PyO3 extension used by the Python distribution.

Load a state with `StateLoadOption::load()`. Its options select a state directory, boot card, logging overrides, read-only behavior, and optional settings overrides. Once loaded, callers can create a CLI-style session or use dedicated structured operations. A raw command string is the compatibility fallback, not a replacement for a typed operation where one exists.

```
use std::path::PathBuf;
use gammaloop_api::{state::CommandHistory, StateLoadOption};

let mut loaded = StateLoadOption {
    state_folder: Some(PathBuf::from("./state")),
    ..StateLoadOption::default()
}.load()?;

let command = CommandHistory::from_raw_string("display settings global"?);
loaded.cli_session().execute_command(command)?;
```

Some Rust types are public so that GammaLoop's packages can work together, but are not intended as stable integration points. Prefer the state-loading and structured-operation APIs described here; use the [Rust orientation](#) to choose a crate, then use that revision's Rustdoc for exact signatures, trait implementations, and lower-level types.

12.1.1 Rust reference map

This authored map separates the supported workflow from the much larger compiled surface. Follow these exact Rustdoc paths instead of beginning in an arbitrary internal module:

- **Load and command a state:** begin with `StateLoadOption`, retain the returned `LoadedState`, and execute parsed `CommandHistory` values through `CliSession`.

- **Replay and inspect:** use `RunHistory` for run cards and `IntegrandInfo` for structured graph-group, orientation, loop-basis, cut, and threshold metadata.
- **Evaluate samples:** construct `EvaluateSamples` for the ordinary f64 boundary. Use `EvaluateSamplesPrecise` only when the caller must retain the active f64, f128, or arbitrary-precision result type.
- **Work below the facade:** the `gammaloops` Rustdoc includes the `integrand` contract, runtime settings, precision-specific result records, and the mergeable `histogram` snapshot boundary. Treat public items not named by a maintained workflow as implementation-facing unless their crate documents a stronger compatibility promise.

12.2 Python packaging

A standalone GammaLoop distribution

The Python distribution and import package are both named `gammaloop`. Its compiled backend is `gammaloop._gammaloop`, which applications normally access through the public package. This is separate from the `symbolica.community.*` modules used by `Spenso`, `Idenso`, and `Vakint`; installing `GammaLoop` does not install those community modules as independent packages.

The main Python entry point is `GammaLoopAPI`. Its constructor loads or creates one stateful session:

```
from gammaloop import GammaLoopAPI

gl = GammaLoopAPI(
    state_folder="./state",
    boot_commands_path="./run.toml",
)
gl.run("display settings global")
```

The Python package requires Python 3.11 or newer. Run `just build-api` when building the bindings from a source checkout.

12.2.1 Python reference map

The generated module reference covers every registered public export, but the objects form a few connected workflows rather than forty unrelated entry points:

- **Session lifecycle:** construct `GammaLoopAPI`, then use `run`, the history getters, and `SettingsValue` to automate the same state and commands as the CLI.
- **Point evaluation:** `evaluate_sample` returns `EvaluationResult`, whose `sample` is a `SampleEvaluationResult`. `evaluate_samples` returns `BatchEvaluationResult` with the same sample records and one batch-level observable snapshot.
- **Generated-integrand structure:** start at `IntegrandInfo`, then follow its graph groups into `graph`, `orientation`, `loop-momentum-basis`, `cut`, and `threshold` records. These objects describe compiled structure; they do not mutate it.
- **Events and observables:** evaluation records lead to `EventGroup` and `Event`. For caller-owned aggregation, `HistogramAccumulator` produces immutable `HistogramSnapshot` records with raw statistics that remain mergeable and reconstructible.

Full integrations still use the command interface

The current Python module does not expose a supported structured `integrate()` method. Run an integration through `GammaLoopAPI.run("integrate ...")` or the CLI and consume its persisted workspace/results. Several integration-result record classes are registered by the native module for ongoing API work, but without a public producer they are not part of the curated Python boundary yet.

Result ownership

Objects returned by evaluation and integration are snapshots. Mutating a Python list or dictionary derived from them does not update the live GammaLoop session. The explicit mutable exception is `HistogramAccumulator`, whose methods update caller-owned aggregation state.

Caller-owned histogram correlation limit

Do not yet use `HistogramAccumulator.fill_continuous_sample` or `fill_discrete_sample` to replay raw correlated event entries when more than one entry can land in the same bin. The helper counts the call as one sample but currently accumulates the entries' squared weights separately, unlike the native observable path, which groups their weights before recording one bin sample. Keep production histograms in the configured native observable pipeline until this statistical contract is aligned.

12.2.2 Aggregate independent histogram samples

This safe standalone use keeps one entry per bin in each independent sample. Merge pending worker state before committing it, then retain raw sums and squared sums for later combinations:

```
from gammaloop import HistogramAccumulator

left = HistogramAccumulator.continuous("energy", 0.0, 4.0, 4)
right = HistogramAccumulator.continuous("energy", 0.0, 4.0, 4)
left.fill_continuous_sample([(0.5, 2.0)])
right.fill_continuous_sample([(2.5, 3.0)])
left.merge_in_place(right)
left.update_results()

snapshot = left.snapshot()
assert snapshot.sample_count == 2
assert snapshot.bins[0].sum_weights == 2.0
assert snapshot.bins[0].sum_weights_squared == 4.0
assert snapshot.bins[0].sum_weights / snapshot.sample_count == 1.0
assert snapshot.bins[2].sum_weights == 3.0
assert snapshot.bins[2].sum_weights_squared == 9.0
assert right.snapshot().sample_count == 0
assert len(left.rebin(2).snapshot().bins) == 2
```

`snapshot()` includes both committed and pending samples. `update_results()` moves pending values into the completed counters; it is not needed merely to inspect the current snapshot. A successful `merge_in_place` consumes only the donor's pending samples, so merge worker accumulators before committing them.

12.3 Inspect and evaluate an existing state

The following workflow assumes that `./state` contains a generated integrand. Evaluation points are integrand-specific: their length must match the selected integrand and any discrete dimensions. Use the generated reference for the exact single-sample and batch contracts.

```
from collections.abc import Sequence

from gammaloop import GammaLoopAPI

api = GammaLoopAPI(state_folder="./state", read_only_state=True)
api.run("display processes")

print(api.get_run_history())
```

```
runtime = api.get_default_runtime_settings()
print(runtime.get("integrator.n_start"))

def evaluate_one(point: Sequence[float]) -> complex:
    result = api.evaluate_sample(
        point,
        process_id=0,
        minimal_output=True,
    )
    return result.integrand_result
```

Verification tier: compile

The documentation checks compile this example as Python syntax. They do not import or execute the native module: a runtime check additionally needs a built GammaLoop package, a provisioned backend and license, an existing generated state, and a point with the correct dimension.

The `run` method uses the same command language as the CLI and can change the in-memory state, settings, and run history. `read_only_state=True` protects files inside the active state directory; it does not make the Python object immutable or automatically persist the session. Inspect the live session through `get_run_history`, `get_global_settings`, and `get_active_command_blocks`.

For structured inspection, `get_integrand_info` describes the selected backend and graph structure, while `get_integrand_settings` and `get_default_runtime_settings` return detached, read-only `SettingsValue` snapshots. Use `get(path)`, attribute access, indexing, or `to_dict()` to read them; modifying derived Python values does not update the live session.

12.4 Sample evaluation contract

All three supported interfaces use the same two input layouts:

- An **integration-space** row contains the unit-hypercube coordinates expected by the selected integrand and discrete dimensions. Its required length is integrand-specific.
- A **momentum-space** row is `[k1x, k1y, k1z, k2x, k2y, k2z, ...]`: exactly one spatial (px, py, pz) triplet per independent loop momentum. It contains neither loop-energy components nor external momenta; GammaLoop obtains the latter from the integrand's kinematics. Select momentum space explicitly with `--momentum-space`, `momentum_space=true`, or `momentum_space=True`.

Every momentum-space row must therefore have a coordinate count divisible by three, and its number of complete triplets must match the selected integrand, graph, or graph group. `approach` axes use the same layout and dimension as their midpoint. The CLI, structured Rust API, and Python API all reach the same input builder and reject incomplete triplets before numerical evaluation.

Precision selection is independent of the coordinate layout. With `use_arb_prec=false`, the configured stability ladder may evaluate and escalate through `f64`, `f128`, and arbitrary precision. Setting `use_arb_prec=true` forces arbitrary-precision (Arb) internal evaluation, using the configured Arb stability level when available and a default Arb level otherwise. The `-f` CLI shorthand has the same behavior. CLI output, Python numeric fields, and ordinary Rust `EvaluateSamples` results remain `f64`. Only Rust `EvaluateSamplesPrecise` retains the numeric type used by the selected stability level.

`evaluate_sample` returns one sample result and the observable bundle for that one-sample batch. `evaluate_samples` accepts a two-dimensional NumPy array and returns per-sample results plus a batch-global observable bundle. Per-sample weights, discrete coordinates, graph names, and orientations must have the same row count as the input batch when provided. Graph and orientation selection applies only to momentum-space evaluation.

Both the ordinary Rust and Python endpoints expose numeric results through an `f64` contract, even when `use_arb_prec=True` forces arbitrary-precision internal evaluation. Evaluation may warm the integrand and update in-memory caches or observable snapshots, including in a read-only-state session. Rust-only callers that must retain the active precision use `evaluate_sample_precise` and `evaluate_samples_precise`.

Point evaluation returns the integrand before the parameterization Jacobian. The `kinematics, normalization, and weights` guide defines the exact $I_{\text{returned}} J_{\text{parameterization}} w_{\text{MC}}$ relation used during integration and the correlated event-weight boundary.

For a complete, source-backed run card and scripts that expose event groups, cut metadata, selectors, and merged histogram snapshots, follow the `events and observables` guide.

12.5 Symbolic conversion helpers

The supported module-level helpers are `atom_to_canonical_string` for parsing and canonicalizing a Symbolica expression, `evaluate_graph_overall_factor` for evaluating a graph's symbolic prefactor, and `to_dots` for rewriting tensor contractions into Idenso dot-product notation. Their generated entries document accepted strings, return values, failure modes, and task-oriented examples.

12.6 CLI and settings reference

12.6.1 Shell completion

`--completions` emits a static script from the same Clap command tree as `--help`. Load it for the current shell or save it in the shell's normal completion directory:

```
# Bash for the current session
source <(/gammaLoop --completions bash)

# Zsh for the current session
source <(/gammaLoop --completions zsh)
```

Fish, Elvish, PowerShell, and Nushell are also supported values. For Fish, pipe the output to `source`; for Nushell, save the generated module and then source it. Bash and Fish output also registers the repository wrapper spelling `./gammaLoop`.

Static and state-aware completion

The generated shell script covers executable subcommands, flags, enumerated values, and path hints. Completion inside the interactive GammaLoop prompt additionally knows the active state's processes, integrands, settings, model objects, graphs, cuts, and orientations. A static shell script cannot contain that changing session data.

Use `./gammaLoop --help` and the generated CLI and settings reference for command names, aliases, flags, positional arguments, defaults, possible values, and setting paths. The tutorials explain how commands and settings combine into a persistent workflow. The `logging and diagnostics` guide covers startup precedence, selective tag filters, sink routing, release-build limitations, and copyable investigation patterns.

13 Logging and diagnostics

This guide explains the default tracing configuration used by the CLI and API at startup and gives copyable filters for narrowing a noisy calculation to the subsystem and work unit that matter.

Before you start

Prerequisites: a built GammaLoop CLI and a state or run card that reaches the behavior you want to inspect.

Filter changes take effect immediately and add negligible setup time, but verbose inspect or dump events can produce large files and slow a run. The expected invariant is that a narrow directive changes diagnostic visibility, not numerical results. If a filter produces nothing, first use a broader target at debug, confirm that release compilation has not removed the callsite, and then add tag constraints. After isolating the event, record the exact directive with the run card and continue to the CLI/settings reference for persistence and state controls.

13.1 Default directives

Normal session defaults come from GlobalSettings:

- `display_directive = "info"`
- `logfile_directive = "off"`

These are the application defaults written into `global_settings.toml` when defaults are shown or persisted.

In practice, `info` is the current convention for normal screen-facing output. Selective internal diagnostics should generally stay on debug and be turned on via narrower target/tag filters rather than by raising the whole display logger.

13.2 Startup precedence

Startup applies logging in this order:

1. Base settings come from GlobalSettings.
2. Environment overrides replace the base spec:
 - `GL_ALL_LOG_FILTER` overrides both stderr and logfile filters.
 - `GL_DISPLAY_FILTER` overrides only the stderr/display filter.
 - `GL_LOGFILE_FILTER` overrides only the logfile filter.
3. CLI overrides are then applied:
 - `-l/--level` overrides the stderr/display filter for the session.
 - `-L/--logfile-level` overrides the logfile filter for the session.
4. Some CLI modes hard-disable logfile logging for the session:
 - `--read-only-state`
 - `--logfile-level off`

When logfile logging is hard-disabled at boot, later settings changes cannot re-enable it for that session.

13.3 CLI level mapping

`-l/--level` and `-L/--logfile-level` expand to explicit crate directives:

- `off` -> `gammaloop_api=off,gammalooprs=off`
- `error` -> `gammaloop_api=error,gammalooprs=error`
- `warn` -> `gammaloop_api=warn,gammalooprs=warn`
- `info` -> `gammaloop_api=info,gammalooprs=info`
- `debug` -> `gammaloop_api=debug,gammalooprs=debug`
- `trace` -> `gammaloop_api=trace,gammalooprs=trace`

13.4 Empty-spec fallback floors

The filter builders also have hardcoded fallback floors used when a spec is empty:

- display/stderr builder fallback: `off`
- logfile builder fallback: `warn`

This is separate from the normal application defaults above. In other words:

- if startup uses the normal settings path, the defaults are `info` for display and `off` for logfile

- if an empty filter string is explicitly parsed, the display builder falls back to off and the logfile builder falls back to warn

13.5 Runtime updates

Changing `global.display_directive` or `global.logfile_directive` after startup reloads the active tracing filters. The CLI `stderr` override from `-l/--level` is treated as a session override and is separate from the persisted global setting.

13.6 Tag-based debug filtering

For selective debug logging, GammaLoop uses its own logging DSL rather than raw `EnvFilter`.

This follows the general idea in Tom Mrazik's [tag-based logging note](#).

The main reason for owning the DSL is that GammaLoop needs composable tag groups and stable semantics around presence, absence, and explicit boolean values.

- Use stable targets for broad subsystems such as `gammalooprs::uv::forest` or `gammalooprs::integrands::process::cross_section`.
- Add boolean event fields as composable tags.
- Filter by field presence with `target[{tag_a,tag_b,!tag_c}]=debug`, or by displayed boolean values with `target[{-#tag_a,#!tag_c}]=debug`.

This is preferable to span-name filtering because span-based filters can admit child-library events emitted while the span is active. GammaLoop tag filters only look at the event target and the boolean tag fields on the event itself.

13.6.1 Supported directive syntax

The supported directive forms are:

- `level`
- `target=level`
- `target[{tag_a,tag_b,!tag_c}]=level`
- `target[{-#tag_a,#!tag_c}]=level`
- `target`

Notes:

- Directives are comma-separated.
- `target` is matched as a module-style prefix, so `gammalooprs::uv=debug` matches `gammalooprs::uv` and `gammalooprs::uv::forest`.
- A directive without an explicit `=level` is treated as `=trace`.
- Tag groups are conjunctions: `[{generation,uv}]` means both tags must match.
- `!tag` means the field is absent.
- `#tag` means the field is present with boolean value `true`.
- `#!tag` means the field is present with boolean value `false`.
- `field=value` matches an explicit field value.

13.6.2 Tag matching model

Tags are represented by event fields.

- `#generation` at the callsite emits `generation = true`.
- In a directive, `generation` means the event must carry a field named `generation`.
- In a directive, `#generation` means the event must carry `generation = true`.
- In a directive, `!inspect` means the event must not carry a field named `inspect`.
- In a directive, `#!inspect` means the event must carry `inspect = false`.

- In a directive, `inspect=true`, `mode=summary`, or `label="soft region"` means the event must carry that value specifically.

This means the callsite controls both:

- whether a log is selectable by a presence/absence query
- whether a log can be selected by an explicit value query such as `inspect=false` or `mode=summary`

13.6.3 Static vs dynamic filtering

Presence/absence-only directives stay on the lazy metadata path.

- `generation`
- `!inspect`
- `gammaloops::uv::forest[{generation,uv,!dump}]=debug`

These can be decided from the callsite target and declared field names alone, so the filter can answer always or never at callsite registration time.

Value-matching directives are dynamic.

- `inspect=false`
- `#!inspect`
- `#generation`
- `mode=summary`
- `label="soft region"`

Those depend on the event instance, so they are evaluated in the per-event pass.

13.6.4 Precedence

When multiple directives match the same event, GammaLoop prefers the most specific one:

- longer target prefix wins
- then the directive with more tag requirements wins
- then later directives win if the earlier specificity is identical

This lets broad directives such as `gammaloops=info` coexist with narrow tag-specific directives such as `gammaloops::uv::forest[{generation,uv,dump}]=debug`.

13.6.5 Copy-pasteable display tags

Display logs render boolean fields next to the source as a directive tag group:

```
@gammaloops::uv::forest[{#generation, #uv, #!inspect}] DEBUG: message
```

Every boolean field is rendered this way, not only the standard tag vocabulary. `true` becomes `#field_name`; `false` becomes `#!field_name`. These boolean fields are removed from the normal display field table.

Use the full logging prefix when you want the rendered source to be a valid directive head:

```
gammaloop --logging-prefix full -l debug ...
```

Then the text after `@` and before the log level can be copied into a directive by adding `=debug`, for example:

```
display_directive = "gammaloops::uv::forest[{#generation, #uv, #!inspect}]=debug"
```

This copy-paste form assumes the display source is the module target. Enabling `full_line_source` adds file and line information to the source display, which is useful for locating code but is not a valid directive target.

13.6.6 Sink-only field prefixes

This repo also has sink-routing prefixes for fields:

- `file.<name>`: only rendered into the logfile/json sink
- `display.<name>`: only rendered into the stderr/display sink

Examples:

- `file.integrands = %...` will appear only in the file logger output
- `display.progress = %...` will appear only in the display logger output

These prefixes are a formatting/routing feature, not a separate event kind. They decide where a field is rendered after the event has been emitted. This lets a callsite attach large payloads such as `file.integrands` without dumping them to stderr.

13.6.7 Pipeline-wide tag set

Prefer a small stable vocabulary that cuts across the whole pipeline.

Primary phase tags:

- `generation`: work that builds or prepares runtime objects before Monte Carlo integration starts
- `integration`: work performed while evaluating samples or managing the adaptive integration loop
- `profile`: UV/IR/profile-style diagnostic scans and their analysis
- `persistence`: reading or writing saved state, manifests, checkpoints, and exported results

Core domain tags:

- `uv`: ultraviolet counterterms, UV forests, UV profiles, or UV-specific generation/evaluation logic
- `ir`: infrared subtraction, IR profiles, or IR-specific generation/evaluation logic
- `subtraction`: threshold, UV, or IR subtraction logic when the main concern is subtraction rather than the specific regime
- `sampling`: channel choice, discrete axes, parameterizations, or sample-generation choices
- `stability`: precision escalation, retries, instability diagnosis, and numerical safety checks
- `observables`: histogramming, event-to-observable projection, and observable snapshot production
- `selectors`: event-selection logic and selector decisions
- `cache`: cache lookup, reuse, invalidation, or cache-debug instrumentation

Common work-unit tags:

- `graph`: the log is about one graph or graph-local data
- `group`: the log is about a graph group or another explicitly grouped aggregate
- `orientation`: the log is about orientation-dependent data or choosing/summing orientations
- `channel`: the log is about multi-channeling or a particular channel
- `cut`: the log is about a cut, raised cut, or cut-local computation
- `event`: the log is about generated/retained event objects or event-group processing
- `sample`: the log is about one evaluation sample, its coordinates, or per-sample intermediate values
- `iteration`: the log is about one adaptive integration iteration or iteration-level summaries
- `term`: the log is about one algebraic term, summand, or term-local contribution

Common purpose tags:

- `solver`: the log is about root-finding, linear solves, fitting, or similar numerical solver state
- `compile`: the log is about evaluator/code generation or compilation-oriented preparation
- `inspect`: the log exposes detailed intermediate state for debugging, rather than a high-level milestone
- `summary`: the log is a compact roll-up rather than a step-by-step trace
- `dump`: the log emits large or structured payloads such as expressions, tables, or serialized views

13.6.8 Tag boundaries

Use the most general tag that accurately captures the reason you want to turn the log on or off.

- Prefer generation over compile when the message is a broad generation milestone.
- Add compile only when the message is specifically about evaluator construction or compilation-like work.
- Prefer uv or ir when the regime matters to the user; use subtraction when the subtraction mechanism is the real concern.
- Prefer inspect for verbose intermediate values that are mainly useful while debugging internals.
- Add dump when the payload is large enough that users may want to suppress it separately from lighter debug logs.
- Do not use graph, cut, or sample as substitutes for generation or integration; they refine phase tags rather than replace them.

13.6.9 Naming guidance

- Use phase tags first. They answer “when in the pipeline did this happen?”
- Use domain tags second. They answer “what subsystem is this about?”
- Use work-unit tags third. They answer “what object is being worked on?”
- Use purpose tags last for optional refinement.
- Prefer tags that are meaningful across multiple modules.
- Avoid tags that merely restate a function name.
- Avoid tags tied to one internal representation unless that representation is a stable concept in user-facing debugging.

parametric is usually not a core pipeline tag. It is acceptable as a local refinement when needed, but should not be treated as part of the primary vocabulary unless it becomes a consistently useful cross-cutting concept.

13.6.10 Example queries

- all generation-time UV forest logs:
 - `gammaloops::uv::forest[{generation,uv}]=debug`
- only the large UV forest dumps for orientation-dependent generation logs:
 - `gammaloops::uv::forest[{generation,uv,orientation,dump}]=debug`
- UV forest term-by-term generation logs:
 - `gammaloops::uv::forest[{generation,uv,term}]=debug`
- all integration-time subtraction debug in amplitude evaluation:
 - `gammaloops::integrands::process::amplitude[{integration,subtraction}]=debug`
- per-sample integration inspection in cross-section evaluation:
 - `gammaloops::integrands::process::cross_section[{integration,sample,inspect}]=debug`
- all integration-time cut solver debug in cross-section evaluation:
 - `gammaloops::integrands::process::cross_section[{integration,cut,solver}]=debug`
- integration-time debug excluding inspect-tagged logs:
 - `gammaloops::integrands::process::cross_section[{integration,!inspect}]=debug`
- only events that explicitly set inspect=true:
 - `gammaloops::integrands::process::cross_section[{integration,inspect=true}]=debug`
- only events with a specific textual mode field:
 - `gammaloops::integrands::process::cross_section[{integration,mode=summary}]=debug`

Example display directive:

```
[cli_settings.global]
display_directive =
"gamma_loop_api=info,gammaloops=info,symbolica=off,poly::gcd=off,gammaloops::uv::forest[{generation,uv,orientation,dump}]=debug"
```

13.7 Unsupported EnvFilter syntax

GammaLoop no longer treats the directive string as generic EnvFilter syntax.

In particular, do not rely on:

- span-name filters such as `target[span_name]=debug`
- generic field filters such as `[{field=value}]`
- `EnvFilter` regex semantics

If those are needed later, they must be added explicitly to the GammaLoop DSL.

13.8 Release-build note

`gammaloops` is compiled with tracing feature `release_max_level_info`, so `debug!` and `trace!` callsites in that crate are compiled out in release builds.

13.9 Authoritative implementation

The startup precedence and sink wiring live in the [API tracing setup](#). The shared directive parser, CLI level mapping, and filter behavior live in the [runtime tracing utilities](#), while persisted defaults are owned by `GlobalSettings`.

14 Kurvst curve and path API

Kurvst is GammaLoop's Typst-facing WebAssembly layer for Bezier and Hobby paths, arc-length trimming, sampled path patterns, parallel curves, and CeTZ conversion. This page embeds the complete maintained Kurvst manual used by the drawing pipeline.

Geometry rather than topology

Kurvst transforms curve geometry. Linnet and Linnest own graph topology and layout; GammaLoop's drawing templates combine those results with Kurvst paths and styles.

`kurvst` is a Typst package backed by `kurvst.wasm`, a small Kurbo-based plugin. Its public API is path-based: construct a path dictionary, pass that path into transforms, and draw the returned path.

It exposes Bezier utilities that are awkward or unavailable in native Typst:

- constructing cubic and Hobby paths,
- trimming paths by arc length,
- generating sampled path patterns,
- fitting Kurbo offset/parallel paths,
- converting returned path geometry to CeTZ drawing commands.

14.1 Choose an import path

Kurvst is currently a bundled source package, not a Typst Universe package. A Clinnet run writes it below `build/templates/crates/kurvst/typst/`; a custom template in `build/templates/` can therefore import it with:

```
#import "crates/kurvst/typst/src/lib.typ" as kurvst
```

Repository examples live one directory beside `src/` and instead use `#import "../src/lib.typ" as kurvst`. Keep `kurvst.wasm`, `typst.toml`, and the `src/` tree together when copying the package to another Typst project.

Path geometry points are two-item tuples:

```
#let p = (1.2, -0.4)
```

Cubic segments use `start`, `control-start`, `control-end`, and `end`:

```
#let segment = (
  start: (0, 0),
  control-start: (1, 0.5),
```

```
control-end: (2, -0.5),
end: (3, 0),
)
```

Use `from-cubic(segment)` once to turn that cubic dictionary into a path dictionary. Returned paths contain a curve-command wire path in `path`. Rust converts that wire path to Kurbo's `BezPath` internally, and every path-level Kurvst function accepts either a returned dictionary or the raw wire path.

```
#let path = kurvst.from-cubic(segment)
#let trimmed = kurvst.trim(path, start-outset: 0.2, end-outset: 0.1)
#let shifted = kurvst.parallel(trimmed, distance: 0.15)
```

14.2 Path Wire Format

A Kurvst wire path is a dictionary with one `elements` array. The elements mirror Typst's native curve commands, but points are plain numeric tuples:

```
#let path = (
  elements: (
    (kind: "move", start: (0, 0)),
    (kind: "line", end: (0.6, 0.3)),
    (kind: "quad", control: (1.0, 1.0), end: (1.4, 0.3)),
    (
      kind: "cubic",
      control-start: (1.8, -0.4),
      control-end: (2.4, 1.0),
      end: (3.0, 0),
    ),
    (kind: "close", mode: "straight"),
  ),
)
```

The supported element kinds are:

- `move`: starts a subpath at `start`.
- `line`: adds a straight segment ending at `end`.
- `quad`: adds a quadratic segment using `control` and `end`.
- `cubic`: adds a cubic segment using `control-start`, `control-end`, and `end`.
- `close`: closes the current subpath. `mode` is optional and defaults to `"straight"` when emitted by Kurvst.

Prefer the path fragment helpers for new code. `line`, `quad`, and `cubic` include their start points, so fragments can be built independently:

```
#let custom = kurvst.path(
  kurvst.line((0, 0), (0.6, 0.3)),
  kurvst.quad((0.6, 0.3), (1.0, 1.0), (1.4, 0.3)),
  kurvst.cubic((1.4, 0.3), (1.8, -0.4), (2.4, 1.0), (3.0, 0)),
)
```

`path` and `append` flatten fragments. If an appended fragment starts where the current path ends, its leading move is skipped; if it starts elsewhere, the move begins a new subpath. The edited path can go straight back into Kurvst transforms:

```
#let base = kurvst.from-cubic(segment)
#let extended = kurvst.append(base, kurvst.line(segment.end, (3.4, 0.2)))
```

```
#let trimmed = kurvst.trim(extended, start-outset: 0.15)
#let shifted = kurvst.parallel(trimmed, distance: 0.1)

#kurvst.to-native(shifted, unit: 36pt, stroke: rgb("#1b7f4c") + 0.7pt)
```

Use elements when you need the raw command stream, points for the visited endpoints, segments for cubic segment dictionaries, to-native for native Typst drawing, and to-cetz-data or to-cetz for CeTZ.

A typical chain keeps the returned dictionaries intact until the final drawing step:

```
#let base = kurvst.hobby-through(demo-start, demo-through, demo-end)
#let trimmed = kurvst.trim(base, start-outset: 0.2, end-outset: 0.1)
#let shifted = kurvst.parallel(trimmed, distance: 0.15)

#cetz.canvas({
  kurvst.to-cetz(base, stroke: rgb("#bbbbbb") + 0.4pt)
  kurvst.to-cetz(trimmed, stroke: rgb("#d72638") + 0.6pt)
  kurvst.to-cetz(shifted, stroke: rgb("#1b7f4c") + 0.6pt)
})
```

14.3 Paths And Trimming

cubic constructs a path from one cubic Bezier. trim trims by curve distance from the start and/or end and returns another path dictionary.

```
#let path = kurvst.from-cubic(segment)
#let trimmed = kurvst.trim(path, start-outset: 0.15, end-outset: 0.1)
```

intersections(a, b) returns transverse crossings sorted by arc distance along a. Each record includes point, distance-a, distance-b, segment indices, and local segment parameters. Path-endpoint and tangential contacts are omitted, so the distances can be passed directly to path-splitting logic.

hobby-through(start, through, end) builds a smooth open curve through three points; segments returns the two cubic halves split at through. hobby-spline(points) does the same for any open point sequence with at least two points. Both return path dictionaries and can be passed directly to path-level helpers.

```
#let spline = kurvst.hobby-spline((
  (0.0, 0.0),
  (0.9, 0.8),
  (1.8, -0.3),
  (2.8, 0.4),
))
#let shifted = kurvst.parallel(spline, distance: 0.14)
#let wiggle = kurvst.pattern(
  spline,
  pattern: kurvst.wave(samples-per-period: 24),
  amplitude: 0.1,
  wavelength: 0.55,
)
#cetz.canvas({
  kurvst.to-cetz(spline, stroke: rgb("#bbbbbb") + 0.45pt)
  kurvst.to-cetz(shifted, stroke: rgb("#1b7f4c") + 0.6pt)
  kurvst.to-cetz(wiggle, stroke: rgb("#355c9a") + 0.55pt)
})
```

split-through combines Hobby spline construction with endpoint trimming and returns one path part between each consecutive point. Consumers such as Linnest can wrap it for graph-edge geometry.

14.4 Path Patterns

`pattern` generates a one-dimensional pattern along any path dictionary. Built-ins are regular Typst dictionaries:

```
#let wave = kurvst.wave()
#let zigzag = kurvst.zigzag()
#let coil = kurvst.coil(longitudinal-scale: 1.6)
```

String names "wave", "zigzag", and "coil" are accepted for convenience, but they are resolved in Typst before calling `wasm`.

Custom patterns use the same object shape:

```
#let hook = (
  kind: "points",
  name: "hook",
  interpolation: "linear",
  points: (
    (at: 0, x: 0, y: 0),
    (at: 0.25, x: 0.15, y: 1),
    (at: 0.5, x: 0, y: 0),
    (at: 0.75, x: -0.15, y: -1),
    (at: 1, x: 0, y: 0),
  ),
)
```

`at` is the phase position inside one wavelength, from 0 to 1. The `x` coordinate offsets along the path tangent and `y` offsets along the path normal; both are scaled by amplitude. If `at` is omitted, points are spaced evenly. Use `interpolation: "linear"` for corners and `"smooth"` for a spline through sampled points.

`endpoint-ramp: true` tapers amplitude at anchored endpoints. This is useful for coils, whose longitudinal offset would otherwise put the first and last visible points inside the turn near nodes.

```
#let base = kurvst.from-cubic(segment)
#let path = kurvst.pattern(
  base,
  pattern: hook,
  amplitude: 0.15,
  wavelength: 0.7,
)
#native-scene({
  native-cubics(kurvst.segments(base), stroke: rgb("#c8c8c8") + 0.45pt)
  native-polyline(kurvst.points(path), stroke: rgb("#1b7f4c") + 0.8pt)
})
```

14.5 Parallel Paths

`parallel` uses Kurbo's offset curve fitter to produce a path at a fixed normal distance from the source path. Positive distances follow the left normal of the path direction; negative distances follow the right normal. `start-outset` and `end-outset` trim the fitted path by arc length after the offset is computed.

```
#let base = kurvst.from-cubic(segment)
#let left = kurvst.parallel(base, distance: 0.18, start-outset: 0.35, end-outset: 0.35)
#let right = kurvst.parallel(base, distance: -0.18)
#native-scene({
  native-cubics(kurvst.segments(base), stroke: rgb("#c8c8c8") + 0.45pt)
  native-cubics(kurvst.segments(left), stroke: rgb("#1b7f4c") + 0.8pt)
})
```

```
native-cubics(kurvst.segments(right), stroke: rgb("#355c9a") + 0.8pt)
})
```

14.6 Path Layers

layer is a convenience wrapper for drawing derived visible paths. It combines side-aware offsetting, endpoint outsets, and shortening into one path-in/path-out operation. Offsetting happens first: length is a fixed visible arc length, ratio is a fraction of the full offset path length before trimming, and resolve-length decides how to combine them. The default "min" keeps whichever limit is shorter. start-outset, end-outset, and shift are arc distances on the offset path. Positive shift moves the shortened interval toward the path end; it is clamped to preserve the endpoint outsets.

```
#let base = kurvst.hobby-spline((
  (0.0, 0.0),
  (0.9, 0.8),
  (1.8, -0.3),
  (2.8, 0.4),
))
#let layer = kurvst.layer(
  base,
  offset: 0.16,
  length: 1.6,
  ratio: 0.5,
  resolve-length: "min",
  shift: 0.35,
)
#cetz.canvas({
  kurvst.to-cetz(base, stroke: rgb("#bbbbbb") + 0.45pt)
  kurvst.to-cetz(layer, stroke: rgb("#1b7f4c") + 0.8pt)
})
```

Use side-point to choose the sign of the offset from a point on the desired side of the original path, before offsetting or trimming. Drawing packages can use this to place derived layers on the same side as an edge label without knowing anything about the physics or graph style that requested the layer.

14.7 Native Drawing Primitives

Kurvst returns dictionaries and arrays. The core geometry can be drawn without CeTZ by emitting native curve content:

```
#kurvst.to-native(kurvst.from-cubic(segment),
unit: 36pt, stroke: black + 0.7pt)
```



The generated reference below keeps drawing code inline. It only uses the small common helpers above for coordinate scaling, native curve construction, point markers, and fixed-size preview blocks.

14.8 CeTZ Interoperability

The CeTZ helpers are thin adapters over the same returned geometry. Use them when the surrounding document already lives in a CeTZ canvas, or when you want CeTZ path merging and styling:

```
#cetz.canvas({
  let base = kurvst.from-cubic(segment)
```

```

    kurvst.to-cetz(base, stroke: rgb("#d72638")
+ 0.6pt)

    let path = kurvst.pattern(
      base,
      pattern: kurvst.coil(longitudinal-scale:
1.6),
      amplitude: 0.12,
      wavelength: 0.55,
    )
    kurvst.to-cetz(path, stroke: rgb("#355c9a")
+ 0.55pt)
  })

```



14.9 Generated Reference

14.10 kurvst

- append()
- center-outset()
- close()
- coil()
- cubic()
- cubic-point()
- cubic-tangent()
- cubic-to()
- elements()
- from-cubic()
- from-elements()
- hobby-spline()
- hobby-through()
- intersections()
- layer()
- length()
- line()
- line-segment()
- line-to()
- move-to()
- outset-point()
- parallel()
- path()
- pattern()
- point()
- points()
- quad()
- quad-to()
- resolve-length()
- segments()
- split-through()
- to-cetz()
- to-cetz-data()
- to-native()
- trim()

- wave()
- zigzag()

Variables

- layer-defaults

14.10.1 append

Return a path with additional fragments or elements appended.

14.10.1.1 Parameters

```
append(
  path: dictionary,
  ..parts: any
) -> dictionary
```

14.10.1.1.1 path dictionary

Base Kurvst path dictionary.

14.10.1.1.2 ..parts any

Path fragments, path elements, or element arrays to append.

14.10.2 center-outset

Compute the symmetric trim needed to center a shorter path layer.

14.10.2.1 Parameters

```
center-outset(
  base-length: int float,
  length: none int float,
  ratio: none int float,
  resolve-length: string function,
  start-outset: int float,
  end-outset: int float
) -> int float
```

14.10.2.1.1 base-length int or float

Full base path arc length.

14.10.2.1.2 length none or int or float

Fixed target visible length.

Default: none

14.10.2.1.3 ratio `none` or `int` or `float`

Relative target visible length as a fraction of base-length.

Default: `none`

14.10.2.1.4 resolve-length `string` or `function`

Resolution strategy for fixed and relative targets.

Default: `"min"`

14.10.2.1.5 start-outset `int` or `float`

Already-applied trim at the start of the path.

Default: `0`

14.10.2.1.6 end-outset `int` or `float`

Already-applied trim at the end of the path.

Default: `0`

14.10.3 close

Build a close path element.

14.10.3.1 Parameters

```
close(mode: string) -> dictionary
```

14.10.3.1.1 mode `string`

Native Typst curve close mode.

Default: `"straight"`

14.10.4 coil

A smooth coil path pattern.

14.10.4.1 Parameters

```
coil(  
  samples-per-period: int,  
  longitudinal-scale: int float  
) -> dictionary
```

14.10.4.1.1 samples-per-period `int`

Number of samples used to approximate one coil period.

Default: `16`

14.10.4.1.2 longitudinal-scale `int` or `float`

Horizontal scale of the coil before it is mapped onto a path.

Default: `1.25`

14.10.5 cubic

Build a cubic path fragment.

14.10.5.1 Parameters

```
cubic(  
    start: array ,  
    control-start: array ,  
    control-end: array ,  
    end: array  
) -> dictionary
```

14.10.5.1.1 start `array`

Start point.

14.10.5.1.2 control-start `array`

Cubic control point near start.

14.10.5.1.3 control-end `array`

Cubic control point near end.

14.10.5.1.4 end `array`

Endpoint.

14.10.6 cubic-point

Evaluate a cubic segment at parameter `t`.

14.10.6.1 Parameters

```
cubic-point(  
  segment: dictionary ,  
  t: int float  
) -> array
```

14.10.6.1.1 segment dictionary

Segment with start, control-start, control-end, and end.

14.10.6.1.2 t int or float

Segment parameter in the range [0, 1].

14.10.7 cubic-tangent

Evaluate the tangent of a cubic segment at parameter t.

14.10.7.1 Parameters

```
cubic-tangent(  
  segment: dictionary ,  
  t: int float  
) -> array
```

14.10.7.1.1 segment dictionary

Segment with start, control-start, control-end, and end.

14.10.7.1.2 t int or float

Segment parameter in the range [0, 1].

14.10.8 cubic-to

Build a cubic path element.

14.10.8.1 Parameters

```
cubic-to(  
  control-start: array ,  
  control-end: array ,  
  end: array  
) -> dictionary
```

14.10.8.1.1 control-start array

Cubic control point near the start point.

14.10.8.1.2 control-end array

Cubic control point near the endpoint.

14.10.8.1.3 end array

Cubic endpoint.

14.10.9 elements

Return the command elements that make up a Kurvst path.

14.10.9.1 Parameters

```
elements(path: dictionary) -> array
```

14.10.9.1.1 path dictionary

Kurvst path dictionary to inspect.

14.10.10 from-cubic

Build a path fragment from a cubic segment dictionary.

14.10.10.1 Parameters

```
from-cubic(segment: dictionary) -> dictionary
```

14.10.10.1.1 segment dictionary

Segment with start, control-start, control-end, and end.

14.10.11 from-elements

Build a path dictionary from an existing element array.

14.10.11.1 Parameters

```
from-elements(elements: array) -> dictionary
```

14.10.11.1.1 elements array

Array of Kurvst path elements.

14.10.12 hobby-spline

Construct a Hobby spline through an arbitrary point sequence.

14.10.12.1 Parameters

```
hobby-spline(  
  points: array ,  
  omega: float ,  
  accuracy: float  
) -> dictionary
```

14.10.12.1.1 points array

Two or more points for the open spline to pass through.

14.10.12.1.2 omega float

Hobby curl/tension parameter.

Default: 1.0

14.10.12.1.3 accuracy float

Geometry approximation accuracy passed to the Rust geometry engine.

Default: 0.001

14.10.13 hobby-through

Construct a cubic Hobby path through three points.

14.10.13.1 Parameters

```
hobby-through(  
  start: array ,  
  through: array ,  
  end: array ,  
  omega: float ,  
  accuracy: float  
) -> dictionary
```

14.10.13.1.1 start array

Start point.

14.10.13.1.2 through array

Intermediate point that the curve passes through.

14.10.13.1.3 end array

Endpoint.

14.10.13.1.4 omega float

Hobby curl/tension parameter.

Default: 1.0

14.10.13.1.5 accuracy float

Geometry approximation accuracy passed to the Rust geometry engine.

Default: 0.001

14.10.14 intersections

Find transverse crossings between two paths, sorted by arc distance along the first path.

14.10.14.1 Parameters

```
intersections(  
  a: dictionary ,  
  b: dictionary ,  
  accuracy: float  
) -> array
```

14.10.14.1.1 a dictionary

First Kurvst path dictionary.

14.10.14.1.2 b dictionary

Second Kurvst path dictionary.

14.10.14.1.3 accuracy float

Absolute geometry and arc-length tolerance.

Default: 0.001

14.10.15 layer

Build a derived visible path layer.

14.10.15.1 Parameters

```
layer(  
  path: dictionary ,  
  offset: int float ,  
  length: none int float ,  
  ratio: none int float ,  
  resolve-length: string function ,  
  shift: int float ,  
  start-outset: int float ,  
  end-outset: int float ,  
  side-point: none array ,  
  accuracy: float ,  
  optimize: bool  
) -> dictionary
```

14.10.15.1.1 path dictionary

Base Kurvst path dictionary.

14.10.15.1.2 offset int or float

Signed normal offset distance.

Default: 0

14.10.15.1.3 length none or int or float

Fixed target visible length.

Default: none

14.10.15.1.4 ratio none or int or float

Relative target visible length as a fraction of the full offset path length.

Default: none

14.10.15.1.5 resolve-length `string` or `function`

Resolution strategy for fixed and relative targets.

Default: `"min"`

14.10.15.1.6 shift `int` or `float`

Arc-length displacement on the offset path; positive moves toward its end.

Default: `0`

14.10.15.1.7 start-outset `int` or `float`

Arc length removed from the start.

Default: `0`

14.10.15.1.8 end-outset `int` or `float`

Arc length removed from the end.

Default: `0`

14.10.15.1.9 side-point `none` or `array`

Optional point used to choose the sign of offset.

Default: `none`

14.10.15.1.10 accuracy `float`

Geometry approximation accuracy passed to the Rust geometry engine.

Default: `0.001`

14.10.15.1.11 optimize `bool`

Let Kurbo simplify/optimize fitted parallel paths.

Default: `true`

14.10.16 length

Compute the arc length of a path dictionary.

14.10.16.1 Parameters

```
length(  
  path: dictionary ,  
  accuracy: float  
) -> int float
```

14.10.16.1.1 path dictionary

Kurvst path dictionary to measure.

14.10.16.1.2 accuracy float

Arc-length approximation accuracy passed to the Rust geometry engine.

Default: 0.001

14.10.17 line

Build a straight-line path fragment.

14.10.17.1 Parameters

```
line(  
  start: array ,  
  end: array  
) -> dictionary
```

14.10.17.1.1 start array

Start point.

14.10.17.1.2 end array

Endpoint.

14.10.18 line-segment

Build a cubic segment dictionary for a straight line.

14.10.18.1 Parameters

```
line-segment(  
  start: array ,  
  end: array  
) -> dictionary
```

14.10.18.1.1 start array

Start point.

14.10.18.1.2 end array

Endpoint.

14.10.19 line-to

Build a line path element.

14.10.19.1 Parameters

```
line-to(end: array) -> dictionary
```

14.10.19.1.1 end array

Line endpoint.

14.10.20 move-to

Build a move path element.

14.10.20.1 Parameters

```
move-to(start: array) -> dictionary
```

14.10.20.1.1 start array

New current point and subpath start.

14.10.21 outset-point

Return from moved toward toward by distance.

14.10.21.1 Parameters

```
outset-point(  
  from: array ,  
  toward: array ,  
  distance: int float  
) -> array
```

14.10.21.1.1 from array

Point to move.

14.10.21.1.2 toward array

Target point that defines the direction.

14.10.21.1.3 distance int or float

Distance to move from from toward toward.

Default: 0

14.10.22 parallel

Generate a parallel path for a path.

14.10.22.1 Parameters

```
parallel(  
  path: dictionary,  
  distance: int float,  
  start-outset: int float,  
  end-outset: int float,  
  accuracy: float,  
  optimize: bool  
) -> dictionary
```

14.10.22.1.1 path dictionary

Base Kurvst path dictionary.

14.10.22.1.2 distance int or float

Signed normal offset distance.

Default: 0

14.10.22.1.3 start-outset int or float

Arc length removed from the start of the offset path.

Default: 0

14.10.22.1.4 end-outset `int` or `float`

Arc length removed from the end of the offset path.

Default: `0`

14.10.22.1.5 accuracy `float`

Geometry approximation accuracy passed to the Rust geometry engine.

Default: `0.001`

14.10.22.1.6 optimize `bool`

Let Kurbo simplify/optimize the fitted path.

Default: `true`

14.10.23 path

Build a path dictionary from path fragments or elements.

14.10.23.1 Parameters

```
path(..parts: any) -> dictionary
```

14.10.23.1.1 ..parts `any`

Path fragments, path elements, or element arrays to concatenate.

14.10.24 pattern

Apply a repeated path pattern to a base path.

14.10.24.1 Parameters

```
pattern(  
  path: dictionary,  
  pattern: string dictionary,  
  amplitude: int float,  
  wavelength: int float,  
  phase: int float,  
  samples-per-period: int,  
  coil-longitudinal-scale: int float,  
  anchor-start: bool,  
  anchor-end: bool,  
  accuracy: float  
) -> dictionary
```

14.10.24.1.1 **path** dictionary

Base Kurvst path dictionary.

14.10.24.1.2 **pattern** string or dictionary

Pattern dictionary or built-in pattern name.

Default: "wave"

14.10.24.1.3 **amplitude** int or float

Normal amplitude of the pattern in path units.

Default: 0.1

14.10.24.1.4 **wavelength** int or float

Arc length of one pattern period.

Default: 1.0

14.10.24.1.5 **phase** int or float

Initial phase offset in pattern periods.

Default: 0

14.10.24.1.6 **samples-per-period** int

Samples per period for string-resolved smooth patterns.

Default: 16

14.10.24.1.7 **coil-longitudinal-scale** int or float

Longitudinal scale used when resolving the built-in coil pattern.

Default: 1.25

14.10.24.1.8 **anchor-start** bool

Force the generated path to start on the base path.

Default: true

14.10.24.1.9 anchor-end `bool`

Force the generated path to end on the base path.

Default: `true`

14.10.24.1.10 accuracy `float`

Geometry approximation accuracy passed to the Rust geometry engine.

Default: `0.001`

14.10.25 point

Build a numeric point tuple.

14.10.25.1 Parameters

```
point(  
  x: int float ,  
  y: int float  
) -> array
```

14.10.25.1.1 x `int` or `float`

X coordinate.

14.10.25.1.2 y `int` or `float`

Y coordinate.

14.10.26 points

Return the points visited by a Kurvst path's command stream.

14.10.26.1 Parameters

```
points(path: dictionary) -> array
```

14.10.26.1.1 path `dictionary`

Kurvst path dictionary to inspect.

14.10.27 quad

Build a quadratic path fragment.

14.10.27.1 Parameters

```
quad(  
  start: array ,  
  control: array ,  
  end: array  
) -> dictionary
```

14.10.27.1.1 start array

Start point.

14.10.27.1.2 control array

Quadratic control point.

14.10.27.1.3 end array

Endpoint.

14.10.28 quad-to

Build a quad path element.

14.10.28.1 Parameters

```
quad-to(  
  control: array ,  
  end: array  
) -> dictionary
```

14.10.28.1.1 control array

Quadratic control point.

14.10.28.1.2 end array

Quadratic endpoint.

14.10.29 resolve-length

Resolve a fixed and relative visible path length.

14.10.29.1 Parameters

```
resolve-length(  
    base-length: int float,  
    length: none int float,  
    ratio: none int float,  
    method: string function  
) -> none int float
```

14.10.29.1.1 base-length int or float

Full base path arc length.

14.10.29.1.2 length none or int or float

Fixed target arc length.

Default: none

14.10.29.1.3 ratio none or int or float

Relative target length as a fraction of base-length.

Default: none

14.10.29.1.4 method string or function

Resolution strategy for fixed and relative targets.

Default: "min"

14.10.30 segments

Return drawable cubic segments for any Kurvst path dictionary.

14.10.30.1 Parameters

```
segments(path: dictionary) -> array
```

14.10.30.1.1 path dictionary

Kurvst path dictionary to convert.

14.10.31 split-through

Split a path through a point sequence into per-span paths.

14.10.31.1 Parameters

```
split-through(  
  points: array ,  
  omega: float ,  
  start-outset: int float ,  
  end-outset: int float ,  
  accuracy: float  
) -> dictionary
```

14.10.31.1.1 points array

Two or more points for the curve to pass through.

14.10.31.1.2 omega float

Hobby curl/tension parameter.

Default: 1.0

14.10.31.1.3 start-outset int or float

Arc length removed from the first span start.

Default: 0

14.10.31.1.4 end-outset int or float

Arc length removed from the last span end.

Default: 0

14.10.31.1.5 accuracy float

Geometry approximation accuracy passed to the Rust geometry engine.

Default: 0.001

14.10.32 to-cetz

Draw a path dictionary through CeTZ.

14.10.32.1 Parameters

```
to-cetz(  
  path: dictionary ,  
  unit: int float length ratio ,  
  ..style: any  
) -> content
```

14.10.32.1.1 path dictionary

Kurvst path dictionary to draw.

14.10.32.1.2 unit int or float or length or ratio

Coordinate multiplier for emitted CeTZ points.

Default: 1

14.10.32.1.3 ..style any

CeTZ draw style arguments forwarded to merge-path.

14.10.33 to-cetz-data

Emit a Kurvst path as CeTZ path data.

14.10.33.1 Parameters

```
to-cetz-data(  
  path: dictionary ,  
  unit: int float length ratio  
) -> array
```

14.10.33.1.1 path dictionary

Kurvst path dictionary to convert.

14.10.33.1.2 unit int or float or length or ratio

Coordinate multiplier for emitted CeTZ points.

Default: 1

14.10.34 to-native

Emit a Kurvst path as native Typst curve content.

14.10.34.1 Parameters

```
to-native(  
  path: dictionary ,  
  unit: int float length ratio ,  
  ..style: any  
) -> content
```

14.10.34.1.1 **path** dictionary

Kurvst path dictionary to emit.

14.10.34.1.2 **unit** `int` or `float` or `length` or `ratio`

Coordinate multiplier for emitted Typst curve points.

Default: `1`

14.10.34.1.3 **..style** any

Native curve style arguments.

14.10.35 **trim**

Trim a path by arc length from each end.

14.10.35.1 **Parameters**

```
trim(  
  path: dictionary ,  
  start-outset: int float ,  
  end-outset: int float ,  
  accuracy: float  
) -> dictionary
```

14.10.35.1.1 **path** dictionary

Kurvst path dictionary to trim.

14.10.35.1.2 **start-outset** `int` or `float`

Arc length removed from the start.

Default: `0`

14.10.35.1.3 **end-outset** `int` or `float`

Arc length removed from the end.

Default: `0`

14.10.35.1.4 accuracy `float`

Arc-length approximation accuracy passed to the Rust geometry engine.

Default: `0.001`

14.10.36 wave

A smooth sinusoidal path pattern.

14.10.36.1 Parameters

`wave(samples-per-period: int) -> dictionary`

14.10.36.1.1 samples-per-period `int`

Number of samples used to approximate one wave period.

Default: `16`

14.10.37 zigzag

A straight-segment triangular path pattern.

14.10.37.1 Parameters

`zigzag()` -> `dictionary`

14.10.38 layer-defaults `dictionary`

Default geometry options for derived path layers.

15 Version history

History coverage

GammaLoop does not yet have a consolidated changelog. Repository tags and their linked pull requests are the available release record. This page makes that gap explicit instead of presenting development documentation as a complete release history.

15.1 Components and version sources

- Repository revision: GammaLoop tags and releases.
- Python distribution: `pyproject.toml`.
- Core Rust library: `gammalooprs` package metadata.
- Rust/Python application API: `gammaloop-api` package metadata.

These components can evolve independently. Record all of them when reporting a result or asking for support.

15.2 Choosing the matching documentation

The `latest` channel follows current development. Documentation under `snapshots/<tag>` stays with a tagged release. Use the snapshot matching your checkout whenever command options, state files, or API signatures differ from `latest`.

15.3 Upgrade checklist

Release notes currently live with repository tags and their linked pull requests rather than in one consolidated changelog. Review them before upgrading, especially when you depend on persisted states, CLI scripts, Python bindings, or numerical results. Keep a copy of valuable state directories and re-run validation samples after changing versions.

15.4 Reproducibility record

Include the repository tag or commit, the Python distribution version, the `gammaloops` version, the run card, and any relevant settings overrides. This makes a calculation easier to reproduce and distinguishes a software change from a configuration change.

Python API reference

The supported Python packages available in this version are listed below. The HTML manual provides a separate page for every public class, function, and constant; this printable edition keeps a compact inventory. Rust APIs use canonical Rustdoc in the HTML manual.

gammaloop-python

Exports registered by gammaloop.

AdditionalWeight

Named auxiliary complex weight attached to a generated event.

Named auxiliary complex weight attached to a generated event.

class AdditionalWeight:

Requires features: python_api, python_abi, python_stubgen

key

Kind: Getter

def key(self) -> str:

Stable weight name, optionally followed by colon-separated identifiers.

value

Kind: Getter

def value(self) -> Any:

Complex auxiliary event weight associated with ``key``.

Exhaustive reference · Source

BatchEvaluationResult

Per-sample evaluations paired with one observable snapshot for the complete batch.

Per-sample evaluations paired with one observable snapshot for the complete batch.

class BatchEvaluationResult:

Requires features: python_api, python_abi, python_stubgen

samples

Kind: Getter

def samples(self) -> list[SampleEvaluationResult]:

Evaluation records in the same order as the requested samples.

observables

Kind: Getter

def observables(self) -> dict:

Observable snapshots accumulated across the complete sample batch.

numerical_stability

Kind: Getter

def numerical_stability(self) -> Optional[dict]:

__str__

Kind: Method

```
def __str__(self) -> str:
```

Return a human-readable batch and observable summary.

__repr__

Kind: Method

```
def __repr__(self) -> str:
```

Return the human-readable batch and observable summary.

Exhaustive reference · Source

CutInfo

Process, graph, orientation, and loop-basis identifiers for one cut event.

Process, graph, orientation, and loop-basis identifiers for one cut event.

class CutInfo:

Requires features: python_api, python_abi, python_stubgen

incoming_pdgs

Kind: Getter

```
def incoming_pdgs(self) -> list[int]:
```

PDG identifiers aligned with ``Event.incoming\_momenta``.

outgoing_pdgs

Kind: Getter

```
def outgoing_pdgs(self) -> list[int]:
```

PDG identifiers aligned with ``Event.outgoing\_momenta``.

cut_id

Kind: Getter

```
def cut_id(self) -> int:
```

Zero-based cut identifier within the selected graph.

graph_id

Kind: Getter

```
def graph_id(self) -> int:
```

Zero-based graph identifier within the integrand.

graph_group_id

Kind: Getter

```
def graph_group_id(self) -> Optional[int]:
```

Graph-group identifier, when group metadata is available.

orientation_id

Kind: Getter

```
def orientation_id(self) -> Optional[int]:
```

Causal-flow orientation identifier, when sampled explicitly.

lmb_channel_id

Kind: Getter

```
def lmb_channel_id(self) -> Optional[int]:
```

Loop-momentum-basis multichannel identifier, when sampled explicitly.

lmb_channel_edge_ids

Kind: Getter

```
def lmb_channel_edge_ids(self) -> Optional[list[int]]:
```

Edge identifiers defining the selected loop-momentum basis, when available.

Exhaustive reference · Source

DotExportSettings

Controls which graph details and algebraic transformations are included in DOT exports.

Controls which graph details and algebraic transformations are included in DOT exports.

```
class DotExportSettings:
```

Requires features: python_api, python_abi, python_stubgen

combine_diagrams

Kind: Getter

```
def combine_diagrams(self) -> bool:
```

Write all diagrams of an integrand to one file during filesystem export.

combine_diagrams

Kind: Setter

```
def combine_diagrams(self, value: bool) -> None:
```

Write all diagrams of an integrand to one file during filesystem export.

value

Kind: Parameter

bool

with_uv

Kind: Getter

```
def with_uv(self) -> bool:
```

Request UV counterterm graph output; currently retained for compatibility.

with_uv

Kind: Setter

```
def with_uv(self, value: bool) -> None:
```

Request UV counterterm graph output; currently retained for compatibility.

value

Kind: Parameter

bool

output_full_numerator**Kind:** Getter

```
def output_full_numerator(self) -> bool:
```

Add the complete symbolic numerator as the graph-level `full\_num` field.

output_full_numerator**Kind:** Setter

```
def output_full_numerator(self, value: bool) -> None:
```

Add the complete symbolic numerator as the graph-level `full\_num` field.

value**Kind:** Parameter

bool

split_xs_by_initial_states**Kind:** Getter

```
def split_xs_by_initial_states(self) -> bool:
```

Split cross-section graphs by distinct initial-state assignments.

split_xs_by_initial_states**Kind:** Setter

```
def split_xs_by_initial_states(self, value: bool) -> None:
```

Split cross-section graphs by distinct initial-state assignments.

value**Kind:** Parameter

bool

do_gamma_algebra**Kind:** Getter

```
def do_gamma_algebra(self) -> bool:
```

Simplify gamma-matrix algebra in the full numerator before formatting it.

do_gamma_algebra**Kind:** Setter

```
def do_gamma_algebra(self, value: bool) -> None:
```

Simplify gamma-matrix algebra in the full numerator before formatting it.

value**Kind:** Parameter

bool

do_color_algebra**Kind:** Getter

```
def do_color_algebra(self) -> bool:
```

Simplify color algebra in the full numerator before formatting it.

do_color_algebra**Kind:** Setter

```
def do_color_algebra(self, value: bool) -> None:
```

Simplify color algebra in the full numerator before formatting it.

value**Kind:** Parameter

bool

include_autogenerated_fields**Kind:** Getter

```
def include_autogenerated_fields(self) -> bool:
```

Include vertex and edge fields whose values GammaLoop generated automatically.

include_autogenerated_fields**Kind:** Setter

```
def include_autogenerated_fields(self, value: bool) -> None:
```

Include vertex and edge fields whose values GammaLoop generated automatically.

value**Kind:** Parameter

bool

__new__**Kind:** AssociatedFunction

```
def __new__(cls) -> DotExportSettings:
```

Construct DOT export settings with GammaLoop's defaults.

Exhaustive reference · Source

EvaluationResult

Single-sample evaluation paired with the observable snapshot for that sample.

Single-sample evaluation paired with the observable snapshot for that sample.

class EvaluationResult:

Requires features: python_api, python_abi, python_stubgen

sample**Kind:** Getter

```
def sample(self) -> SampleEvaluationResult:
```

Evaluation record for the requested sample.

integrand_result**Kind:** Getter

```
def integrand_result(self) -> complex:
```

Complex integrand value before applying the parameterization Jacobian.

integrator_weight**Kind:** Getter

```
def integrator_weight(self) -> float:
```

Monte Carlo weight supplied by the integrator, excluding the parameterization Jacobian.

generated_event_count**Kind:** Getter

```
def generated_event_count(self) -> Optional[int]:
```

Number of candidate events generated, or ``None`` when metadata was omitted.

accepted_event_count**Kind:** Getter

```
def accepted_event_count(self) -> Optional[int]:
```

Number of generated events accepted by selectors, or ``None`` without metadata.

event_processing_time_seconds**Kind:** Getter

```
def event_processing_time_seconds(self) -> Optional[float]:
```

Time spent building and selecting events, in seconds, or ``None`` without metadata.

parameterization_jacobian**Kind:** Getter

```
def parameterization_jacobian(self) -> Optional[float]:
```

Sample parameterization Jacobian, or ``None`` when no Jacobian was supplied.

is_nan**Kind:** Getter

```
def is_nan(self) -> Optional[bool]:
```

Whether evaluation metadata flagged a non-finite result, or ``None`` without metadata.

stability_results**Kind:** Getter

```
def stability_results(self) -> Optional[list[StabilityResult]]:
```

Per-precision stability attempts, or ``None`` when metadata was omitted.

event_groups**Kind:** Getter

```
def event_groups(self) -> list[EventGroup]:
```

Correlated event groups produced while evaluating this sample.

observables**Kind:** Getter

```
def observables(self) -> dict:
```

Observable snapshots produced from the same Monte Carlo sample.

__str__

Kind: Method

```
def __str__(self) -> str:
```

Return a human-readable evaluation and observable summary.

__repr__

Kind: Method

```
def __repr__(self) -> str:
```

Return the human-readable evaluation and observable summary.

Exhaustive reference · Source

Event

Accepted cut event with momenta, its primary weight, and auxiliary weights.

Accepted cut event with momenta, its primary weight, and auxiliary weights.

class Event:

Requires features: python_api, python_abi, python_stubgen

incoming_momenta

Kind: Getter

```
def incoming_momenta(self) -> list[FourMomentum]:
```

Incoming four-momenta, aligned with ``cut\_info.incoming\_pdgs``.

outgoing_momenta

Kind: Getter

```
def outgoing_momenta(self) -> list[FourMomentum]:
```

Outgoing four-momenta, aligned with ``cut\_info.outgoing\_pdgs``.

cut_info

Kind: Getter

```
def cut_info(self) -> CutInfo:
```

Cut, graph, orientation, and loop-basis identifiers for this event.

weight

Kind: Getter

```
def weight(self) -> Any:
```

Primary complex event weight.

additional_weights

Kind: Getter

```
def additional_weights(self) -> list[AdditionalWeight]:
```

Named auxiliary complex weights such as threshold-counterterm contributions.

__str__

Kind: Method

```
def __str__(self) -> str:
```

Return a human-readable event summary.

__repr__

Kind: Method

```
def __repr__(self) -> str:
```

Return the human-readable event summary.

[Exhaustive reference](#) · [Source](#)

EventGroup

Correlated accepted events produced by one graph group for one sample.

Correlated accepted events produced by one graph group for one sample.

```
class EventGroup:
```

Requires features: `python_api`, `python_abi`, `python_stubgen`

events

Kind: Getter

```
def events(self) -> list[Event]:
```

Correlated accepted events in this group.

__str__

Kind: Method

```
def __str__(self) -> str:
```

Return a human-readable summary of the grouped events.

__repr__

Kind: Method

```
def __repr__(self) -> str:
```

Return the human-readable grouped-event summary.

[Exhaustive reference](#) · [Source](#)

FourMomentum

One energy-momentum four-vector returned with a generated event.

One energy-momentum four-vector returned with a generated event.

```
class FourMomentum:
```

Requires features: `python_api`, `python_abi`, `python_stubgen`

e

Kind: Getter

```
def e(self) -> float:
```

Energy component.

px

Kind: Getter

```
def px(self) -> float:
```

Momentum along the x axis.

py

Kind: Getter

```
def py(self) -> float:
Momentum along the y axis.
```

pz

Kind: Getter

```
def pz(self) -> float:
Momentum along the z axis.
```

Exhaustive reference · Source

GammaLoopAPI

Load, inspect, and evaluate one mutable GammaLoop session.

Load, inspect, and evaluate one mutable GammaLoop session.

One instance owns a GammaLoop state, run history, CLI settings, default runtime settings, and session state. Calls to ``run`` and the evaluation methods all act on that same in-memory session.

Notes

``read\_only\_state=True`` prevents writes inside the active state directory; it does not make this Python object immutable. Commands may still change in-memory settings, processes, or run history. Create separate instances when independent sessions are required.

```
class GammaLoopAPI:
```

Requires features: python_api, python_abi, python_stubgen

read_only_state

Kind: Getter

```
def read_only_state(self) -> bool:
```

active_state_folder

Kind: Getter

```
def active_state_folder(self) -> str:
```

__new__

Kind: AssociatedFunction

```
def __new__(cls, state_folder: Optional[str | os.PathLike | pathlib.Path] = None,
boot_commands_path: Optional[str | os.PathLike | pathlib.Path] = None, model_file:
Optional[str | os.PathLike | pathlib.Path] = None, trace_logs_filename: Optional[str]
= None, level: Optional[LogLevel] = None, logfile_level: Optional[LogLevel] = None,
logging_prefix: object | None = None, read_only_state: bool = False,
settings_global_path: Optional[str | os.PathLike | pathlib.Path] = None,
settings_runtime_defaults_path: Optional[str | os.PathLike | pathlib.Path] = None,
clean_state: bool = False) -> GammaLoopAPI:
```

Load or create a GammaLoop state and initialize its CLI session.

Parameters

state_folder : path-like, optional

State directory to load or create. The default is ``./gammaloop\_state``.

boot_commands_path : path-like, optional
 TOML run card whose commands are applied during startup.

model_file : path-like, optional
 Model file override used while loading or initializing the state.

trace_logs_filename : str, optional
 File receiving native trace records for this session.

level : LogLevel, optional
 Terminal log-level override for this session.

logfile_level : LogLevel, optional
 File log-level override for this session.

logging_prefix : object, optional
 Native logging-prefix configuration.

read_only_state : bool, default=False
 Prevent writes whose target lies inside the active state directory and disable file logging there. In-memory session changes remain possible.

settings_global_path : path-like, optional
 TOML file overriding the global settings loaded at startup.

settings_runtime_defaults_path : path-like, optional
 TOML file overriding the default runtime settings loaded at startup.

clean_state : bool, default=False
 Remove the resolved state path before startup. This is destructive and cannot be combined with ``read\_only\_state=True``.

Returns

GammaLoopAPI

A stateful API instance sharing one state, history, and settings session.

Raises

Exception

If startup options conflict, the state or settings cannot be loaded, a boot command fails, or a boot card requests process exit.

Examples

Open an existing generated state without permitting writes to it:

```

```python
api = GammaLoopAPI(state_folder="./state", read_only_state=True)
```

```

state_folder

Kind: Parameter

Optional[str | os.PathLike | pathlib.Path]

Default: None

State directory to load or create. The default is ``./gammaloop\_state``.

boot_commands_path

Kind: Parameter

Optional[str | os.PathLike | pathlib.Path]

Default: None

TOML run card whose commands are applied during startup.

model_file**Kind:** Parameter

Optional[str | os.PathLike | pathlib.Path]

Default: None

Model file override used while loading or initializing the state.

trace_logs_filename**Kind:** Parameter

Optional[str]

Default: None

File receiving native trace records for this session.

level**Kind:** Parameter

Optional[LogLevel]

Default: None

Terminal log-level override for this session.

logfile_level**Kind:** Parameter

Optional[LogLevel]

Default: None

File log-level override for this session.

logging_prefix**Kind:** Parameter

object | None

Default: None

Native logging-prefix configuration.

read_only_state**Kind:** Parameter

bool

Default: False

Prevent writes whose target lies inside the active state directory and disable file logging there. In-memory session changes remain possible.

settings_global_path**Kind:** Parameter

Optional[str | os.PathLike | pathlib.Path]

Default: None

TOML file overriding the global settings loaded at startup.

settings_runtime_defaults_path

Kind: Parameter

Optional[str | os.PathLike | pathlib.Path]

Default: None

TOML file overriding the default runtime settings loaded at startup.

clean_state

Kind: Parameter

bool

Default: False

Remove the resolved state path before startup. This is destructive and cannot be combined with ``read\_only\_state=True``.

is_read_only_state

Kind: Method

```
def is_read_only_state(self) -> bool:
```

state_access_mode

Kind: Method

```
def state_access_mode(self) -> str:
```

evaluate_sample

Kind: Method

```
def evaluate_sample(self, point: Sequence[float], process_id: Optional[int] = None,
    integrand_name: Optional[str] = None, use_arb_prec: bool = False, minimal_output:
    bool = False, return_events: Optional[bool] = None, momentum_space: bool = False,
    integrator_weight: Optional[float] = None, discrete_dim: Optional[Sequence[int]] =
    None, graph_name: Optional[str] = None, orientation: Optional[int] = None) ->
    EvaluationResult:
```

Evaluate one integration or momentum-space sample.

Parameters

point : Sequence[float]

Coordinates for one sample. In integration space, the length must match the selected integrand and ``discrete\_dim``. In momentum space, values are grouped as ``(px, py, pz)`` with one triplet per independent loop momentum. Energy components and external momenta are not accepted.

process_id : int, optional

Process containing the integrand. Supply this when selection is ambiguous.

integrand_name : str, optional

Integrand to evaluate. Supply this when selection is ambiguous.

use_arb_prec : bool, default=False

Force arbitrary-precision (Arb) internal evaluation instead of following the configured stability ladder.

Returned numeric fields remain ``float64``.

minimal_output : bool, default=False

Omit the optional evaluation metadata from the returned sample.

return_events : bool, optional

Temporarily override event generation for this call. The integrand setting

is restored afterward.

`momentum_space` : bool, default=False
 Interpret ``point`` as consecutive spatial loop-momentum ``(px, py, pz)`` triplets instead of integration-space coordinates.

`integrator_weight` : float, optional
 Weight associated with this sample. The default is 1.0.

`discrete_dim` : Sequence[int], optional
 Discrete integration coordinates used to determine the expected dimension.

`graph_name` : str, optional
 Graph selected for momentum-space evaluation.

`orientation` : int, optional
 Orientation index for ``graph\_name`` in momentum-space evaluation.

Returns

EvaluationResult

The sample evaluation and the observable snapshot for its one-row batch.

Raises

Exception

If integrand selection is ambiguous or invalid, dimensions do not match, graph or orientation selection is invalid, or warm-up/evaluation fails.

Notes

With ``use\_arb\_prec=False``, evaluation follows the configured ``f64``, ``f128``, and arbitrary-precision stability ladder. ``use\_arb\_prec=True`` forces arbitrary-precision (Arb) internal evaluation. Python-visible numeric fields use the package's ``float64`` output contract. Evaluation may warm the integrand and update in-memory caches or observable snapshots even in a read-only-state session.

See Also

GammaLoop's sample-evaluation contract in the interface guide and the maintained events-and-observables example.

Examples

Evaluate one point from the repository's differential API regression fixture:

```

python
from pathlib import Path

from gammaloop import GammaLoopAPI

example = Path("examples/api/python/epem_a_ddxg_xs_L0")
api = GammaLoopAPI(
    state_folder=example / "state",
    boot_commands_path=example / "run.toml",
    clean_state=True,
)
point = [0.17, 0.31, 0.53, 0.23, 0.41, 0.67]
result = api.evaluate_sample(point, return_events=True)
assert result.parameterization_jacobian is not None

```

```
assert result.stability_results
assert result.event_groups
...
```

This card verifies API and event plumbing. Its powered coupling selector is not an independently reviewed perturbative-order definition or normalization benchmark.

point

Kind: Parameter

Sequence[float]

Coordinates for one sample. In integration space, the length must match the selected integrand and ``discrete\_dim``. In momentum space, values are grouped as ``(px, py, pz)`` with one triplet per independent loop momentum. Energy components and external momenta are not accepted.

process_id

Kind: Parameter

Optional[int]

Default: None

Process containing the integrand. Supply this when selection is ambiguous.

integrand_name

Kind: Parameter

Optional[str]

Default: None

Integrand to evaluate. Supply this when selection is ambiguous.

use_arb_prec

Kind: Parameter

bool

Default: False

Force arbitrary-precision (Arb) internal evaluation instead of following the configured stability ladder. Returned numeric fields remain ``float64``.

minimal_output

Kind: Parameter

bool

Default: False

Omit the optional evaluation metadata from the returned sample.

return_events

Kind: Parameter

Optional[bool]

Default: None

Temporarily override event generation for this call. The integrand setting is restored afterward.

momentum_space

Kind: Parameter

bool

Default: False

Interpret ``point`` as consecutive spatial loop-momentum ``(px, py, pz)`` triplets instead of integration-space coordinates.

integrator_weight

Kind: Parameter

Optional[float]

Default: None

Weight associated with this sample. The default is 1.0.

discrete_dim

Kind: Parameter

Optional[Sequence[int]]

Default: None

Discrete integration coordinates used to determine the expected dimension.

graph_name

Kind: Parameter

Optional[str]

Default: None

Graph selected for momentum-space evaluation.

orientation

Kind: Parameter

Optional[int]

Default: None

Orientation index for ``graph\_name`` in momentum-space evaluation.

evaluate_samples

Kind: Method

```
def evaluate_samples(self, points: numpy.ndarray[numpy.float64], process_id:
Optional[int] = None, integrand_name: Optional[str] = None, use_arb_prec: bool =
False, minimal_output: bool = False, return_events: Optional[bool] = None,
momentum_space: bool = False, integrator_weights:
Optional[numpy.ndarray[numpy.float64]] = None, discrete_dims:
numpy.ndarray[numpy.unsignedinteger] | None = None, graph_names:
Optional[Sequence[Optional[str]]] = None, orientations:
Optional[Sequence[Optional[int]]] = None) -> BatchEvaluationResult:
```

Evaluate a batch of integration or momentum-space samples.

Parameters

points : numpy.ndarray[numpy.float64]

Two-dimensional array with one sample per row. Integration-space columns must match the selected integrand; momentum-space columns are flattened ``(px, py, pz)`` groups with one triplet per independent loop momentum. Energy components and external momenta are not accepted.

`process_id` : int, optional
Process containing the integrand. Supply this when selection is ambiguous.

`integrand_name` : str, optional
Integrand to evaluate. Supply this when selection is ambiguous.

`use_arb_prec` : bool, default=False
Force arbitrary-precision (Arb) internal evaluation instead of following the configured stability ladder.
Returned numeric fields remain ``float64``.

`minimal_output` : bool, default=False
Omit the optional evaluation metadata from every returned sample.

`return_events` : bool, optional
Temporarily override event generation for this call. The integrand setting is restored afterward.

`momentum_space` : bool, default=False
Interpret each row as consecutive spatial loop-momentum ``(px, py, pz)`` triplets instead of integration-space coordinates.

`integrator_weights` : numpy.ndarray[numpy.float64], optional
One weight per row. Defaults to 1.0 for every sample.

`discrete_dims` : numpy.ndarray[numpy.unsignedinteger], optional
Two-dimensional array with one row of discrete coordinates per sample.

`graph_names` : Sequence[str | None], optional
Momentum-space graph selection for each sample.

`orientations` : Sequence[int | None], optional
Momentum-space orientation selection for each sample.

Returns

BatchEvaluationResult

Per-sample evaluations and one observable snapshot for the complete batch.

Raises

Exception

If integrand selection is ambiguous or invalid, array or option lengths do not match, dimensions are invalid, or warm-up/evaluation fails.

Notes

With ``use\_arb\_prec=False``, evaluation follows the configured ``f64``, ``f128``, and arbitrary-precision stability ladder. ``use\_arb\_prec=True`` forces arbitrary-precision (Arb) internal evaluation. Python-visible numeric fields use the package's ``float64`` output contract. Evaluation may update in-memory caches or observable snapshots in a read-only-state session.

See Also

GammaLoop's sample-evaluation contract in the interface guide and the maintained events-and-observables example.

Examples

Evaluate two rows and inspect their per-sample events and batch-level histograms:

```

```python
from pathlib import Path

import numpy as np
from gammaloop import GammaLoopAPI

example = Path("examples/api/python/epem_a_ddxg_xs_L0")
api = GammaLoopAPI(
 state_folder=example / "state",
 boot_commands_path=example / "run.toml",
 clean_state=True,
)
points = np.array([
 [0.17, 0.31, 0.53, 0.23, 0.41, 0.67],
 [0.11, 0.29, 0.47, 0.19, 0.37, 0.59],
], dtype=float)
result = api.evaluate_samples(points, return_events=True)
assert len(result.samples) == 2
assert all(sample.event_groups for sample in result.samples)
assert result.observables["leading_jet_pt_hist"].sample_count == 2
assert len(result.observables["leading_jet_pt_hist"].bins) == 8
```

```

The fixture exercises the API surface; its powered coupling selector is not a validated perturbative-order or normalization benchmark.

points

Kind: Parameter

numpy.ndarray[numpy.float64]

Two-dimensional array with one sample per row. Integration-space columns must match the selected integrand; momentum-space columns are flattened `` (px, py, pz) `` groups with one triplet per independent loop momentum. Energy components and external momenta are not accepted.

process_id

Kind: Parameter

Optional[int]

Default: None

Process containing the integrand. Supply this when selection is ambiguous.

integrand_name

Kind: Parameter

Optional[str]

Default: None

Integrand to evaluate. Supply this when selection is ambiguous.

use_arb_prec

Kind: Parameter

bool

Default: False

Force arbitrary-precision (Arb) internal evaluation instead of following the configured stability ladder. Returned numeric fields remain ``float64``.

minimal_output

Kind: Parameter

bool

Default: False

Omit the optional evaluation metadata from every returned sample.

return_events

Kind: Parameter

Optional[bool]

Default: None

Temporarily override event generation for this call. The integrand setting is restored afterward.

momentum_space

Kind: Parameter

bool

Default: False

Interpret each row as consecutive spatial loop-momentum ``(px, py, pz)`` triplets instead of integration-space coordinates.

integrator_weights

Kind: Parameter

Optional[numpy.ndarray[numpy.float64]]

Default: None

One weight per row. Defaults to 1.0 for every sample.

discrete_dims

Kind: Parameter

numpy.ndarray[numpy.unsignedinteger] | None

Default: None

Two-dimensional array with one row of discrete coordinates per sample.

graph_names

Kind: Parameter

Optional[Sequence[Optional[str]]]

Default: None

Momentum-space graph selection for each sample.

orientations

Kind: Parameter

Optional[Sequence[Optional[int]]]

Default: None

Momentum-space orientation selection for each sample.

import_graphs

Kind: Method

```
def import_graphs(self, graphs: str, process_name: Optional[str] = None, process_id:
Optional[int] = None, integrand_name: Optional[str] = None, format: str = 'dot',
overwrite: bool = False, append: bool = False) -> None:
```

Import DOT graphs into a new or existing process/integrand collection.

Parameters

graphs : str

DOT file path when ``format="dot"`` or inline DOT text when
``format="string"``.

process_name, process_id : str or int, optional

Process to create or update. Inline text requires one of these selectors.

integrand_name : str, optional

Integrand within the selected process.

format : {"dot", "string"}, default="dot"

Select file-backed or inline input.

overwrite, append : bool, default=False

Replace an existing collection or append to it; these modes conflict.

Raises

Exception

If selectors conflict, the source is missing or malformed, or importing fails.

graphs

Kind: Parameter

str

DOT file path when ``format="dot"`` or inline DOT text when ``format="string"``.

process_name

Kind: Parameter

Optional[str]

Default: None

Process to create or update. Inline text requires one of these selectors.

process_id

Kind: Parameter

Optional[int]

Default: None

Process to create or update. Inline text requires one of these selectors.

integrand_name

Kind: Parameter

Optional[str]

Default: None

Integrand within the selected process.

format

Kind: Parameter

str

Default: 'dot'

Select file-backed or inline input.

overwrite

Kind: Parameter

bool

Default: False

Replace an existing collection or append to it; these modes conflict.

append

Kind: Parameter

bool

Default: False

Replace an existing collection or append to it; these modes conflict.

get_lmbs

Kind: Method

```
def get_lmbs(self, graphs: str, format: str = 'dot') -> list[list[tuple[list[int],
list[int], dict[int, tuple[list[int], list[int]]]]]]:
```

Generate loop-momentum bases for each supplied graph.

Parameters

graphs : str

DOT file path or inline DOT text, as selected by ``format``.

format : {"dot", "string"}, default="dot"

Select file-backed or inline input.

Returns

list

Per graph, a list of ``(loop\_edges, external\_edges, edge\_signatures)``
tuples. Each signature contains its loop and external coefficients.

graphs

Kind: Parameter

str

DOT file path or inline DOT text, as selected by ``format``.

format**Kind:** Parameter

str

Default: 'dot'

Select file-backed or inline input.

get_orientations**Kind:** Method

```
def get_orientations(self, graph_name: str, process_id: Optional[int] = None,
    integrand_name: Optional[str] = None) -> list[dict[int, int]]:
```

Return the causal-flow orientations generated for one graph.

Each returned dictionary maps an edge id to ``1`` (default), ``-1`` (reversed), or ``0`` (undirected). Supply process and integrand selectors when the active state does not identify a unique integrand.

Parameters

graph_name : str

Name of the graph within the selected integrand.

process_id : int, optional

Numeric process identifier; omit when process selection is unambiguous.

integrand_name : str, optional

Integrand containing the graph; omit when integrand selection is unambiguous.

Returns

list[dict[int, int]]

One edge-direction mapping per generated orientation.

graph_name**Kind:** Parameter

str

Name of the graph within the selected integrand.

process_id**Kind:** Parameter

Optional[int]

Default: None

Numeric process identifier; omit when process selection is unambiguous.

integrand_name**Kind:** Parameter

Optional[str]

Default: None

Integrand containing the graph; omit when integrand selection is unambiguous.

get_model

Kind: Method

```
def get_model(self) -> str:
```

Serialize the active physics model as JSON.

Returns

str

JSON representation of the model currently owned by this session.

evaluate

Kind: Method

```
def evaluate(self, process_id: Optional[int] = None, graphs_group_name: Optional[str] = None, result_path: Optional[str | os.PathLike | pathlib.Path] = None, numerical: bool = True, number_of_terms_in_epsilon_expansion: Optional[int] = None) -> str:
```

Evaluate one generated graph group as a symbolic or numerical expression.

Parameters

process_id : int, optional

Process containing the requested graph group.

graphs_group_name : str, optional

Group to evaluate when the current state is ambiguous.

result_path : path-like, optional

Optional destination for the evaluated expression.

numerical : bool, default=True

Evaluate numerically instead of retaining a symbolic result.

number_of_terms_in_epsilon_expansion : int, optional

Truncate the dimensional-regulator expansion to this many terms.

Returns

str

Canonical Symbolica representation of the result.

process_id

Kind: Parameter

Optional[int]

Default: None

Process containing the requested graph group.

graphs_group_name

Kind: Parameter

Optional[str]

Default: None

Group to evaluate when the current state is ambiguous.

result_path

Kind: Parameter

Optional[str | os.PathLike | pathlib.Path]

Default: None

Optional destination for the evaluated expression.

numerical

Kind: Parameter

bool

Default: True

Evaluate numerically instead of retaining a symbolic result.

number_of_terms_in_epsilon_expansion

Kind: Parameter

Optional[int]

Default: None

Truncate the dimensional-regulator expansion to this many terms.

import_model

Kind: Method

```
def import_model(self, model_specifier: str | os.PathLike | pathlib.Path,
simplify_model: bool = True) -> None:
```

Replace the active model from a GammaLoop model file or supported model source.

``simplify\_model`` applies the standard symbolic simplification pass while importing. Existing process data may no longer be compatible with a replaced model, so import the model before generating processes.

Parameters

model_specifier : path-like

Path or model specifier accepted by GammaLoop's model importer.

simplify_model : bool, default=True

Apply the standard symbolic simplification pass while importing.

model_specifier

Kind: Parameter

str | os.PathLike | pathlib.Path

Path or model specifier accepted by GammaLoop's model importer.

simplify_model

Kind: Parameter

bool

Default: True

Apply the standard symbolic simplification pass while importing.

list_outputs

Kind: Method

```
def list_outputs(self) -> tuple[dict[str, int], dict[str, int]]:
```

List generated amplitude and cross-section names with their process ids.

Returns

tuple[dict[str, int], dict[str, int]]

Amplitude mapping followed by the cross-section mapping.

get_integrand_info

Kind: Method

```
def get_integrand_info(self, process_id: Optional[int] = None, integrand_name:
Optional[str] = None) -> IntegrandInfo:
```

Describe the selected generated integrand and its graph structure.

Parameters

process_id : int, optional

Process containing the integrand. Supply this when selection is ambiguous.

integrand_name : str, optional

Integrand to inspect. Supply this when selection is ambiguous.

Returns

IntegrandInfo

Structured process, backend, graph, orientation, cut, and size metadata.

Raises

Exception

If no unique generated integrand matches the selection.

Examples

Inspect the generated graph groups in the repository's differential API fixture:

```
```python
from pathlib import Path

from gammaloop import GammaLoopAPI

example = Path("examples/api/python/epem_a_ddxg_xs_L0")
api = GammaLoopAPI(
 state_folder=example / "state",
 boot_commands_path=example / "run.toml",
 clean_state=True,
)
info = api.get_integrand_info()
assert info.kind == "cross section"
assert info.graph_count == 2
assert info.graph_group_count == len(info.graph_groups)
assert all(
 sum(graph.is_master for graph in group.graphs) == 1
 for group in info.graph_groups
)
```
```

This fixture's powered coupling selector is a regression input, not a reviewed physical perturbative-order definition.

process_id

Kind: Parameter

Optional[int]

Default: None

Process containing the integrand. Supply this when selection is ambiguous.

integrand_name

Kind: Parameter

Optional[str]

Default: None

Integrand to inspect. Supply this when selection is ambiguous.

get_integrand_settings

Kind: Method

```
def get_integrand_settings(self, process_id: Optional[int] = None, integrand_name: Optional[str] = None) -> SettingsValue:
```

Return a detached, read-only snapshot of one integrand's settings.

Parameters

process_id : int, optional

Process containing the integrand. Supply this when selection is ambiguous.

integrand_name : str, optional

Integrand whose settings are required.

Returns

SettingsValue

Serialized settings snapshot supporting ``get(path)``, attribute access, indexing, and ``to\_dict()``. Mutating it does not update the live session.

Raises

Exception

If selection fails, the integrand has not been generated, or its settings cannot be serialized.

Examples

Read a nested setting without changing the live integrand:

```
```python
settings = api.get_integrand_settings(process_id=0)
print(settings.get("general.generate_events"))
```
```

process_id**Kind:** Parameter

Optional[int]

Default: None

Process containing the integrand. Supply this when selection is ambiguous.

integrand_name**Kind:** Parameter

Optional[str]

Default: None

Integrand whose settings are required.

get_run_history**Kind:** Method

```
def get_run_history(self) -> str:
```

Render the current in-memory run history as TOML.

Returns

str

TOML representation of the history owned by this API instance.

Raises

Exception

If the current history cannot be serialized.

Notes

This reports the live session, including commands run through ``run``; it does not imply that the history has been persisted to the state directory.

Examples

Capture a reproducible run card from the current session:

```
```python
run_card_toml = api.get_run_history()
```
```

get_global_settings**Kind:** Method

```
def get_global_settings(self) -> str:
```

Render the current effective CLI and global settings as TOML.

Returns

str

TOML representation of the settings used by this API session.

Raises

Exception

If the settings cannot be rendered.

Examples

Record the effective settings after applying startup overrides:

```
```python
settings_toml = api.get_global_settings()
```
```

get_active_command_blocks

Kind: Method

```
def get_active_command_blocks(self) -> dict[str, list[str]]:
```

Return the named command blocks in the current run history.

Returns

dict[str, list[str]]

Mapping from block name to its rendered CLI commands.

Examples

Inspect the commands currently grouped under each block:

```
```python
for name, commands in api.get_active_command_blocks().items():
 print(name, commands)
```
```

get_default_runtime_settings

Kind: Method

```
def get_default_runtime_settings(self) -> SettingsValue:
```

Return a detached, read-only snapshot of the default runtime settings.

Returns

SettingsValue

Serialized settings including defaults. Use ``get(path)`` or ``to\_dict()`` to inspect it; changes to derived Python values do not affect the session.

Raises

Exception

If the settings cannot be serialized.

Examples

Inspect a runtime default by its documented settings path:

```
```python
runtime = api.get_default_runtime_settings()
```
```

```
print(runtime.get("integrator.n_start"))
```
```

### **get\_dot\_files**

**Kind:** Method

```
def get_dot_files(self, process: Optional[int | str] = None, integrand_name:
Optional[str] = None, settings: DotExportSettings = ...) -> str:
```

Render a selected amplitude or cross section as Graphviz DOT text.

Parameters

-----

process : int or str, optional

Process id or name; omit only when selection is unambiguous.

integrand\_name : str, optional

Integrand to render.

settings : DotExportSettings, optional

Controls diagram combination, UV terms, algebra, and generated fields.

Returns

-----

str

DOT source suitable for Graphviz or GammaLoop's drawing pipeline.

### **process**

**Kind:** Parameter

Optional[int | str]

**Default:** None

Process id or name; omit only when selection is unambiguous.

### **integrand\_name**

**Kind:** Parameter

Optional[str]

**Default:** None

Integrand to render.

### **settings**

**Kind:** Parameter

DotExportSettings

**Default:** ...

Controls diagram combination, UV terms, algebra, and generated fields.

### **run**

**Kind:** Method

```
def run(self, command: str) -> None:
```

Parse and execute a CLI command in this API instance's session.

Parameters

-----

command : str

GammaLoop CLI command text.

Returns

-----

None

The command's normal output is emitted through the configured CLI/logging sinks; inspect structured state through the corresponding getter methods.

Raises

-----

Exception

If the command cannot be parsed or execution fails.

Notes

-----

Commands share and may mutate the instance's in-memory state, settings, and run history. ``read\_only\_state=True`` only blocks writes inside the active state directory. The API does not automatically persist the session after this call; persistence depends on the executed command's explicit output behavior.

Examples

-----

Display the processes loaded in the current state:

```
```python
api.run("display processes")
```
```

**command**

**Kind:** Parameter

str

GammaLoop CLI command text.

Exhaustive reference · Source

**HistogramAccumulator**

Mutable continuous or discrete histogram accumulator with sample-level statistics.

Mutable continuous or discrete histogram accumulator with sample-level statistics.

Notes

-----

The example below deliberately places at most one entry in each bin. If several correlated entries land in one bin, the current helper records their squared weights separately rather than grouping their weights like GammaLoop's native observable pipeline. Do not replay raw event groups through this class until that statistical contract is aligned.

Examples

-----

Merge two pending, statistically independent samples before committing them:

```
```python
from gammaloop import HistogramAccumulator
```

```

left = HistogramAccumulator.continuous("energy", 0.0, 4.0, 4)
right = HistogramAccumulator.continuous("energy", 0.0, 4.0, 4)
left.fill_continuous_sample([(0.5, 2.0)])
right.fill_continuous_sample([(2.5, 3.0)])
left.merge_in_place(right)
left.update_results()

snapshot = left.snapshot()
assert snapshot.sample_count == 2
assert snapshot.bins[0].sum_weights == 2.0
assert snapshot.bins[0].sum_weights_squared == 4.0
assert snapshot.bins[0].sum_weights / snapshot.sample_count == 1.0
assert snapshot.bins[2].sum_weights == 3.0
assert snapshot.bins[2].sum_weights_squared == 9.0
assert right.snapshot().sample_count == 0
assert len(left.rebin(2).snapshot().bins) == 2
```

```

```
class HistogramAccumulator:
```

**Requires features:** python\_api, python\_abi, python\_stubgen

**continuous**

**Kind:** AssociatedFunction

```
def continuous(title: str, x_min: float, x_max: float, n_bins: int, type_description:
str = 'AL', phase: str = 'real', value_transform: str = 'identity', log_x_axis: bool
= False, log_y_axis: bool = True) -> HistogramAccumulator:
```

Create an evenly binned continuous histogram accumulator.

Parameters

-----

title : str

Human-readable title used by snapshots and exported output.

x\_min : float

Lower edge of the histogram range.

x\_max : float

Upper edge of the histogram range.

n\_bins : int

Number of equal-width in-range bins.

type\_description : str, default="AL"

HwU ``TYPE@`` metadata.

phase : {"real", "imag"}, default="real"

Component of each complex event weight to accumulate.

value\_transform : {"identity", "log10"}, default="identity"

Transformation applied to coordinates before binning.

log\_x\_axis : bool, default=False

Request logarithmic horizontal-axis rendering.

log\_y\_axis : bool, default=True

Request logarithmic vertical-axis rendering.

**title**

**Kind:** Parameter

str

Human-readable title used by snapshots and exported output.

**x\_min**

**Kind:** Parameter

float

Lower edge of the histogram range.

**x\_max**

**Kind:** Parameter

float

Upper edge of the histogram range.

**n\_bins**

**Kind:** Parameter

int

Number of equal-width in-range bins.

**type\_description**

**Kind:** Parameter

str

**Default:** 'AL'

HwU ``TYPE@`` metadata.

**phase**

**Kind:** Parameter

str

**Default:** 'real'

Component of each complex event weight to accumulate.

**value\_transform**

**Kind:** Parameter

str

**Default:** 'identity'

Transformation applied to coordinates before binning.

**log\_x\_axis**

**Kind:** Parameter

bool

**Default:** False

Request logarithmic horizontal-axis rendering.

**log\_y\_axis**

**Kind:** Parameter

bool

**Default:** True

Request logarithmic vertical-axis rendering.

### **discrete**

**Kind:** AssociatedFunction

```
def discrete(title: str, min_bin_id: int, max_bin_id: int, ordering: str =
'ascending_bin_id', labels: Optional[Sequence[str]] = None, type_description: str =
'AL', phase: str = 'real', log_y_axis: bool = True) -> HistogramAccumulator:
```

Create a discrete histogram accumulator over an inclusive integer range.

#### Parameters

-----

**title** : str

Human-readable title used by snapshots and exported output.

**min\_bin\_id** : int

Smallest accepted bin identifier.

**max\_bin\_id** : int

Largest accepted bin identifier, inclusive.

**ordering** : {"ascending\_bin\_id", "value\_descending", "abs\_value\_descending"},  
default="ascending\_bin\_id"

Ordering used when bins are returned or exported.

**labels** : Sequence[str], optional

One label per bin, ordered by ascending bin identifier.

**type\_description** : str, default="AL"

HwU ``TYPE@`` metadata.

**phase** : {"real", "imag"}, default="real"

Component of each complex event weight to accumulate.

**log\_y\_axis** : bool, default=True

Request logarithmic vertical-axis rendering.

#### Raises

-----

**ValueError**

If the range, label count, ordering, or phase is invalid.

### **title**

**Kind:** Parameter

str

Human-readable title used by snapshots and exported output.

### **min\_bin\_id**

**Kind:** Parameter

int

Smallest accepted bin identifier.

### **max\_bin\_id**

**Kind:** Parameter

int

Largest accepted bin identifier, inclusive.

### **ordering**

**Kind:** Parameter

str

**Default:** 'ascending\_bin\_id'

Ordering used when bins are returned or exported.

### **labels**

**Kind:** Parameter

Optional[Sequence[str]]

**Default:** None

One label per bin, ordered by ascending bin identifier.

### **type\_description**

**Kind:** Parameter

str

**Default:** 'AL'

HwU ``TYPE@`` metadata.

### **phase**

**Kind:** Parameter

str

**Default:** 'real'

Component of each complex event weight to accumulate.

### **log\_y\_axis**

**Kind:** Parameter

bool

**Default:** True

Request logarithmic vertical-axis rendering.

### **snapshot**

**Kind:** Method

```
def snapshot(self) -> HistogramSnapshot:
```

Return an immutable snapshot including committed and pending samples.

### **merge\_in\_place**

**Kind:** Method

```
def merge_in_place(self, other: HistogramAccumulator) -> None:
```

Move pending samples from another compatible accumulator into this one.

Parameters

-----

other : HistogramAccumulator

Compatible accumulator whose pending samples are consumed.

Raises

-----

ValueError

If histogram definitions differ.

## **other**

**Kind:** Parameter

HistogramAccumulator

Compatible accumulator whose pending samples are consumed.

## **rebin**

**Kind:** Method

```
def rebin(self, contiguous_bins: int) -> HistogramAccumulator:
```

Return a copy with each run of adjacent continuous bins combined.

Discrete histograms are copied unchanged.

Parameters

-----

contiguous\_bins : int

Positive number of old bins per new bin; it must divide the bin count.

## **contiguous\_bins**

**Kind:** Parameter

int

Positive number of old bins per new bin; it must divide the bin count.

## **rescale**

**Kind:** Method

```
def rescale(self, factor: float) -> None:
```

Multiply all accumulated weights by a constant in place.

Parameters

-----

factor : float

Scale applied to weight sums; squared-weight sums use its square.

## **factor**

**Kind:** Parameter

float

Scale applied to weight sums; squared-weight sums use its square.

## **change\_bin\_ordering**

**Kind:** Method

```
def change_bin_ordering(self, ordering: str) -> None:
```

Change the display ordering of a discrete histogram.

Parameters

-----

ordering : {"ascending\_bin\_id", "value\_descending", "abs\_value\_descending"}

New ordering for snapshots and exported output.

Raises

-----

ValueError

If this is a continuous histogram or the name is invalid.

### **ordering**

**Kind:** Parameter

str

New ordering for snapshots and exported output.

### **update\_results**

**Kind:** Method

def update\_results(self) -> None:

Commit pending samples to the accumulator's completed-result counters.

### **fill\_continuous\_sample**

**Kind:** Method

def fill\_continuous\_sample(self, entries: Sequence[tuple[float, float]]) -> None:

Add one independent continuous sample containing coordinate-weight pairs.

Parameters

-----

entries : Sequence[tuple[float, float]]

``(coordinate, projected\_weight)`` entries for this sample.

Raises

-----

ValueError

If this is not a continuous histogram.

### **entries**

**Kind:** Parameter

Sequence[tuple[float, float]]

``(coordinate, projected\_weight)`` entries for this sample.

### **fill\_discrete\_sample**

**Kind:** Method

def fill\_discrete\_sample(self, entries: Sequence[tuple[int, float]]) -> None:

Add one independent discrete sample containing bin-weight pairs.

Parameters

-----

entries : Sequence[tuple[int, float]]

``(bin\_id, projected\_weight)`` entries for this sample.

Raises

-----

ValueError

If this is not a discrete histogram.

### **entries**

**Kind:** Parameter

Sequence[tuple[int, float]]

`((bin_id, projected_weight))` entries for this sample.

Exhaustive reference · Source

### **HistogramBin**

Raw statistics and optional coordinate metadata for one histogram bin.

Raw statistics and optional coordinate metadata for one histogram bin.

class HistogramBin:

**Requires features:** python\_api, python\_abi, python\_stubgen

#### **x\_min**

**Kind:** Getter

def x\_min(self) -> Optional[float]:

Lower coordinate edge, or `None` for a discrete or overflow bin.

#### **x\_max**

**Kind:** Getter

def x\_max(self) -> Optional[float]:

Upper coordinate edge, or `None` for a discrete or underflow bin.

#### **bin\_id**

**Kind:** Getter

def bin\_id(self) -> Optional[int]:

Discrete bin identifier, or `None` for a continuous bin.

#### **label**

**Kind:** Getter

def label(self) -> Optional[str]:

Optional label of a discrete bin.

#### **entry\_count**

**Kind:** Getter

def entry\_count(self) -> int:

Number of event entries accumulated in this bin.

#### **sum\_weights**

**Kind:** Getter

def sum\_weights(self) -> float:

Sum of per-sample projected weights for this bin.

#### **sum\_weights\_squared**

**Kind:** Getter

def sum\_weights\_squared(self) -> float:

Sum of squared per-sample projected weights for this bin.

**mitigated\_fill\_count****Kind:** Getter

```
def mitigated_fill_count(self) -> int:
```

Number of fills produced by paired boundary-misbinning mitigation.

**average****Kind:** Method

```
def average(self, sample_count: int) -> float:
```

Compute this bin's Monte Carlo mean from its raw weight sum.

Parameters

-----

sample\_count : int

Number of statistically independent samples represented by the histogram.

Returns

-----

float

`sum_weights / sample_count`, or zero when `sample_count` is zero.

**sample\_count****Kind:** Parameter

int

Number of statistically independent samples represented by the histogram.

**error****Kind:** Method

```
def error(self, sample_count: int) -> float:
```

Compute the standard error of this bin's Monte Carlo mean.

Parameters

-----

sample\_count : int

Number of statistically independent samples represented by the histogram.

Returns

-----

float

Sample-mean standard error, or zero when it cannot be estimated reliably.

**sample\_count****Kind:** Parameter

int

Number of statistically independent samples represented by the histogram.

Exhaustive reference · Source

**HistogramSnapshot**

Immutable, mergeable histogram snapshot containing raw per-bin statistics.

Immutable, mergeable histogram snapshot containing raw per-bin statistics.

```
class HistogramSnapshot:
```

**Requires features:** python\_api, python\_abi, python\_stubgen

**kind**

**Kind:** Getter

```
def kind(self) -> str:
```

```
 ``"continuous"`` or ``"discrete"``.
```

**title**

**Kind:** Getter

```
def title(self) -> str:
```

```
 Human-readable histogram title.
```

**type\_description**

**Kind:** Getter

```
def type_description(self) -> str:
```

```
 HwU ``TYPE@`` description retained with the histogram.
```

**phase**

**Kind:** Getter

```
def phase(self) -> str:
```

```
 Complex-weight component accumulated: ``"real"`` or ``"imag"``.
```

**value\_transform**

**Kind:** Getter

```
def value_transform(self) -> str:
```

```
 Coordinate transform: ``"identity"`` or ``"log10"``.
```

**supports\_misbinning\_mitigation**

**Kind:** Getter

```
def supports_misbinning_mitigation(self) -> bool:
```

```
 Whether paired fills can mitigate bin-boundary instability.
```

**x\_min**

**Kind:** Getter

```
def x_min(self) -> Optional[float]:
```

```
 Lower bound of a continuous histogram, otherwise ``None``.
```

**x\_max**

**Kind:** Getter

```
def x_max(self) -> Optional[float]:
```

```
 Upper bound of a continuous histogram, otherwise ``None``.
```

**sample\_count**

**Kind:** Getter

```
def sample_count(self) -> int:
```

Number of statistically independent Monte Carlo samples represented.

### **log\_x\_axis**

**Kind:** Getter

```
def log_x_axis(self) -> bool:
```

Whether compatible renderers should use a logarithmic horizontal axis.

### **log\_y\_axis**

**Kind:** Getter

```
def log_y_axis(self) -> bool:
```

Whether compatible renderers should use a logarithmic vertical axis.

### **discrete\_min\_bin\_id**

**Kind:** Getter

```
def discrete_min_bin_id(self) -> Optional[int]:
```

Smallest discrete bin identifier, otherwise ``None``.

### **discrete\_ordering**

**Kind:** Getter

```
def discrete_ordering(self) -> Optional[str]:
```

Discrete display ordering, otherwise ``None``.

### **bins**

**Kind:** Getter

```
def bins(self) -> list[HistogramBin]:
```

Raw statistics for every in-range bin, in display order.

### **underflow\_bin**

**Kind:** Getter

```
def underflow_bin(self) -> HistogramBin:
```

Raw statistics for entries below a continuous histogram's range.

### **overflow\_bin**

**Kind:** Getter

```
def overflow_bin(self) -> HistogramBin:
```

Raw statistics for entries above a continuous histogram's range.

### **statistics**

**Kind:** Getter

```
def statistics(self) -> HistogramStats:
```

Histogram-wide entry and mitigation counters.

Exhaustive reference · Source

### **HistogramStats**

Aggregate entry, NaN, and misbinning-mitigation counts for a histogram.

Aggregate entry, NaN, and misbinning-mitigation counts for a histogram.

```
class HistogramStats:
```

**Requires features:** python\_api, python\_abi, python\_stubgen

**in\_range\_entry\_count**

**Kind:** Getter

```
def in_range_entry_count(self) -> int:
```

Number of event entries assigned to in-range bins.

**nan\_value\_count**

**Kind:** Getter

```
def nan_value_count(self) -> int:
```

Number of entries skipped because their coordinate was non-finite.

**mitigated\_pair\_count**

**Kind:** Getter

```
def mitigated_pair_count(self) -> int:
```

Number of entry pairs processed by boundary-misbinning mitigation.

Exhaustive reference · Source

**IntegrandActiveThresholdCut**

Viable cut associated with a threshold E-surface.

Viable cut associated with a threshold E-surface.

```
class IntegrandActiveThresholdCut:
```

**Requires features:** python\_api, python\_abi, python\_stubgen

**cut\_id**

**Kind:** Getter

```
def cut_id(self) -> int:
```

Zero-based identifier of a cut on which the E-surface remains viable.

**can\_become\_pinched**

**Kind:** Getter

```
def can_become_pinched(self) -> bool:
```

Whether this cut can make the E-surface pinched for some kinematics.

Exhaustive reference · Source

**IntegrandCut**

Cut edges, raising power, and threshold associations for one cross-section cut.

Cut edges, raising power, and threshold associations for one cross-section cut.

```
class IntegrandCut:
```

**Requires features:** python\_api, python\_abi, python\_stubgen

**cut\_id**

**Kind:** Getter

```
def cut_id(self) -> int:
```

Zero-based cut identifier within the representative graph.

#### **edge\_ids**

**Kind:** Getter

```
def edge_ids(self) -> list[int]:
```

Edge identifiers crossed by the cut.

#### **raising\_power**

**Kind:** Getter

```
def raising_power(self) -> int:
```

Maximum multiplicity of the cut's related threshold group.

#### **left\_thresholds**

**Kind:** Getter

```
def left_thresholds(self) -> list[IntegrandCutThreshold]:
```

Threshold associations on the left side of the cut.

#### **right\_thresholds**

**Kind:** Getter

```
def right_thresholds(self) -> list[IntegrandCutThreshold]:
```

Threshold associations on the right side of the cut.

Exhaustive reference · Source

#### **IntegrandCutThreshold**

Classification and boundary edges of one threshold associated with a cut.

Classification and boundary edges of one threshold associated with a cut.

```
class IntegrandCutThreshold:
```

**Requires features:** python\_api, python\_abi, python\_stubgen

#### **esurface\_id**

**Kind:** Getter

```
def esurface_id(self) -> int:
```

Threshold E-surface identifier within the graph group.

#### **status**

**Kind:** Getter

```
def status(self) -> str:
```

Viability classification for this threshold-cut association.

#### **cut\_boundary\_edge\_ids**

**Kind:** Getter

```
def cut_boundary_edge_ids(self) -> list[int]:
```

Cut edges that bound the associated threshold region.

#### **threshold\_boundary\_edge\_ids**

**Kind:** Getter

```
def threshold_boundary_edge_ids(self) -> list[int]:
```

Threshold edges that bound the associated threshold region.

#### **invariant\_bound\_is\_applicable**

**Kind:** Getter

```
def invariant_bound_is_applicable(self) -> bool:
```

Whether the invariant-bound criterion applies to this association.

Exhaustive reference · Source

#### **IntegrandGraph**

Identity and master-graph status of one graph in an integrand.

Identity and master-graph status of one graph in an integrand.

```
class IntegrandGraph:
```

**Requires features:** python\_api, python\_abi, python\_stubgen

#### **graph\_id**

**Kind:** Getter

```
def graph_id(self) -> int:
```

Zero-based graph identifier within the integrand.

#### **name**

**Kind:** Getter

```
def name(self) -> str:
```

Persistent graph name.

#### **is\_master**

**Kind:** Getter

```
def is_master(self) -> bool:
```

Whether this graph is the representative graph of its group.

Exhaustive reference · Source

#### **IntegrandGraphGroup**

Graphs and shared orientation, loop-basis, threshold, and cut data in one group.

Graphs and shared orientation, loop-basis, threshold, and cut data in one group.

```
class IntegrandGraphGroup:
```

**Requires features:** python\_api, python\_abi, python\_stubgen

#### **group\_id**

**Kind:** Getter

```
def group_id(self) -> int:
```

Zero-based graph-group identifier within the integrand.

#### **graphs**

**Kind:** Getter

```
def graphs(self) -> list[IntegrandGraph]:
```

Graphs in this group, with the representative graph marked as master.

#### **orientation\_edge\_ids**

**Kind:** Getter

```
def orientation_edge_ids(self) -> list[int]:
```

Edge identifiers that establish the ordering of every orientation signature.

#### **orientations**

**Kind:** Getter

```
def orientations(self) -> list[IntegrandOrientation]:
```

Available causal-flow orientations for the representative graph.

#### **loop\_momentum\_bases**

**Kind:** Getter

```
def loop_momentum_bases(self) -> list[IntegrandLoopMomentumBasis]:
```

Available loop-momentum bases for the representative graph.

#### **threshold\_esurface\_ids**

**Kind:** Getter

```
def threshold_esurface_ids(self) -> list[int]:
```

Ordered identifiers of threshold E-surfaces retained for the group.

#### **threshold\_esurfaces**

**Kind:** Getter

```
def threshold_esurfaces(self) -> list[IntegrandThresholdEsurface]:
```

Structured metadata for the retained threshold E-surfaces.

#### **cuts**

**Kind:** Getter

```
def cuts(self) -> list[IntegrandCut]:
```

Cross-section cuts; empty for amplitude graph groups.

Exhaustive reference · Source

#### **IntegrandInfo**

Structured description of a generated integrand and its evaluation backend.

Structured description of a generated integrand and its evaluation backend.

```
class IntegrandInfo:
```

**Requires features:** python\_api, python\_abi, python\_stubgen

#### **process\_id**

**Kind:** Getter

```
def process_id(self) -> int:
```

Numeric identifier of the process that owns the integrand.

#### **process\_name**

**Kind:** Getter

```
def process_name(self) -> str:
```

Persistent folder name of the owning process.

**integrand\_name**

**Kind:** Getter

```
def integrand_name(self) -> str:
```

Canonical name of the resolved integrand.

**kind**

**Kind:** Getter

```
def kind(self) -> str:
```

``"amplitude"`` or ``"cross section"``.

**generation\_backend**

**Kind:** Getter

```
def generation_backend(self) -> str:
```

Compilation backend frozen into the generated integrand.

**generation\_compile\_options**

**Kind:** Getter

```
def generation_compile_options(self) -> Optional[str]:
```

Backend-specific compilation options, when configured.

**active\_f64\_backend**

**Kind:** Getter

```
def active_f64_backend(self) -> str:
```

Floating-point evaluator backend currently active for f64 evaluation.

**graph\_count**

**Kind:** Getter

```
def graph_count(self) -> int:
```

Number of amplitude graphs or cross-section supergraphs.

**graph\_group\_count**

**Kind:** Getter

```
def graph_group_count(self) -> int:
```

Number of graph groups in the generated integrand.

**record\_size\_bytes**

**Kind:** Getter

```
def record_size_bytes(self) -> int:
```

Serialized integrand-record size in bytes, excluding its compiled evaluator.

**graph\_groups**

**Kind:** Getter

```
def graph_groups(self) -> list[IntegrandGraphGroup]:
```

Per-group graph, orientation, basis, threshold, and cut metadata.

[Exhaustive reference](#) · [Source](#)

### **IntegrandLoopMomentumBasis**

Loop-momentum basis and optional multichannel identifier for a graph group.

Loop-momentum basis and optional multichannel identifier for a graph group.

```
class IntegrandLoopMomentumBasis:
```

**Requires features:** `python_api`, `python_abi`, `python_stubgen`

#### **basis\_id**

**Kind:** Getter

```
def basis_id(self) -> int:
```

Zero-based loop-momentum-basis identifier on the representative graph.

#### **channel\_id**

**Kind:** Getter

```
def channel_id(self) -> Optional[int]:
```

Effective multichannel identifier, or ``None`` when this basis is not sampled.

#### **edge\_ids**

**Kind:** Getter

```
def edge_ids(self) -> list[int]:
```

Edge identifiers whose momenta form the basis.

#### **matches\_generation\_basis**

**Kind:** Getter

```
def matches_generation_basis(self) -> bool:
```

Whether this is the loop-momentum basis used during integrand generation.

[Exhaustive reference](#) · [Source](#)

### **IntegrandOrientation**

Edge-direction signature for one causal-flow orientation.

Edge-direction signature for one causal-flow orientation.

```
class IntegrandOrientation:
```

**Requires features:** `python_api`, `python_abi`, `python_stubgen`

#### **orientation\_id**

**Kind:** Getter

```
def orientation_id(self) -> int:
```

Zero-based orientation identifier within the graph group.

#### **signature**

**Kind:** Getter

```
def signature(self) -> list[int]:
```

Direction per ``IntegrandGraphGroup.orientation\_edge\_ids``: ``1``, ``-1``, or ``0``.

[Exhaustive reference](#) · [Source](#)

### **IntegrandThresholdEsurface**

Threshold E-surface metadata and the cuts on which it remains active.

Threshold E-surface metadata and the cuts on which it remains active.

```
class IntegrandThresholdEsurface:
```

**Requires features:** python\_api, python\_abi, python\_stubgen

#### **esurface\_id**

**Kind:** Getter

```
def esurface_id(self) -> int:
```

E-surface identifier within the graph group.

#### **representative\_graph\_id**

**Kind:** Getter

```
def representative_graph_id(self) -> int:
```

Graph whose local E-surface supplies ``edge\_ids``.

#### **edge\_ids**

**Kind:** Getter

```
def edge_ids(self) -> list[int]:
```

Edge identifiers contributing energies to this E-surface.

#### **classification**

**Kind:** Getter

```
def classification(self) -> Optional[str]:
```

Kinematic existence class, or ``None`` when no static classification was computed.

#### **active\_cuts**

**Kind:** Getter

```
def active_cuts(self) -> list[IntegrandActiveThresholdCut]:
```

Cuts on which this E-surface remains viable.

[Exhaustive reference](#) · [Source](#)

### **SampleEvaluationResult**

Numerical value, metadata, stability records, and generated events for one sample.

Numerical value, metadata, stability records, and generated events for one sample.

```
class SampleEvaluationResult:
```

**Requires features:** python\_api, python\_abi, python\_stubgen

#### **integrand\_result**

**Kind:** Getter

```
def integrand_result(self) -> complex:
```

Complex integrand value before applying the parameterization Jacobian.

**integrator\_weight****Kind:** Getter

```
def integrator_weight(self) -> float:
```

Monte Carlo weight supplied by the integrator, excluding the parameterization Jacobian.

**generated\_event\_count****Kind:** Getter

```
def generated_event_count(self) -> Optional[int]:
```

Number of candidate events generated, or ``None`` when metadata was omitted.

**accepted\_event\_count****Kind:** Getter

```
def accepted_event_count(self) -> Optional[int]:
```

Number of generated events accepted by selectors, or ``None`` without metadata.

**event\_processing\_time\_seconds****Kind:** Getter

```
def event_processing_time_seconds(self) -> Optional[float]:
```

Time spent building and selecting events, in seconds, or ``None`` without metadata.

**parameterization\_jacobian****Kind:** Getter

```
def parameterization_jacobian(self) -> Optional[float]:
```

Sample parameterization Jacobian, or ``None`` when no Jacobian was supplied.

**is\_nan****Kind:** Getter

```
def is_nan(self) -> Optional[bool]:
```

Whether evaluation metadata flagged a non-finite result, or ``None`` without metadata.

**stability\_results****Kind:** Getter

```
def stability_results(self) -> Optional[list[StabilityResult]]:
```

Per-precision stability attempts, or ``None`` when metadata was omitted.

**event\_groups****Kind:** Getter

```
def event_groups(self) -> list[EventGroup]:
```

Correlated event groups produced while evaluating this sample.

**\_\_str\_\_****Kind:** Method

```
def __str__(self) -> str:
```

Return a human-readable evaluation summary.

**\_\_repr\_\_**

**Kind:** Method

```
def __repr__(self) -> str:
```

Return the human-readable evaluation summary.

Exhaustive reference · Source

**SettingsValue**

Read-only, detached view over serialized GammaLoop settings.

Read-only, detached view over serialized GammaLoop settings.

```
class SettingsValue:
```

**Requires features:** python\_api, python\_abi, python\_stubgen

**path**

**Kind:** Getter

```
def path(self) -> str:
```

Dot-separated location of this value within the settings tree.

**kind**

**Kind:** Getter

```
def kind(self) -> str:
```

JSON value kind: ``object``, ``array``, ``string``, ``number``, ``boolean``, or ``null``.

**is\_object**

**Kind:** Method

```
def is_object(self) -> bool:
```

Return whether this value is an object with named children.

**is\_array**

**Kind:** Method

```
def is_array(self) -> bool:
```

Return whether this value is an array with indexed children.

**is\_scalar**

**Kind:** Method

```
def is_scalar(self) -> bool:
```

Return whether this value is a scalar JSON value, including ``null``.

**keys**

**Kind:** Method

```
def keys(self) -> list[str]:
```

Return this object's child keys in lexical order.

Raises

-----

**TypeError**

If this value is not an object.

**get****Kind:** Method

```
def get(self, path: str) -> Any:
```

Resolve a dot-separated descendant path.

An empty path returns this value. Objects become ``SettingsValue`` views, while scalar values become their ordinary Python equivalents.

Parameters

-----

path : str

Relative path such as ``"sampling.parameterization"``.

Raises

-----

KeyError

If the path does not exist below this value.

**path****Kind:** Parameter

str

Relative path such as ``"sampling.parameterization"``.

**to\_dict****Kind:** Method

```
def to_dict(self) -> Any:
```

Convert the complete detached value tree to ordinary Python containers and scalars.

**\_\_getattr\_\_****Kind:** Method

```
def __getattr__(self, name: str) -> Any:
```

Resolve an object child by attribute name.

Parameters

-----

name : str

Immediate child key to resolve.

**name****Kind:** Parameter

str

Immediate child key to resolve.

**\_\_dir\_\_****Kind:** Method

```
def __dir__(self) -> list[str]:
```

Return object-child names in lexical order, or an empty list for other kinds.

**\_\_len\_\_****Kind:** Method

```
def __len__(self) -> int:
```

Return the number of object or array children.

**`__str__`**

**Kind:** Method

```
def __str__(self) -> str:
```

Return the detached settings value as pretty-printed JSON.

**`__repr__`**

**Kind:** Method

```
def __repr__(self) -> str:
```

Return a compact representation containing this value's path and kind.

**`__getitem__`**

**Kind:** Method

```
def __getitem__(self, key: Any, /) -> Any:
```

Resolve a relative string path or array index.

Parameters

-----

**key** : str or int

Descendant path for an object, or zero-based index for an array.

**key**

**Kind:** Parameter

Any

Descendant path for an object, or zero-based index for an array.

Exhaustive reference · Source

**StabilityResult**

Outcome and cost of one numerical-stability precision level.

Outcome and cost of one numerical-stability precision level.

class StabilityResult:

**Requires features:** python\_api, python\_abi, python\_stubgen

**precision**

**Kind:** Getter

```
def precision(self) -> str:
```

Numerical precision used for this stability level.

**estimated\_relative\_accuracy**

**Kind:** Getter

```
def estimated_relative_accuracy(self) -> Optional[float]:
```

Estimated relative accuracy, or ``None`` when it could not be estimated.

**estimated\_decimal\_digits**

**Kind:** Getter

```
def estimated_decimal_digits(self) -> Optional[float]:
```

**status**

**Kind:** Getter

```
def status(self) -> str:
```

Human-readable stability outcome and number of rotated samples.

**sample\_count**

**Kind:** Getter

```
def sample_count(self) -> int:
```

Number of rotated samples evaluated at this precision level.

**total\_time\_seconds**

**Kind:** Getter

```
def total_time_seconds(self) -> float:
```

Total wall-clock time spent at this precision level, in seconds.

Exhaustive reference · Source

**atom\_to\_canonical\_string**

Parse a Symbolica expression and return its canonical string form.

Parse a Symbolica expression and return its canonical string form.

Parameters

-----

**atom\_str** : str

Symbolica expression to parse and normalize.

Returns

-----

str

The parsed expression in canonical string form.

Raises

-----

Exception

If ``atom\_str`` is not a valid Symbolica expression.

Examples

-----

Normalize a symbolic expression before comparing or storing it:

```
```python
atom_to_canonical_string("x + x")
```
```

```
def atom_to_canonical_string(atom_str: str) -> str:
```

**Requires features:** python\_api, python\_abi, python\_stubgen

Exhaustive reference · Source

**evaluate\_graph\_overall\_factor**

Evaluate a graph's symbolic overall factor and return its canonical form.

Evaluate a graph's symbolic overall factor and return its canonical form.

Parameters

-----

overall\_factor : str

Symbolica expression used as the graph's overall factor.

Returns

-----

str

The evaluated factor in canonical Symbolica form.

Raises

-----

Exception

If the expression cannot be parsed or evaluated.

Examples

-----

Evaluate the symmetry and fermion-loop factors attached to a graph:

```
```python
evaluate_graph_overall_factor(
    "AutG(2)^-1*InternalFermionLoopSign(-1)"
)
```
```

```
def evaluate_graph_overall_factor(overall_factor: str) -> str:
```

**Requires features:** python\_api, python\_abi, python\_stubgen

Exhaustive reference · Source

**to\_dots**

Rewrite a Symbolica tensor expression into Idenso dot-product notation.

Rewrite a Symbolica tensor expression into Idenso dot-product notation.

Parameters

-----

atom\_str : str

Symbolica tensor expression whose repeated indices encode contractions.

Returns

-----

str

The equivalent expression using Idenso dot-product notation.

Raises

-----

Exception

If ``atom\_str`` cannot be parsed or converted.

Examples

-----

Rewrite a contraction before passing it to an Idenso workflow:

```
```python
```

```
to_dots("p(mu) * q(mu)")
``
```

```
def to_dots(atom_str: str) -> str:
```

Requires features: python_api, python_abi, python_stubgen

Exhaustive reference · Source

CLI commands and settings

Commands and settings available in this version are listed below.

Command tree

Command	Description
gammaLoop	An implementation of the Local Unitarity method for computing differential collider cross-sections.
gammaLoop display	Inspect models, processes, integrands, settings, and named session data
gammaLoop display model	Show model particles, parameters, couplings, and vertices for the selected context
gammaLoop display processes	List processes currently stored in the active state
gammaLoop display integrand	Show generated integrands, graph groups, resources, and selected detail tables
gammaLoop display quantities	List configured named quantities, or inspect one quantity in a selected process
gammaLoop display observables	List configured observables, or inspect one observable in a selected process
gammaLoop display selectors	List configured event selectors, or inspect one selector in a selected process
gammaLoop display command_block	Show one stored command block, or list every block when no name is supplied
gammaLoop display settings	Show effective global, default-runtime, or process-specific settings
gammaLoop display settings global	Show effective global generation, logging, and parallelization settings
gammaLoop display settings default-runtime	Show the default runtime settings inherited by newly generated integrands
gammaLoop display settings process	Show effective settings for one generated process or integrand
gammaLoop duplicate	Copy generated data to a new process or integrand name
gammaLoop duplicate integrand	Copy one generated integrand and its process context under new names
gammaLoop set	Change global, runtime, model, or process settings
gammaLoop set base-dir	Set the base directory for gammaloop state and logs
gammaLoop set global	Change global generation, logging, and parallelism settings
gammaLoop set global file	Merge a TOML file into the current global or default-runtime settings
gammaLoop set global string	Load settings from TOML content passed as a CLI string
gammaLoop set global kv	Merge one or more dotted `KEY=VALUE` assignments into the current settings

Command	Description
gammaLoop set global defaults	Sync process runtime settings from the current default runtime settings
gammaLoop set global stored	Reload the corresponding settings from the active state's stored file
gammaLoop set default-runtime	Change the runtime settings inherited by newly generated integrands
gammaLoop set default-runtime file	Merge a TOML file into the current global or default-runtime settings
gammaLoop set default-runtime string	Load settings from TOML content passed as a CLI string
gammaLoop set default-runtime kv	Merge one or more dotted `KEY=VALUE` assignments into the current settings
gammaLoop set default-runtime defaults	Sync process runtime settings from the current default runtime settings
gammaLoop set default-runtime stored	Reload the corresponding settings from the active state's stored file
gammaLoop set model	Assign model parameters in the selected context or reset them to defaults
gammaLoop set process	Change runtime settings or named analysis objects for one process or integrand
gammaLoop set process file	Merge a TOML file into the selected process or integrand settings
gammaLoop set process string	Load settings from TOML content passed as a CLI string
gammaLoop set process kv	Merge one or more dotted `KEY=VALUE` assignments into the selected settings
gammaLoop set process defaults	Sync process runtime settings from the current default runtime settings
gammaLoop set process stored	Reload the selected process or integrand settings from its stored file
gammaLoop set process add	Add a named quantity/observable/selector
gammaLoop set process add quantity	Add a named derived quantity to the selected process settings
gammaLoop set process add observable	Add a named observable to the selected process settings
gammaLoop set process add selector	Add a named event selector to the selected process settings
gammaLoop set process update	Update a named quantity/observable/selector
gammaLoop set process update quantity	Update fields of an existing named quantity
gammaLoop set process update observable	Update fields of an existing named observable
gammaLoop set process update selector	Update fields of an existing named selector
gammaLoop set process remove	Remove a named quantity/observable/selector

Command	Description
<code>gammaLoop set process remove quantity</code>	Remove a named quantity from the selected process settings
<code>gammaLoop set process remove observable</code>	Remove a named observable from the selected process settings
<code>gammaLoop set process remove selector</code>	Remove a named selector from the selected process settings
<code>gammaLoop import</code>	Import models or previously generated graphs into the active state
<code>gammaLoop import model</code>	Load a UFO model and make it the active model for subsequent generation
<code>gammaLoop import graphs</code>	Load serialized graph data into a new or existing process
<code>gammaLoop save</code>	Export graph data, standalone evaluators, schemas, or the current state
<code>gammaLoop save dot</code>	Export generated graphs as DOT files and drawing templates
<code>gammaLoop save uv-forest</code>	Export the ultraviolet forest for selected generated graphs
<code>gammaLoop save standalone</code>	Export an integrand as a standalone evaluator or serialized data file
<code>gammaLoop save state</code>	Persist the active state, settings, and replayable run history
<code>gammaLoop save schema</code>	Regenerate the JSON schema files for CLI and runtime configuration
<code>gammaLoop run</code>	Execute a stored command block or an inline command list
<code>gammaLoop start_commands_block</code>	Begin recording subsequent commands under a reusable block name
<code>gammaLoop finish_commands_block</code>	Stop recording commands and store the active command block
<code>gammaLoop remove</code>	Remove generated processes from the active state
<code>gammaLoop remove processes</code>	Remove one integrand, one process, or all processes selected by the supplied target
<code>gammaLoop integrate</code>	Integrate one or more generated process integrands
<code>gammaLoop generate</code>	Generate cross-section or amplitude integrands from a process specification
<code>gammaLoop generate xs</code>	Generate a cross-section integrand through the forward-scattering construction
<code>gammaLoop generate amp</code>	Generate an amplitude integrand for the supplied process specification
<code>gammaLoop generate existing</code>	Create another integrand from an existing process without regenerating its graphs
<code>gammaLoop select</code>	Select graph groups and write the selection to a new process or integrand

Command	Description
gammaLoop quit	End the interactive GammaLoop session without executing further commands
gammaLoop inspect	Inspect integrand contributions at one phase-space point or momentum configuration
gammaLoop approach	Sample an integrand while approaching a phase-space point along selected scaling axes
gammaLoop evaluate	Evaluate a vacuum amplitude analytically or numerically with Vakint
gammaLoop renormalize	Compute and export ultraviolet renormalization contributions for an amplitude
gammaLoop bench	Measure evaluation throughput at a fixed point over a target duration
gammaLoop profile	Profile ultraviolet or infrared scaling limits of a generated integrand
gammaLoop profile ultra-violet	Sample ultraviolet scaling rays and report the fitted large-momentum behavior
gammaLoop profile bulk	Probe multiple infrared scaling limits and report their fitted behavior in one run
gammaLoop 3Drep	Validate a graph or build its diagnostic three-dimensional energy representation
gammaLoop 3Drep validate	Check the selected graph for supported energy-representation kinematics
gammaLoop 3Drep build	Construct and export the selected graph's oriented CFF expression
gammaLoop batch	Evaluate a process-definition file against an HPC batch input and write named results
gammaLoop !	Run an operating-system shell command from the interactive GammaLoop session

Settings

Path	Type	Default
cli.global.display_directive	string	"info"
cli.global.generation.compile.compile_mode	CompilationMode	"symjit"
cli.global.generation.compile.compile_language	string	"g++"
cli.global.generation.compile.custom_compiler	array<string>	[]
cli.global.generation.compile.fast_build	boolean	true
cli.global.generation.compile.optimize_level	CompilerOptimizationLevel	0
cli.global.generation.compile.unsafe_optimizations	boolean	true
cli.global.generation.evaluator.abort_level	int	0
cli.global.generation.evaluator.compile	boolean	false
cli.global.generation.evaluator.compile_serializations	integer or null	no serialized default
cli.global.generation.evaluator.disable_translation	boolean	true
cli.global.generation.evaluator.do_codegen	boolean	false
cli.global.generation.evaluator.do_loop_replacement	boolean	false

Path	Type	Default
cli.global.generation.evaluator.horizon	integer	1
cli.global.generation.evaluator.iterative_optimization	boolean	true
cli.global.generation.evaluator.max_integer_pair_cache	integer	100000
cli.global.generation.evaluator.max_integer_pair_distance	integer	1000
cli.global.generation.evaluator.max_integer_scheme_variables	integer	500
cli.global.generation.evaluator.n_integer	integer	1
cli.global.generation.evaluator.samples_execution_mode	enum<ExecutionMode>	"Sequential", "MinResultRank"]
cli.global.generation.evaluator.substitution	boolean	false
cli.global.generation.evaluator.submedian	boolean	false
cli.global.generation.evaluator.submedian_function_map	boolean	false
cli.global.generation.evaluator.tensor_network_contraction_order	enum<ContractionMode>	"DeleteCost"
cli.global.generation.evaluator.verbose	boolean	false
cli.global.generation.explicit_orientation_sum_only	boolean	false
cli.global.generation.feyngen.gamma_normalization	boolean	false
cli.global.generation.force_cuts	array<array<string>>	{}>
cli.global.generation.orientation_patterns_starting	enum<Pattern>	no serialized default
cli.global.generation.override_lmbd_elastics	boolean	false
cli.global.generation.threshold_substitution.assume_positive_external_energies	boolean	true
cli.global.generation.threshold_substitution.check_surface_at_generation	boolean	false
cli.global.generation.threshold_substitution.disable_integrated_ct	boolean	false
cli.global.generation.threshold_substitution.enable_thresholds	boolean	true
cli.global.generation.threshold_substitution.esurface_existence_threshold	integer	7
cli.global.generation.threshold_substitution.skip_thresholds_that_are_cuts	boolean	true
cli.global.generation.tropical_substitution.disable_tropical_generation	boolean	false
cli.global.generation.tropical_substitution.panic_on_fail	boolean	false
cli.global.generation.tropical_substitution.target_omega	enum<Target>	Omega
cli.global.generation.uniform_number_of_samples	integer	100000
cli.global.generation.uv.add_markers	boolean	false
cli.global.generation.uv.final_integrand_dimension	integer	3
cli.global.generation.uv.generate_integrands	boolean	true
cli.global.generation.uv.inner_products	boolean	true
cli.global.generation.uv.keep_markers	boolean	true
cli.global.generation.uv.local_uv_expanded_fdi_integrands	boolean	false
cli.global.generation.uv.orchestrator	enum<Orchestrator>	"hedge_poset"
cli.global.generation.uv.project_integrated_uv_cts	boolean	true
cli.global.generation.uv.renormalization_type	enum<RenormalizationType>	"MUMg_divergent"
cli.global.generation.uv.renormalization_type	enum<RenormalizationType>	"MUMssive_power_divergent"
cli.global.generation.uv.renormalization_type	enum<RenormalizationType>	"MUMssless_power_divergent"
cli.global.generation.uv.renormalization_rules	array<CTRenormalizationRule>	{}>
cli.global.generation.uv.renormalization_serialization_identifier	integer	0

external_pdg_set

Path	Type	Default
cli.global.generation.uv.renormalization_precision	integer none	10. serialized default
cli.global.generation.uv.renormalization_approximation_type	enum	0. serialized default
cli.global.generation.uv.softct	boolean	true
cli.global.generation.uv.subtract	boolean	true
cli.global.generation.uv.vakint.additional_normalization	boolean	true
cli.global.generation.uv.vakint.algebraic_substitution	boolean	true
cli.global.generation.uv.vakint.clean_dir	boolean	true
cli.global.generation.uv.vakint.evaluation_methods	array<string>	["alphaloop", "matad", "fmft"]
cli.global.generation.uv.vakint.expand_masters	boolean	true
cli.global.generation.uv.vakint.expand_substitute_masters	boolean	true
cli.global.generation.uv.vakint.forming_path	string	"form"
cli.global.generation.uv.vakint.map_connect_numerical_substitution	boolean	true
cli.global.generation.uv.vakint.map_expand_master	boolean	true
cli.global.generation.uv.vakint.map_expand_substitute_hosts	boolean	true
cli.global.generation.uv.vakint.map_expand_substitute_masters	boolean	true
cli.global.generation.uv.vakint.normalization	string	"MSbar"
cli.global.generation.uv.vakint.pyintegers_max_n_eval	integer	1000000000000
cli.global.generation.uv.vakint.pyintegers_min_n_eval	integer	10000
cli.global.generation.uv.vakint.pyboolean_quiet	boolean	true
cli.global.generation.uv.vakint.pyboolean_relative_precision	number	1e-15
cli.global.generation.uv.vakint.pyboolean_remove_existing_outputs	boolean	default
cli.global.generation.uv.vakint.pyboolean_exe_path	string	"python3"
cli.global.generation.uv.vakint.run_time_decimal_precision	integer	100
cli.global.generation.uv.vakint.testing_directory	string	no serialized default
cli.global.generation.vector_polarization	enum	0. serialized default
cli.global.log_style.full_line_source	boolean	false
cli.global.log_style.include_fields	boolean	false
cli.global.log_style.log_format	LogFormat	"Long"
cli.global.log_style.short_timestamp	boolean	false
cli.global.logfile_directive	string	"off"
cli.global.n_cores.compile	integer	1
cli.global.n_cores.feyngen	integer	1
cli.global.n_cores.generate	integer	1
cli.global.n_cores.integrate	integer	1
cli.override_state	boolean	false
cli.state.folder	string	"./gamma_loop_state"
cli.state.name	string null	""
cli.try_strings	boolean	true
runtime.general.additional_param_values	array<number>	[]
runtime.general.debug_cache	boolean	false

Path	Type	Default
runtime.general.disable_flux_factor	boolean	false
runtime.general.enable_cache	boolean	false
runtime.general.evaluator_method	EvaluatorMethod	"SingleParametric"
runtime.general.generate_events	boolean	false
runtime.general.integral_unit	IntegralUnit	"auto"
runtime.general.load_compiled_cff	boolean	false
runtime.general.m_uv	number	1000.0
runtime.general.mu_r	number	1000.0
runtime.general.numerator_sampling_number	number	1.0
runtime.general.orientation_path	null string	no serialized default
runtime.general.renormalization_localization_scale	number	1000.0
runtime.general.store_additional_weights_in_event	boolean	false
runtime.general.use_ltd	boolean	false
runtime.h_function.enabled_dampening	boolean	true
runtime.h_function.function	HFunction	"poly_exponential"
runtime.h_function.power	integer null	no serialized default
runtime.h_function.sigma	number	1.0
runtime.integrand.h_function.enabled_dampening	boolean	no serialized default
runtime.integrand.h_function.function	HFunction	no serialized default
runtime.integrand.h_function.power	integer null	no serialized default
runtime.integrand.h_function.sigma	number	no serialized default
runtime.integrand.n_3d_momenta	integer	no serialized default
runtime.integrator.bin_number_evolutionary	array null	no serialized default
runtime.integrator.continuous_dim_learning_rate	number	1.0
runtime.integrator.discrete_dim_learning_rate	number	1.0
runtime.integrator.integrated_phase	IntegratedPhase	"real"
runtime.integrator.max_prob_ratio	number	30.0
runtime.integrator.min_samples_for_integration	integer	1000
runtime.integrator.n_bins	integer	64
runtime.integrator.n_increase	integer	10000
runtime.integrator.n_max	integer	10000000000
runtime.integrator.n_start	integer	100000
runtime.integrator.observables_output_format	array<ObservableFileFormat>	"json"
runtime.integrator.seed	integer	69
runtime.integrator.show_max_wgt_info	boolean	true
runtime.integrator.target_absolute_number	number	no serialized default
runtime.integrator.target_relative_number	number	no serialized default
runtime.integrator.train_on_avg	boolean	false
runtime.kinematics.e_cm	number	64.0
runtime.kinematics.externals.data_header_lines	array<integer string>	[]

Path	Type	Default
runtime.kinematics.externals.data.improvement_settings.large_deformation_check	boolean	true
runtime.kinematics.externals.data.improvement_settings.gsmode	SumMode	"summed"
runtime.kinematics.externals.data.improvement_settings.only_warn_on_large_deformation	boolean	false
runtime.kinematics.externals.data.arrayDep array<number>>	array<number>>	[]
runtime.kinematics.externals.type	string	"constant"
runtime.model	object	{}
runtime.observables	object	{}
runtime.quantities	object	{}
runtime.sampling.alpha	number	3.0
runtime.sampling.b	number	1.0
runtime.sampling.coordinate_system	CoordinateSystem	"spherical"
runtime.sampling.graph_names	array<string>	[]
runtime.sampling.graphs	SumMode	"summed"
runtime.sampling.lmb_basis_ids	object	no serialized default
runtime.sampling.lmb_channel_weight	LmbChannelWeight	"use"
runtime.sampling.lmb_channels	SumMode	"summed"
runtime.sampling.lmb_multichanneling	boolean	false
runtime.sampling.mapping	ParameterizationMapping	"linear"
runtime.sampling.orientations	SumMode	"summed"
runtime.sampling.power	number	1.0
runtime.selectors	object	{}
runtime.stability.check_on_norm	boolean	true
runtime.stability.escalate_if_exact	boolean	false
runtime.stability.levels	array<StabilityLevel>	[{"set_large_for_large_weight_threshold":0.9,"pr {"escalate_for_large_weight_threshold":-1.0,"pr {"escalate_for_large_weight_threshold":-1.0,"pr
runtime.stability.levels[].escalate_for_large_weight_threshold	number	no serialized default
runtime.stability.levels[].precision	precision	no serialized default
runtime.stability.levels[].required_precision_for_time	number	no serialized default
runtime.stability.levels[].required_precision_for_re	number	no serialized default
runtime.stability.loop_momenta_norm	number	1.0
runtime.stability.recording.record_all_stability_levels	boolean	no serialized default
runtime.stability.recording.record_loop_momenta_escalations	boolean	no serialized default
runtime.stability.recording.record_bootstrapped_results	boolean	no serialized default
runtime.stability.rotation_axis	array<object>	[{"alpha":0.1,"beta":0.2,"gamma":0.3,"type":"eu
runtime.stability.rotation_axis[].alpha	number	no serialized default
runtime.stability.rotation_axis[].beta	number	no serialized default
runtime.stability.rotation_axis[].gamma	number	no serialized default
runtime.stability.rotation_axis[].type	string	no serialized default
runtime.subtraction.disable_threshold	boolean	false

Path	Type	Default
runtime.subtraction.esurface_exists_threshold	number	1e-7
runtime.subtraction.integrated_ct_settings.range.h_funct	function	function_settings.enabled_dampening
runtime.subtraction.integrated_ct_settings.range.h_func_type	string	"function_expansion"
runtime.subtraction.integrated_ct_settings.range.h_functional_settings.fwd	boolean	true
runtime.subtraction.integrated_ct_settings.range.h_functional_settings.sigma	float	function_settings.sigma
runtime.subtraction.integrated_ct_settings.range.type	string	"infinite"
runtime.subtraction.local_ct_settings.is_localisation	boolean	false
runtime.subtraction.local_ct_settings.is_force_uv_dampers_to_one	boolean	false
runtime.subtraction.local_ct_settings.number_localisation	integer	0
runtime.subtraction.local_ct_settings.number_sigma_width	integer	10
runtime.subtraction.local_ct_settings.number_sliver_width	integer	10
runtime.subtraction.overlap_settings.is_off_global_center	boolean	true
runtime.subtraction.overlap_settings.is_serialized_default	boolean	true
runtime.subtraction.overlap_settings.is_origin	boolean	true
runtime.subtraction.overlap_settings.is_origin_all	boolean	false
runtime.subtraction.radial_root_residual_tolerance	number	64.0

Version information

Save these identifiers with published results and include them in issue reports so that collaborators can reproduce the same software environment.

- **Documentation channel:** latest
- **Documentation route:** /products/gammaloop/latest/
- **Source revision:** feb59c2d1eaae82af47bc6bd932bc9a3d57d70c0

Package versions and enabled features

- gammaloop/gammalooprs — 0.3.4 (no optional features)
- gammaloop/gammaloop-api — 0.1.0 (features: cli)
- gammaloop/gammaloop — 0.3.4 (features: python_api, python_abi, python_stubgen)
- linnet/linnet — 0.17.0 (features: native, nodestore-vec, serde, bincode, drawing, symbolica)
- linnet/linnet-py — 0.1.0 (features: extension-module, abi3-py310)
- spenso/spenso — 0.6.0 (features: native, shadowing)
- spenso/spenso-macros — 0.3.2 (no optional features)
- spenso/spenso-hep-lib — 0.1.7 (features: native)
- spenso/spynso3 — 0.1.2 (features: python_stubgen)
- idenso/idenso — 0.3.0 (features: native, bincode, reference-cases)
- idenso/idenso — 0.3.0 (features: python, python_stubgen)
- vakint/vakint — 0.1.2 (no optional features)
- vakint/vakint — 0.1.2 (features: symbolica_community_module, python_stubgen)