

FILTERS

Westwood

PREMIUM FUEL FILTERS

ALUMINUM TOP WITH EPOXY COATING INSIDE!

FEATURING THE LATEST COMPUTER DESIGNED CAST ALUMINUM
TOP, CHOICE OF ELEMENT TYPE, AND **EPOXY** COATING INSIDE !

- Advanced design CAST ALUMINUM TOP is the industry's strongest and most corrosion resistant!
- Galvanized canister with EPOXY COATING on the inside - FIRST in the industry!
- Highest UL GPH and pressure rating of any filter in its class
- 360° screwdriver slot makes disassembly for element changing easy



with **Pure Oil™**

Fiber-Welded White Element

High Efficiency Heating Oil Filter
REPLACES ELEMENT ANNUALLY OR WHEN CLOGGED
F10: 17 GPH, 52 PSI
F30: 32 GPH, 52 PSI

W/P No. **F10** W/P No. **F30**

Ultra-10™

10 Micron Pleated Paper Element

High Efficiency Heating Oil Filter
REPLACES ELEMENT ANNUALLY OR WHEN CLOGGED
F12: 17 GPH, 52 PSI
F32: 32 GPH, 52 PSI

W/P No. **F12** W/P No. **F32**

CLASSIC FELT™

Wool Felt Stacked Segment Element

High Efficiency Heating Oil Filter
REPLACES ELEMENT ANNUALLY OR WHEN CLOGGED
F15: 17 GPH, 52 PSI
F35: 32 GPH, 52 PSI

W/P No. **F15** W/P No. **F35**

COMPLETE FILTERS with EPOXY coated can

W/P No.	Element Type	GPH	PSI	Replaces
F10 F12 F15	Pure-Oil™ Ultra-10™ CLASSIC FELT™	17	52	General 1A-25A, Unifilter 77, Sid Harvey (Mitco) 264, 264F
F30 F32 F35	Pure-Oil™ Ultra-10™ CLASSIC FELT™	32	52	General 2A-700A, Unifilter 99, Sid Harvey (Mitco) 265, 265F

All filters have 3/8" - NPT pipe connections



UL approved CANISTER UPGRADE KITS on page F9
Individual FILTER GASKETS on page F8

F1

rev. 5-1-05

Please order by W/P No.