

PIKO Table

STP5



The picture is only illustrative, it may not exactly match the product described.

Product description

Steel weldment. The construction consists of two sides, welded from sheet metal burn parts, which carry 5 wooden boards of rectangular shape of dimensions 140x21 mm (tropical wood, acacia), or eventually 140x26 mm (oak, wood pine ThermoWood®) with a length of 1780 mm fixed by stainless steel screws to the supporting structure.

Material

Construction: steel grade 11
Solid wood: oak, wood pine ThermoWood®, tropical wood, acacia

[DOWNLOAD PDF SAMPLER >](#)

Surface treatment

Galvanized steel treated with powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium), RAL 9003 (white), RAL 3003 (red), RAL 6021 (green), shade of Corten (rusty).

Other RAL shades according to RAL sampler on the web.

Oak – treated with impregnation and a glaze with biocidal effect

Thermally modified wood pine ThermoWood® – penetration coating for wood with UV protection

Tropical wood – treated with teak oil

Acacia – treated with teak oil

Dimensions

1800×708×701 mm / 40 kg

Anchoring

Anchoring is done with four stainless steel threaded rods M12 of length min. 200 mm and four nut cover caps M12 with a chemical anchor into concrete foundations prepared in advance.
A detailed drawing is available for download on the website for each particular product.

