

SADKO Table

STS1



The picture is only illustrative, it may not exactly match the product described.

Product description

Steel weldment. The construction consists of two side rails welded from a bent strip 50 x 10 mm. The desk is made up of 5 rectangular (42 x 117 mm) lathes of length 1800 mm. The laths are inserted among the parts of the structure and secured with M8 metric screws and nuts.

Material

Construction: steel grade 11
Solid wood: spruce, wood pine ThermoWood®

[DOWNLOAD PDF SAMPLER >](#)

Surface treatment

Natural aluminium shade powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium), RAL 9003 (white), RAL 3003 (red), RAL 6021 (green), shade of Corten (rusty).
Other RAL shades according to RAL sampler on the web.
Spruce – two-layer impregnation and lacquer mixed with water with beeswax
Thermally modified wood pine ThermoWood® – penetration coating for wood with UV protection
Oak – treated with impregnation and a glaze with biocidal effect

Dimensions

1800×677×743 mm

Anchoring

Anchoring is done by casting of the legs into 2 concrete base pads directly.
A detailed drawing is available for download on the website for each particular product.

