

ALUMA Bench

LAL3-60



The picture is only illustrative, it may not exactly match the product described.

Product description

The bench is made of aluminium alloy including the longitudinal connecting structure made of galvanized steel treated with powder coating. The seat and backrest are made from solid wooden boards attached to the supporting structure with stainless screws with following dimensions: 6 wooden boards of rectangular shape 117x26 mm – applies for spruce and oak or 6 wooden boards of rectangular shape 117x26 mm – applies for wood pine ThermoWood® or 6 wooden lamellas of rectangular shape 117x21 mm – applies for tropical wood.

Material

Construction: aluminium alloy and steel grade 11
Solid wood: spruce, oak, wood pine ThermoWood®, tropical wood, acacia

[DOWNLOAD PDF SAMPLER >](#)

Surface treatment

Natural aluminium shade optionally with powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium), RAL 9003 (white), RAL 3003 (red), RAL 6021 (green), shade of Corten (rusty).
Other RAL shades according to RAL sampler on request only.
Spruce – two-layer impregnation and lacquer mixed with water with beeswax
Tropical wood – treated with teak oil
Oak – treated with impregnation and a glaze with biocidal effect
Thermally modified wood pine ThermoWood® – penetration coating for wood with UV protection
Acacia – treated with teak oil

Dimensions

600×665×810 mm

Anchoring

Anchoring is done with four stainless steel threaded rods M10 of length min. 200 mm and four nut cover caps M10 with a chemical anchor into concrete foundations prepared in advance.
A detailed drawing is available for download on the website for each particular product.

