

BETLA Bench

LBE6



The picture is only illustrative, it may not exactly match the product described.

Product description

Bench is made of concrete grade C 30/37. To the side rails are attached seat and backrest made from solid wooden lamellas attached to the galvanized supporting structure with stainless screws M8. The seat is made of five wooden lamellas of rectangular shape of dimensions 70x40 mm (TW 68x42 mm), the backrest is made of 3 wooden lamellas of same dimensions.

Material

Construction: concrete grade C 30/37 (possible occurrence of small capillary cracks that do not affect the strength of the structure)
Solid wood: spruce, oak, wood pine ThermoWood®, tropical wood

[DOWNLOAD PDF SAMPLER >](#)

Surface treatment

Concrete shade.
Spruce – two-layer impregnation and lacquer mixed with water with beeswax
Tropical wood – treated with teak oil
Oak – treated with impregnation and a glaze with biocidal effect
Thermally modified wood pine ThermoWood® – penetration coating for wood with UV protection

Dimensions

1800×676×770 mm / 68 kg

Anchoring

Anchoring is done with four stainless steel threaded rods M10 of length min. 200 mm and four nut cover caps M10 with a chemical anchor into concrete foundations prepared in advance.
A detailed drawing is available for download on the website for each particular product.

