

BORDO Bench

LBO2



The picture is only illustrative, it may not exactly match the product described.

Product description

A massive bench consisting of wooden boards and supporting steel construction. Seat is made of solid wood. The construction consists of two legs bent from a 50 x 10 mm stripes carrying hidden threaded rods. The threaded rods pull the wooden boards interleaved with sheet metal of thickness 10 mm and rubber cuts together. The seat is made up in total of 15 rectangular (26 x 140 mm) boards of length 2900 mm in wood pine ThermoWood® or 17 rectangular (21 x 140 mm) boards of length 2900 mm in tropical wood.

Material

Construction: steel grade 11
Solid wood: wood pine ThermoWood®, tropical wood

[DOWNLOAD PDF SAMPLER >](#)

Surface treatment

Galvanized steel treated with powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium), RAL 9003 (white), RAL 3003 (red), RAL 6021 (green), shade of Corten (rusty).
Other RAL shades according to RAL sampler on request only.
Tropical wood – treated with teak oil
Thermally modified wood pine ThermoWood® – penetration coating for wood with UV protection

Dimensions

2900×530×420 mm / 90-155 kg

Anchoring

Anchoring is done with four stainless steel threaded rods M10 of length min. 200 mm and four nut cover caps M10 with a chemical anchor into concrete foundations prepared in advance.
A detailed drawing is available for download on the website for each particular product..

