

## DINA Bench

LDI3



The picture is only illustrative, it may not exactly match the product described.

## Product description

Steel weldment. The construction consists of two side rails welded from a bent strip and bent L profiles. A seat and backrest are made of solid wood attached to the supporting structure with stainless screws. The seat is made up of 6 rectangular (70 x 40 mm) lathes of length 1744 mm. The backrest consists of 1 rectangular wooden board (180 x 32 mm) of length 1800 mm.

## Material

Construction: steel grade 11  
Solid wood: spruce, oak, wood pine ThermoWood®, tropical wood

[DOWNLOAD PDF SAMPLER >](#)

## Surface treatment

Galvanized steel treated with powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium), RAL 9003 (white), RAL 3003 (red), RAL 6021 (green), shade of Corten (rusty).  
Other RAL shades according to RAL sampler on request only.  
Spruce – two-layer impregnation and lacquer mixed with water with beeswax  
Tropical wood – treated with teak oil  
Oak – treated with impregnation and a glaze with biocidal effect  
Thermally modified wood pine ThermoWood® – penetration coating for wood with UV protection

## Dimensions

1800×740×795 mm / 41 kg

## Anchoring

Anchoring is done with four stainless steel threaded rods M10 of length min. 200 mm and four nut cover caps M10 with a chemical anchor into concrete foundations prepared in advance.  
A detailed drawing is available for download on the website for each particular product.

