

NISHA Bench

LNI1-60



The picture is only illustrative, it may not exactly match the product described.

Product description

The construction consists of two cast iron side rails to which wooden boards of the following dimensions are fixed: 2 boards of rectangular shape (117x26 mm), 2 boards of rectangular shape (92x26 mm), 2 boards of rectangular shape (68x26 mm) and 3 boards of atypical arched profile. They are attached to the construction by stainless steel screws. The boards are reinforced in the middle by steel strip.

Material

Construction: cast iron
Solid wood: oak, wood pine ThermoWood®, tropical wood

[DOWNLOAD PDF SAMPLER >](#)

Surface treatment

Hot-dip zinc treated with powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium), RAL 9003 (white), RAL 3003 (red), RAL 6021 (green), shade of Corten (rusty).
Other RAL shades according to RAL sampler on request only.
Tropical wood – treated with teak oil
Oak – treated with impregnation and a glaze with biocidal effect
Thermally modified wood pine ThermoWood® – penetration coating for wood with UV protection

Dimensions

600×655×775 mm

Anchoring

Anchoring is done with four stainless steel threaded rods M10 of length min. 200 mm and four nut cover caps M10 with a chemical anchor into concrete foundations prepared in advance.
A detailed drawing is available for download on the website for each particular product.

