

NISHA Bench

LNI4



The picture is only illustrative, it may not exactly match the product described.

Product description	The construction consists of steel strips firmly anchored to the concrete foundations and steel weldments screwed to them. On the steel weldments, wooden boards with the following dimensions are fixed: 2 rectangular boards (117×26 mm), 1 rectangular board (92×26 mm) and 2 boards of atypical arch profile. They are attached to the construction by stainless steel screws.	
Material	Construction: stainless steel Solid wood: oak, wood pine ThermoWood®, tropical wood	DOWNLOAD PDF SAMPLER >
Surface treatment	Galvanized steel treated with powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium), RAL 9003 (white), RAL 3003 (red), RAL 6021 (green), shade of Corten (rusty). Other RAL shades according to RAL sampler on request only. Tropical wood – treated with teak oil Oak – treated with impregnation and a glaze with biocidal effect Thermally modified wood pine ThermoWood® – penetration coating for wood with UV protection	
Dimensions	1800×505×61 mm	
Anchoring	Anchoring is done with six stainless steel threaded rods M10 of length min. 80 mm with a chemical anchor into concrete foundations prepared in advance. A detailed drawing is available for download on the website for each particular product.	

