

## RADIANO Bench

LRA11, R2000



The picture is only illustrative, it may not exactly match the product described.

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                           |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|
| Product description | Steel weldment. The construction is made of sheet metal shavings thick 8 mm (leg) and weldment made of sheet metal flakes thick 5 mm (45 ° arc shape support structure), which are connected to each other by three M8 screws. To the supporting structure are attached 16 pieces of radially placed trapezoidal wooden laths of length 440 mm fixed to the structure by stainless steel screws.                                                                                                                                                                                                               |                                           |
| Material            | Construction: steel grade 11<br>Solid wood: spruce, oak, wood pine ThermoWood®, tropical wood                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | <a href="#">DOWNLOAD PDF SAMPLER &gt;</a> |
| Surface treatment   | Galvanized steel treated with powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium), RAL 9003 (white), RAL 3003 (red), RAL 6021 (green), shade of Corten (rusty).<br>Other RAL shades according to RAL sampler on request only.<br>Spruce – two-layer impregnation and lacquer mixed with water with beeswax<br>Tropical wood – treated with teak oil<br>Oak – treated with impregnation and a glaze with biocidal effect<br>Thermally modified wood pine ThermoWood® – penetration coating for wood with UV protection |                                           |
| Dimensions          | 440×435 mm / R2000                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                           |
| Anchoring           | Anchoring is done with four stainless steel threaded rods M10 of length min. 200 mm and four nut cover caps M10 with a chemical anchor into concrete foundations prepared in advance.<br>A detailed drawing is available for download on the website for each particular product.                                                                                                                                                                                                                                                                                                                              |                                           |

