

## RADIANO Bench

LRA14, R2000



The picture is only illustrative, it may not exactly match the product described.

### Product description

Steel weldment. The construction (forming an arc 45 °) is made of sheet metal shavings thick 5 mm which are connected to each other by three M8 screws. To the supporting structure are attached 16 pieces of radially placed trapezoidal wooden laths of length 440 mm fixed to the structure by stainless steel screws.

### Material

Construction: steel grade 11  
Solid wood: spruce, oak, wood pine ThermoWood®, tropical wood

[DOWNLOAD PDF SAMPLER >](#)

### Surface treatment

Galvanized steel treated with powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium), RAL 9003 (white), RAL 3003 (red), RAL 6021 (green), shade of Corten (rusty).  
Other RAL shades according to RAL sampler on request only.  
Spruce – two-layer impregnation and lacquer mixed with water with beeswax  
Tropical wood – treated with teak oil  
Oak – treated with impregnation and a glaze with biocidal effect  
Thermally modified wood pine ThermoWood® – penetration coating for wood with UV protection

### Dimensions

440×66 mm / R2000

### Anchoring

Anchoring is done with four stainless steel threaded rods M10 of length min. 100 mm and four nut cover caps M10 into concrete wall prepared in advance of 400 mm height and same shape as the bench.  
A detailed drawing is available for download on the website for each particular product.

