

VELA Bench

LVL1



The picture is only illustrative, it may not exactly match the product described.

Product description

Steel weldment. The construction consists of two side rails welded from a bent strip 50 x 8 mm and sheet blasts of thickness 5 mm. A seat and backrest are made of solid wood attached to the supporting structure with stainless screws. The seat and backrest are made up of 2 rectangular (70 x 32 mm) lathes of length 1800 mm and another 17 lathes (40 x 32 mm) of same length.

Material

Construction: steel grade 11
Solid wood: oak, tropical wood, acacia

[DOWNLOAD PDF SAMPLER >](#)

Surface treatment

Galvanized steel treated with powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium), RAL 9003 (white), RAL 3003 (red), RAL 6021 (green), shade of Corten (rusty).
Other RAL shades according to RAL sampler on request only.
Tropical wood – treated with teak oil
Oak – treated with impregnation and a glaze with biocidal effect
Acacia - treated with teak oil

Dimensions

1800×969×732 mm

Anchoring

Anchoring is done with four stainless steel threaded rods M10 of length min. 200 mm and four nut cover caps M10 with a chemical anchor into concrete foundations prepared in advance.
A detailed drawing is available for download on the website for each particular product.

