

VELA Bench

LVL8



The picture is only illustrative, it may not exactly match the product described.

Product description

The construction consists of steel strips firmly anchored to the concrete foundations and steel weldments screwed to them. On the steel weldments, wooden laths with the following dimensions are fixed: 2 rectangular laths (70x32 mm) and 5 rectangular laths (40x32 mm). They are attached to the construction by stainless steel screws.

Material

Construction: steel grade 11
Solid wood: oak, tropical wood, acacia

[DOWNLOAD PDF SAMPLER >](#)

Surface treatment

Galvanized steel treated with powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium), RAL 9003 (white), RAL 3003 (red), RAL 6021 (green), shade of Corten (rusty).
Other RAL shades according to RAL sampler on request only.
Tropical wood – treated with teak oil
Oak – treated with impregnation and a glaze with biocidal effect
Acacia - treated with teak oil

Dimensions

1800×424×72 mm

Anchoring

Anchoring is done with six stainless steel threaded rods M10 of length min. 80 mm with a chemical anchor into concrete foundations prepared in advance.
A detailed drawing is available for download on the website for each particular product.

