

ALUMA Bench

LAL3



The picture is only illustrative, it may not exactly match the product described.

Product description	The bench is made of aluminium alloy including the longitudinal connecting structure made of galvanized steel treated with powder coating. The seat and backrest are made from solid wooden boards attached to the supporting structure with stainless screws with following dimensions: 6 wooden boards of rectangular shape 117x26 mm – applies for spruce and oak or 6 wooden boards of rectangular shape 117x26 mm – applies for wood pine ThermoWood® or 6 wooden lamellas of rectangular shape 117x21 mm – applies for tropical wood.
Material	Construction: aluminium alloy and steel grade 11 Solid wood: spruce, oak, wood pine ThermoWood®, tropical wood, acacia
Surface treatment	Natural aluminium shade optionally with powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium), RAL 9003 (white), RAL 3003 (red), RAL 6021 (green), shade of Corten (rusty). Other RAL shades according to RAL sampler on request only. Spruce – two-layer impregnation and lacquer mixed with water with beeswax Tropical wood – treated with teak oil Oak – treated with impregnation and a glaze with biocidal effect Thermally modified wood pine ThermoWood® – penetration coating for wood with UV protection Acacia - treated with teak oil
Dimensions	1800x665x810 mm / 29 kg
Anchoring	Anchoring is done with four stainless steel threaded rods M10 of length min. 200 mm and four nut cover caps M10 with a chemical anchor into concrete foundations prepared in advance. A detailed drawing is available for download on the website for each particular product.

