


# AUDITO Outdoor seating

LAU2L1



The picture is only illustrative, it may not exactly match the product described.

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product description | This is an add-on (connecting) module for the base module LAU201. The structure consists of a side plate made from a 5 mm thick laser-cut steel plate and bent laser-cut components made from 3 mm thick steel plate in various lengths, which support the individual seat slats. The trapezoidal seat uses slats with a cross-section of 70 × 40 mm for the outer slats and 32 × 40 mm for the intermediate slats. The slats are fastened to the structure with stainless steel screws. The assembly is connected using M8 carriage bolts conforming to DIN 603. |
| Material            | Construction: steel grade 11<br>Solid wood: tropical wood, wood pine ThermoWood®                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Surface treatment   | Natural aluminium shade optionally with powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium), RAL 9003 (white), RAL 3003 (red), RAL 6021 (green), shade of Corten (rusty).<br>Other RAL shades according to RAL sampler on the web.<br>Tropical wood – treated with teak oil<br>Thermally modified wood pine ThermoWood® – penetration coating for wood with UV protection                                                                                                |
| Dimensions          | 1307x1308x700 mm / 85 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Anchoring           | Anchoring is done with two stainless steel threaded rods M10 of length min. 200 mm and two nut cover caps M10 with a chemical anchor into concrete foundations prepared in advance.<br>A detailed drawing is available for download on the website for each particular product.                                                                                                                                                                                                                                                                                   |

