

AUDITO Outdoor seating

LAU302



The picture is only illustrative, it may not exactly match the product described.

Product description	Steel weldment. The structure consists of a side plates made from a 5 mm thick laser-cut steel plates and bent laser-cut components made from 3 mm thick steel plate in various lengths, which support the individual seat slats. The trapezoidal seat uses slats with a cross-section of 70 × 40 mm for the outer slats and 32 × 40 mm for the intermediate slats. The slats are fastened to the structure with stainless steel screws. The assembly is connected using M8 carriage bolts conforming to DIN 603.
Material	Construction: steel grade 11 Solid wood: tropical wood, wood pine ThermoWood®
Surface treatment	Natural aluminium shade optionally with powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium), RAL 9003 (white), RAL 3003 (red), RAL 6021 (green), shade of Corten (rusty). Other RAL shades according to RAL sampler on the web. Tropical wood – treated with teak oil Thermally modified wood pine ThermoWood® – penetration coating for wood with UV protection
Dimensions	1685x1995x1000 mm / 221 kg
Anchoring	Anchoring is done with four stainless steel threaded rods M10 of length min. 200 mm and four nut cover caps M10 with a chemical anchor into concrete foundations prepared in advance. A detailed drawing is available for download on the website for each particular product.

