

INOA Bench

LIN6



The picture is only illustrative, it may not exactly match the product described.

Product description	Steel weldment. The construction consists of two side walls welded from bent sheet metal pieces of 8 mm thickness, the seat is reinforced in the middle with a strip. The supporting structure is supported by 2 rectangular plates of 185 × 40 mm cross-section rounded with R20 radius, 2 rectangular plates of 140 × 40 mm cross-section and 1 rectangular plate of 68 × 40 mm length 1800 mm, fixed with stainless steel screws.
Material	Construction: steel grade 11 Solid wood: wood pine ThermoWood®, oak
Surface treatment	Hot-dip zinc treated with powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium), RAL 9003 (white), RAL 3003 (red), RAL 6021 (green), shade of Corten (rusty). Other RAL shades according to RAL sampler on the web. Thermally modified wood pine ThermoWood® – penetration coating for wood with UV protection Oak – treated with impregnation and a glaze with biocidal effect
Dimensions	1800×681×779 mm / 62 kg
Anchoring	Anchoring is done with four stainless steel threaded rods M10 of length min. 200 mm and four nut cover caps M10 with a chemical anchor into concrete foundations prepared in advance. A detailed drawing is available for download on the website for each particular product.

