

VELA Bench

LVL1



The picture is only illustrative, it may not exactly match the product described.

Product description	Steel weldment. The construction consists of two side rails welded from a bent strip 50 x 8 mm and sheet blasts of thickness 5 mm. A seat and backrest are made of solid wood attached to the supporting structure with stainless screws. The seat and backrest are made up of 2 rectangular (70 x 32 mm) lathes of length 1800 mm and another 17 lathes (40 x 32 mm) of same length.
Material	Construction: steel grade 11 Solid wood: oak, tropical wood, acacia
Surface treatment	Galvanized steel treated with powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium), RAL 9003 (white), RAL 3003 (red), RAL 6021 (green), shade of Corten (rusty). Other RAL shades according to RAL sampler on request only. Tropical wood – treated with teak oil Oak – treated with impregnation and a glaze with biocidal effect Acacia - treated with teak oil
Dimensions	1800×969×732 mm
Anchoring	Anchoring is done with four stainless steel threaded rods M10 of length min. 200 mm and four nut cover caps M10 with a chemical anchor into concrete foundations prepared in advance. A detailed drawing is available for download on the website for each particular product.

