

## VELA Lounger

LVL6



The picture is only illustrative, it may not exactly match the product described.

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product description | Steel weldment. The construction consists of two side rails welded from a bent strip 50×8 mm and sheet blasts of thickness 5 mm. The supporting structure carries wooden laths of 600 mm length attached to the structure by stainless steel screws of the following dimensions: 2 laths of rectangular shape (70×32 mm) and 23 laths of rectangular shape (40×32 mm). The construction is rotatable by 360°.                                                    |
| Material            | Construction: steel grade 11<br>Solid wood: oak, tropical wood, acacia                                                                                                                                                                                                                                                                                                                                                                                           |
| Surface treatment   | Galvanized steel treated with powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium), RAL 9003 (white), RAL 3003 (red), RAL 6021 (green), shade of Corten (rusty).<br>Other RAL shades according to RAL sampler on the web.<br>Tropical wood – treated with teak oil<br>Oak – treated with impregnation and a glaze with biocidal effect<br>Acacia - treated with teak oil |
| Dimensions          | 1572×600×990 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Anchoring           | Anchoring is done with four stainless steel threaded rods M10 of length min. 100 mm and four nut cover caps M10 with a chemical anchor into concrete foundations prepared in advance.<br>A detailed drawing is available for download on the website for each particular product.                                                                                                                                                                                |

