

TECHNICAL DATA SHEET

This data is provided in the belief it is accurate with in generally accepted standards and is provided for the information of qualified personnel. It does not constitute an offer by the manufacturer warranty or guarantee its accuracy or completeness is describing the performance or suitability of the various products. The users therefore should make their own determination in using the product of the data contained here in for any application.

INO MASTIC (ACRYLIC SEALANT)

INO MASTIC is a permanent, flexible sealant for a wide variety internal application where low (+/-5%) Movement is anticipated. Excellent adhesion to most substrates.

INO MASTIC, Acrylic flexible filler is a non-staining, sealant that resist cracking and gives a smooth finish that requires no sanding

USES

Ideal for caulking and scaling

- Door and windows frames
- Skirting Boards
- Floor boards
- Walls
- Ceilings
- Plasterboards

ADHERES TO:-

- Brick
- Concrete
- Plastics
- Ceramics
- Tiles

SURFACE PREPARATION AND APPLICATION

Ensure gaps and cracks to be filled are dry and free of grease, dirt, dust and any loose internal. Fill the scam with sample amount of filler can be over-painted approximately two hours after application.

FOR BEST RESULTS

- Reseal container for storage and re-use .Store away from extreme hear and cold
- Joint sizes more than 20 min wide or 10 mm deep must be filled with backing rod as back-up filler.
- Do not use for below water line application.

Do not use as a putty. Do not apply when temperature is below 7°C

TEL: 07 2662359, FAX: 07 2662453, PO BOX. 6157, AL RAMS, R.A.K, U.A.E.



TYPICAL PROPERTIES

Application temperature : 7° C to 40° C Working time : 10 to 20 minutes

Complete drying time : 36 hour (Depending upon the substrate)

Percentage Solids : 78 +2% Specific gravity : 1.56 Movement joint : 10%

CLEANING

Clean tools with soap and water after use.

SHELF LIFE

Up to 8 months in unopened pack stored under 30°C kept out of direct sunlight.

COLOUR

White / Grey

PACKAGING

Available in 5 kg and 20kg pails

SPECIFICATIONS

Conforms to ASTM C 733

HEALTH AND SAFETY

As with all chemical products, caution should always be exercised. Protective clothing, such as gloves and goggles should be worn. (See packing for specific instruction) Troat any splashes to the skin or eyes with fresh water immediately. Should any of the products be accidentally swallowed, do not induce vomiting but call for medical assistance immediately. Ensure the container as available for the medical attendant to examine any relevant instruction and contents details. Reseal all containers after use and ensure product is stored as instructed on the safety section of the labeling.

CAUTION

Avoid contact with eyes and skin. Only use in well-ventilated areas. Keep out of reach of children.

TEL: 07 2662359, FAX: 07 2662453, PO BOX. 6157, AL RAMS, R.A.K, U.A.E.