A Appendix

A.1 Parameter Analysis

Table 1. Parameter Analysis for conflict time limit.

conflict time limit	1	2	3	4	5	10
Total Collisions	344	322	310	306	321	199
Collision Types	6	8	11	11	10	5

Table 2. Parameter Analysis for spatial conflict time limit.

spatial conflict time limit	5	10	15	20	30
Total Collisions	200	289	310	333	211
Collision Types	6	10	11	10	7

This section presents a parameter analysis for two key parameters: the conflict time limit (t_c) and the spatial time limit (t_s). The results, detailed in Tables 1 and 2, evaluate how variations in these parameters affect the performance, specifically focusing on total collisions and collision types.

The analysis indicates that the model's performance exhibits robustness within certain value ranges for both parameters. For instance, in Table 1, performance remains relatively stable for t_c values between 3 and 5. However, performance can change significantly when parameter values are set at the extremes of the tested range (e.g., t_c = 10 in Table 1 or t_s = 5 in Table 2). This behavior confirms that while our method is not overly sensitive to minor adjustments within an optimal window, selecting appropriate values is crucial for achieving desired outcomes.

A.2 Examples for collision types for RQ1

A catalog of all 12 discovered collision types, each with a figure and a detailed description, is provided in the following.




Fig. 1. Example of 1st type of collision scenario.

Example 1: shown as Figure 1, the NPC vehicle is initially stopped between two lanes. As the EV approaches, the NPC vehicle begins to slowly merge into the lane occupied by the EV. The EV cannot avoid the NPC vehicle and collides with it. In this case, the Prediction module likely fails to assign sufficient probability to the high-risk action of merging when encountering a vehicle stopped in an ambiguous position between lanes.




Fig. 2. Example of 2nd type of collision scenario.

Example 2: shown as Figure 2, the ego and NPC vehicles are traveling in different lanes. The NPC vehicle merges into the EV's lane and then immediately returns to its original lane. The EV

fails to decelerate in time, resulting in a collision with the NPC vehicle. In this case, the Prediction module likely struggles to accurately forecast the trajectory of a highly erratic vehicle performing rapid, successive lane changes, leading to unstable or incorrect planning by the EV.




Fig. 3. Example of 3rd type of collision scenario.

Example 3: shown as Figure 3, the NPC vehicle is stopped between two lanes, with its front end oriented away from the EV's lane. As the EV passes by, it sideswipes the NPC vehicle from the side, resulting in a collision. In this case, the Planning module likely fails to calculate a safe path with sufficient lateral clearance around the stationary NPC vehicle.




Fig. 4. Example of 4th type of collision scenario.

Example 4: shown as Figure 4, the ego and NPC vehicles are traveling in different lanes. As the NPC vehicle approaches an intersection, it suddenly turns its front end toward another lane. Although the EV begins to brake, it does not fully decelerate and ultimately collides with the NPC vehicle. In this case, the Planning module likely fails to execute a sufficiently aggressive emergency braking maneuver in response to the NPC's sudden turn, potentially underestimating the collision risk presented by the rapidly changing situation near the intersection.




Fig. 5. Example of 5th type of collision scenario.

Example 5: shown as Figure 5, the ego and NPC vehicles are traveling in different lanes. As the NPC vehicle approaches an intersection, it decelerates and attempts to merge into the EV's lane. However, midway through the lane change, while straddling the center line, the NPC vehicle abruptly returns to its original lane. The EV cannot avoid the NPC vehicle and collides with it. In this case, the Prediction module fails to cope with the highly erratic and indecisive behavior of the NPC vehicle, as the abrupt reversal of the merge maneuver invalidates the system's short-term trajectory forecast.




Fig. 6. Example of 6th type of collision scenario.

Example 6: shown as Figure 6, the NPC vehicle is stopped at an angle in the intersection. Although the EV decelerates, it does not slow down enough and collides with the NPC vehicle. In this case, the Planning module fails to correctly calculate the required deceleration or stopping

distance to avoid the stationary hazard, likely underestimating the risk posed by the NPC vehicle's ambiguous angular position in the intersection.




Fig. 7. Example of 7th type of collision scenario.

Example 7: shown as Figure 7, the ego and NPC vehicles are initially in different lanes. The NPC vehicle is positioned side-rear relative to the EV. It then accelerates, moves to side-front position, and merges in front of the EV and decelerates. The EV is unable to slow down in time and collides with the NPC vehicle. In this case, the Planning module fails to re-establish a safe following distance immediately after the aggressive cut-in maneuver, making a collision unavoidable when the NPC abruptly decelerates in front of the EV.




Fig. 8. Example of 8th type of collision scenario.

Example 8: shown as Figure 8, the NPC vehicle is traveling in an adjacent lane near the center line and gradually moves closer to the EV's lane. As the NPC vehicle partially enters the lane occupied by the EV, the EV fails to decelerate and collides with the NPC vehicle. In this case, the Planning module fails to apply a sufficient safety margin or react decisively to the NPC's gradual lane drift, potentially because its thresholds for lane intrusion are set too high to prevent overly sensitive reactions in normal traffic.




Fig. 9. Example of 9th type of collision scenario.

Example 9: shown as Figure 9, the first NPC vehicle is stationary in the same lane as the EV. A second NPC vehicle initially merges into the EV's lane and, upon approaching the first NPC vehicle, attempts to overtake it by merging back to its original lane and then braking. The EV does not slow down in time, resulting in a collision with the second NPC vehicle. In this case, the Prediction module fails to accurately forecast the complex, multi-stage maneuver of the second NPC, specifically its decision to brake after changing lanes to overtake another vehicle.




Fig. 10. Example of 10th type of collision scenario.

Example 10: shown as Figure 10, both NPC vehicles are initially in different lanes from the EV. The first NPC vehicle is stopped, while the second NPC vehicle is waiting in another lane. The second NPC vehicle then begins to merge into the EV's lane. However, once the first NPC vehicle starts moving, the second NPC vehicle aborts its lane change and merges back. The EV fails to decelerate in time and collides with the second NPC vehicle. In this case, the Prediction module fails to model the complex, coupled interaction between the two NPCs, specifically by not anticipating

that the second NPC's decision to merge and then abort is dependent on the first NPC starting to move.




Fig. 11. Example of 11th type of collision scenario.

Example 11: shown as Figure 11, the first NPC vehicle is stopped in a different lane from the EV. The second NPC vehicle, also in a different lane from the EV, completes a lane change to overtake the first NPC vehicle but remains at a lower speed than the EV. As a result, the EV does not decelerate in time and collides with the second NPC vehicle. In this case, the Planning module fails to adjust the EV's speed to match the slower velocity of NPC 2 after it completes the lane change, indicating a failure in the system's longitudinal control or target acquisition logic.




Fig. 12. Example of 12th type of collision scenario.

Example 12: shown as Figure 12, the NPC vehicle is traveling with part of its body straddling the yellow center line of the oncoming lane. As the EV passes by, it makes side contact with the NPC vehicle, resulting in a sideswipe collision. In this case, the Planning module fails to calculate a safe trajectory with sufficient lateral clearance while passing the oncoming NPC, underestimating the risk or misjudging the precise boundaries of the vehicle encroaching on its lane.

A.3 Examples for extra collision types for RQ2




Fig. 13. Example of 13th type of collision scenario.

Example 13: shown as Figure 13, the NPC vehicle and the EV are both initially traveling on the same road. When the EV is approaching the intersection, the NPC positions to turn right. As the EV proceeds forward into the intersection and tries to turn right, it doesn't wait for the NPC to complete the turning and collide with the turning NPC. In this case, the Prediction module likely failed to accurately predict the path or turning radius of the NPC vehicle.




Fig. 14. Example of 14th type of collision scenario.

Example 14: shown as Figure 14, the NPC vehicle and the EV are both trying to merge into the same lane from different lanes. The NPC vehicle first completes the lane changing and accelerates, maintaining partial forward overlap with the EV and occupying the target space. The EV fails to yield and continues the lane change maneuver, resulting in a side-impact collision with the

NPC vehicle. In this case, the Planning module fails to abort the lane change maneuver when the target space becomes contested, likely because the Prediction module does not accurately model the NPC's defensive acceleration in response to the EV's merge attempt.




Fig. 15. Example of 15th type of collision scenario.

Example 15: shown as Figure 15, the NPC vehicle initially locates two lanes away from the EV. The NPC then initiates a double lane change to move into the EV's lane. As the NPC vehicle executes the second phase of this maneuver, entering the lane directly ahead of or adjacent to the EV, the EV fails to decelerate in time and collides with the NPC vehicle. In this case, the Prediction module fails to recognize the NPC's continuous lateral movement as a double lane change, likely incorrectly anticipating that the NPC would stabilize in the adjacent lane rather than continuing into the EV's lane.




Fig. 16. Example of 16th type of collision scenario.

Example 16: shown as Figure 16, the NPC vehicle is initially positioned significantly ahead of the EV in an adjacent lane when it begins changing into the EV's lane. In response to the NPC's maneuver, the EV starts to decelerate. However, after the NPC successfully completes the lane change and occupies the space ahead of the EV, the EV's deceleration proves insufficient to maintain a safe following distance, resulting in a rear-end collision with the NPC. In this case, the Planning module fails to calculate the appropriate deceleration required to match speeds and establish a safe following distance after the NPC enters the EV's lane.

A.4 Videos of collision types

https://drive.google.com/drive/folders/1x-PcVdAkWJ3T3dfXY4ctllTwNN4whlnv?usp=sharing contains video recordings of our experimental scenarios, which we believe will help reviewers better understand the results.