

MDM CMA HitCount Reporter — How One Command Reaches the Management Web API

Four interchangeable clients, one API — same flags, same results. Pick the client that fits your environment.

INPUT

Admin types ONE command — any client below:

```
$ hitcount --zero-only --from 2026-01-01
```

5 Final output — table / JSON

flags applied client-side

CLIENTS

RUNS ON YOUR WORKSTATION (REMOTE)

Official SDK (cpapi)

Python + cpapi package

Python (stdlib)

zero extra dependencies

RUNS ON THE MDS (EXPERT MODE)

mgmt_cli version

bundled CLI binary

Gaia Clish version

Gaia shell, batch mode

TRANSPORT

HTTPS + cert fingerprint pinning

cached read-only sessions:
~/.hitcount_sdk_sessions.json

HTTPS POST /web_api/<command>

session id in X-chkp-sid header
TLS verified by default

local binary → API server

login -r true, --session-id
(root login, no password prompt)

batch file per call

clish -i -f: login + show + logout
no persistent session

MANAGEMENT

MDS (Multi-Domain Server) — API server :443 — the single front door for all four clients

System Data (MDS context)

1 login here first
show-domains →
lists every CMA

CMA-EMEA

2 own login · own sid
3 show-access-layers
4 rulebase + hits

CMA-US

2 own login · own sid
3 show-access-layers
4 rulebase + hits

CMA-APAC ...

2 own login · own sid
3 show-access-layers
4 rulebase + hits

ENFORCEMENT

cl-paris
cluster (EMEA)

fw-dallas
firewall (US)

fw-tokyo ...
firewalls (APAC)

Enforcing firewalls & clusters — hit counters are recorded here as traffic matches rules

Note — no enforcing firewall in a domain → every rule reports 0 hits

One run, step by step

- 1 login → System Data · show-domains
- 2 login to EACH CMA separately — new sid, scoped to that domain
- 3 show-access-layers
container key: "access-layers"
- 4 show-access-rulebase
+ show-hits: true + hits-settings
{from-date, to-date, target}
paginated, sections flattened
- 5 client-side filters: --zero-only,
--min-hits, --top → table / JSON