📄 Brief Overview of the Generator Script

The generator script (`generate_sa818s_at_commands.py`) creates a JSON file (`sa818s_at_commands.json`) containing:

- **Initialization Commands**: One-time setup commands for the transmitter and receiver, ensuring proper module operation.
- **Configurations**: 1,952 `AT+DMOSETGROUP` command pairs for the PMR446 band (16 frequencies × 122 CXCSS codes), with:
  - **Transmitter**: Transmit-only, using valid `TFV` (frequency) and `Tx_CXCSS`, with dummy `RFV` (400.0000 MHz) and `Rx_CXCSS` (0000).
  - **Receiver**: Receive-only, using valid `RFV`, `Rx_CXCSS`, and `SQ=4`, with dummy `TFV` and `Tx_CXCSS`.
  - Format per entry:

```
{
  "id": <1-1952>,
  "type": "NONE" | "CTCSS" | "CDCSS",
  "frequency": "<e.g., 446.0063>",
  "at_tx_cmd": "AT+DMOSETGROUP=0,<freq>,400.0000,
<cxcss>,4,0000\r\n",
  "at_rx_cmd": "AT+DMOSETGROUP=0,400.0000,<freq>,0000,4,
<cxcss>\r\n"
}
```

Purpose: Generates all possible PMR446 configurations for a transmit-only SA818S module (PTT pin low) and a receive-only module (PTT pin high), ensuring compliance with PMR446 standards (12.5 kHz bandwidth, 500 mW via H/L pin low).

Key Features:

PROF

- Covers 16 PMR446 frequencies (446.00625–446.19375 MHz).
- Includes 122 CXCSS codes (1 NONE, 38 CTCSS, 83 CDCSS).
- Uses fixed squelch (4) and dummy values for irrelevant parameters.
- Saves to a compact JSON (~500–600 KB).

📡 Initialization Commands

The initialization commands are included in the `initialization` block of `sa818s_at_commands.json`. They are applied once to set up the modules before sending `AT+DMOSETGROUP` commands. Based on the generator script, they are:

Transmitter Initialization (Transmit-Only):

- **AT+DMOCONNECT**: Handshake to confirm module operation.
- **AT+SETFILTER=0,0,0**: Enables pre-emphasis/de-emphasis, high-pass, and low-pass filters for audio quality.

- **AT+SETTAIL=0**: Disables tail tone to avoid unnecessary tones after transmission.

JSON Representation:

```
"transmitter": [
  "AT+DMOCONNECT\r\n",
  "AT+SETFILTER=0,0,0\r\n",
  "AT+SETTAIL=0\r\n"
]
```

Note: PTT pin (Pin 5) must be set to low (0) via hardware to lock in transmit-only mode (SA818S datasheet, Page 10).

Receiver Initialization (Receive-Only):

- **AT+DMOCONNECT**: Handshake to confirm module operation.
- **AT+DMOSETVOLUME=4**: Sets volume to mid-level (1–8 scale, 4 chosen as default per your example).
- **AT+SETFILTER=0,0,0**: Enables all filters for optimal audio reception.

JSON Representation:

```
"receiver": [
  "AT+DMOCONNECT\r\n",
  "AT+DMOSETVOLUME=4\r\n",
  "AT+SETFILTER=0,0,0\r\n"
]
```

Note: PTT pin must be set to high (1) to lock in receive-only mode.

PROF

⚙ Usage Context

- **How to Use**:
  - Send initialization commands once via serial port (9600 bps, 8N1, datasheet Page 5) using a terminal (e.g., PuTTY) or script.
  - Example: For transmitter, send `AT+DMOCONNECT\r\n`, then `AT+SETFILTER=0,0,0\r\n`, then `AT+SETTAIL=0\r\n`.
  - Follow with an `AT+DMOSETGROUP` command from the configurations block (e.g., ID 1049: `AT+DMOSETGROUP=0,446.2000,400.0000,223I,4,0000\r\n` for transmitter).
  - Set H/L pin (Pin 7) low for 500 mW to comply with PMR446 in UAE.

- **Regulatory Notes**:
  - **UAE**: PMR446 is license-free (500 mW, 12.5 kHz, TDRA-approved equipment).
  - **Egypt**: PMR446 likely requires a license. Contact NTRA (info@tra.gov.eg) for confirmation and ETA certification.

🚀 Next Steps

- **Run the Generator**: If not done, run `generate_sa818s_at_commands.py` to create `sa818s_at_commands.json`.
- **Use the State Script**: Run the second script (`print_next_sa818s_config.py`) to print initialization commands and cycle through configurations, saving state in `state.json`.
- **Further Assistance**:
  - Need the initialization commands tested with a serial communication script?
  - Want an NTRA inquiry email draft for Egypt?
  - Prefer adjustments to initialization (e.g., different volume or filter settings)?





PROF