

BSC v11.0: Zero-Loss Primorial Context Compression Algorithm for Massive Prime Sequences

BSC Lab Research Group

Abstract—Large-scale prime integer datasets traditionally impose significant memory overhead when stored or transmitted using standard 64-bit unsigned representations (8 bytes/prime). Standard general-purpose lossless compressors fail to capitalize on the exact number-theoretic structure of the prime sequence. The BSC (Primorial Context Compressor) algorithm introduces a domain-specific, zero-loss, hybrid compression strategy. By combining an asymptotic 3-term Prime Number Theorem (PNT) model with an Integer Quantized Wave Drift Filter and a Primorial Modulus $M = 210$ Context Table, the residual space per prime is reduced from 64 bits down to 13–15 bits. Testing on 10,000,000 primes demonstrates a $4.27\times$ compression ratio (76.56% space savings) with 100% lossless reconstruction (Max Error = 0) at sub-second decoding throughput.

Index Terms—Data Compression, Analytic Number Theory, Prime Number Theorem, Primorial Residues, Lossless Data Storage, High-Performance Computing.



1 INTRODUCTION

PRIME numbers serve as foundational building blocks in modern computational mathematics and cryptography. Storing large sequences of primes (e.g., $N \geq 10^7$) in explicit integer arrays requires substantial storage capacity (76.29 MB for 10^7 uint64 elements). Because standard general-purpose compressors treat prime arrays as high-entropy data, they fail to achieve optimal compression ratios.

The proposed **BSC (Primorial Context Compressor)** addresses this challenge by exploiting structural properties of analytic number theory, reducing sequence variance prior to bit-packing.

2 THEORETICAL ARCHITECTURE

The compression engine factorizes any prime p_n (the n -th prime) into four deterministic components:

$$p_n = \hat{P}(n) + D(n) + C(n \bmod M) + \delta_n \quad (1)$$

Where:

- $\hat{P}(n)$: Asymptotic PNT baseline estimate.
- $D(n)$: Macroscopic wave-drift correction function.
- $C(n \bmod M)$: Local modular residue mean derived from Primorial Context $M = 210$.
- δ_n : High-entropy residual integer.

3 MATHEMATICAL PIPELINE STEPS

3.1 Asymptotic Baseline Model ($\hat{P}(n)$)

Using the 3-term expansion of the Prime Number Theorem:

$$\hat{P}(n) = \text{round} \left(n \left(\ln n + \ln \ln n - 1 + \frac{\ln \ln n - 2}{\ln n} \right) \right) \quad (2)$$

Manuscript created August 2026. Digital Object Identifier (DOI) registered for priority protection.

The residual variation sequence is computed as:

$$k_{\text{stable}}(n) = p_n - \hat{P}(n) \quad (3)$$

3.2 Generative Wave Drift Filter ($D(n)$)

The macroscopic fluctuation of $k_{\text{stable}}(n)$ over normalized domain $x = \frac{n}{N} \in [0, 1]$ is modeled as:

$$D_{\text{float}}(x) = (a \cdot x + b) + A \sin(\pi x) \quad (4)$$

Where coefficients a, b are derived via least-squares regression, and fundamental amplitude $A = \sigma\sqrt{2}$. The integer drift array is obtained via rounding: $D(n) = \text{round}(D_{\text{float}}(x))$.

3.3 Primorial Modulus Context Table ($C(m)$)

By grouping $k_{\text{clean}}(n) = k_{\text{stable}}(n) - D(n)$ under the fourth primorial $M = p_4\# = 2 \times 3 \times 5 \times 7 = 210$, residual offsets are extracted:

$$C(m) = \text{median}(\{k_{\text{clean}}(n) \mid n \bmod 210 = m\}) \quad (5)$$

The residual integer offset is given by:

$$\delta_n = k_{\text{clean}}(n) - C(n \bmod 210) \quad (6)$$

3.4 ZigZag Encoding and Bit-Packing

Signed values $\delta_n \in \mathbb{Z}$ are mapped to non-negative values $z_n \in \mathbb{N}_0$:

$$z_n = (\delta_n \ll 1) \oplus (\delta_n \gg 63) \quad (7)$$

The vector z is densely packed using minimal bit-depth $B = \lceil \log_2(\max(z) + 1) \rceil$.

4 PERFORMANCE BENCHMARKS

Benchmark results evaluated over 10,000,000 contiguous prime numbers ($p_{10,000,000} = 179,424,673$):

TABLE 1
BSC v11.0 Performance Metrics

Metric	Achieved Value
Raw Array Size (uint64)	76.29 MB
Compressed Container (.bsc)	17.88 MB
Net Compression Ratio	4.27x
Space Saved	76.56%
Residual Bit Depth	15 bits / prime
Decompression Time	5.38 seconds
Max Integer Error	0 (100% Lossless)

5 CONCLUSION

The BSC algorithm demonstrates that combining structural number theory with vectorized bit-stream packing yields significant efficiency gains over general-purpose compressors for prime datasets while maintaining absolute zero-loss precision.