

The **alttex** package

Arno L. Trautmann*

Version 0.a.3 April 30, 2009

This is the package **alttex** which will try to give an experimental new way to write \LaTeX ¹ code. So far it is mostly done with very dirty code and actually it's a collection of things that come into my mind during boring lectures. Maybe someone will have fun with the following code fragments.

Contents

1	introduction	2
2	Textmode	4
2.1	no escape	4
2.2	tabular	4
2.3	excel tabulars	5
2.4	tabbing	5
3	Math stuff	6
3.1	braces	6
3.2	huge display math	6
3.3	unicode math	7
3.4	Lazy underscript and superscript	8
4	Lists and such things	9
4.1	itemize with a single character	9
4.2	enumerate with a single character	11

*arno.trautmann@gmx.de

¹If you don't know about \LaTeX , see the appendix.4.2

1 introduction

The problem I have with \LaTeX ² is the antique way of typing. Because most people still use a hopelessly outdated keyboard layout («qwerty» or slightly adapted versions of that), \LaTeX doesn't make use of some cool features. I'm not talking about writing chinese or arabic text! Maybe this example will make the idea clear:

In standard \LaTeX , one has to write

This is the normal text, then comes the itemization:

```
\begin{itemize}
  \item text for first item
  \item \begin{itemize}
    \item this is an item inside an item...
    \item[ $\rightarrow$ ] Here an item with a formula:  $\int_a^b x^2 dx$ 
  \end{itemize}
  \item and the outer itemize goes on...
\end{itemize}
```

Using this package and having a superior keyboard layout³, you can simply write:⁴

This is the normal text, then comes the itemization:

- text for first item
- - this is an item inside an item
 - [\Rightarrow] Here an item with a formula: $\int_a^b x^2 dx$
- and the outer itemize goes on...

And your normal text goes on...

Well, actually I'm lying now because this is not fully implemented so far. But it's the aim of this package to provide this – besides many, many other funny and cool things. The aim is to offer a more „wysiwyg“ way, without loosing anything of logical markup. One still can re\define the • if he doesn't like the way his items look. I have just started to write the package, there will be much more stuff here in the future.

Ok, enough blahblah, now comes the code. We begin with the uninteresting preamble stuff:

²I'll write \LaTeX instead of \XeLaTeX —saves me two keystrokes. Most of the code below *only* works with \XeLaTeX . If you need support for `[utf8]inputenc` or \LuaTeX , please contact the author.

³E.g. the ergonomic layout Neo: <http://neo-layout.org/>

⁴The lmodern font I'm using here does not have the symbol for the inner item , so we change to DejaVu Sans Mono here.

`\usepackage` Now, this is the first highlight. It is an extremely simple and stupid approach to load missing packages on-the-fly, just like MikTeX does. We re`\define` the `\usepackage` and hope, it works. Only working with texlive! If you're using MikTeX, put a

into your preamble, *directly* after loading `alttex`. If this does not work, delete the following lines from your `alttex.sty`.

So far, this code seems to be a bit buggy, but it should work anyhow.

```

12 \RequirePackage{exscale}
13 \RequirePackage{ifxetex}
14 \RequirePackage{hhline}
15 \ifxetex
16 \typeout{Loading XeTeX, everything's fine.}
17 \else
18   \typeout{^^J%
19     !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!^^J%
20     ! This package can only be compiled with XeLaTeX. ^^J%
21     ! pdfLaTeX cannot handle unicode the way it is used here. ^^J%
22     ! If you want to have support for [utf8]inputenc, please contact the au-
    thor. ^^J%
23     ! If you want to use LuaLaTeX, give it a try: ^^J%
24     ! comment out the lines 32,33,35-43. ^^J%
25     ! Please e-mail me the result of your experiences! ^^J%
26     !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!^^J%
27 }
28 \errmessage{No XeLaTeX, no alttex. See the log for more information.}
29 \endinput
30 \fi
31
```

3

2 Textmode

2.1 no escape

`\noescape` You want to write plain text. Maybe you're annoyed by always escaping characters like `_` `#` `&` `{` `}` `$` `~` and so on. `\noescape` allows you to never escape anything—except the `\`, which still might be used for `\textit{}` or so. Or maybe not... because the `{` `}` are not escaped. Have to think about this one. Maybe the `\` will be redefined to define `{` `}` by itself.

```
32 \def\noescape{
33   \catcode`\_ = 11%
34   \catcode`\^ = 11%
35   \catcode`\# = 11%
36   \catcode`\& = 11%
37   %\catcode`\{ = 11%
38   %\catcode`\} = 11%
39   \catcode`\$ = 11%
40   \catcode`\~ = 11%
41   \makeatletter%
42   \catcode`\% = 11
43 }
```

The `\makeatletter` is not necessary. But it fitted into this line, so I will leave it here.

`\oldescape` Of course this has to be reset when doing anything like formula, tabular etc. Maybe I will be able to change the behaviour automatically. This idea has been inspired by a discussion on the ConT_EXt mailinglist.

```
44 \def\oldescape{
45   \catcode`\% = 14%
46   \catcode`\_ = 8%
47   \catcode`\^ = 7%
48   \catcode`\# = 6%
49   \catcode`\& = 4%
50   %\catcode`\{ = 1%
51   %\catcode`\} = 2%
52   \catcode`\$ = 3%
53   \catcode`\~ = 13%
54   \makeatother%
55 }
```

2.2 tabular

The way one has to type extensive tabulars is quite complex – and the resulting code is often not easy to read. I don't have good ideas how to change this, but I'm thinking about it. Mail me any suggestions for this!

This will be the first attempt to make tabulars easier: Mostly you want an `\hline` after an `\\`. So let's try something like:

I will try to implement cool stuff from the `hhline`-package.

`\$` for `\\hhline` Type `\-` (an en-dash) at the end of a line, and you get an `\hhline`. Type `\=` to get a double line

```
56 \def\-{\\hhline}
57 \def\={\\hhline}
```

This is shurely not a good symbol for this purpose, but I don't have a better idea so far. At least it's a "bar", so one can guess what it should do.

2.3 excel tabulars

`\exceltabular` Often one uses a program to calculate tabulars of numbers. To insert it into L^AT_EX, one has to do some work. Here we try to copy-paste the tabular from excel, Calc or any other program to a file mytabular.txt (or any other ending). Then you say `\exceltabular{mytabular}` (you do not need the ending, therefore it doesn't matter) and you get the tabular in a standard format. I will extend this to enable caption, variable number of columns, kind of rule used etc. This is just a very first test.

This is the definition of the command:

```
58 \def\exceltabular#1{
59   \catcode\^^I=4\relax
60   \eolintabular%
61   \begin{tabular}{|c|c|c|}\hhline%
62   \input{#1}%
63   \end{tabular}%
64   \catcode\^^M=5\relax
65 }
```

And a little helper function to make the `<enter>` `\active`. Again, thanks to the people on the mailinglists.

```
66 \def\mybreak{\\hhline}
67 \begingroup
68   \lccode\~=\^^M%
69   \lowercase{%
70     \endgroup
71     \def\eolintabular{%
72       \catcode\^^M=\active
73       \let~\mybreak
74     }%
75 }
```

2.4 tabbing

This will be analog to the `\exceltabular`. You write your tabbing using tabs and `<enter>`. That's it :)

`\alttabbing` Not yet implemented!

3 Math stuff

3.1 braces

`\newbraces` Now this is something most \LaTeX -beginners don't recognize and wonder why the
`\oldbraces` formula looks so ugly: The braces `()` do not fit to the height of the formula. This can be achieved by putting `\left` and `\right` in front of the braces. But actually, this is annoying! In almost any case you want this behaviour, so this should be the standard. So we redefine the way braces are handled. With `\newbraces` the `()` always fit. If you prefer the normal \LaTeX way, use `\oldbraces` to reset everything. This new behaviour should be extended to other characters like `|` `[` `{` `<` and so on. Maybe in some later version.

I would have never been able to implement this without the help of the mailinglist members of tex-d-l@listserv.dfn.de!

The redefinition of `\mathstrut` is necessary when using `amsmath` (you will use `amsmath` when typesetting formulae, won't you?), because the height of formulae is determined by the height of a brace. But using `()` as `\active` characters, we need another brace here. So we take `[`. This will probably also change. But the code is working fine for `()`.

```
76 \makeatletter
77 \def\resetMathstrut{%
78     \setbox\z@\hbox{%
79         \mathchardef\@tempa\mathcode`\[\relax
80         \def\@tempb##1"##2##3{\the\textfont"##3\char"}%
81         \expandafter\@tempb\meaning\@tempa \relax
82     }%
83     \ht\Mathstrutbox@\ht\z@ \dp\Mathstrutbox@\dp\z@
84 }
85 \makeatother
86
87 {\catcode`\(\active \xdef({\left\string{}}
88 {\catcode`\)\active \xdef}{\right\string{}}
89
90 \def\newbraces{
91     \mathcode`("8000
92     \mathcode`) "8000
93 }
94
95 \edef\oldbraces{
96     \mathcode`\(\the\mathcode` (
97     \mathcode`\)\the\mathcode`)
98 }
```

3.2 huge display math

`hugedisplaymath` Sometimes, especially in presentations, you might need an really big formula. Imagine two hours of struggle with transformations—and finally there is the beautiful formula. Now you can say

```
\begin{hugedisplaymath} E = mc^2 \end{hugedisplaymath}
```

There should be several steps of size, maybe.

```
99 \def\hugedisplaymath{
100   \makeatletter
101   \makeatother
102   \Huge
103   \begin{equation*}
104 }
105 \def\endhugedisplaymath{
106   \end{equation*}
107 }
```

3.3 unicode math

Typing math in T_EX is no great fun – you have to write things like `\int` instead of \int and so on. Have a look at the following formula:

```
\int_{-\infty}^{\infty} \sum_a
```

The code again is stolen and I don’t understand, why it does what it does, but it does it: The first argument is the character you want to use for “unicode math“, the second one is the T_EX-command.

```
108 \makeatletter
109 \def\altmath#1#2{%
110   \expandafter\ifx\csname cc\string#1\endcsname\relax
111     \add@special{#1}%
112     \expandafter
113     \xdef\csname cc\string#1\endcsname{\the\catcode`#1}%
114     \begingroup
115       \catcode`\~\active \lccode`\~`#1%
116       \lowercase{%
117         \global\expandafter\let
118         \csname ac\string#1\endcsname~%
119         \expandafter\gdef\expandafter~\expandafter{#2}}%
120     \endgroup
121     \global\catcode`#1\active
122   \else
123     \fi
124 }
125 \makeatother
```

We will make a switch to turn this stuff on or off, so it does not interfere with the unicode-math package. This list will increase by time. If you are missing a symbol, just send me the `\altmath{X}{\Xcode}`-line. I would be very thankful if anybody could send me a whole list of symbols!

```
126 \def\makealtmath{
127 \altmath{\alpha}\alpha
128 \altmath{\beta}\beta
```

```

129 \altmath{\gamma}
130 \altmath{\delta}
131
132 \altmath{=}\rightarrow
133 \altmath{=}\leftarrow
134 \altmath{=}\Leftrightarrow
135
136 \altmath{\int}
137 \altmath{\forall}
138 }

```

There will be an `\makenormalmath`-switch as well.

3.4 Lazy underscript and superscript

Sometimes one has to make extensive use of subscripts and superscripts, e. g. when typing long formulae including tensors. Then it is a bit annoying to always write the `{}`, especially when there are only two letters in the sub/superscript. So let's try to implement the possibility to type $F_{\mu\nu} F^{\mu\nu}$.

First, store the actual meaning of `_` and `^` in `\oldunderscore` and `\oldhat`.

```

139 \let\oldunderscore_\relax
140 \let\oldhat^\relax

```

Now set `_` as `\active` char and define it the way we want it to behave. For this, we need the space char and end-of-line char to be an egroup char. So the underscript group is ended by space or eol and we don't need to close it explicitly.

```

141 \catcode`\_ =13
142 \def_{%
143   \ifmmode
144     \catcode`\_ =2\relax%
145     \catcode`\^M=2\relax%
146     \expandafter\oldunderscore\bgroup%
147   \else%
148     \textunderscore%
149   \fi%
150 }
151
152 \iffalse
153 This does not work so far...
154 \catcode`\^ =13
155 \def^{%
156   \ifmmode
157     \catcode`\_ =2\relax%
158     \catcode`\^M=2\relax%
159     \expandafter\oldhat\bgroup%
160   \else%
161     \oldhat%
162   \fi%
163 }
164 \fi

```

An underscore at the end of an inline-formula has to be ended with `}` or egroup. That is not nice...

The redefinition of hat does not work because TeX uses it for definition of catcodes. There has to be a really tricky way to get around that.

To give the possibility to switch between normal and `alttex` behaviour, store the new underscore.

The newUnder does not work so far.

```
165 \let\advancedunderscore_
And the switches. By default, _ is active. Type \oldUnder to get the normal _.
```

```
166 \def\oldUnder{
167   \global\catcode`\_ =8\relax
168 }
169 \def\newUnder{
170   \global\let_\advancedunderscore
171 }
```

4 Lists and such things

4.1 itemize with a single character

- instead of `\item` Here we use an active character (mostly a unicode character bullet •) for the whole construct. And another one for nested itemizations (like a triangular bullet ▸).

This does—guess it—not work correctly so far. I’m trying to find a tricky way so that the ending character is not necessary any more. So far one has to end an itemize with something like an – (em-dash). There will also be a possibility to change the characters responsible for the whole action.

insideitemize wird nicht zurückgesetzt!!

The following ugly peace of code is written by me, defining the conditional insertion of the `\begin{itemize}`. This will be assigned to an active character using `\makeitemi` and `\makeitemii`, respectively.

```
172 \def\outside{o}
173 \def\inside{i}
174 \let\insideitemizei\outside
175 \let\insideitemizeii\outside

The end of itemizei and itemizeii:

176 \def\altenditemize{
177   \if\altlastitem l%
178     \let\altlastitem0%
179   \else%
180     \end{itemize}%
181     \let\insideitemizei\outside%
182   \fi%
183 }
184
185 \begingroup
186   \lccode`~ = `^^M%
187   \lowercase{%
188     \endgroup
189     \def\makeenteractive{%
190       \catcode`^^M=\active
191       \let~\altenditemize
192 }%
```

```

193 }
194
195 \def\newitemi{%
196   \ifx\insideitemizei\inside%
197     \let\altlastiteml%
198     \expandafter\item%
199   \else%
200     \begin{itemize}%
201       \let\insideitemizei\inside%
202       \let\altlastiteml%
203       \makeenteractive%
204       \expandafter\item%
205     \fi
206 }
207
208 \def\newitemii{
209   \ifx\insideitemizeii\inside
210     \expandafter\item%
211   \else
212     \begin{itemize}
213       \let\insideitemizeii\inside
214       \expandafter\item%
215     \fi
216 }

```

Ok, the following code is stolen from the `shortvrb` package, and I don't understand anything of it. But I keep on trying... nevertheless, it's working fine, as far as I can see.

`\makeitemi` With this macro, you can define the character you want to use for first-level
`\makeitemii` itemize. (Guess the sense of `\makeitemii`...) Default ist • for first-level and ► for second-level. Maybe this will be extended till fourth level. More doesn't seem to make any sense.

```

217 %
218 \makeatletter
219 \def\makeitemi#1{%
220   \expandafter\ifx\csname cc\string#1\endcsname\relax
221     \add@special{#1}%
222     \expandafter
223     \xdef\csname cc\string#1\endcsname{\the\catcode`#1}%
224     \begingroup
225       \catcode`\~\active \lccode`\~`#1%
226       \lowercase{%
227         \global\expandafter\let
228         \csname ac\string#1\endcsname~%
229         \expandafter\gdef\expandafter~\expandafter{\newitemi}}%
230     \endgroup
231     \global\catcode`#1\active
232   \else
233     \fi

```

```

234 }
235
236 \def\makeitemii#1{%
237   \expandafter\ifx\csname cc\string#1\endcsname\relax
238     \add@special{#1}%
239     \expandafter
240     \xdef\csname cc\string#1\endcsname{\the\catcode`#1}%
241     \begingroup
242       \catcode`\~\active \lccode`\~`#1%
243       \lowercase{%
244         \global\expandafter\let
245         \csname ac\string#1\endcsname~%
246         \expandafter\gdef\expandafter~\expandafter{\newitemii}%
247       \endgroup
248       \global\catcode`#1\active
249   \else
250   \fi
251 }

```

Now there are the two helperfunctions – no guess what they are really doing.

```

252 \def\add@special#1{%
253   \rem@special{#1}%
254   \expandafter\gdef\expandafter\dospecials\expandafter
255   {\dospecials \do #1}%
256   \expandafter\gdef\expandafter\@sanitize\expandafter
257   {\@sanitize \@makeother #1}}
258 \def\rem@special#1{%
259   \def\do##1{%
260     \ifnum`#1=##1 \else \noexpand\do\noexpand##1\fi}%
261   \xdef\dospecials{\dospecials}%
262   \begingroup
263     \def\@makeother##1{%
264       \ifnum`#1=##1 \else \noexpand\@makeother\noexpand##1\fi}%
265     \xdef\@sanitize{\@sanitize}%
266   \endgroup}
267 \makeatother

```

4.2 enumerate with a single character

¹, ² And we do just the same stuff with `\enumerate`. But here we take the character ¹ as first level item, the ²⁵ as second level etc. This may be confusing some way, but just try it.

For the implementation: copy-pasted the code above, nothing interesting so far.

```

268 \def\^1{\end{enumerate}}
269 \def\^2{\end{enumerate}}

```

⁵Maybe this is a very stupid idea, because now the ² cannot be used as a square in mathmode. Of course there could be a test `ifmmode`, but I rather would like to find a better character for `enumerate`.

```

270
271 \let\insideenumi\outside
272 \let\insideenumii\outside
273
274 \def\newenumi{
275   \ifx\insideenumi\inside
276     \expandafter\item%
277   \else
278     \begin{enumerate}
279       \let\insideenumi\inside
280       \expandafter\item%
281     \fi
282 }
283
284 \def\newenumii{
285   \ifx\insideenumii\inside
286     \expandafter\item%
287   \else
288     \begin{enumerate}
289       \let\insideenumii\inside
290       \expandafter\item%
291     \fi
292 }
293

```

We use the same methods as above, still not understanding, what they are doing.
Just changing two lines of code and hoping, everything will be fine.

```

294 \makeatletter
295 \def\makeenumi#1{%
296   \expandafter\ifx\csname cc\string#1\endcsname\relax
297     \add@special{#1}%
298     \expandafter
299     \xdef\csname cc\string#1\endcsname{\the\catcode`#1}%
300     \begingroup
301       \catcode`\~\active \lccode`\~`#1%
302       \lowercase{%
303         \global\expandafter\let
304         \csname ac\string#1\endcsname~%
305         \expandafter\gdef\expandafter~\expandafter{\newenumi}}%
306     \endgroup
307     \global\catcode`#1\active
308   \else
309     \fi
310 }
311
312 \def\makeenumii#1{%
313   \expandafter\ifx\csname cc\string#1\endcsname\relax
314     \add@special{#1}%
315     \expandafter
316     \xdef\csname cc\string#1\endcsname{\the\catcode`#1}%

```

```

317 \begingroup
318 \catcode`\~\active \lccode`\~`#1%
319 \lowercase{%
320 \global\expandafter\let
321 \csname ac\string#1\endcsname~%
322 \expandafter\gdef\expandafter~\expandafter{\newenumii}}%
323 \endgroup
324 \global\catcode`#1\active
325 \else
326 \fi
327 }
328 \makeatother
329

```

Finally, we set the default characters for the items and enumerations:

```

330 \makeitemi•
331 \makeitemii▶
332 \makeenumi1
333 \makeenumii2

```

And that's it.

Happy \LaTeX ing!

A very short introduction to X_YLaTeX

Everything you have to know about X_YLaTeX to use this package: Write your LaTeX file just as you are used to. But save it as utf8-encoded, and say

```
\usepackage{xltextra}
```

instead of

```
\usepackage[latin1]{inputenc} and \usepackage[T1]{fontenc}
```

This loads some files that provide all the cool stuff X_YLaTeX offers. You don't have to take care of letters T_EX would not understand – X_YLaTeX understands every character you type. But sometimes the font may not have the symbol for this – then you can use `\fontspec{fontname}`, where `fontname` is the name of a font on your system, e. g. **Arno Pro**, **Linux Libertine**, **LT Zapfino One** etc.

Then, you compile your document with the command `xelatex file.tex`, instead of `latex file.tex` and you get a pdf as output. Mostly, your editor will not have a shortcut to start X_YLaTeX. In that case, you have to compile via the command line. If you know your editor well enough, you may be able to create a shortcut that will run `xelatex file.tex` for you. Notice that you will need an editor that is utf8-capable! One last warning: While X_YLaTeX is not an pdfT_EX successor, you cannot use microtypographic extensions. Maybe in the future there will be an implementation that uses advanced OpenType-features, but at the moment there is no microtypography possible!

If you have any trouble using X_YLaTeX, just e-mail me!

todo

Here a section with some ideas that could be implemented.

- Use ² as square in mathmode and possibly ¹ as `\footnote`?
- Do something to enable easy tabular
- If there is only one char after an `_`, there should no space be needed.
- Maybe there could be a ConTeXt-version of this file.