

# lernkarten

Arno Trautmann  
arno.trautmann@gmx.de

March 3, 2011

## Abstract

This is the documentation of the class `lernkarten`. I am writing this class to have an easy way to typeset my cards for learning for exams, especially diploma-exams. As I always loose and forget things, I wanted to have all important stuff on my computer so I will not forget it. – Just print and learn.

If you have any suggestions or comments, just drop me a mail, I'll be happy to get any response!

## Contents

<b>1</b>	<b>Usage</b>	<b>1</b>
1.1	Class Options	1
1.2	Typesetting Cards	2
1.3	Structurising	3
1.4	Open Questions	3
1.5	Sections to Read	3
<b>2</b>	<b>Implementation</b>	<b>3</b>
<b>3</b>	<b>Known Bugs</b>	<b>8</b>
<b>4</b>	<b>To Dos</b>	<b>9</b>

## 1 Usage

### 1.1 Class Options

The usage of this class is quite easy. Just load it with

```
\documentclass[class options]{lernkarten}
```

where possible class options are:

**number** The number of cards per page. This directly affects the size of each card. You must take care that none of your cards does exceed the given size! Else the gates to hell will open and the sun will explode.

A reasonable number, and therefore preset, is 10 cards per page.

**noheader** If you use sections and/or parts to structure your cards, they will be in the header. `noheader` will turn this off.

**sectionsoncards** Prints the section on every card. So you always know what theme this cards belongs to. Default is off. Take care that it is *sectionsoncards*, but not *sectionscards*.

**enumerate** By default, all cards are enumerated. `enumerate=false` turns enumeration off. With `enumerate=section`, the cards will be enumerated section-wise.

**language** Basic language support is available. Give the language as class option `[german]` or say `[language=german]`. So far only english (default) and german is supported.

## 1.2 Typesetting Cards

There are approximately three ways to typeset a card: Write

```
\card[ion optics]{How many electrodes are needed for a single lens}{3}
```

for a short question–answer-pair. For longer sentences or formulae, write:

```
\question
questiontext...
\answer
3
□
```

It is extremely important that you leave an *empty line* after the answer, as this empty line is part of the command!

For the lazy guys:

```
\shortquestion
questiontext

answertext
```

Again, the empty lines *must* be given! Else your document will most probably not compile! The `questiontext` or `answertext` can be anything that has no empty lines. For such, use `\card` or `\question`.

## 1.3 Structurising

You can structure your document using the normal commands `\section` and `\part`. Depending on class options, the regarding part and section will be printed on the top of the pages and/or on the cards itself.

You might prefer to use `\begin{section}{sectiontitle} ... \end{section}` instead. This will produce exactly the same output, but the entire section will be “foldable” in your editor so you can fold sections you are not working on. This will concentrate your work on the current stuff.

## 1.4 Open Questions

Whenever anything is not clear when writing the cards, you can put an `\openquestion{}` at that position. At the end of the document, there will be a table of open questions (tooq) where the arguments of `\openquestion{}` are listed with page numbers and links to the cards. `\oq{}` and german `\unklar{}` are aliases for `\openquestion{}`.

If there is an open question, a small ☹️ (`\frownie`) will be set. If you want to change that symbol or want none at all, say `\openquestionmark{your mark}`.

## 1.5 Sections to Read

If you jump over a certain section in your book/script and want to remember that, just type `\sectiontoread{4.4.3. Phasenfluktuationen}`. This will be listed at the end of the document, after the table of open questions. `\str{}` is an alias. No german alias so far.

# 2 Implementation

We begin with loading of options and setting of constants that are needed even before defining the keys:

```
1 \def\cards@per@page{10}
2 \def\cards@enumerate@value{}
3
4 \newif\ifcards@header
5 \newif\ifcards@sections
6 \newif\ifcards@sectioncards
7 \newif\ifcards@enumerate
8 \newif\ifcards@enumerate@section
9 \newif\ifcards@printonly
10 \cards@headertrue
11 \cards@sectioncardsfalse
12 \cards@enumeratetrue
13 \cards@enumerate@sectionfalse
14 \cards@printonlyfalse
15 \def\cards@print@only{}
16
```

```

17 \RequirePackage{xkeyval}
18 \DeclareOptionX{number}{\def\cards@per@page{#1}}
19 \DeclareOptionX{noheader}{\cards@headerfalse}
20 \DeclareOptionX{enumerate}{\def\cards@enumerate@value{#1}}
21 \DeclareOptionX{printonly}{\def\cards@print@only{#1}\cards@printonlytrue}
22 \DeclareOptionX{sectionsoncards}{\cards@sectioncardstrue}
23 \DeclareOptionX{german}{\def\cards@language{german}}
24 \DeclareOptionX{language}{\def\cards@language{#1}}
25 \ProcessOptionsX

```

Now loading of the class and usefull packages. amsmath is surely needed for any mathematic typesetting, boxedminipage is needed for the cards, etc. Then setup of the hyperlinks and page layout.

```

26 \LoadClass{scrartcl}
27 \PassOptionsToClass{fleqn}{scrartcl}
28 \RequirePackage{
29   amsmath,
30   babel,
31   boxedminipage,
32   calc,
33   fontspec,
34   geometry,
35   hyperref,
36   ifthen,
37   scrpage2,
38 }
39 \hypersetup{%
40   pdfborder=false,%
41   colorlinks=true,%
42   linkcolor=blue%
43 }
44 \geometry{
45   bindingoffset=0cm,
46   margin=1cm,
47   headsep=0.2cm
48 }

```

We don't want to waste space on our important cards, so set parindent and mathindent to zero.

```

49 \setlength{\parindent}{0em}
50 %% \setlength{\mathindent}{0em} %% FIXME: where did this go? ...

```

Language specific settings. Only german and english are available so far! (So a simple \ifthenelse does the job.)

```

51 \ifthenelse{\equal{\languagesname}{german}}{
52   \def\cards@answertext{Antwort}
53   \def\cards@openquestiontext{Liste offener Fragen}
54   \def\cards@sectionstoreadtext{Übersprungene Abschnitte}
55 }{
56   \def\cards@answertext{answer}
57   \def\cards@openquestiontext{List of Open Questions}

```

```

58 \def\cards@sectionstoreadtext{Sections still to read}
59 }

```

Now, the pagelayout. `scrheadings` is used and `part:section` is written on top of every site. If option `noheader` is given, there will be no header. This might be useful for printing, while headers are useful for view on screen.

```

60 \def\cards@part{}
61 \def\cards@sect{}
62
63 \pagestyle{scrheadings}
64 \setkomafont{pageheadfoot}{\normalfont\bfseries}
65 \cfoot{}
66 \ifcards@header
67   \head{\cards@part\cards@sect}
68 \else
69 \fi

```

The definition of the sections is a bit tricky. For the table of contents, we need a valid `\section*` command, so we save it by the `\@ifstar` construct. The rest is for setting the sections as wished by the user: resetting the counters, writing the section on the cards and/or in the headings. Definition of `\part` is way more straight-forward. `\subsection` and `\subsubsection` have no effect at the moment, but can be used.

```

70 \let\oldsection\section
71 \renewcommand\section{\@ifstar{\oldsection*}{\cards@section}}
72 \let\sec\relax
73 \newenvironment{sec}[1]{\section{#1}}{}
74
75 %
76 \AtBeginDocument{
77   \let\oldcard\card
78 }
79 \newcommand\cards@section[1]{
80   \ifcards@printonly
81     \ifthenelse{\equal{\zap@space #1 \@empty}}{\cards@print@only}}
82     {\let\card\oldcard}
83     {\def\card##1##2##3{}}
84   \fi
85   \ifnum \thequestion@page > 1 %% needed here for consistent page numbering
86     \set@answers
87   \fi
88   \def\cards@sect{#1}
89   \ifcards@enumerate@section
90     \setcounter{total@question}{0}
91     \setcounter{total@answer}{0}
92   \fi
93   \refstepcounter{section}%
94   \addcontentsline{toc}{section}{%
95     \protect\numberline{\thesection}#1}%
96 }

```

```

97 \renewcommand\part[1]{
98   \ifnum \thequestion@page > 1
99     \set@answers
100   \fi
101   \def\cards@part{#1:~}
102   \refstepcounter{part}%
103   \addcontentsline{toc}{part}{%
104     \protect\numberline{#1}}%
105 }
106 \renewcommand\subsection[1]{\unskip}
107 \renewcommand\subsubsection[1]{\unskip}

```

Need `\TeXeTstate=1` for the right-to-left typesetting of the answers

```

108 %% \TeXeTstate=1 %%FIXME: change from Xe to lua ...

```

For evaluation of the enumeration we need some booleans. First one: enumeration at all, second one: section-wise enumeration.

```

109 \ifthenelse{\equal{\cards@enumerate@value}{false}}{\cards@enumeratefalse}{}
110 \ifthenelse{\equal{\cards@enumerate@value}{section}}{\cards@enumerate@sectiontrue}{}

```

The calculation of the height of the cards is quite straight-forward: Textheight divided by the number of cards – divided by 2 for each column. Minus a certain amount for each row of cards because of intercard-spacing. (Hence the empirical(!) value 2.3em) This is still a bit dirty and unstable, but gives good output for 2 – 28 cards/page (every reasonable value is in that intervall, I guess ...

```

111 \newlength\cards@textheight
112 \setlength\cards@textheight{\textheight-2.3em*\cards@per@page/2}
113 \def\height@of@boxes{\cards@textheight/\cards@per@page*2}
114 \newcommand\lernkarte[1]{%
115   \boxedminipage{.49\textwidth}%
116   \hspace*{0.01\textwidth}%
117   \minipage[t]{.98\textwidth}\textbf{#1}\[2ex}%
118 }
119 \def\endlernkarte{
120   \endminipage\vphantom{\rule[-\height@of@boxes]{0pt}{\height@of@boxes}}
121   \endboxedminipage\kern.01\textwidth
122 }

```

Now set some counters. They will be used to number the cards. So you might sort your cards and you can see how far you come on one day ... or you can exchange with your partners ("Having trouble on question 1357 – can you explain that equation?")

```

123 \newcounter{total@question}          %% total number of questions
124 \setcounter{total@question}{0}
125 \newcounter{total@answer}            %% total number of answers
126 \setcounter{total@answer}{0}
127 \newcounter{question@page}          %% the N-th question on one page
128 \setcounter{question@page}{1}
129 \newcounter{answer@page}             %% the N-th answer@page on one page
130 \def\card#1#2#3{ % {Title}{question}{answer}
131 % typesetting the question: using the environment lernkarte for the layout:

```

```

132 \begin{lernkarte}{%
133   \stepcounter{total@question}%
134   \ifcards@sectioncards
135     \cards@sect~%
136   \fi
137   \ifcards@enumerate%
138     \thetotal@question: %
139   \fi%
140   #1%
141 }
142 #2
143 \end{lernkarte}
144 % save answer nr. N in a macro \cs{answer@N@page}:
145 \expandafter\def\csname answer@\thequestion@page \endcsname{#3}
146 \stepcounter{question@page}
147 % typeset the answers when the page is full of questions:
148 \ifnum\thequestion@page > \cards@per@page
149   \set@answers
150 \fi\unskip
151 }

```

Now we try a nicer way to typeset the answers:

```

152 \def\set@answers{
153   \clearpage
154   \setcounter{answer@page}{1}
155 % and typeset them L to R, so every answer is on the back of the correct question
156 %% \beginR\unskip %% FIXME: change from Xe to lua
157 \luatextextdir TRT\unskip
158 % we loop through all saved answers
159 \whiledo{\theanswer@page < \thequestion@page}{%
160   \begin{lernkarte}{\cards@answertext: \stepcounter{total@answer}\thetotal@answer}
161   \csname answer@\theanswer@page\endcsname
162   \end{lernkarte}
163   \stepcounter{answer@page}
164 } \kern-1em %% FIXME why is this kern needed here?
165 \newpage%
166 \setcounter{question@page}{1}%
167 \setcounter{answer@page}{0}%
168 }

```

Now the definition and setting of the *table of open questions* (tooq):

```

169 \addtotoclist[tooq]{tooq}
170 \newcommand{\listoftooqname}{\cards@openquestiontext}
171 \newcounter{openquestion}
172 \def\frownie{\bgroup\color{blue}\raisebox{2ex}{\bfseries\rotatebox{-90}{\small :-{}}\egroup}
173 \def\cards@mark@oq{\frownie}
174 \def\openquestion#1{
175   \refstepcounter{openquestion}%
176   \newcommand*{\l@tooq}{\l@figure}%
177   \addcontentsline{tooq}{figure}{%
178     \protect\numberline{\textbf{\theopenquestion}}\textbf{#1}}%

```

```

179 \cards@mark@oq
180 }
181
182 \addtotoclist[tsr]{tsr}
183 \newcommand{\listoftosrname}{\cards@sectionstoreadtext}
184 \newcounter{sectionstoread}
185 \newcommand*{\l@tsr}{\l@figure}%
186 \def\sectiontoread#1{
187   \refstepcounter{sectionstoread}%
188   \addcontentsline{tsr}{figure}{%
189     \protect\numberline{\textbf{\thesectionstoread}}\textbf{#1}}%
190 }

```

typeset the missing answers and the table of open questions.

```

191 \AtEndDocument{
192   \part{\cards@openquestiontext}
193   \listoftoc{tooq}
194   \newpage
195   \part{\cards@sectionstoreadtext}
196   \listoftoc{tsr}
197 }
198 \author{no author given}
199 \title{no title given}
200 \date{}
201 \AtBeginDocument{
202   \maketitle
203   \newpage
204   \tableofcontents
205   \newpage
206 }

```

And finally the user-interface. German aliases and shorthands for above \def'd functions:

```

207 \newcommand\karte[3][]{\card{#1}{#2}{#3}}
208 \long\def\question#1\answer#2\par{\karte{#1}{#2}}
209 \long\def\frage#1\antwort#2\par{\karte{#1}{#2}}
210 \def\shortquestion#1\par#2\par{\frage #1 \antwort #2 \par}
211 \newenvironment{cardsection}[1]{\section{TEST}\bgroup}{\egroup}
212 \let\unklar\openquestion
213 \let\oq\openquestion
214 \let\str\sectiontoread
215 \def\openquestionmark#1{\def\cards@mark@oq{#1}}

```

</class>

### 3 Known Bugs

There are several bugs, some only regarding the code, some heavily destroying the layout:



**display formula** Under certain circumstances (which are not clear to me), there will be a problem if you write only one display formula as answer. This can enlarge the regarding card, which destroys the whole layout.

Just *add* an empty line or a single \ or whatever – this will in fact then *decrease* the size of the answer-card to the correct size.

**tabular** The same things for tabulars. But so far I have no idea how to fix this :(

**references** The references in this documentation are broken! (Avoided so it is not visible to you ...)

## 4 To Dos

Some things that should be implemented but aren't so far or are very poor at the moment:

**\section** should have an optional argument for short titles.