STONE

Professional Credible and Successful

Model Description

Industrial Type

Size (inch)	Model	Colour	Resolution	Voltage(V)	Perpherals	Interface	Brightness	Temp(℃)	Viewing Area (mm)	Power (W)
3.5"	**STI035WT-01**	**65K (16 bit)**	**320*240 (4:3)**	**DC 5-20**	**Touch-Screen &KB&RTC**	**RS232/RS485/TTL/USB**	**250cd/m²**	**-20℃/+70℃**	**69.9*52.5**	**0.8**
4.3"	**STI043WT-01**	**65K (16 bit)**	**480*272 (16:9)**	**DC 5-20**	**Touch-Screen &KB&RTC**	**RS232/RS485/TTL/USB**	**300cd/m²**	**-20℃/+70℃**	**95.0*53.9**	**1.0**
5"	STI050WT-01	65K (16 bit)	640*480 (4:3)	DC 5-20	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	280cd/m²	-20℃/+70℃	101.6*76.2	2.2
5"	**STI050WT-02**	**65K (16 bit)**	**480*272 (16:9)**	**DC 5-20**	**Touch-Screen &KB&RTC**	**RS232/RS485/TTL/USB**	**350cd/m²**	**-20℃/+70℃**	**110.9*62.8**	**1.3**
5"	STI050WT-03	65K (16 bit)	800*480 (16:9)	DC 5-20	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	350cd/m²	-20℃/+70℃	108.0*64.8	2.4
5.6"	**STI056WT-01**	**65K (16 bit)**	**640*480 (4:3)**	**DC 5-20**	**Touch-Screen &KB&RTC**	**RS232/RS485/TTL/USB**	**280cd/m²**	**-20℃/+70℃**	**112.9*84.7**	**2.2**
7"	**STI070WT-01**	**65K (16 bit)**	**800*480 (16:9)**	**DC 5-20**	**Touch-Screen &KB&RTC**	**RS232/RS485/TTL/USB**	**300cd/m²**	**-20℃/+70℃**	**152.1*85.9**	**2.6**
7"	STI070WT-02	65K (16 bit)	800*600 (4:3)	DC 5-20	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	300cd/m²	-20℃/+70℃	141.6*106.2	1.9
7"	STI070WT-03	65K (16 bit)	1024*600 (16:9)	DC 5-20	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	450cd/m²	-20℃/+70℃	153.6*90.0	3.0
8"	**STI080WT-01**	**65K (16 bit)**	**800*600 (4:3)**	**DC 5-20**	**Touch-Screen &KB&RTC**	**RS232/RS485/TTL/USB**	**500cd/m²**	**-20℃/+70℃**	**162.0*121.5**	**2.8**
8"	STI080WT-02	65K (16 bit)	800*480 (16:9)	DC 5-20	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	450cd/m²	-20℃/+70℃	176.6*99.4	2.6
8"	STI080WT-03	65K (16 bit)	1024*768 (4:3)	DC 5-20	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	300cd/m²	-20℃/+70℃	162.0*121.5	3.0
10.1"	STI101WT-01	65K (16 bit)	1024*600 (16:9)	DC 5-20	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	300cd/m²	-20℃/+70℃	222.7*125.3	3.0
10.4"	**STI104WT-01**	**65K (16 bit)**	**800*600 (4:3)**	**DC 5-20**	**Touch-Screen &KB&RTC**	**RS232/RS485/TTL/USB**	**300cd/m²**	**-20℃/+70℃**	**211.2*158.4**	**3.0**
12.1"	STI121WT-01	65K (16 bit)	800*600 (4:3)	DC 5-20	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	330cd/m²	-20℃/+70℃	246.0*184.5	7.2
15.1"	STI151WT-01	65K (16 bit)	1024*768 (4:3)	DC 9-20	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	350cd/m²	-20℃/+70℃	304.1*228.1	10.2
Plastic Frame:		PS-043 / PS-056 / PS-070 / PS-080 / PS-104								
Metal Shell:		MS-070 / MS-080 / MS-104								

STONE

Professional Credible and Successful

Advanced Type

Size (inch)	Model	Colour	Resolution	Voltage(V)	Perpherals	Interface	Brightness	Temp(℃)	Viewing Area (mm)	Power (W)
3.5"	STA035WT-01	65K (16 bit)	320*240 (4:3)	DC 5-42	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	1000cd/m²	-30℃/+85℃	69.9*52.5	1.5
4.3"	STA043WT-01	65K (16 bit)	480*272 (16:9)	DC 5-42	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	900cd/m²	-30℃/+85℃	95.0*53.9	2.0
5"	STA050WT-02	65K (16 bit)	480*272 (16:9)	DC 5-42	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	900cd/m²	-30℃/+85℃	110.9*62.8	2.0
5"	STA050WT-03	65K (16 bit)	800*480 (16:9)	DC 5-42	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	900cd/m²	-30℃/+85℃	108.0*64.8	2.6
5.6"	STA056WT-01	65K (16 bit)	640*480 (4:3)	DC 5-42	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	500cd/m²	-30℃/+85℃	112.9*84.7	2.2
5.7"	STA057WT-01	65K (16 bit)	640*480 (4:3)	DC 5-42	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	700cd/m²	-30℃/+85℃	115.2*86.4	5.2
6.5"	STA065WT-01	65K (16 bit)	640*480 (4:3)	DC 5-42	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	800cd/m²	-30℃/+85℃	132.5*99.4	6.2
7"	STA070WT-01	65K (16 bit)	800*480 (16:9)	DC 5-42	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	1000cd/m²	-30℃/+85℃	154.1*85.9	4.0
8"	STA080WT-01	65K (16 bit)	800*600 (4:3)	DC 5-42	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	600cd/m²	-30℃/+85℃	162.0*121.5	4.0
8.4"	STA084WT-01	65K (16 bit)	800*600 (4:3)	DC 5-42	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	600cd/m²	-30℃/+85℃	165.0*124.5	6.4
10.1"	STA101WT-01	65K (16 bit)	1024*600 (16:9)	DC 5-42	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	900cd/m²	-30℃/+85℃	222.7*125.3	4.6
10.4"	STA104WT-01	65K (16 bit)	800*600 (4:3)	DC 5-42	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	700cd/m²	-30℃/+85℃	211.2*158.4	10.0
12.1"	STA121WT-01	65K (16 bit)	800*600 (4:3)	DC 5-42	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	500cd/m²	-30℃/+85℃	246.0*184.5	9.0
15.1"	STA151WT-01	65K (16 bit)	1024*768(16:9)	DC 9-42	Touch-Screen &KB&RTC	RS232/RS485/TTL/USB	500cd/m²	-30℃/+85℃	304.1*228.1	12.0

Note:

1. Supply the customization service.

a. Custom any size TFT-LCD Module.
b. Develop the customization function.
c. Update the standard memory to 2 GB
d. Change to RS485 port or other port.
e. Update TFT screen to 16.7M colour (24 bit colour)

2. Naming Rule (Taking STI070WT- 01 as example)

ST	Company Code
I	A=Advanced Type I=Industrial Type
070	TFT Panel Dimension: 7 inch
W	W=Wide Voltage (5V-20V) S=Super Wide Voltage (5V-42V)
T	T=With Resistive Touch Screen N=Without Touch Screen C=With Capacitive Touch Screen
0	0=RS232 4=RS485 1=TTL
1	Hardware Code

3. Main Differences for I-series & A-series

	Industry Type	Advanced Type
CPU	32bit Cortex-M3	32bit Cortex-M3
All of Components	Import product (the best components in the world)	Import product (the best components in the world)
TFT Screen Class	A class industrial TFT screen (5% TFT with no more than 3 dead pixels in the nconspicuous area.)	A+ class industrial TFT screen (All TFT with no dead pixels)
TFT Backlight Life	30000 hours	50000 or 100000 hours
Brightness	Normal Industrial Standard	High-Brightness (Visible in Sunlight)
Flash Memory	256MB Industrial Memory	256MB Industrial Memory
Voltage	DC 5-20 V	DC 5-42 V
Operation Temperature	-20℃ to +70℃	-30℃ to +85℃
PCB Surface Coating	None	With
Duration of Aging Test	24 hours	72 hours
Warranty Period	3 year (Replace by new one)	4 years (Replace by new one)
Price	High Cost Performance	30%-50% more than BasicType
Application	Satisfy the international standard of industry	Meet the advanced requirement