

Gym & Fitness Centre Management System

Logical Database Design & Enhanced Entity-Relationship Diagram (EERD)

Course activity:	Advanced Database — Activity 1: Logical Database Design
Group:	Group 5
Team members:	Hidalgo Altesse Imena, Noah Jobse, Melody Shih
Modelling tool used:	Graphviz (crow's-foot notation, EER extensions) for the EERD; Markdown for documentation
Repository:	advdb-activity1-Group5

1. Design Process

We started from the scenario's core operations — managing members, trainers, classes, and payments — and identified the nouns that needed to persist data as candidate entities. We then walked through the day-to-day questions the gym would need to answer (Who can lead this class? What times does it run? Who is enrolled? Has this member paid?) to surface the relationships and constraints between entities. Attributes were assigned to whichever entity they functionally depend on, primary keys were chosen as single-column surrogate identifiers for stability (except for the weak entity ClassSchedule and the associative entity Enrollment, whose composite keys include the keys of the entities they depend on), and foreign keys were added everywhere a relationship needed to be enforced. The model was then normalized to third normal form (3NF) to remove repeating groups and update anomalies (see Section 3). The final logical model was drawn as an Enhanced ER Diagram (EERD) in Graphviz using crow's-foot cardinality notation, an ISA triangle for the trainer specialization, and double-bordered boxes for the two weak/associative entities.

2. Entities and Business Rules

Main entities: Member, Trainer (specialized into PersonalTrainer and GroupInstructor), Class, Payment.

Additional supporting entities: MembershipType (plan pricing/duration), Room (facility used to host a class session), ClassSchedule (a specific date/time/room a class runs — weak entity), Enrollment (associative entity resolving the Member–ClassSchedule many-to-many relationship), and PaymentMethod (separated out to satisfy 3NF, see Section 3).

Business rules

1. Every member must belong to exactly one membership type at a time; a membership type can be held by many members (Member is on the “many” side, total participation — a member cannot exist without a plan).
2. A trainer can lead many classes, but each class is led by exactly one trainer. Trainers are specialized as either a Personal Trainer or a Group Instructor (disjoint, partial specialization — a trainer row is not required to belong to a subtype, e.g. a newly hired trainer awaiting certification).


3. A class can run as many separate scheduled sessions (different dates, times, and rooms); each schedule entry belongs to exactly one class and cannot exist without it, making ClassSchedule a weak entity identified by (ClassID, ScheduleID), where ScheduleID is a partial key that numbers the sessions within each class.
4. A member can enroll in many class schedules, and a class schedule can hold many enrolled members. This many-to-many relationship is resolved through the Enrollment associative entity, which also records the enrollment date and attendance status.
5. Each payment is made by exactly one member using exactly one payment method; a member can make many payments over time, and a given payment method can be reused across many payments.
6. A room can host many class schedules over time, but a single class schedule takes place in exactly one room at one time slot (double-booking a room for overlapping times is prevented at the application layer).

3. Normalization to 3NF — Key Decisions

- **Repeating class-session columns removed (1NF).** An early draft stored each class's sessions as repeating columns on Class (Day1/Time1, Day2/Time2 ...). This violates 1NF. We extracted a separate ClassSchedule entity with one row per session instead.
- **MembershipType separated from Member (3NF).** Plan price and duration were originally copied onto every Member row. Since Price and DurationMonths depend on the plan, not on the individual member, leaving them on Member created a transitive dependency and an update anomaly (changing a plan's price would require updating every member on that plan). We moved them into their own MembershipType entity.
- **Payment method details separated from Payment (3NF).** Processor name and processing-fee percentage depend on the payment method chosen, not on the specific payment transaction — a transitive dependency on a non-key attribute. We split this into a PaymentMethod lookup entity referenced by Payment via PaymentMethodID.
- **Member–ClassSchedule many-to-many resolved with an associative entity.** Because the relationship itself carries data (EnrollmentDate, AttendanceStatus), it cannot be represented as a plain M:N line; we created the Enrollment entity with a composite key (MemberID, ClassID, ScheduleID).
- **Room kept independent of ClassSchedule.** RoomName, Location, and Capacity depend only on the room, not on any one scheduled session, so keeping Room separate avoids repeating room details for every session held there.
- **EndTime derived instead of stored (3NF).** A session's end time is determined by its StartTime and the class's DurationMinutes, so storing EndTime on ClassSchedule would create a transitive dependency and risk inconsistent values. EndTime is therefore a derived attribute, computed at query time.
- After these changes, every non-key attribute in every entity depends on the whole primary key and nothing else, satisfying 3NF.

4. Enhanced Entity-Relationship Diagram (EERD)

Notation: rectangles are entities (primary keys underlined, foreign keys marked “FK”); double-bordered rectangles are weak/associative entities, and the partial key of the weak entity is shown in italics and marked “partial key”; crow's-foot line endings show cardinality and participation (a fanned-out end = “many”, a perpendicular bar = “one”, a double bar = “exactly one”, a circle = “zero”/optional); the thicker line marks the identifying relationship; attributes in italics marked “(derived)” are derived attributes; the triangle labelled “ISA” shows the disjoint (d), partial specialization of Trainer into PersonalTrainer and GroupInstructor.



5. Data Dictionary

Entity	Attribute	Definition	Data Type	Validation / Rule
MembershipType	MembershipTypeID (PK)	Unique identifier for a membership plan.	Integer	Auto-increment; not null
MembershipType	TypeName	Name of the plan (e.g., Basic, Premium, Student).	Varchar(30)	Not null; unique
MembershipType	DurationMonths	Length of the plan in months.	Integer	> 0
MembershipType	Price	Cost of the plan for its duration.	Decimal(8,2)	>= 0
MembershipType	Description	Short description of plan benefits.	Varchar(255)	Optional
Member	MemberID (PK)	Unique identifier for a gym member.	Integer	Auto-increment; not null
Member	FirstName	Member's first name.	Varchar(50)	Not null
Member	LastName	Member's last name.	Varchar(50)	Not null
Member	Email	Contact email, used for login/notifications.	Varchar(100)	Not null; unique; valid email format
Member	Phone	Contact phone number.	Varchar(20)	Optional; numeric format
Member	DateOfBirth	Member's date of birth.	Date	Not null; must be in the past
Member	JoinDate	Date the member joined the gym.	Date	Not null; defaults to current date
Member	Age (derived)	Current age, calculated from DateOfBirth.	Integer (derived)	Not stored; computed at query time
Member	MembershipTypeID (FK)	References the member's current plan.	Integer	Not null; must exist in MembershipType
Trainer	TrainerID (PK)	Unique identifier for a trainer.	Integer	Auto-increment; not null
Trainer	FirstName	Trainer's first name.	Varchar(50)	Not null
Trainer	LastName	Trainer's last name.	Varchar(50)	Not null
Trainer	Email	Contact email.	Varchar(100)	Not null; unique
Trainer	Phone	Contact phone number.	Varchar(20)	Optional
Trainer	HireDate	Date the trainer was hired.	Date	Not null

Entity	Attribute	Definition	Data Type	Validation / Rule
Trainer	TrainerType	Discriminator: 'Personal' or 'Group', or null if unassigned.	Varchar(10)	Optional (partial specialization)
PersonalTrainer	TrainerID (PK, FK)	Links to the specialized trainer record.	Integer	Must exist in Trainer
PersonalTrainer	HourlyRate	Rate charged per one-on-one session.	Decimal(6,2)	> 0
PersonalTrainer	MaxClientsPerWeek	Cap on weekly one-on-one clients.	Integer	> 0
GroupInstructor	TrainerID (PK, FK)	Links to the specialized trainer record.	Integer	Must exist in Trainer
GroupInstructor	CertificationLevel	Instructor's certification tier.	Varchar(30)	Not null
GroupInstructor	GroupSizeLimit	Max participants the instructor can supervise.	Integer	> 0
Class	ClassID (PK)	Unique identifier for a class offering.	Integer	Auto-increment; not null
Class	ClassName	Name of the class (e.g., Spin, Yoga).	Varchar(50)	Not null
Class	Description	Overview of what the class covers.	Varchar(255)	Optional
Class	Category	Category/type of workout.	Varchar(30)	Not null
Class	DurationMinutes	Length of one session in minutes.	Integer	> 0
Class	TrainerID (FK)	Trainer assigned to lead the class.	Integer	Not null; must exist in Trainer
Room	RoomID (PK)	Unique identifier for a facility room.	Integer	Auto-increment; not null
Room	RoomName	Name/number of the room.	Varchar(30)	Not null
Room	Location	Location within the facility.	Varchar(50)	Optional
Room	Capacity	Maximum occupancy of the room.	Integer	> 0
ClassSchedule	ClassID (PK, FK)	Class this session belongs to (owner of the weak entity).	Integer	Not null; must exist in Class
ClassSchedule	ScheduleID (PK, partial key)	Number of the session within its class (1, 2, 3 ...); unique only together with ClassID.	Integer	Not null; > 0; (ClassID, ScheduleID) unique

Entity	Attribute	Definition	Data Type	Validation / Rule
ClassSchedule	RoomID (FK)	Room the session is held in.	Integer	Not null; must exist in Room
ClassSchedule	SessionDate	Date the session takes place.	Date	Not null
ClassSchedule	StartTime	Session start time.	Time	Not null
ClassSchedule	EndTime (derived)	Session end time, calculated as StartTime + Class.DurationMinutes.	Time (derived)	Not stored; computed at query time
Enrollment	MemberID (PK, FK)	Member enrolled in the session.	Integer	Not null; must exist in Member
Enrollment	ClassID (PK, FK)	Class of the scheduled session the member enrolled in.	Integer	Not null; (ClassID, ScheduleID) must exist in ClassSchedule
Enrollment	ScheduleID (PK, FK)	Scheduled session the member enrolled in.	Integer	Not null; (ClassID, ScheduleID) must exist in ClassSchedule
Enrollment	EnrollmentDate	Date the member enrolled.	Date	Not null; defaults to current date
Enrollment	AttendanceStatus	Attendance outcome for the session.	Varchar(15)	One of Registered/Attended/No-show/Cancelled
PaymentMethod	PaymentMethodID (PK)	Unique identifier for a payment method.	Integer	Auto-increment; not null
PaymentMethod	MethodName	Name of the method (Credit Card, Cash, E-transfer).	Varchar(20)	Not null
PaymentMethod	ProcessorName	Third-party processor, if any.	Varchar(30)	Optional (e.g., null for Cash)
PaymentMethod	ProcessingFeePercent	Fee percentage charged by the processor.	Decimal(4,2)	>= 0
Payment	PaymentID (PK)	Unique identifier for a payment transaction.	Integer	Auto-increment; not null
Payment	MemberID (FK)	Member who made the payment.	Integer	Not null; must exist in Member
Payment	PaymentMethodID (FK)	Method used for this payment.	Integer	Not null; must exist in PaymentMethod
Payment	Amount	Amount charged.	Decimal(8,2)	> 0
Payment	PaymentDate	Date/time the payment was made.	Datetime	Not null; defaults to current timestamp

Entity	Attribute	Definition	Data Type	Validation / Rule
Payment	Notes	Optional free-text note.	Varchar(255)	Optional

6. Team Contribution Table

Team Member	Role	Specific Tasks
Hidalgo Altesse Imena	Database Designer / EERD Lead	Identified entities and business rules; defined attributes, keys, and relationships; carried out 3NF normalization; built the EERD; assembled the GitHub repository and this report.
Noah Jobse	Documentation & Business Rules	Drafted business rules; wrote/reviewed the README design rationale; reviewed relationship cardinalities.
Melody Shih	Data Dictionary & QA	Compiled the data dictionary; validated attribute data types and rules; proofread the final report.