



Faculty of Science




# Towards Automatic Program Specification Using SME Models

Communicating Process Architectures 2018 – Technische Universität Dresden

**Alberte Thegler**

Niels Bohr Institute, University of Copenhagen, Denmark



# Why should we verify hardware?

Ariane-5

4th June 1996



# Why should we verify hardware?

Ariane-5

4th June 1996

Total failure on launch



# Why should we verify hardware?

Ariane-5

4th June 1996

Total failure on launch

Converting a 64-bit floating point number to signed 16-bit integer.



# Why should we verify hardware?

## Ariane-5

4th June 1996

Total failure on launch

Converting a 64-bit floating point number to signed 16-bit integer.

Overflow caused the self-destruct mechanism in both primary and backup computer



# Why should we verify hardware?

## Ariane-5

4th June 1996

Total failure on launch

Converting a 64-bit floating point number to signed 16-bit integer.

Overflow caused the self-destruct mechanism in both primary and backup computer

No people where harmed



# Why should we verify hardware?

## The Patriot Missile Failure

25th February 1991 in the Persian Gulf war



# Why should we verify hardware?

## The Patriot Missile Failure

25th February 1991 in the Persian Gulf war

A Patriot missile failed to intercept an incoming "Scud" which struck a U.S Army barracks, killing 28 soldiers.





# Why should we verify hardware?

## The Patriot Missile Failure

25th February 1991 in the Persian Gulf war

A Patriot missile failed to intercept an incoming "Scud" which struck a U.S Army barracks, killing 28 soldiers.

A bug in the system's weapons control computer caused an inaccurate tracking calculation. Conversion of time since last boot from an integer to a real number was performed using a 24 bit register.



# Why should we verify hardware?

## The Patriot Missile Failure

25th February 1991 in the Persian Gulf war

A Patriot missile failed to intercept an incoming "Scud" which struck a U.S Army barracks, killing 28 soldiers.

A bug in the system's weapons control computer caused an inaccurate tracking calculation. Conversion of time since last boot from an integer to a real number was performed using a 24 bit register.

Inaccurate results == missile misses target



# What can SME do?

The SME model builds on the CSP algebra



# SMEIL

You have just been introduced to SMEIL in the previous presentation



# SMEIL

You have just been introduced to SMEIL in the previous presentation

We transpile from SMEIL to  $\text{CSP}_M$   
And then verify it in FDR4



# SMEIL

You have just been introduced to SMEIL in the previous presentation

We transpile from SMEIL to  $\text{CSP}_M$   
And then verify it in FDR4




Figure. SMEIL transpiler structure.



# Simple example

## Seven Segment Display

Figure (Truls or something else?)



# Seven Segment Display example

Write the seven segment circuit in SMEIL





# Seven Segment Display example

Write the seven segment circuit in SMEIL

Transpile it to  $\text{CSP}_M$



# Seven Segment Display example

Write the seven segment circuit in SMEIL

Transpile it to  $\text{CSP}_M$

Verify in FDR4



# Simple example

## What are we verifying

One seven segment example can only display the numbers 0-9.

4 bits can represent the data, but also more than needed.



# Simple example

## What are we verifying

One seven segment example can only display the numbers 0-9.

4 bits can represent the data, but also more than needed.

We can verify that the values communicated to the seven segment displays does not exceed the expected values.



# Simple example


Seven Segments SMEIL Structure

SMEIL code



# Simple example

## Seven Segments SMEIL Structure



**Figure.** SMEIL network for a seven segment display clock. Each SMEIL process is represented by a circle with a letter corresponding to the processes Input, Hours, Minutes and Seconds respectively.



# CSPm process structure

Code example



# Monitor process

Code example





## Example continued

### Run

All of the following CPU examples have been run on a Intel(R) Core(TM) i7-3770 CPU @ 3.40GHz.

The GPGPU examples are run on GeForce GTX 680 (OpenCL C 1.1).

All examples were run 10 times and the average was measured.



# Results - time to verify in FDR4?

The seven segment example have been run on a ...

The example were run x times and the average was measured.



# Conclusion

Productivity and performance

....



# Future work

DSL

....



# Questions?

## Comments?

Feel free to ask anything.

