


Exploring data #1

Factors in R

Factors in R

Factor vectors are used in R for **categorical variables**, where more than one observation can have the same category.



Factor variables have one or more **levels**. While you will always see a factor printed with its factor level labels, R “remembers” the variable with each level assigned a number.

Factors in R

In tibbles, factors will be noted with “fctr” under the column name. For example, look at the aqi column in the beijing_pm data:

```
head(beijing_pm, n = 3)
```

```
## # A tibble: 3 x 4
##   sample_time    value qc      aqi
##   <chr>         <dbl> <chr> <fctr>
## 1 1/1/2017 0:00    505 Valid Beyond Index
## 2 1/1/2017 1:00    485 Valid Hazardous
## 3 1/1/2017 2:00    466 Valid Hazardous
```

Factors in R

You can use the `levels` function to see the levels of a factor vector, as well as the order those levels are recorded in R.

```
levels(beijing_pm$aqi)
```

```
## [1] "Good"  
## [2] "Moderate"  
## [3] "Unhealthy for Sensitive Groups"  
## [4] "Unhealthy"  
## [5] "Very Unhealthy"  
## [6] "Hazardous"  
## [7] "Beyond Index"
```


To explore a factor vector, you'll often want to **count** the number of observations in each category. You can do that with two functions in the `dplyr` package, `group_by` and `count`.

Start with a dataframe that includes the factor variable as a column. First `group_by` the factor, then pipe the output of that into the `count` function.

This will create a new summary dataframe, with a row for each level of the factor. A column called `n` will give the number of observations in the original data that had that level of the factor.

Factors in R

You can **count** how many observations have each level of a factor.



Factors in R

```
beijing_pm %>%  
  group_by(aqi) %>%  
  count()
```

```
## # A tibble: 8 x 2  
## # Groups:   aqi [8]  
##   aqi          n  
##   <fct>      <int>  
## 1 Good      2438  
## 2 Moderate  1021  
## 3 Unhealthy for Sensitive Groups 374  
## 4 Unhealthy  167  
## 5 Very Unhealthy 179  
## 6 Hazardous  107  
## 7 Beyond Index  27  
## 8 <NA>       31
```



You can jointly explore multiple columns in a dataframe.

For example, if one column is a factor and one is numeric, it can be useful to explore values of the numeric column within each level of the factor column.

For the Beijing data, you may want to find out the mean concentration of $\text{PM}_{2.5}$ within each AQI level.

Factors in R

You can **summarize** a numeric column within levels of a factor column:



`group-by(hair_color) %>%`

`summarize(mean_wt = mean(wt))`

	<u>hair_color</u>	<u>mean_wt</u>
(1)	"blond"	175.0
(2)	"brown"	173.5
(3)	"red"	173.0

Factors in R

To do this, pipe the dataframe into `group_by` (where you can group by the factor column) and then into `summarize`, where you can calculate summaries.

```
beijing_pm %>%  
  group_by(aqi) %>%  
  summarize(mean_pm = mean(value))
```

```
## # A tibble: 8 x 2
```

##	aqi	mean_pm
##	<fct>	<dbl>
## 1	Good	23.5
## 2	Moderate	70.7
## 3	Unhealthy for Sensitive Groups	122.
## 4	Unhealthy	172.
## 5	Very Unhealthy	243.
## 6	Hazardous	378.
## 7	Beyond Index	554.

Factors in R

You can create several summaries at once:

```
beijing_pm %>%  
  group_by(aqi) %>%  
  summarize(min_pm = min(value),  
            max_pm = max(value))
```

```
## # A tibble: 8 x 3  
##   aqi                min_pm max_pm  
##   <fct>            <dbl>  <dbl>  
## 1 Good              1      50  
## 2 Moderate          51     100  
## 3 Unhealthy for Sensitive Groups 101     150  
## 4 Unhealthy        151     200  
## 5 Very Unhealthy   202     300  
## 6 Hazardous        301     500  
## 7 Beyond Index     505     684  
## 8 <NA>            -999     -2
```

Factors in R

As a note, there's a function called `n()` that you can use inside `summarize` to replace `count`. For example, these two expressions give the same output:

```
beijing_pm %>%  
  group_by(aqi) %>%  
  count()
```

```
beijing_pm %>%  
  group_by(aqi) %>%  
  summarize(n = n())
```

Factors in R

If a column is in a character class, but you'd like it to be a factor, you can use `as_factor` from the `forcats` package:

```
library("forcats")
```

```
beijing_pm %>%
```

```
  mutate(qc = as_factor(qc))
```

```
## # A tibble: 4,344 x 4
```

```
##   sample_time    value qc      aqi
```

```
##   <chr>          <dbl> <fct> <fct>
```

```
## 1 1/1/2017 0:00    505 Valid Beyond Index
```

```
## 2 1/1/2017 1:00    485 Valid Hazardous
```

```
## 3 1/1/2017 2:00    466 Valid Hazardous
```

```
## 4 1/1/2017 3:00    435 Valid Hazardous
```

```
## 5 1/1/2017 4:00    405 Valid Hazardous
```

```
## 6 1/1/2017 5:00    402 Valid Hazardous
```

```
## 7 1/1/2017 6:00    407 Valid Hazardous
```

```
## 8 1/1/2017 7:00    435 Valid Hazardous
```