12: Inference for Linear Combinations

Stat 230 - Spring 2026

```
library(ggformula)
library(broom)
```

> **Note**
>
> I recommend finishing the Inference for MLR activity before starting. This activity will use the same data and it will be helpful to have worked through the equations for each category before starting!

1 Overview

The `cars` data set loaded below contains information on used cars for sale, including their `Price`, `Mileage`, and `Make` (a categorical variable with six levels).

```
# cars <- read.csv("https://aluby.github.io/stat230/data/Cars.csv", stringsAsFactors
cars <- read.csv(here::here("data/Cars.csv"), stringsAsFactors = TRUE)
```

We'll proceed with the `car_lm2` model:

```
car_lm2 <- lm(log(Price) ~ Mileage * Make, data = cars)

tidy(car_lm2)
```

```
# A tibble: 12 x 5
   term                    estimate  std.error statistic       p.value
   <chr>                      <dbl>      <dbl>     <dbl>         <dbl>
 1 (Intercept)           10.1          0.0845      119.     0
 2 Mileage               -0.00000710   0.00000392   -1.81   0.0704
 3 MakeCadillac           0.647        0.106         6.13   0.00000000141
 4 MakeChevrolet         -0.263        0.0915       -2.88   0.00411
```

```
 5 MakePontiac            -0.182        0.0987       -1.84   0.0657
 6 MakeSAAB                0.356        0.104         3.42   0.000664
 7 MakeSaturn             -0.322        0.117        -2.75   0.00617
 8 Mileage:MakeCadillac    0.000000158  0.00000495    0.0319 0.975
 9 Mileage:MakeChevrolet -0.00000162   0.00000425   -0.382  0.703
10 Mileage:MakePontiac     0.00000202   0.00000462    0.438  0.662
11 Mileage:MakeSAAB       -0.0000000492 0.00000476   -0.0103 0.992
12 Mileage:MakeSaturn     -0.00000367   0.00000539   -0.681  0.496
```

2 Calculating CIs for linear combinations

To calculate a confidence interval for a linear combination of coefficients, we must first calculate the estimate and standard error of the linear combination.

Let's calculate a 95% confidence interval for the slope of the Cadillac model. Refer to your notes/slides and determine the formulas for the estimate and standard error of this slope.

Now that you know the formulas, you'll use R to implement them. First, extract the coefficients and covariance matrix from the model object. Try printing the results to see what they look like and make note of where the Cadillac coefficients are located.

```
car_coefs <- coef(car_lm2)                                    ①
car_vcov <- vcov(car_lm2)                                     ②
```

① Extract the coefficients from the model object and store them in `car_coefs`.
② Extract the covariance matrix from the model object and store it in `car_vcov`.

Next, calculate the estimate of the slope for Cadillacs.

```
estimate <- car_coefs[2] + car_coefs[8]                       ③
estimate
```

③ `car_coefs` is a vector, so we pull off the necessary coefficients using their position in square brackets. Here, `car_coefs[2]` pulls off the coefficient for `Mileage` and `car_coefs[8]` pulls off the coefficient for the interaction term `Mileage:MakeCadillac`.

```
     Mileage
-6.940914e-06
```

Now, calculate the standard error of the slope for Cadillacs.

```
se <- sqrt(car_vcov[2,2] + car_vcov[8,8] + 2*car_vcov[2,8])          ④
se
```

④ car_vcov is a matrix, so we pull off the necessary variances and covariances using their row and column positions in square brackets. Here, car_vcov[2,2] pulls off the variance for Mileage, car_vcov[8,8] pulls off the variance for the interaction term Mileage:MakeCadillac, and car_vcov[2,8] pulls off the covariance between these two coefficients.

```
[1] 3.029984e-06
```

Finally, use the estimate and standard error to calculate a 95% confidence interval for the slope of the Cadillac model. You can use the qt() function to find the appropriate critical value.

Q1. Calculate a 95% confidence interval for the slope of the Cadillac model.

```
# Calculate the 95% CI here
```

---

3 Function quick reference

The following table summarizes the functions we used today:

Function	Purpose
coef()	Extract the estimated coefficients from a fitted model (as a named vector)
vcov()	Extract the covariance matrix of the estimated coefficients from a fitted model
x[i], m[i, j]	Pull off element i of a vector, or the entry in row i and column j of a matrix
sqrt()	Take the square root (e.g., to turn a variance into a standard error)