PORTFOLIO SNAPSHOT | DET-02

Two routes. One blind spot.

From configured monitoring to evidence-backed assessment

THE QUESTION

Does the documented file-download detection rule cover both ways users can access support attachments?

THE APPROACH

I used Python to reconstruct expected triggers from successful file-access events, reconcile collector receipts and alerts, and separate incident-period activity from approved retests. I then compared the results with the exercise requirement and configuration snapshots.

WHAT THE EVIDENCE SHOWED

September's configuration listed only the case-view event type, omitting the required file-library route. November and February snapshots listed both. Later settings addressed the documented coverage gap, but did not prove continuous operation.

DET-02 file-monitoring results	Incident period	Early retest
Expected trigger events	21	2
Timely, consistent collector receipts	21	2
Matching alerts within 5 minutes	0	2

The two early-retest triggers were approved cases, one per route. All 23 trigger receipts arrived in 180 seconds.

THE ASSESSMENT

Design: September's documented route coverage did not meet the requirement. Later snapshots met the event-type inclusion requirement. Operation: both early-retest cases produced timely alerts. Sustained effectiveness and the technical cause of missing incident-period alerts remain unestablished.

WHAT I'M LEARNING

Python can establish what happened in the supplied records. Control assessment is deciding which conclusion that evidence can support—and where the conclusion must stop.

Independent simulation informed by the 2023 Okta support-system incident. All assessed records and thresholds are fictional; these are not findings about Okta's actual internal controls. Scope: DET-02 route coverage and selected monitoring results—not an overall SUP-03 conclusion.